


# CCIE Lab Center

## CLC

# CCIE Security v6.0: Practice Lab v3.0



# CCIE Lab Center

## Workbook Description

**Author:** CCIE Lab Center (CLC)

**Focus:** Practice

**Level:** Expert (CCIE)

**Stream:** CCIE Security v6: DMVPN Technology

**Lab:** Lab v 3.0

**Content:** Topology, Questions, Initial Configuration, Solutions, Verifications.

**Format:** PDF

**Protection:** N/A

**Price/Cost:** \$50 USD

# CCIE Lab Center

Table of Contents	Page No
<b>1. Lab Details</b>	<b>4</b>
1.1 Lab Summary	4
1.2 Lab Objective	10
<b>2. Deployment of Singapore DC</b>	<b>12</b>
2.1 Initial Configuration	12
2.2 DMVPN Dual HUB Phase3 basic configuration	14
<b>3. Deployment of USA Spoke site</b>	<b>20</b>
3.1 Initial Configuration	20
3.2 Configuring DMVPN basic configuration	21
3.3 Redistributing OSPF into RIP & vice versa	22
3.4 Tunnel 0 should PRI path for all outgoing traffic	22
<b>4. Deployment of Japan Spoke site</b>	<b>25</b>
4.1 Initial Configuration	25
4.2 DMVPN Basic configuration	26
4.3 Redistributing Static, Connected Routes into OSPF	27
4.4 DMVPN Basic configuration	28
4.5 Redistributing Static, connected routes into OSPF	29
4.6 Configuring IPSLA & make tunnel 0 has PRI path (10.10.10.17)	30
<b>5. Deployment of UAE Spoke site</b>	<b>34</b>
5.1 Initial Configuration	34
5.2 Redistributing EIGRP into OSPF & vice versa	35
5.3 DMVPN Basic configuration	35
5.4 Redistributing EIGRP into OSPF & vice versa	37
5.5 DMVPN Basic configuration	37
<b>6. Deployment of Hong Kong Spoke site</b>	<b>42</b>
6.1 Initial Configuration	42
6.2 Redistributing EIGRP into OSPF & vice versa	43
6.3 VPN Basic configuration	43
6.4 Redistributing EIGRP into OSPF & vice versa	45
6.5 DMVPN Basic configuration	45
<b>7. Deployment of London Spoke site</b>	<b>50</b>
7.1 Initial Configuration	50
7.2 DMVPN Basic configuration	51
7.3 DMVPN Basic configuration	53
<b>8. Configuring DMVPN Phase3 in all Hubs &amp; Spokes</b>	<b>59</b>
8.1 Phase3 configuration on R1 & R2 (Hubs)	59
8.2 Phase3 configuration on R18,R3,4,6,7,9,10,12 & 13 (Spokes)	60
8.3 Verification of DMVPN Phase3	61

# CCIE Lab Center

## 1: LAB Details


### 1.1: LAB Summary

#### 1.1. a: Hardware details

Phase3:Hub & spoke with spoke to spoke direct communication allowed with better scalability using NHRP redirect.

CPU 4 core  
RAM 8 GB  
HDD 500 GB


**Note:** After starting all nodes wait for 10 minutes for CPU utilization getting back to normal.




# CCIE Lab Center

## 1.1. b: How to upload images into EVE-NG

**Step1:** After starting eve-ng instance Login with filezilla (with your displayed ip address using username & password as root & eve respectively)



**Step2:** Upload qemu images as shown below




**Step3:** Login to your eve-ng server/hypervisor/vmware/etc. with username root & password eve

**Step4:** Run below command using cli

`/opt/unetlab/wrappers/unl_wrapper -a fixpermissions`

# CCIE Lab Center

**Step5: Uploading IOL images as shown below**



**Step6: Run below command using cli**


`/opt/unetlab/wrappers/unl_wrapper -a fixpermissions`

For more details on uploading images you can visit the below link.

<https://www.eve-ng.net/index.php/documentation/howtos/howto-add-cisco-iol-ios-on-linux/>


# CCIE Lab Center

## 1.1. c: Lab Topology in Light Mode



# CCIE Lab Center

## 1.1. d: Lab Topology in Dark Mode



# CCIE Lab Center

## 1.1. e: IP Details

S/N	Router	Hub/Spoke	Tunnel0	Tunnel1	ASN	Loopback0
1	R1	Hub1	100.100.100.1/24	NA	12	1.1.1.1/24
2	R2	Hub2	NA	200.200.200.1/24	12	1.1.1.2/24
3	R18	Spoke	100.100.100.18/24	200.200.200.18/24	18	1.1.1.18/24
2	R3	Spoke	100.100.100.3/24	NA	34	1.1.1.3/24
3	R4	Spoke	NA	200.200.200.4/24	34	1.1.1.4/24
2	R6	Spoke	100.100.100.6/24	NA	67	1.1.1.6/24
3	R7	Spoke	NA	200.200.200.7/24	67	1.1.1.7/24
3	R9	Spoke	NA	200.200.200.9/24	109	1.1.1.9/24
2	R10	Spoke	100.100.100.10/24	NA	109	1.1.1.10/24
3	R12	Spoke	100.100.100.12/24	NA	1213	1.1.1.12/24
3	R13	Spoke	NA	200.200.200.13/24	1213	1.1.1.13/24

## 1.1. f: Lab Nodes Used

Image versions used in Lab.

- ISP Router: i86bi-linux-l3-adventerprisek9-15.5.bin
- HUB & Spoke Router: i86bi-linux-l3-adventerprisek9-15.5.bin

# CCIE Lab Center

## 1.2: Lab Objective

Configure DMVPN Phase 3 network between R1,R2,R18,R3,R4,R6,R7,R9,R10,R12 & R13 with below configuration

1. R1 & R2 are DMVPN Hubs
2. R18,R3,R4,R6,R7,R9,R10,R12 & R13 are DMVPN spokes.
3. Source the tunnel from the router's Ethernet0/0 & Ethernet0/1 interfaces
4. Use IP addressing of PRI Tunnel 0 100.100.100.X/24, & 200.200.200.X/24 where X is the router number.
5. Use an NHRP network ID of 100 of PRI & 200 of SEC.
6. Use an NHRP authentication string of CLC@123
7. Use GRE tunnel key of 100 of PRI & 200 of SEC.
8. Configure the DMVPN Hub to redirect NHRP requests for spoke-to-spoke resolutions.
9. Configure the DMVPN Spokes to be able to install NHRP shortcut routes for spoke-to-spoke routing.
10. Ensure that the spokes can send multicast traffic to the hub, and vice versa.
11. To prevent the tunnel endpoints from having to do IPsec fragmentation, configure the GRE tunnel's IP MTU to 1400 bytes, and set them to adjust the TCP MSS 1360 accordingly.
12. Configure point to multipoint @all Hubs & Spokes

Configure IGP routing over the DMVPN tunnel as follows:

- 1 Configuring OSPF Area 0 @all Routers in Singapore DC R1,R2,R17
- 2 Configuring OSPF Area 0 in R18 Router & RIP v2 in R19 router.
- 3 Configuring OSPF Area 0 in R3 & R4 Routers & R5 as Static routes using IPSLA.
- 4 Configuring OSPF & Name EIGRP of AS 100 in R7,R7 & R8 Routers.
- 5 Configuring OSPF & EIGRP of AS 100 in R9,R10 & R11 Routers.
- 6 Configuring OSPF Area 0 in R12,13,14,15,16 Routers

# CCIE Lab Center

Configure IPsec over the DMVPN tunnels as follows:

- 1 Use an ISAKMP Policy with the following options:
- 2 Pre-Shared Key: CLC@123
- 3 Encryption: AES
- 4 Hash: SHA1
- 5 Diffie-Hellman Group: 2
- 6 Use a single wildcard Pre-Shared Key for all DMVPN peers.
- 7 Use a Crypto IPsec Profile named CLC with the following options:
- 8 Encrypt the traffic using AES
- 9 Authenticate the traffic using SHA1
- 10 Use ESP Transport mode to save additional encapsulation overhead.

When all tasks are completed, ensure that R1,R2,R18,R3,R4,R6,R7,R9,R10,R12 & R13 can reach each other's Loopback0 network over the DMVPN network.

Additionally, ensure that spoke-to-spoke traffic does not transit the hub after initial NHRP mappings are formed.

# CCIE Lab Center

## 2. Deployment of Singapore DC

### 2.1: Initial Configuration

R1,R2 & R17 are normal router configurations are given below.

#### Start-up Configuration

##### I. Hub R1

```
Hostname R1
interface Loopback0
ip address 1.1.1.1 255.255.255.0

interface Ethernet0/0
description *** Connected to PRI MPLS ***
ip address 192.168.100.1 255.255.255.0
ip ospf network point-to-multipoint

interface Ethernet0/2
description *** Connected to R2 ***
ip address 10.10.10.9 255.255.255.252
ip ospf network point-to-point
!
interface Ethernet0/3
description *** Connected to R17 ***
ip address 10.10.10.1 255.255.255.252
ip ospf network point-to-point

router ospf 10
router-id 1.1.1.1
network 1.1.1.1 0.0.0.0 area 0
network 10.10.10.0 0.0.0.3 area 0
network 10.10.10.8 0.0.0.3 area 0
```

##### II. R2 (Hub)

```
hostname R2
```

# CCIE Lab Center

```
interface Loopback0
ip address 1.1.1.2 255.255.255.0

interface Ethernet0/1
description *** Connected to SEC MPLS ***
ip address 192.168.200.2 255.255.255.0
ip ospf network point-to-multipoint
!
interface Ethernet0/2
description *** Connected to R1 ***
ip address 10.10.10.10 255.255.255.252
ip ospf network point-to-point
!
interface Ethernet0/3
description *** Connected to R17 ***
ip address 10.10.10.5 255.255.255.252
ip ospf network point-to-point
!
router ospf 10
router-id 1.1.1.2
network 1.1.1.2 0.0.0.0 area 0
network 10.10.10.4 0.0.0.3 area 0
network 10.10.10.8 0.0.0.3 area 0
```

### III. R17

```
interface Loopback10
ip address 172.16.10.1 255.255.255.0
ip ospf network point-to-point
!
interface Loopback20
ip address 172.16.20.1 255.255.255.0
ip ospf network point-to-point
!
interface Ethernet0/0
description *** Connected to R1 ***
ip address 10.10.10.2 255.255.255.252
ip ospf network point-to-point
!
interface Ethernet0/1
description *** Connected to R2 ***
ip address 10.10.10.6 255.255.255.252
ip ospf network point-to-point

router ospf 10
network 10.10.10.0 0.0.0.3 area 0
network 10.10.10.4 0.0.0.3 area 0
network 172.16.10.0 0.0.0.255 area 0
network 172.16.20.0 0.0.0.255 area 0
```

# CCIE Lab Center

## 2.2: DMVPN Dual HUB Phase3 basic configuration

### QUESTION

- Configure Hub-and-Spoke mGRE tunnels between R1 and R2 (hubs) is acting as a Hub.
- Use the following settings when configuring tunnels.

### Solution

#### On Hub1 (R1)

Tunnel Parameters:

- IP address : 100.100.100.1/24
- IP MTU : 1400
- Tunnel Authentication Key : 100

NHRP Parameters

- NHRP ID : 100
- NHRP Authentication key : clc@123
- NHRP Hub : R1
- NHRP dynamic mapping :ip nhrp map multicast dynamic

Use the following settings when configuring tunnels.

ISAKMP Parameters:

- Authentication : Pre-Shared
- Encryption : AES
- Hashing : SHA
- DH Group : 2
- Pre-Shared Key : clc@123

IPSec Parameters

- Encryption : ESP-aes
- Authentication : ESP-SHA-HMAC

**Others parameter**

```
ip tcp adjust-mss 1360
ip ospf network point-to-multipoint
```

# CCIE Lab Center

```
ip ospf dead-interval 4
ip ospf hello-interval 1
tunnel source Ethernet0/0
tunnel mode gre multipoint
```

## Final Configuration on R1

```
crypto isakmp policy 10
  encr aes
  authentication pre-share
  group 2
crypto isakmp key clc@123 address 0.0.0.0
!
!
crypto ipsec transform-set CLC esp-aes esp-sha-hmac
mode transport
!
crypto ipsec profile CLC
set transform-set CLC

interface Tunnel0
description *** PRI Tunnel ***
bandwidth 102400
ip address 100.100.100.1 255.255.255.0
no ip redirects
ip mtu 1400
ip nhrp authentication clc@123
ip nhrp map multicast dynamic
ip nhrp network-id 100
ip tcp adjust-mss 1360
ip ospf network point-to-multipoint
ip ospf dead-interval 4
ip ospf hello-interval 1
tunnel source Ethernet0/0
tunnel mode gre multipoint
tunnel key 100
tunnel protection ipsec profile CLC
```

## On Hub1 (R2)

### Tunnel Parameters:

- IP address : 200.200.200.1/24
- IP MTU : 1400
- Tunnel Authentication Key : 200

### NHRP Parameters

- NHRP ID : 200
- NHRP Authentication key : clc@123
- NHRP Hub : R2
- NHRP dynamic mapping :ip nhrp map multicast dynamic

# CCIE Lab Center

Use the following settings when configuring tunnels.

## ISAKMP Parameters:

- Authentication : Pre-Shared
- Encryption : AES
- Hashing : SHA
- DH Group : 2
- Pre-Shared Key : clc@123

## IPSec Parameters

- Encryption : ESP-aes
- Authentication : ESP-SHA-HMAC

## Others parameter

```
ip tcp adjust-mss 1360
ip ospf network point-to-multipoint
ip ospf dead-interval 4
ip ospf hello-interval 1
tunnel source Ethernet0/0
tunnel mode gre multipoint
```

## Final Configuration on R2

```
crypto isakmp policy 10
  encr aes
  authentication pre-share
  group 2
crypto isakmp key clc@123 address 0.0.0.0
!
!
crypto ipsec transform-set CLC esp-aes esp-sha-hmac
  mode transport
!
crypto ipsec profile CLC
  set transform-set CLC

interface Tunnel1
  description *** SEC Tunnel ***
  bandwidth 92160
  ip address 200.200.200.2 255.255.255.0
  no ip redirects
  ip mtu 1400
  ip nhrp authentication clc@123
  ip nhrp map multicast dynamic
  ip nhrp network-id 200
  ip tcp adjust-mss 1360
```

# CCIE Lab Center

```
ip ospf network point-to-multipoint
ip ospf dead-interval 4
ip ospf hello-interval 1
tunnel source Ethernet0/0
tunnel mode gre multipoint
tunnel key 200
tunnel protection ipsec profile CLC
```

## Verification

### On R1

R1#sh ip ospf neighbor

Neighbor ID	Pri	State	Dead Time	Address	Interface
1.1.1.2	0	FULL/ -	00:00:35	10.10.10.10	Ethernet0/2
172.16.20.1	0	FULL/ -	00:00:35	10.10.10.2	Ethernet0/3

```
R1#sh ip route 172.16.10.0
Routing entry for 172.16.10.0/24
  Known via "ospf 10", distance 110, metric 11, type intra area
  Redistributing via nhrp
  Last update from 10.10.10.2 on Ethernet0/3, 1d07h ago
  Routing Descriptor Blocks:
    * 10.10.10.2, from 172.16.20.1, 1d07h ago, via Ethernet0/3
      Route metric is 11, traffic share count is 1
R1#sh ip route 172.16.20.0
Routing entry for 172.16.20.0/24
  Known via "ospf 10", distance 110, metric 11, type intra area
  Redistributing via nhrp
  Last update from 10.10.10.2 on Ethernet0/3, 1d07h ago
  Routing Descriptor Blocks:
    * 10.10.10.2, from 172.16.20.1, 1d07h ago, via Ethernet0/3
      Route metric is 11, traffic share count is 1
R1#ping 172.16.10.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.10.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/1/2 ms
R1#ping 172.16.20.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.20.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/1/1 ms
R1#sh ip os
R1#sh ip ospf in
R1#sh ip ospf interface b
R1#sh ip ospf interface br
R1#sh ip ospf interface brief
Interface  PID  Area          IP Address/Mask  Cost  State Nbrs F/C
-----  ---  ---          -
Lo0        10  0            1.1.1.1/24       1     LOOP  0/0
Tu0        10  0            100.100.100.1/24 1     P2MP  5/5
Et0/2     10  0            10.10.10.9/30    10    P2P   1/1
Et0/3     10  0            10.10.10.1/30    10    P2P   1/1
R1#
```

# CCIE Lab Center

```

R1#sh int tunnel 0
Tunnel0 is up, line protocol is up
Hardware is Tunnel
Description: *** PRI Tunnel ***
Internet address is 100.100.100.1/24
MTU 17912 bytes, BW 102400 Kbit/sec, DLY 50000 usec,
    reliability 255/255, txload 1/255, rxload 1/255
Encapsulation TUNNEL, loopback not set
Keepalive not set
Tunnel linstat evaluation up
Tunnel source 192.168.100.1 (Ethernet0/0)
Tunnel Subblocks:
  src-track:
    Tunnel0 source tracking subblock associated with Ethernet0/0
    Set of tunnels with source Ethernet0/0, 1 member (includes iterators), on interface <OK>
Tunnel protocol/transport multi-GRE/IP
  Key 0x64, sequencing disabled
  Checksumming of packets disabled
  Tunnel TTL 255, Fast tunneling enabled
  Tunnel transport MTU 1472 bytes
  Tunnel transmit bandwidth 8000 (kbps)
  Tunnel receive bandwidth 8000 (kbps)
  Tunnel protection via IPSec (profile "CLC")
Last input 00:00:00, output never, output hang never
Last clearing of "show interface" counters 1d07h
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 3
Queueing strategy: fifo
Output queue: 0/0 (size/max)
  5 minute input rate 5000 bits/sec, 5 packets/sec
  5 minute output rate 5000 bits/sec, 6 packets/sec
  590276 packets input, 63979409 bytes, 0 no buffer
    Received 0 broadcasts (0 IP multicasts)
    0 runts, 0 giants, 0 throttles
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
  599185 packets output, 74698133 bytes, 0 underruns
    0 output errors, 0 collisions, 0 interface resets
    0 unknown protocol drops
    0 output buffer failures, 0 output buffers swapped out
R1#

```

## On R2

```
R2#sh ip ospf neighbor
```

Neighbor ID	Pri	State	Dead Time	Address	Interface
1.1.1.1	0	FULL/ -	00:00:39	10.10.10.9	Ethernet0/2
172.16.20.1	0	FULL/ -	00:00:38	10.10.10.6	Ethernet0/3

```

R2#sh ip route 172.16.10.0
Routing entry for 172.16.10.0/24
  Known via "ospf 10", distance 110, metric 11, type intra area
  Last update from 10.10.10.6 on Ethernet0/3, 1d07h ago
  Routing Descriptor Blocks:
    * 10.10.10.6, from 172.16.20.1, 1d07h ago, via Ethernet0/3
      Route metric is 11, traffic share count is 1
R2#sh ip route 172.16.20.0
Routing entry for 172.16.20.0/24
  Known via "ospf 10", distance 110, metric 11, type intra area
  Last update from 10.10.10.6 on Ethernet0/3, 1d07h ago
  Routing Descriptor Blocks:
    * 10.10.10.6, from 172.16.20.1, 1d07h ago, via Ethernet0/3
      Route metric is 11, traffic share count is 1
R2#ping 172.16.10.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.10.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/1/2 ms
R2#ping 172.16.20.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.20.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/1/2 ms
R2#sh ip os
R2#sh ip ospf in
R2#sh ip ospf interface br
R2#sh ip ospf interface brief
Interface  PID  Area          IP Address/Mask  Cost  State Nbrs F/C
Lo0        10  0             1.1.1.2/24       1     LOOP  0/0
Tu1        10  0             200.200.200.2/24 1     P2MP  5/5
Et0/2      10  0             10.10.10.10/30   10    P2P   1/1
Et0/3      10  0             10.10.10.5/30   10    P2P   1/1
R2#

```

# CCIE Lab Center

```

R2#sh int tunnel 1
Tunnell is up, line protocol is up
Hardware is Tunnel
Description: *** Sec Tunnel ***
Internet address is 200.200.200.2/24
MTU 17912 bytes, BW 92160 Kbit/sec, DLY 50000 usec,
    reliability 255/255, txload 1/255, rxload 1/255
Encapsulation TUNNEL, loopback not set
Keepalive not set
Tunnel linestate evaluation up
Tunnel source 192.168.200.2 (Ethernet0/1)
Tunnel Subblocks:
  src-track:
    Tunnel source tracking subblock associated with Ethernet0/1
    Set of tunnels with source Ethernet0/1, 1 member (includes iterators), on interface <OK>
Tunnel protocol/transport multi-GRE/IP
  Key 0xC8, sequencing disabled
  Checksumming of packets disabled
  Tunnel TTL 255, Fast tunneling enabled
  Tunnel transport MTU 1472 bytes
  Tunnel transmit bandwidth 8000 (kbps)
  Tunnel receive bandwidth 8000 (kbps)
  Tunnel protection via IPSec (profile "CLC")
Last input 00:00:00, output never, output hang never
Last clearing of "show interface" counters 1d07h
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 2
Queueing strategy: fifo
Output queue: 0/0 (size/max)
5 minute input rate 4000 bits/sec, 4 packets/sec
5 minute output rate 4000 bits/sec, 4 packets/sec
591629 packets input, 64084651 bytes, 0 no buffer
Received 0 broadcasts (0 IP multicasts)
0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
599764 packets output, 74733103 bytes, 0 underruns
0 output errors, 0 collisions, 0 interface resets
0 unknown protocol drops
0 output buffer failures, 0 output buffers swapped out
R2#
```

# CCIE Lab Center

## 3. Deployment of USA Spoke site

### 3.1: Initial Configuration

#### Start-up Configuration

##### I. Spoke R18

```
hostname R18

interface Loopback0
 ip address 1.1.1.18 255.255.255.0
!

interface Ethernet0/0
 description *** Connected to PRI DMVPN Cloud ***
 ip address 192.168.100.18 255.255.255.0
 ip ospf network point-to-multipoint
!
interface Ethernet0/1
 description *** Connected to SEC DMVPN Cloud ***
 ip address 192.168.200.18 255.255.255.0
 ip ospf network point-to-multipoint
!
interface Ethernet0/2
 description *** Connected to R19 ***
 ip address 10.10.10.13 255.255.255.252

router ospf 10
 router-id 1.1.1.18
 network 1.1.1.18 0.0.0.0 area 0
 network 100.100.100.0 0.0.0.255 area 0
 network 200.200.200.0 0.0.0.255 area 0
!
router rip
 version 2
 network 10.0.0.0
 no auto-summary
```

# CCIE Lab Center

## 3.2: Configuring DMVPN basic configuration

### On R18

```
interface Tunnel0
description *** PRI Tunnel ***
ip address 100.100.100.18 255.255.255.0
no ip redirects
ip mtu 1400
ip nhrp authentication clc@123
ip nhrp map 100.100.100.1 192.168.100.1
ip nhrp map multicast 192.168.100.1
ip nhrp network-id 100
ip nhrp nhs 100.100.100.1
ip tcp adjust-mss 1360
ip ospf network point-to-multipoint
ip ospf dead-interval 4
ip ospf hello-interval 1
tunnel source Ethernet0/0
tunnel mode gre multipoint
tunnel key 100
tunnel protection ipsec profile CLC

interface Tunnel1
description *** SEC Tunnel ***
ip address 200.200.200.18 255.255.255.0
no ip redirects
ip mtu 1400
ip nhrp authentication clc@123
ip nhrp map 200.200.200.2 192.168.200.2
ip nhrp map multicast 192.168.200.2
ip nhrp network-id 200
ip nhrp nhs 200.200.200.2
ip tcp adjust-mss 1360
ip ospf network point-to-multipoint
ip ospf dead-interval 4
ip ospf hello-interval 1
tunnel source Ethernet0/1
tunnel mode gre multipoint
tunnel key 200
tunnel protection ipsec profile CLC

crypto isakmp policy 10
encr aes
authentication pre-share
group 2
crypto isakmp key clc@123 address 0.0.0.0
!
crypto ipsec transform-set CLC esp-aes esp-sha-hmac
mode transport

crypto ipsec profile CLC
set transform-set CLC
```

# CCIE Lab Center

## 3.3: Redistributing OSPF into RIP & vice versa

### On R18

```
router ospf 10
 redistribute rip metric 20 subnets
```

```
router rip
 redistribute ospf 10 metric 10
```

## 3.4: Tunnel 0 should PRI path for all outgoing traffic

### On R18

```
interface Tunnel0
 ip ospf cost 50
```

### On R19

#### hostname R19

```
interface Loopback10
 ip address 172.16.30.1 255.255.255.0
 !
interface Loopback20
 ip address 172.16.40.1 255.255.255.0
 !
interface Ethernet0/0
 ip address 10.10.10.14 255.255.255.252
```

```
router rip
 version 2
 network 10.0.0.0
 network 172.16.0.0
 no auto-summary
```

# CCIE Lab Center

## Verification

On R19

```
R19#sh ip route 172.16.10.0
Routing entry for 172.16.10.0/24
  Known via "rip", distance 120, metric 10
  Redistributing via rip
  Last update from 10.10.10.13 on Ethernet0/0, 00:00:14 ago
  Routing Descriptor Blocks:
    * 10.10.10.13, from 10.10.10.13, 00:00:14 ago, via Ethernet0/0
      Route metric is 10, traffic share count is 1
R19#sh ip route 172.16.20.0
Routing entry for 172.16.20.0/24
  Known via "rip", distance 120, metric 10
  Redistributing via rip
  Last update from 10.10.10.13 on Ethernet0/0, 00:00:20 ago
  Routing Descriptor Blocks:
    * 10.10.10.13, from 10.10.10.13, 00:00:20 ago, via Ethernet0/0
      Route metric is 10, traffic share count is 1
R19#ping 172.16.10.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.10.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 2/2/3 ms
R19#ping 172.16.20.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.20.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 2/3/5 ms
R19#tr
R19#traceroute 172.16.10.1 nu
R19#traceroute 172.16.10.1 numeric
Type escape sequence to abort.
Tracing the route to 172.16.10.1
VRF info: (vrf in name/id, vrf out name/id)
  1 10.10.10.13 1 msec 1 msec 1 msec
  2 100.100.100.1 3 msec 3 msec 2 msec
  3 10.10.10.2 4 msec * 3 msec
R19#traceroute 172.16.20.1 numeric
Type escape sequence to abort.
Tracing the route to 172.16.20.1
VRF info: (vrf in name/id, vrf out name/id)
  1 10.10.10.13 1 msec 1 msec 1 msec
  2 100.100.100.1 2 msec 2 msec 2 msec
  3 10.10.10.2 3 msec * 4 msec
R19#
```

# CCIE Lab Center

On R18

```
R18#sh ip route 172.16.10.0
Routing entry for 172.16.10.0/24
  Known via "ospf 10", distance 110, metric 61, type intra area
  Redistributing via rip
  Advertised by rip metric 10
  Last update from 100.100.100.1 on Tunnel0, 1d20h ago
  Routing Descriptor Blocks:
    * 100.100.100.1, from 172.16.20.1, 1d20h ago, via Tunnel0
      Route metric is 61, traffic share count is 1
R18#sh ip route 172.16.20.0
Routing entry for 172.16.20.0/24
  Known via "ospf 10", distance 110, metric 61, type intra area
  Redistributing via rip
  Advertised by rip metric 10
  Last update from 100.100.100.1 on Tunnel0, 1d20h ago
  Routing Descriptor Blocks:
    * 100.100.100.1, from 172.16.20.1, 1d20h ago, via Tunnel0
      Route metric is 61, traffic share count is 1
R18#ping 172.16.10.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.10.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 7/7/8 ms
R18#ping 172.16.20.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.20.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 3/5/7 ms
R18#tr
R18#traceroute 172.16.10.1 nu
R18#traceroute 172.16.10.1 numeric
Type escape sequence to abort.
Tracing the route to 172.16.10.1
VRF info: (vrf in name/id, vrf out name/id)
  0 100.100.100.1 7 msec 7 msec 7 msec
  1 10.10.10.2 7 msec * 8 msec
R18#traceroute 172.16.20.1 numeric
Type escape sequence to abort.
Tracing the route to 172.16.20.1
VRF info: (vrf in name/id, vrf out name/id)
  0 100.100.100.1 7 msec 10 msec 6 msec
  1 10.10.10.2 6 msec * 8 msec
R18#
```

# CCIE Lab Center

## 4. Deployment of Japan Spoke site

### 4.1: Initial Configuration

#### Start-up Configuration

##### I. Spoke R3

```
interface Loopback0
ip address 1.1.1.3 255.255.255.0

interface Ethernet0/0
description *** Connected to PRI MPLS ***
ip address 192.168.100.3 255.255.255.0
ip ospf network point-to-multipoint

interface Ethernet0/3
description *** Connected to R5 ***
ip address 10.10.10.17 255.255.255.252

router ospf 10
router-id 1.1.1.3
network 1.1.1.3 0.0.0.0 area 0
network 100.100.100.0 0.0.0.255 area 0
!

ip route 172.16.50.0 255.255.255.0 10.10.10.18
ip route 172.16.60.0 255.255.255.0 10.10.10.18
```

# CCIE Lab Center

## 4.2: DMVPN Basic configuration

### On R3

```
crypto isakmp policy 10
  encr aes
  authentication pre-share
  group 2
crypto isakmp key clc@123 address 0.0.0.0
!
!
crypto ipsec transform-set CLC esp-aes esp-sha-hmac
  mode transport
!
crypto ipsec profile CLC
  set transform-set CLC

!
interface Tunnel0
  description *** PRI Tunnel ***
  ip address 100.100.100.3 255.255.255.0
  no ip redirects
  ip mtu 1400
  ip nhrp authentication clc@123
  ip nhrp map 100.100.100.1 192.168.100.1
  ip nhrp map multicast 192.168.100.1
  ip nhrp network-id 100
  ip nhrp nhs 100.100.100.1
  ip tcp adjust-mss 1360
  ip ospf network point-to-multipoint
  ip ospf dead-interval 4
  ip ospf hello-interval 1
  ip ospf cost 50
  tunnel source Ethernet0/0
  tunnel mode gre multipoint
  tunnel key 100
  tunnel protection ipsec profile CLC
!
```

# CCIE Lab Center

## 4.3: Redistributing Static, Connected Routes into OSPF

### On R3

```
router ospf 10
 redistribute connected subnets
 redistribute static subnets
```

### I. Spoke R4

```
interface Loopback0
 ip address 1.1.1.4 255.255.255.0
```

```
interface Ethernet0/0
 description *** Connected to Sec DMVPN Cloud ***
 ip address 192.168.200.4 255.255.255.0
 ip ospf network point-to-multipoint
```

```
interface Ethernet0/3
 description *** Connected to R5 ***
 ip address 10.10.10.21 255.255.255.252
```

```
!
router ospf 10
 router-id 1.1.1.4
 network 1.1.1.4 0.0.0.0 area 0
 network 200.200.200.0 0.0.0.255 area 0
```

```
ip route 172.16.50.0 255.255.255.0 10.10.10.22
 ip route 172.16.60.0 255.255.255.0 10.10.10.22
```

# CCIE Lab Center

## 4.4: DMVPN Basic configuration

### On R4

```
crypto isakmp policy 10
  encr aes
  authentication pre-share
  group 2
crypto isakmp key clc@123 address 0.0.0.0
!
!
crypto ipsec transform-set CLC esp-aes esp-sha-hmac
  mode transport
!
crypto ipsec profile CLC
  set transform-set CLC

interface Tunnel1
  description *** PRI Tunnel ***
  ip address 200.200.200.4 255.255.255.0
  no ip redirects
  ip mtu 1400
  ip nhrp authentication clc@123
  ip nhrp map 200.200.200.2 192.168.200.2
  ip nhrp map multicast 192.168.200.2
  ip nhrp network-id 200
  ip nhrp nhs 200.200.200.2
  ip tcp adjust-mss 1360
  ip ospf network point-to-multipoint
  ip ospf dead-interval 4
  ip ospf hello-interval 1
  tunnel source Ethernet0/0
  tunnel mode gre multipoint
  tunnel key 200
  tunnel protection ipsec profile CLC
```

# CCIE Lab Center

## 4.5 : Redistributing Static, connected routes into OSPF

### On R4

```
router ospf 10
router-id 1.1.1.4
redistribute connected subnets
redistribute static subnets
```

### On R5

```
interface Loopback10
ip address 172.16.50.1 255.255.255.0
!
interface Loopback20
ip address 172.16.60.1 255.255.255.0
!
interface Ethernet0/0
description *** Connected to R3 ***
ip address 10.10.10.18 255.255.255.252
!
interface Ethernet0/1
description *** Connected to R4 ***
ip address 10.10.10.22 255.255.255.252

ip route 0.0.0.0 0.0.0.0 10.10.10.17 name PRI-MPLS
ip route 0.0.0.0 0.0.0.0 10.10.10.21 10 name SEC-MPLS
```

# CCIE Lab Center

## 4.6: Configuring IPSLA & make tunnel 0 has PRI path (10.10.10.17)

On R5

```
ip sla 1
icmp-echo 100.100.100.1 source-interface Ethernet0/0
threshold 2
frequency 5
ip sla schedule 1 life forever start-time now

track 1 ip sla 1 reachability

ip route 0.0.0.0 0.0.0.0 10.10.10.17 name PRI-MPLS track 1
ip route 0.0.0.0 0.0.0.0 10.10.10.21 10 name SEC-MPLS
```

### Verification


On R5

Now PRI path is 10.10.10.17

```
R5#ping 172.16.10.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.10.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 3/3/4 ms
R5#ping 172.16.20.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.20.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 3/3/4 ms
R5#tr
R5#traceroute 172.16.10.1 nu
R5#traceroute 172.16.10.1 numeric
Type escape sequence to abort.
Tracing the route to 172.16.10.1
VRF info: (vrf in name/id, vrf out name/id)
 0 10.10.10.17 1 msec 0 msec 1 msec
 1 100.100.100.1 3 msec 3 msec 3 msec
 2 10.10.10.2 4 msec * 3 msec
R5#
```

# CCIE Lab Center

Lets suspended 10.10.10.17



```

R5#ping 172.16.10.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.10.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 3/3/5 ms
R5#traceroute 172.16.10.1 numeric
Type escape sequence to abort.
Tracing the route to 172.16.10.1
VRF info: (vrf in name/id, vrf out name/id)
 1 *
  1 10.10.10.21 2 msec 0 msec
  2 200.200.200.2 2 msec 2 msec 2 msec
  3 10.10.10.6 2 msec
*Oct 23 07:19:56.214: %LINK-3-UPDOWN: Interface Ethernet0/0, changed state to down
*Oct 23 07:19:57.214: %LINEPROTO-5-UPDOWN: Line protocol on Interface Ethernet0/0, changed state to down * 4 msec
R5#traceroute 172.16.10.1 numeric
Type escape sequence to abort.
Tracing the route to 172.16.10.1
VRF info: (vrf in name/id, vrf out name/id)
 1 10.10.10.21 1 msec 1 msec 1 msec
  2 200.200.200.2 3 msec 2 msec 2 msec
  3 10.10.10.6 3 msec
*Oct 23 07:20:05.797: %TRACK-6-STATE: 1 ip sla 1 reachability Up -> Down * 3 msec
R5#

```

Traffic shifted to 10.10.10.21 on Secondary Path

```

R5#sh ip sla summary
IPSLAs Latest Operation Summary
Codes: * active, ^ inactive, ~ pending

ID          Type      Destination      Stats      Return      Last
           (ms)      (ms)             Code       Run
-----
*1          icmp-echo 10.10.10.17      -          Timeout    9 seconds ago

R5#sh ip route
R5#sh ip route 0.0.0.0
Routing entry for 0.0.0.0/0, supernet
  Known via "static", distance 10, metric 0, candidate default path
  Routing Descriptor Blocks:
    * 10.10.10.21
      Route metric is 0, traffic share count is 1
R5#

```

# CCIE Lab Center

On R3

```
R3#
R3#ping 172.16.10.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.10.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 2/5/7 ms
R3#ping 172.16.20.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.20.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 4/6/7 ms
R3#tr
R3#sh ip route
R3#sh ip route 172.16.10.0
Routing entry for 172.16.10.0/24
  Known via "ospf 10", distance 110, metric 61, type intra area
  Last update from 100.100.100.1 on Tunnel0, 1d21h ago
  Routing Descriptor Blocks:
    * 100.100.100.1, from 172.16.20.1, 1d21h ago, via Tunnel0
      Route metric is 61, traffic share count is 1
R3#sh ip route 172.16.20.0
Routing entry for 172.16.20.0/24
  Known via "ospf 10", distance 110, metric 61, type intra area
  Last update from 100.100.100.1 on Tunnel0, 1d21h ago
  Routing Descriptor Blocks:
    * 100.100.100.1, from 172.16.20.1, 1d21h ago, via Tunnel0
      Route metric is 61, traffic share count is 1
R3#tr
R3#traceroute 172.16.10.1 nu
R3#traceroute 172.16.10.1 numeric
Type escape sequence to abort.
Tracing the route to 172.16.10.1
VRF info: (vrf in name/id, vrf out name/id)
  1 100.100.100.1 7 msec 7 msec 6 msec
  2 10.10.10.2 7 msec * 7 msec
R3#traceroute 172.16.20.1 numeric
Type escape sequence to abort.
Tracing the route to 172.16.20.1
VRF info: (vrf in name/id, vrf out name/id)
  1 100.100.100.1 7 msec 7 msec 6 msec
  2 10.10.10.2 7 msec * 8 msec
R3#
```

# CCIE Lab Center

On R4

```
.....
Success rate is 40 percent (2/5), round-trip min/avg/max = 8/8/8 ms
R4#ping 172.16.10.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.10.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 7/7/8 ms
R4#ping 172.16.20.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.20.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 4/7/8 ms
R4#sh ip route
R4#sh ip route 172.16.10.0
Routing entry for 172.16.10.0/24
  Known via "ospf 10", distance 110, metric 1011, type intra area
  Last update from 200.200.200.2 on Tunnell, 00:02:30 ago
  Routing Descriptor Blocks:
  * 200.200.200.2, from 172.16.20.1, 00:02:30 ago, via Tunnell
    Route metric is 1011, traffic share count is 1
R4#sh ip route 172.16.20.0
Routing entry for 172.16.20.0/24
  Known via "ospf 10", distance 110, metric 1011, type intra area
  Last update from 200.200.200.2 on Tunnell, 00:02:34 ago
  Routing Descriptor Blocks:
  * 200.200.200.2, from 172.16.20.1, 00:02:34 ago, via Tunnell
    Route metric is 1011, traffic share count is 1
R4#te
R4#tr
R4#traceroute 172.16.10.1 so
R4#traceroute 172.16.10.1 source loo
R4#traceroute 172.16.10.1 source loopback 0
R4#traceroute 172.16.10.1 source loopback 0 nu
R4#traceroute 172.16.10.1 source loopback 0 numeric
Type escape sequence to abort.
Tracing the route to 172.16.10.1
VRF info: (vrf in name/id, vrf out name/id)
  1 200.200.200.2 7 msec 6 msec 7 msec
  2 10.10.10.6 7 msec * 7 msec
R4#traceroute 172.16.20.1 source loopback 0 numeric
Type escape sequence to abort.
Tracing the route to 172.16.20.1
VRF info: (vrf in name/id, vrf out name/id)
  1 200.200.200.2 7 msec 7 msec 7 msec
  2 10.10.10.6 8 msec * 8 msec
R4#
```

# CCIE Lab Center

## 5. Deployment of UAE Spoke site

### 5.1: Initial Configuration

#### On R6

```
interface Ethernet0/0
description *** Connected to PRI MPLS ***
ip address 192.168.100.6 255.255.255.0
ip ospf network point-to-multipoint
!
interface Ethernet0/2
description *** Connected to R7 ***
ip address 10.10.10.29 255.255.255.252
!
interface Ethernet0/3
description *** Connected to R8 ***
ip address 10.10.10.25 255.255.255.252
!
!
router eigrp CLC
!
address-family ipv4 unicast autonomous-system 100
!
topology base
  exit-af-topology
  network 10.10.10.24 0.0.0.3
  network 10.10.10.28 0.0.0.3
exit-address-family
!
router ospf 10
router-id 1.1.1.6
network 1.1.1.6 0.0.0.0 area 0
network 100.100.100.0 0.0.0.255 area 0
```

# CCIE Lab Center

## 5.2: Redistributing EIGRP into OSPF & vice versa

### On R6

```
router eigrp CLC
!
address-family ipv4 unicast autonomous-system 100
!
topology base
 redistribute ospf 10 metric 10000 1000 255 1 1500

router ospf 10
 redistribute eigrp 100 metric 50 subnets
```

## 5.3: DMVPN Basic configuration

### On R6

```
crypto isakmp policy 10
 encr aes
 authentication pre-share
 group 2
 crypto isakmp key clc@123 address 0.0.0.0
!
!
crypto ipsec transform-set CLC esp-aes esp-sha-hmac
 mode transport
!
crypto ipsec profile CLC
 set transform-set CLC

interface Tunnel0
 description *** PRI Tunnel ***
 ip address 100.100.100.6 255.255.255.0
 no ip redirects
 ip mtu 1400
 ip nhrp authentication clc@123
 ip nhrp map 100.100.100.1 192.168.100.1
 ip nhrp map multicast 192.168.100.1
 ip nhrp network-id 100
 ip nhrp nhs 100.100.100.1
 ip tcp adjust-mss 1360
```

# CCIE Lab Center

```
ip ospf network point-to-multipoint
ip ospf dead-interval 4
ip ospf hello-interval 1
ip ospf cost 50
tunnel source Ethernet0/0
tunnel mode gre multipoint
tunnel key 100
tunnel protection ipsec profile CLC
```

## On R7

```
interface Loopback0
ip address 1.1.1.7 255.255.255.0
```

```
interface Ethernet0/0
description *** Connected to SEC MPLS ***
ip address 192.168.200.7 255.255.255.0
ip ospf network point-to-multipoint
!
interface Ethernet0/2
description *** Connected to R6 ***
ip address 10.10.10.30 255.255.255.252
!
interface Ethernet0/3
description *** Connected to R8 ***
ip address 10.10.10.33 255.255.255.252
```

```
router eigrp CLC
!
address-family ipv4 unicast autonomous-system 100
!
topology base
  exit-af-topology
  network 10.10.10.28 0.0.0.3
  network 10.10.10.32 0.0.0.3
exit-address-family
!
router ospf 10
router-id 1.1.1.7
network 1.1.1.7 0.0.0.0 area 0
network 50.50.50.12 0.0.0.3 area 0
network 200.200.200.0 0.0.0.255 area 0
```

# CCIE Lab Center

## 5.4: Redistributing EIGRP into OSPF & vice versa

### On R7

```
router eigrp CLC
!
address-family ipv4 unicast autonomous-system 100
!
topology base
 redistribute ospf 10 metric 1000 1000 255 1 1500

router ospf 10
 redistribute eigrp 100 metric 100 subnets
```

## 5.5: DMVPN Basic configuration

### On R7

```
crypto isakmp policy 10
 encr aes
 authentication pre-share
 group 2
 crypto isakmp key clc@123 address 0.0.0.0
!
crypto ipsec transform-set CLC esp-aes esp-sha-hmac
 mode transport
!
crypto ipsec profile CLC
 set transform-set CLC

interface Tunnel1
 description *** SEC Tunnel ***
 ip address 200.200.200.7 255.255.255.0
 no ip redirects
 ip mtu 1400
 ip nhrp authentication clc@123
 ip nhrp map 200.200.200.2 192.168.200.2
 ip nhrp map multicast 192.168.200.2
 ip nhrp network-id 200
 ip nhrp nhs 200.200.200.2
 ip tcp adjust-mss 1360
 ip ospf network point-to-multipoint
 ip ospf dead-interval 4
 ip ospf hello-interval 1
```

# CCIE Lab Center

```
tunnel source Ethernet0/0
tunnel mode gre multipoint
tunnel key 200
tunnel protection ipsec profile CLC
```

## On R8

```
interface Loopback10
ip address 172.16.70.1 255.255.255.0
!
interface Loopback20
ip address 172.16.80.1 255.255.255.0
!
interface Ethernet0/0
ip address 10.10.10.26 255.255.255.252
!
interface Ethernet0/1
ip address 10.10.10.34 255.255.255.252

router eigrp CLC
!
address-family ipv4 unicast autonomous-system 100
!
topology base
exit-af-topology
network 10.10.10.24 0.0.0.3
network 10.10.10.32 0.0.0.3
network 172.16.70.0 0.0.0.255
network 172.16.80.0 0.0.0.255
exit-address-family
```

# CCIE Lab Center

## Verification

### On R6

```

R6#ping 172.16.10.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.10.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 2/2/4 ms
R6#ping 172.16.20.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.20.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 3/3/4 ms
R6#sh ip route
R6#sh ip route 172.16.10.0
Routing entry for 172.16.10.0/24
  Known via "eigrp 100", distance 170, metric 10752000, type external
  Redistributing via eigrp 100, ospf 10
  Advertised by ospf 10 metric 50 subnets
  Last update from 10.10.10.30 on Ethernet0/2, 07:16:13 ago
  Routing Descriptor Blocks:
  * 10.10.10.30, from 10.10.10.30, 07:16:13 ago, via Ethernet0/2
    Route metric is 10752000, traffic share count is 1
    Total delay is 11000 microseconds, minimum bandwidth is 1000 Kbit
    Reliability 255/255, minimum MTU 1500 bytes
    Loading 1/255, Hops 1
R6#sh ip route 172.16.20.0
Routing entry for 172.16.20.0/24
  Known via "eigrp 100", distance 170, metric 10752000, type external
  Redistributing via eigrp 100, ospf 10
  Advertised by ospf 10 metric 50 subnets
  Last update from 10.10.10.30 on Ethernet0/2, 07:16:17 ago
  Routing Descriptor Blocks:
  * 10.10.10.30, from 10.10.10.30, 07:16:17 ago, via Ethernet0/2
    Route metric is 10752000, traffic share count is 1
    Total delay is 11000 microseconds, minimum bandwidth is 1000 Kbit
    Reliability 255/255, minimum MTU 1500 bytes
    Loading 1/255, Hops 1

```

```

R6#traceroute 172.16.10.1 source loopback 0
R6#traceroute 172.16.10.1 source loopback 0
Type escape sequence to abort.
Tracing the route to 172.16.10.1
VRF info: (vrf in name/id, vrf out name/id)
  1 100.100.100.1 7 msec 7 msec 6 msec
  2 10.10.10.2 7 msec 7 msec *
R6#traceroute 172.16.20.1 source loopback 0
Type escape sequence to abort.
Tracing the route to 172.16.20.1
VRF info: (vrf in name/id, vrf out name/id)
  1 100.100.100.1 7 msec 6 msec 6 msec
  2 10.10.10.2 6 msec 8 msec *
R6#

```

# CCIE Lab Center

On R7

```
R7#ping 172.16.10.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.10.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 7/7/8 ms
R7#ping 172.16.20.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.20.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 7/7/8 ms
R7#sh ip route
R7#sh ip route 172.16.10.0
Routing entry for 172.16.10.0/24
  Known via "ospf 10", distance 110, metric 1011, type intra area
  Redistributing via eigrp 100
  Advertised by eigrp 100 metric 1000 1000 255 1 1500
  Last update from 200.200.200.2 on Tunnel1, 07:25:02 ago
  Routing Descriptor Blocks:
  * 200.200.200.2, from 172.16.20.1, 07:25:02 ago, via Tunnel1
    Route metric is 1011, traffic share count is 1
R7#sh ip route 172.16.20.0
Routing entry for 172.16.20.0/24
  Known via "ospf 10", distance 110, metric 1011, type intra area
  Redistributing via eigrp 100
  Advertised by eigrp 100 metric 1000 1000 255 1 1500
  Last update from 200.200.200.2 on Tunnel1, 07:25:05 ago
  Routing Descriptor Blocks:
  * 200.200.200.2, from 172.16.20.1, 07:25:05 ago, via Tunnel1
    Route metric is 1011, traffic share count is 1
R7#
```

```
R7#tracert 172.16.10.1 source 100
R7#tracert 172.16.10.1 source loopback 0
Type escape sequence to abort.
Tracing the route to 172.16.10.1
VRF info: (vrf in name/id, vrf out name/id)
  1 200.200.200.2 8 msec 7 msec 6 msec
  2 10.10.10.6 8 msec 9 msec *
R7#tracert 172.16.20.1 source loopback 0 nu
R7#tracert 172.16.20.1 source loopback 0 numeric
Type escape sequence to abort.
Tracing the route to 172.16.20.1
VRF info: (vrf in name/id, vrf out name/id)
  1 200.200.200.2 8 msec 6 msec 4 msec
  2 10.10.10.6 8 msec * 7 msec
R7#
```

# CCIE Lab Center

## On R8

```
R8#ping 172.16.10.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.10.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 2/3/5 ms
R8#ping 172.16.20.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.20.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 3/3/4 ms
R8#tr
R8#sh ip route
R8#sh ip route 172.16.10.0
Routing entry for 172.16.10.0/24
  Known via "eigrp 100", distance 170, metric 6144000, type external
  Redistributing via eigrp 100
  Last update from 10.10.10.25 on Ethernet0/0, 00:05:39 ago
  Routing Descriptor Blocks:
  * 10.10.10.25, from 10.10.10.25, 00:05:39 ago, via Ethernet0/0
    Route metric is 6144000, traffic share count is 1
    Total delay is 11000 microseconds, minimum bandwidth is 10000 Kbit
    Reliability 255/255, minimum MTU 1500 bytes
    Loading 1/255, Hops 1
R8#sh ip route 172.16.20.0
Routing entry for 172.16.20.0/24
  Known via "eigrp 100", distance 170, metric 6144000, type external
  Redistributing via eigrp 100
  Last update from 10.10.10.25 on Ethernet0/0, 00:05:44 ago
  Routing Descriptor Blocks:
  * 10.10.10.25, from 10.10.10.25, 00:05:44 ago, via Ethernet0/0
    Route metric is 6144000, traffic share count is 1
    Total delay is 11000 microseconds, minimum bandwidth is 10000 Kbit
    Reliability 255/255, minimum MTU 1500 bytes
    Loading 1/255, Hops 1
R8#
```

```
R8#tracert 172.16.10.1
R8#tracert 172.16.10.1 numeric
Type escape sequence to abort.
Tracing the route to 172.16.10.1
VRF info: (vrf in name/id, vrf out name/id)
  0 10.10.10.25 1 msec 1 msec 1 msec
  1 100.100.100.1 3 msec 3 msec 2 msec
  2 10.10.10.2 3 msec * 3 msec
R8#tracert 172.16.20.1 numeric
Type escape sequence to abort.
Tracing the route to 172.16.20.1
VRF info: (vrf in name/id, vrf out name/id)
  0 10.10.10.25 1 msec 0 msec 0 msec
  1 100.100.100.1 3 msec 3 msec 3 msec
  2 10.10.10.2 4 msec * 5 msec
R8#
```

# CCIE Lab Center

## 6. Deployment of Hong Kong Spoke site

### 6.1: Initial Configuration

#### On R10

```
interface Loopback0
ip address 1.1.1.10 255.255.255.0

interface Ethernet0/0
description *** Connected to PRI MPLS ***
ip address 192.168.100.10 255.255.255.0
ip ospf network point-to-multipoint

!
interface Ethernet0/2
description connected to R9 ***
ip address 10.10.10.37 255.255.255.252
!
interface Ethernet0/3
description connected to R11 ***
ip address 10.10.10.41 255.255.255.252
!
!
router eigrp 200
network 10.10.10.36 0.0.0.3
network 10.10.10.40 0.0.0.3
redistribute ospf 10 metric 100000 100 255 1 1500
!
router ospf 10
router-id 1.1.1.10
redistribute eigrp 200 metric 50 subnets
network 1.1.1.10 0.0.0.0 area 1
network 100.100.100.0 0.0.0.255 area 0
network 192.168.10.16 0.0.0.3 area 0
```

# CCIE Lab Center

## 6.2: Redistributing EIGRP into OSPF & vice versa

### On R10

```
router eigrp 200
redistribute ospf 10 metric 100000 100 255 1 1500
!
router ospf 10
redistribute eigrp 200 metric 50 subnets
```

## 6.3: DMVPN Basic configuration

### On R10

```
crypto isakmp policy 10
encr aes
authentication pre-share
group 2
crypto isakmp key clc@123 address 0.0.0.0
!
!
crypto ipsec transform-set CLC esp-aes esp-sha-hmac
mode transport
!
crypto ipsec profile CLC
set transform-set CLC
!
interface Tunnel0
description *** PRI Tunnel ***
ip address 100.100.100.10 255.255.255.0
no ip redirects
ip mtu 1400
ip nhrp authentication clc@123
ip nhrp map 100.100.100.1 192.168.100.1
ip nhrp map multicast 192.168.100.1
ip nhrp network-id 100
ip nhrp nhs 100.100.100.1
ip tcp adjust-mss 1360
ip ospf network point-to-multipoint
ip ospf cost 50
tunnel source Ethernet0/0
tunnel mode gre multipoint
tunnel key 100
tunnel protection ipsec profile CLC
```

# CCIE Lab Center

## on R9

```
interface Loopback0
ip address 1.1.1.9 255.255.255.0

interface Ethernet0/0
description *** Connected to SEC-MPLS ***
ip address 192.168.200.9 255.255.255.0
ip ospf network point-to-multipoint
!
interface Ethernet0/1
no ip address
shutdown
!
interface Ethernet0/2
description *** Conected to R10 ***
ip address 10.10.10.38 255.255.255.252
!
interface Ethernet0/3
description *** Conected to R11 ***
ip address 10.10.10.45 255.255.255.252
!
!
router eigrp 200
network 10.10.10.36 0.0.0.3
network 10.10.10.44 0.0.0.3
redistribute ospf 10 metric 1000 100 255 1 1500

router ospf 10
router-id 1.1.1.9
redistribute eigrp 200 metric 100 subnets
network 1.1.1.9 0.0.0.0 area 0
network 50.50.50.16 0.0.0.3 area 0
network 200.200.200.0 0.0.0.255 area 0
```

# CCIE Lab Center

## 6.4: Redistributing EIGRP into OSPF & vice versa

### On R9

```
router eigrp 200
 redistribute ospf 10 metric 1000 100 255 1 1500
```

```
router ospf 10
 redistribute eigrp 200 metric 100 subnets
```

## 6.5: DMVPN Basic configuration

### On R9

```
crypto isakmp policy 10
 encr aes
 authentication pre-share
 group 2
 crypto isakmp key clc@123 address 0.0.0.0
 !
 !
 crypto ipsec transform-set CLC esp-aes esp-sha-hmac
 mode transport
 !
 crypto ipsec profile CLC
 set transform-set CLC
```

```
interface Tunnel1
 description *** SEC Tunnel ***
 ip address 200.200.200.9 255.255.255.0
 no ip redirects
 ip mtu 1400
 ip nhrp authentication clc@123
 ip nhrp map 200.200.200.2 192.168.200.2
 ip nhrp map multicast 192.168.200.2
 ip nhrp network-id 200
 ip nhrp holdtime 300
 ip nhrp nhs 200.200.200.2
 ip ospf dead-interval 4
 ip ospf hello-interval 1
 ip ospf network point-to-multipoint
 tunnel source Ethernet0/0
 tunnel mode gre multipoint
```

# CCIE Lab Center

```
tunnel key 200
tunnel protection ipsec profile CLC
```

## On R11

```
interface Loopback10
 ip address 172.16.90.1 255.255.255.0
 !
interface Loopback20
 ip address 172.16.100.1 255.255.255.0
 !
interface Ethernet0/0
 description *** Connected to R10 ***
 ip address 10.10.10.42 255.255.255.252
 !
interface Ethernet0/1
 description *** Connected to R10 ***
 ip address 10.10.10.46 255.255.255.252

router eigrp 200
 network 10.10.10.40 0.0.0.3
 network 10.10.10.44 0.0.0.3
 network 172.16.90.0 0.0.0.255
 network 172.16.100.0 0.0.0.255
```

# CCIE Lab Center

## Verification

On R10

```
R10
Sending 5, 100-byte ICMP Echos to 172.16.10.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 5/7/8 ms
R10#ping 172.16.20.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.20.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 7/7/8 ms
R10#sh ip route
R10#sh ip route 172.16.10.0
Routing entry for 172.16.10.0/24
  Known via "ospf 10", distance 110, metric 61, type intra area
  Redistributing via eigrp 200
  Advertised by eigrp 200 metric 100000 100 255 1 1500
  Last update from 100.100.100.1 on Tunnel0, 00:29:52 ago
  Routing Descriptor Blocks:
  * 100.100.100.1, from 172.16.20.1, 00:29:52 ago, via Tunnel0
    Route metric is 61, traffic share count is 1
R10#sh ip route 172.16.20.0
Routing entry for 172.16.20.0/24
  Known via "ospf 10", distance 110, metric 61, type intra area
  Redistributing via eigrp 200
  Advertised by eigrp 200 metric 100000 100 255 1 1500
  Last update from 100.100.100.1 on Tunnel0, 00:29:55 ago
  Routing Descriptor Blocks:
  * 100.100.100.1, from 172.16.20.1, 00:29:55 ago, via Tunnel0
    Route metric is 61, traffic share count is 1
R10#tr
R10#traceroute 172.16.10.1 so
R10#traceroute 172.16.10.1 source loopback 0 nu
R10#traceroute 172.16.10.1 source loopback 0 numeric
Type escape sequence to abort.
Tracing the route to 172.16.10.1
VRF info: (vrf in name/id, vrf out name/id)
  1 100.100.100.1 7 msec 3 msec 7 msec
  2 10.10.10.2 8 msec * 5 msec
R10#traceroute 172.16.20.1 source loopback 0 numeric
Type escape sequence to abort.
Tracing the route to 172.16.20.1
VRF info: (vrf in name/id, vrf out name/id)
  1 100.100.100.1 7 msec 4 msec 6 msec
  2 10.10.10.2 6 msec * 7 msec
R10#
```

# CCIE Lab Center

## On R9

```
R9#ping 172.16.10.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.10.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 4/6/7 ms
R9#ping 172.16.20.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.20.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 6/7/8 ms
R9#sh ip route
R9#sh ip route 172.16.10.0
Routing entry for 172.16.10.0/24
  Known via "ospf 10", distance 110, metric 1011, type intra area
  Redistributing via eigrp 200
  Advertised by eigrp 200 metric 1000 100 255 1 1500
  Last update from 200.200.200.2 on Tunnell, 00:11:01 ago
  Routing Descriptor Blocks:
  * 200.200.200.2, from 172.16.20.1, 00:11:01 ago, via Tunnell
    Route metric is 1011, traffic share count is 1
R9#sh ip route 172.16.20.0
Routing entry for 172.16.20.0/24
  Known via "ospf 10", distance 110, metric 1011, type intra area
  Redistributing via eigrp 200
  Advertised by eigrp 200 metric 1000 100 255 1 1500
  Last update from 200.200.200.2 on Tunnell, 00:11:05 ago
  Routing Descriptor Blocks:
  * 200.200.200.2, from 172.16.20.1, 00:11:05 ago, via Tunnell
    Route metric is 1011, traffic share count is 1
R9#trac
R9#traceroute 172.16.10.1 sou loo 0 nu
Type escape sequence to abort.
Tracing the route to 172.16.10.1
VRF info: (vrf in name/id, vrf out name/id)
  1 200.200.200.2 6 msec 7 msec 4 msec
  2 10.10.10.6 9 msec * 8 msec
R9#traceroute 172.16.20.1 sou loo 0 nu
Type escape sequence to abort.
Tracing the route to 172.16.20.1
VRF info: (vrf in name/id, vrf out name/id)
  1 200.200.200.2 7 msec 7 msec 6 msec
  2 10.10.10.6 7 msec * 5 msec
R9#
```

# CCIE Lab Center

## On R11

```
R11
Sending 5, 100-byte ICMP Echos to 172.16.10.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 3/3/5 ms
R11#ping 172.16.20.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.20.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/2/4 ms
R11#sh ip route 172.16.10.0
Routing entry for 172.16.10.0/24
  Known via "eigrp 200", distance 170, metric 307200, type external
  Redistributing via eigrp 200
  Last update from 10.10.10.41 on Ethernet0/0, 00:12:55 ago
  Routing Descriptor Blocks:
  * 10.10.10.41, from 10.10.10.41, 00:12:55 ago, via Ethernet0/0
    Route metric is 307200, traffic share count is 1
    Total delay is 2000 microseconds, minimum bandwidth is 10000 Kbit
    Reliability 255/255, minimum MTU 1500 bytes
    Loading 1/255, Hops 1
R11#sh ip route 172.16.20.0
Routing entry for 172.16.20.0/24
  Known via "eigrp 200", distance 170, metric 307200, type external
  Redistributing via eigrp 200
  Last update from 10.10.10.41 on Ethernet0/0, 00:13:02 ago
  Routing Descriptor Blocks:
  * 10.10.10.41, from 10.10.10.41, 00:13:02 ago, via Ethernet0/0
    Route metric is 307200, traffic share count is 1
    Total delay is 2000 microseconds, minimum bandwidth is 10000 Kbit
    Reliability 255/255, minimum MTU 1500 bytes
    Loading 1/255, Hops 1
R11#trac 172.16.10.1 sou loo 0 nu
^
% Invalid input detected at '^' marker.

R11#trac 172.16.10.1 nu
R11#trac 172.16.10.1 numeric
Type escape sequence to abort.
Tracing the route to 172.16.10.1
VRF info: (vrf in name/id, vrf out name/id)
  0  10.10.10.1  0  0  0  0
  1  10.10.10.41  2 msec 1 msec 1 msec
  2  100.100.100.1  4 msec 2 msec 3 msec
  3  10.10.10.2  2 msec *  4 msec
R11#
```

# CCIE Lab Center

## 7. Deployment of London Spoke site

### 7.1: Initial Configuration

#### On R12

```
interface Loopback0
ip address 1.1.1.12 255.255.255.0

interface Ethernet0/0
description *** Connected to PRI MPLS ***
ip address 192.168.100.12 255.255.255.0
ip ospf network point-to-multipoint
!
!
interface Ethernet0/2
description *** Connected to R13 ***
ip address 10.10.10.49 255.255.255.252
ip ospf network point-to-point
!
interface Ethernet0/3
description *** Connected to R14 ***
ip address 10.10.10.53 255.255.255.252
ip ospf network point-to-point
!
router ospf 10
router-id 1.1.1.12
network 1.1.1.12 0.0.0.0 area 0
network 10.10.10.48 0.0.0.3 area 0
network 10.10.10.52 0.0.0.3 area 0
network 100.100.100.0 0.0.0.255 area 0
```

# CCIE Lab Center

## 7.2: DMVPN Basic configuration

### On R12

```
crypto isakmp policy 10
  encr aes
  authentication pre-share
  group 2
crypto isakmp key clc@123 address 0.0.0.0
!
!
crypto ipsec transform-set CLC esp-aes esp-sha-hmac
  mode transport
!
crypto ipsec profile CLC
  set transform-set CLC
!
interface Tunnel0
  description *** PRI Tunnel ***
  ip address 100.100.100.12 255.255.255.0
  no ip redirects
  ip mtu 1400
  ip nhrp authentication clc@123
  ip nhrp map 100.100.100.1 192.168.100.1
  ip nhrp map multicast 192.168.100.1
  ip nhrp network-id 100
  ip nhrp nhs 100.100.100.1
  ip tcp adjust-mss 1360
  ip ospf network point-to-multipoint
  tunnel source Ethernet0/0
  tunnel mode gre multipoint
  tunnel key 100
  tunnel protection ipsec profile CLC
```

### on R13

```
interface Loopback0
  ip address 1.1.1.13 255.255.255.0

interface Ethernet0/0
  description *** Connected to PRI MPLS ***
  ip address 192.168.200.13 255.255.255.0
  ip ospf network point-to-multipoint
!
interface Ethernet0/1
  no ip address
  shutdown
```

# CCIE Lab Center

```
!  
interface Ethernet0/2  
description *** Connected to R12 ***  
ip address 10.10.10.50 255.255.255.252  
ip ospf network point-to-point  
!  
interface Ethernet0/3  
description *** Connected to R15 ***  
ip address 10.10.10.57 255.255.255.252  
ip ospf network point-to-point  
!  
router ospf 10  
router-id 1.1.1.13  
network 1.1.1.13 0.0.0.0 area 0  
network 10.10.10.48 0.0.0.3 area 0  
network 10.10.10.56 0.0.0.3 area 0  
network 50.50.50.20 0.0.0.3 area 0  
network 200.200.200.0 0.0.0.255 area 0
```

# CCIE Lab Center

## 7.3: DMVPN Basic configuration

### On R13

```
crypto isakmp policy 10
  encr aes
  authentication pre-share
  group 2
crypto isakmp key clc@123 address 0.0.0.0
!
!
crypto ipsec transform-set CLC esp-aes esp-sha-hmac
  mode transport
!
crypto ipsec profile CLC
  set transform-set CLC
!
interface Loopback0
  ip address 1.1.1.13 255.255.255.0
!
interface Tunnel1
  description *** SEC Tunnel ***
  ip address 200.200.200.13 255.255.255.0
  no ip redirects
  ip mtu 1400
  ip nhrp authentication clc@123
  ip nhrp map 200.200.200.2 192.168.200.2
  ip nhrp map multicast 192.168.200.2
  ip nhrp network-id 200
  ip nhrp nhs 200.200.200.2
  ip tcp adjust-mss 1360
  ip ospf network point-to-multipoint
  ip ospf dead-interval 4
  ip ospf hello-interval 1
  tunnel source Ethernet0/0
  tunnel mode gre multipoint
  tunnel key 200
  tunnel protection ipsec profile CLC
```

### On R14

```
interface Ethernet0/0
  description *** Connected to R12 ***
  ip address 10.10.10.54 255.255.255.252
  ip ospf network point-to-point
!
interface Ethernet0/1
  description *** Connected to R16 ***
  ip address 10.10.10.65 255.255.255.252
```

# CCIE Lab Center

```
ip ospf network point-to-point
!
```

```
router ospf 10
network 10.10.10.52 0.0.0.3 area 0
network 10.10.10.64 0.0.0.3 area 1
```

## On R16

```
interface Loopback10
ip address 172.16.110.1 255.255.255.0
ip ospf network point-to-point
!
interface Loopback20
ip address 172.16.120.1 255.255.255.0
ip ospf network point-to-point
!
interface Ethernet0/0
description *** Connected to R15 ***
ip address 10.10.10.62 255.255.255.252
ip ospf network point-to-point
!
interface Ethernet0/1
description *** Connected to R14 ***
ip address 10.10.10.66 255.255.255.252
ip ospf network point-to-point
!
!
router ospf 10
network 10.10.10.60 0.0.0.3 area 1
network 10.10.10.64 0.0.0.3 area 1
network 172.16.110.0 0.0.0.255 area 1
network 172.16.120.0 0.0.0.255 area 1
```

## On R15

```
interface Ethernet0/0
description *** COnnected to R13 ***
ip address 10.10.10.58 255.255.255.252
ip ospf network point-to-point
!
interface Ethernet0/1
description *** COnnected to R16 ***
ip address 10.10.10.61 255.255.255.252
ip ospf network point-to-point
!
interface Ethernet0/2
no ip address
shutdown
```

# CCIE Lab Center

```
!  
interface Ethernet0/3  
no ip address  
shutdown  
!  
router ospf 10  
network 10.10.10.56 0.0.0.3 area 0  
network 10.10.10.60 0.0.0.3 area 1
```

## Verification

On R12

```
R12>en  
R12#ping 172.16.10.1  
Type escape sequence to abort.  
Sending 5, 100-byte ICMP Echos to 172.16.10.1, timeout is 2 seconds:  
!!!!  
Success rate is 100 percent (5/5), round-trip min/avg/max = 7/7/8 ms  
R12#ping 172.16.20.1  
Type escape sequence to abort.  
Sending 5, 100-byte ICMP Echos to 172.16.20.1, timeout is 2 seconds:  
!!!!  
Success rate is 100 percent (5/5), round-trip min/avg/max = 7/7/8 ms  
R12#sh ip route  
R12#sh ip route 172.16.10.0  
Routing entry for 172.16.10.0/24  
  Known via "ospf 10", distance 110, metric 1011, type intra area  
  Last update from 100.100.100.1 on Tunnel0, 02:38:39 ago  
  Routing Descriptor Blocks:  
    * 100.100.100.1, from 172.16.20.1, 02:38:39 ago, via Tunnel0  
      Route metric is 1011, traffic share count is 1  
R12#sh ip route 172.16.20.0  
Routing entry for 172.16.20.0/24  
  Known via "ospf 10", distance 110, metric 1011, type intra area  
  Last update from 100.100.100.1 on Tunnel0, 02:38:42 ago  
  Routing Descriptor Blocks:  
    * 100.100.100.1, from 172.16.20.1, 02:38:42 ago, via Tunnel0  
      Route metric is 1011, traffic share count is 1  
R12#trac 172.16.10.1 sou loo 0 nu  
Type escape sequence to abort.  
Tracing the route to 172.16.10.1  
VRF info: (vrf in name/id, vrf out name/id)  
  1 100.100.100.1 7 msec 7 msec 6 msec  
  2 10.10.10.2 8 msec * 7 msec  
R12#trac 172.16.20.1 sou loo 0 nu  
Type escape sequence to abort.  
Tracing the route to 172.16.20.1  
VRF info: (vrf in name/id, vrf out name/id)  
  1 100.100.100.1 7 msec 6 msec 7 msec  
  2 10.10.10.2 5 msec * 7 msec  
R12#
```

# CCIE Lab Center

## On R13

```
R13
Success rate is 100 percent (5/5), round-trip min/avg/max = 6/7/8 ms
R13#ping 172.16.20.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.20.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 7/7/7 ms
R13#sh ip route
R13#sh ip route 172.16.10.0
Routing entry for 172.16.10.0/24
  Known via "ospf 10", distance 110, metric 1011, type intra area
  Last update from 200.200.200.2 on Tunnel1, 00:13:47 ago
  Routing Descriptor Blocks:
    * 200.200.200.2, from 172.16.20.1, 00:13:47 ago, via Tunnel1
      Route metric is 1011, traffic share count is 1
R13#sh ip route 172.16.20.0
Routing entry for 172.16.20.0/24
  Known via "ospf 10", distance 110, metric 1011, type intra area
  Last update from 200.200.200.2 on Tunnel1, 00:13:50 ago
  Routing Descriptor Blocks:
    * 200.200.200.2, from 172.16.20.1, 00:13:50 ago, via Tunnel1
      Route metric is 1011, traffic share count is 1
R13#trace 172.16.10.1 sou loo 0 nu
Type escape sequence to abort.
Tracing the route to 172.16.10.1
VRF info: (vrf in name/id, vrf out name/id)
  1 200.200.200.2 7 msec 6 msec 7 msec
  2 10.10.10.6 7 msec * 8 msec
R13#trace 172.16.10.2 sou loo 0 nu
Type escape sequence to abort.
Tracing the route to 172.16.10.2
VRF info: (vrf in name/id, vrf out name/id)
  1 200.200.200.2 7 msec 7 msec 7 msec
  2 10.10.10.6 7 msec 7 msec 6 msec
  3 * * *
  4 *
R13#
R13#trace 172.16.20.1 sou loo 0 nu
Type escape sequence to abort.
Tracing the route to 172.16.20.1
VRF info: (vrf in name/id, vrf out name/id)
  1 200.200.200.2 6 msec 6 msec 7 msec
  2 10.10.10.6 6 msec * 8 msec
R13#
```

# CCIE Lab Center

On R16

Make PRI MPLS as preferred Secondary MPLS

```

R16#ping 172.16.10.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.10.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 2/3/5 ms
R16#ping 172.16.20.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.20.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 2/3/5 ms
R16#sh ip route
R16#sh ip route 172.16.10.0
Routing entry for 172.16.10.0/24
  Known via "ospf 10", distance 110, metric 1031, type inter area
  Last update from 10.10.10.65 on Ethernet0/1, 02:41:42 ago
  Routing Descriptor Blocks:
    10.10.10.65, from 10.10.10.65, 02:41:42 ago, via Ethernet0/1
      Route metric is 1031, traffic share count is 1
    * 10.10.10.61, from 10.10.10.61, 10:16:46 ago, via Ethernet0/0
      Route metric is 1031, traffic share count is 1
R16#sh ip route 172.16.20.0
Routing entry for 172.16.20.0/24
  Known via "ospf 10", distance 110, metric 1031, type inter area
  Last update from 10.10.10.65 on Ethernet0/1, 02:41:46 ago
  Routing Descriptor Blocks:
    10.10.10.65, from 10.10.10.65, 02:41:46 ago, via Ethernet0/1
      Route metric is 1031, traffic share count is 1
    * 10.10.10.61, from 10.10.10.61, 10:16:50 ago, via Ethernet0/0
      Route metric is 1031, traffic share count is 1

```

Configuring ip ospf cost 50 on Tunnel0 at R12 router

Interface tunnel 0

Configuring ip ospf cost 50

```

Route metric is 1031, traffic share count is 1
R16#sh ip route 172.16.20.0
Routing entry for 172.16.20.0/24
  Known via "ospf 10", distance 110, metric 81, type inter area
  Last update from 10.10.10.65 on Ethernet0/1, 00:00:00 ago
  Routing Descriptor Blocks:
    * 10.10.10.65, from 10.10.10.65, 00:00:00 ago, via Ethernet0/1
      Route metric is 81, traffic share count is 1
R16#sh ip route 172.16.20.0
Routing entry for 172.16.20.0/24
  Known via "ospf 10", distance 110, metric 81, type inter area
  Last update from 10.10.10.65 on Ethernet0/1, 00:00:02 ago
  Routing Descriptor Blocks:
    * 10.10.10.65, from 10.10.10.65, 00:00:02 ago, via Ethernet0/1
      Route metric is 81, traffic share count is 1
R16#

```

Now its preferred

# CCIE Lab Center

R16>R14>R12

```
R16#traceroute 172.16.10.1 numeric
Type escape sequence to abort.
Tracing the route to 172.16.10.1
VRF info: (vrf in name/id, vrf out name/id)
 1 10.10.10.65 2 msec 1 msec 1 msec
 2 10.10.10.53 1 msec 2 msec 1 msec
 3 100.100.100.1 3 msec 3 msec 3 msec
 4 10.10.10.2 3 msec * 4 msec
R16#traceroute 172.16.20.1 numeric
Type escape sequence to abort.
Tracing the route to 172.16.20.1
VRF info: (vrf in name/id, vrf out name/id)
 1 10.10.10.65 1 msec 1 msec 1 msec
 2 10.10.10.53 2 msec 1 msec 1 msec
 3 100.100.100.1 3 msec 2 msec 2 msec
 4 10.10.10.2 17 msec * 5 msec
R16#
```

# CCIE Lab Center

## 8. Configuring DMVPN Phase3 in all Hubs & Spokes

Configure DMVPN Hub to redirect NHRP requests for spoke-to-spoke resolutions.

### 8.1: Phase3 Configuration on R1 & R2 (Hubs)

#### On R1

```
interface Tunnel0  
ip nhrp redirect
```

#### On R2

```
interface Tunnel1  
ip nhrp redirect
```

# CCIE Lab Center

## 8.2: Phase3 Configuration on R18,R3,4,6,7,9,10,12 & 13 (Spokes)

Configure the DMVPN Spokes to be able to install NHRP shortcut routes for spoke-to-spoke routing.

### On R18

```
interface Tunnel0  
ip nhrp shortcut
```

### on R2

```
interface Tunnel1  
ip nhrp shortcut
```

### on R3

```
interface Tunnel0  
ip nhrp shortcut
```

### on R4

```
interface Tunnel1  
ip nhrp shortcut
```

### on R6

```
interface Tunnel0  
ip nhrp shortcut
```

### on R7

```
interface Tunnel1  
ip nhrp shortcut
```

### on R12

```
interface Tunnel0  
ip nhrp shortcut
```

### on R13

```
interface Tunnel1  
ip nhrp shortcut
```

# CCIE Lab Center

## 8.3: Verification of DMVPN Phase3

On R18

Task

Ping 172.16.110.1,120.1 & check traceroute

```
Oct 26 09:55:29.562: %SYS-5-CONFIG_I: Configured from console by console
R18#ping 172.16.110.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.110.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 8/9/10 ms
R18#tr
R18#traceroute 172.16.110.1 nu
R18#traceroute 172.16.110.1 numeric
Type escape sequence to abort.
Tracing the route to 172.16.110.1
VRF info: (vrf in name/id, vrf out name/id)
  1 100.100.100.12 7 msec 7 msec 7 msec
  2 10.10.10.54 8 msec 7 msec 8 msec
  3 10.10.10.66 9 msec * 8 msec
R18#traceroute 172.16.110.1 numeric
Type escape sequence to abort.
Tracing the route to 172.16.110.1
VRF info: (vrf in name/id, vrf out name/id)
  1 100.100.100.12 7 msec 8 msec 8 msec
  2 10.10.10.54 8 msec 8 msec 9 msec
  3 10.10.10.66 8 msec * 6 msec
R18#
```

1<sup>st</sup> time its goes via hub & 2<sup>nd</sup> time its goes to spoke directly

# CCIE Lab Center

```

R18#sh dmvpn
Legend: Attrb --> S - Static, D - Dynamic, I - Incomplete
        N - NATed, L - Local, X - No Socket
        T1 - Route Installed, T2 - Nexthop-override
        C - CTS Capable
        # Ent --> Number of NHRP entries with same NBMA peer
        NHS Status: E --> Expecting Replies, R --> Responding, W --> Waiting
        UpDn Time --> Up or Down Time for a Tunnel
=====

Interface: Tunnel0, IPv4 NHRP Details
Type:Spoke, NHRP Peers:2,

# Ent Peer NBMA Addr Peer Tunnel Add State UpDn Tm Attrb
-----
  1 192.168.100.1    100.100.100.1    UP   1d02h    S
  2 192.168.100.12  100.100.100.12  UP 00:01:33 DT2
                                100.100.100.12  UP 00:01:33 DT2

Interface: Tunnell1, IPv4 NHRP Details
Type:Spoke, NHRP Peers:1,

# Ent Peer NBMA Addr Peer Tunnel Add State UpDn Tm Attrb
-----
  1 192.168.200.2    200.200.200.2    UP   1d02h    S

R18#

```

All traffic is going to PRI DMVPN

```

R18#traceroute 172.16.110.1 source loopback 0 nu
R18#traceroute 172.16.110.1 source loopback 0 numeric
Type escape sequence to abort.
Tracing the route to 172.16.110.1
VRF info: (vrf in name/id, vrf out name/id)
  1 100.100.100.12 7 msec 8 msec 7 msec
  2 10.10.10.54 8 msec 8 msec 8 msec
  3 10.10.10.66 9 msec * 9 msec
R18#

```

On R1

```

R1#sh dmvpn
Legend: Attrb --> S - Static, D - Dynamic, I - Incomplete
        N - NATed, L - Local, X - No Socket
        T1 - Route Installed, T2 - Nexthop-override
        C - CTS Capable
        # Ent --> Number of NHRP entries with same NBMA peer
        NHS Status: E --> Expecting Replies, R --> Responding, W --> Waiting
        UpDn Time --> Up or Down Time for a Tunnel
=====

Interface: Tunnel0, IPv4 NHRP Details
Type:Hub, NHRP Peers:5,

# Ent Peer NBMA Addr Peer Tunnel Add State UpDn Tm Attrb
-----
  1 192.168.100.3    100.100.100.3    UP   1d02h    D
  1 192.168.100.6    100.100.100.6    UP   1d02h    D
  1 192.168.100.10   100.100.100.10   UP   1d02h    D
  1 192.168.100.12   100.100.100.12   UP   1d02h    D
  1 192.168.100.18   100.100.100.18   UP   1d02h    D

R1#

```

# CCIE Lab Center

Lets check route % - next hop override

```
R18#sh ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
       a - application route
       + - replicated route, % - next hop override

Gateway of last resort is not set


  1.0.0.0/8 is variably subnetted, 11 subnets, 2 masks
  C    1.1.1.0/24 is directly connected, Loopback0
  O    1.1.1.1/32 [110/51] via 100.100.100.1, 19:00:18, Tunnel0
  O    1.1.1.2/32 [110/61] via 100.100.100.1, 19:00:18, Tunnel0
  O    1.1.1.4/32 [110/62] via 100.100.100.1, 19:00:18, Tunnel0
  O    1.1.1.6/32 [110/52] via 100.100.100.1, 19:00:18, Tunnel0
  O    1.1.1.7/32 [110/62] via 100.100.100.1, 19:00:18, Tunnel0
  O    1.1.1.9/32 [110/62] via 100.100.100.1, 18:38:23, Tunnel0
  O IA 1.1.1.10/32 [110/52] via 100.100.100.1, 18:59:03, Tunnel0
  O    1.1.1.12/32 [110/52] via 100.100.100.1, 18:58:41, Tunnel0
  O    1.1.1.13/32 [110/62] via 100.100.100.1, 19:00:18, Tunnel0
  L    1.1.1.18/32 is directly connected, Loopback0
  10.0.0.0/8 is variably subnetted, 17 subnets, 2 masks
  O    10.10.10.0/30 [110/60] via 100.100.100.1, 19:00:18, Tunnel0
  O    10.10.10.4/30 [110/70] via 100.100.100.1, 19:00:18, Tunnel0
  O    10.10.10.8/30 [110/60] via 100.100.100.1, 19:00:18, Tunnel0
  C    10.10.10.12/30 is directly connected, Ethernet0/2
  L    10.10.10.13/32 is directly connected, Ethernet0/2
  O E2 10.10.10.20/30 [110/20] via 100.100.100.1, 19:00:18, Tunnel0
  O E2 10.10.10.24/30 [110/50] via 100.100.100.1, 19:00:18, Tunnel0
  O E2 10.10.10.28/30 [110/50] via 100.100.100.1, 19:00:18, Tunnel0
  O E2 10.10.10.32/30 [110/50] via 100.100.100.1, 19:00:18, Tunnel0
  O E2 10.10.10.36/30 [110/50] via 100.100.100.1, 18:59:03, Tunnel0
  O E2 10.10.10.40/30 [110/50] via 100.100.100.1, 18:59:03, Tunnel0
  O E2 10.10.10.44/30 [110/50] via 100.100.100.1, 18:59:03, Tunnel0
  O    10.10.10.48/30 [110/61] via 100.100.100.1, 18:58:41, Tunnel0
```

# CCIE Lab Center

```

C 100.100.100.0/24 is directly connected, Tunnel0
O 100.100.100.1/32 [110/50] via 100.100.100.1, 19:00:18, Tunnel0
O 100.100.100.6/32 [110/51] via 100.100.100.1, 19:00:18, Tunnel0
O 100.100.100.10/32 [110/51] via 100.100.100.1, 18:59:03, Tunnel0
O % 100.100.100.12/32 [110/51] via 100.100.100.1, 18:58:41, Tunnel0
L 100.100.100.18/32 is directly connected, Tunnel0
172.16.0.0/24 is subnetted, 12 subnets
O 172.16.10.0 [110/61] via 100.100.100.1, 19:00:18, Tunnel0
O 172.16.20.0 [110/61] via 100.100.100.1, 19:00:18, Tunnel0
R 172.16.30.0 [120/1] via 10.10.10.14, 00:00:01, Ethernet0/2
R 172.16.40.0 [120/1] via 10.10.10.14, 00:00:01, Ethernet0/2
O E2 172.16.50.0 [110/20] via 100.100.100.1, 19:00:18, Tunnel0
O E2 172.16.60.0 [110/20] via 100.100.100.1, 19:00:18, Tunnel0
O E2 172.16.70.0 [110/50] via 100.100.100.1, 19:00:18, Tunnel0
O E2 172.16.80.0 [110/50] via 100.100.100.1, 19:00:18, Tunnel0
O E2 172.16.90.0 [110/50] via 100.100.100.1, 18:35:30, Tunnel0
O E2 172.16.100.0 [110/50] via 100.100.100.1, 18:35:22, Tunnel0
O IA% 172.16.110.0 [110/72] via 100.100.100.1, 18:58:41, Tunnel0
O IA 172.16.120.0 [110/72] via 100.100.100.1, 18:58:41, Tunnel0
192.168.100.0/24 is variably subnetted, 2 subnets, 2 masks
C 192.168.100.0/24 is directly connected, Ethernet0/0
L 192.168.100.18/32 is directly connected, Ethernet0/0
192.168.200.0/24 is variably subnetted, 2 subnets, 2 masks
C 192.168.200.0/24 is directly connected, Ethernet0/1
L 192.168.200.18/32 is directly connected, Ethernet0/1
200.200.200.0/24 is variably subnetted, 7 subnets, 2 masks
C 200.200.200.0/24 is directly connected, Tunnel1
O 200.200.200.2/32 [110/60] via 100.100.100.1, 19:00:18, Tunnel0
O 200.200.200.4/32 [110/61] via 100.100.100.1, 19:00:18, Tunnel0
O 200.200.200.7/32 [110/61] via 100.100.100.1, 19:00:18, Tunnel0
O 200.200.200.9/32 [110/61] via 100.100.100.1, 18:38:23, Tunnel0
O 200.200.200.13/32 [110/61] via 100.100.100.1, 19:00:18, Tunnel0
L 200.200.200.18/32 is directly connected, Tunnel1
R18#
R18#
R18#
    
```

Let's do the failover suspending PRI tunnel 0



# CCIE Lab Center

```

R18#
R18#ping 172.16.110.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.110.1, timeout is 2 seconds:
.
*Oct 26 09:47:27.610: %LINK-3-UPDOWN: Interface Ethernet0/0, changed state to down.
*Oct 26 09:47:28.610: %LINEPROTO-5-UPDOWN: Line protocol on Interface Ethernet0/0, changed state to down...
Success rate is 0 percent (0/5)
R18#
*Oct 26 09:47:34.617: %LINEPROTO-5-UPDOWN: Line protocol on Interface Tunnel0, changed state to down
*Oct 26 09:47:34.618: %OSPF-5-ADJCHG: Process 10, Nbr 1.1.1.1 on Tunnel0 from FULL to DOWN, Neighbor Down: Interface down or detached
R18#ping 172.16.110.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.110.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 7/8/10 ms
R18#tr
R18#traceroute 172.16.110.1 sou
R18#traceroute 172.16.110.1 source loo
R18#traceroute 172.16.110.1 source loopback 0 nu
R18#traceroute 172.16.110.1 source loopback 0 numeric
Type escape sequence to abort.
Tracing the route to 172.16.110.1
VRF info: (vrf in name/id, vrf out name/id)
 0  1 200.200.200.2 7 msec 7 msec 7 msec
 1  2 200.200.200.13 10 msec 9 msec 8 msec
 2  3 10.10.10.50 9 msec 9 msec 4 msec
 3  4 10.10.10.62 10 msec * 13 msec

```

Now it's going to SEC DMVPN path.

On R2

```

R2#sh dm
R2#sh dmvpn
Legend: Attrb --> S - Static, D - Dynamic, I - Incomplete
         N - NATed, L - Local, X - No Socket
         T1 - Route Installed, T2 - Nexthop-override
         C - CTS Capable
# Ent --> Number of NHRP entries with same NBMA peer
NHS Status: E --> Expecting Replies, R --> Responding, W --> Waiting
UpDn Time --> Up or Down Time for a Tunnel
-----

Interface: Tunnel1, IPv4 NHRP Details
Type:Hub, NHRP Peers:5,

# Ent Peer NBMA Addr Peer Tunnel Add State UpDn Tm Attrb
-----
 1 192.168.200.4 200.200.200.4 UP 1d02h D
 1 192.168.200.7 200.200.200.7 UP 1d02h D
 1 192.168.200.9 200.200.200.9 UP 1d02h D
 1 192.168.200.13 200.200.200.13 UP 1d02h D
 1 192.168.200.18 200.200.200.18 UP 1d02h D

R2#

```

# CCIE Lab Center

On R3

```

R3#tracert 172.16.90.1 numeric
Type escape sequence to abort.
Tracing the route to 172.16.90.1
VRF info: (vrf in name/id, vrf out name/id)
  1 100.100.100.1 7 msec 7 msec 7 msec
  2 100.100.100.10 9 msec 8 msec 9 msec
  3 10.10.10.42 9 msec * 6 msec
R3#tracert 172.16.90.1 numeric
Type escape sequence to abort.
Tracing the route to 172.16.90.1
VRF info: (vrf in name/id, vrf out name/id)
  1 100.100.100.10 8 msec 7 msec 8 msec
  2 10.10.10.42 7 msec * 9 msec
R3#
  
```

Next hop override

```

R3#sh ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route, H - NHRP, L - LISP
       a - application route
       + - replicated route, % - next hop override

Gateway of last resort is not set

1.0.0.0/8 is variably subnetted, 12 subnets, 2 masks
C       1.1.1.0/24 is directly connected, Loopback0
O       1.1.1.1/32 [110/51] via 100.100.100.1, 00:05:01, Tunnel0
O       1.1.1.2/32 [110/61] via 100.100.100.1, 00:05:01, Tunnel0
L       1.1.1.3/32 is directly connected, Loopback0
O       1.1.1.4/32 [110/62] via 100.100.100.1, 00:05:01, Tunnel0
O       1.1.1.6/32 [110/52] via 100.100.100.1, 00:05:01, Tunnel0
O       1.1.1.7/32 [110/62] via 100.100.100.1, 00:05:01, Tunnel0
O       1.1.1.9/32 [110/62] via 100.100.100.1, 00:05:01, Tunnel0
O IA    1.1.1.10/32 [110/52] via 100.100.100.1, 00:05:01, Tunnel0
O       1.1.1.12/32 [110/52] via 100.100.100.1, 00:05:01, Tunnel0
O       1.1.1.13/32 [110/62] via 100.100.100.1, 00:05:01, Tunnel0
O       1.1.1.18/32 [110/52] via 100.100.100.1, 00:05:01, Tunnel0
10.0.0.0/8 is variably subnetted, 18 subnets, 2 masks
O       10.10.10.0/30 [110/60] via 100.100.100.1, 00:05:01, Tunnel0
O       10.10.10.4/30 [110/70] via 100.100.100.1, 00:05:01, Tunnel0
O       10.10.10.8/30 [110/60] via 100.100.100.1, 00:05:01, Tunnel0
O E2    10.10.10.12/30 [110/20] via 100.100.100.1, 00:05:01, Tunnel0
C       10.10.10.16/30 is directly connected, Ethernet0/3
L       10.10.10.17/32 is directly connected, Ethernet0/3
O E2    10.10.10.20/30 [110/20] via 100.100.100.1, 00:05:01, Tunnel0
O E2    10.10.10.24/30 [110/50] via 100.100.100.1, 00:05:01, Tunnel0
O E2    10.10.10.28/30 [110/50] via 100.100.100.1, 00:05:01, Tunnel0
O E2    10.10.10.32/30 [110/50] via 100.100.100.1, 00:05:01, Tunnel0
O E2    10.10.10.36/30 [110/50] via 100.100.100.1, 00:05:01, Tunnel0
O E2    10.10.10.40/30 [110/50] via 100.100.100.1, 00:05:01, Tunnel0
O E2    10.10.10.44/30 [110/50] via 100.100.100.1, 00:05:01, Tunnel0
O       10.10.10.48/30 [110/61] via 100.100.100.1, 00:05:01, Tunnel0
O       10.10.10.52/30 [110/61] via 100.100.100.1, 00:05:01, Tunnel0
  
```

# CCIE Lab Center

```

O E2 10.10.10.24/30 [110/50] via 100.100.100.1, 00:05:01, Tunnel0
O E2 10.10.10.28/30 [110/50] via 100.100.100.1, 00:05:01, Tunnel0
O E2 10.10.10.32/30 [110/50] via 100.100.100.1, 00:05:01, Tunnel0
O E2 10.10.10.36/30 [110/50] via 100.100.100.1, 00:05:01, Tunnel0
O E2 10.10.10.40/30 [110/50] via 100.100.100.1, 00:05:01, Tunnel0
O E2 10.10.10.44/30 [110/50] via 100.100.100.1, 00:05:01, Tunnel0
O 10.10.10.48/30 [110/61] via 100.100.100.1, 00:05:01, Tunnel0
O 10.10.10.52/30 [110/61] via 100.100.100.1, 00:05:01, Tunnel0
O 10.10.10.56/30 [110/71] via 100.100.100.1, 00:05:01, Tunnel0
O IA 10.10.10.60/30 [110/81] via 100.100.100.1, 00:05:01, Tunnel0
O IA 10.10.10.64/30 [110/71] via 100.100.100.1, 00:05:01, Tunnel0
100.0.0.0/8 is variably subnetted, 7 subnets, 2 masks
C 100.100.100.0/24 is directly connected, Tunnel0
O 100.100.100.1/32 [110/50] via 100.100.100.1, 00:05:01, Tunnel0
L 100.100.100.3/32 is directly connected, Tunnel0
O 100.100.100.6/32 [110/51] via 100.100.100.1, 00:05:01, Tunnel0
O % 100.100.100.10/32 [110/51] via 100.100.100.1, 00:05:01, Tunnel0
O 100.100.100.12/32 [110/51] via 100.100.100.1, 00:05:01, Tunnel0
O 100.100.100.18/32 [110/51] via 100.100.100.1, 00:05:01, Tunnel0
172.16.0.0/24 is subnetted, 12 subnets
O 172.16.10.0 [110/61] via 100.100.100.1, 00:05:01, Tunnel0
O 172.16.20.0 [110/61] via 100.100.100.1, 00:05:01, Tunnel0
O E2 172.16.30.0 [110/20] via 100.100.100.1, 00:05:01, Tunnel0
O E2 172.16.40.0 [110/20] via 100.100.100.1, 00:05:01, Tunnel0
S 172.16.50.0 [1/0] via 10.10.10.18
S 172.16.60.0 [1/0] via 10.10.10.18
O E2 172.16.70.0 [110/50] via 100.100.100.1, 00:05:01, Tunnel0
O E2 172.16.80.0 [110/50] via 100.100.100.1, 00:05:01, Tunnel0
O E2% 172.16.90.0 [110/50] via 100.100.100.1, 00:05:01, Tunnel0
O E2 172.16.100.0 [110/50] via 100.100.100.1, 00:05:01, Tunnel0
O IA 172.16.110.0 [110/72] via 100.100.100.1, 00:05:01, Tunnel0
O IA 172.16.120.0 [110/72] via 100.100.100.1, 00:05:01, Tunnel0
192.168.100.0/24 is variably subnetted, 2 subnets, 2 masks
C 192.168.100.0/24 is directly connected, Ethernet0/0
L 192.168.100.3/32 is directly connected, Ethernet0/0
--More--

```

```

R3#sh dm
R3#sh dmvpn
Legend: Attrb --> S - Static, D - Dynamic, I - Incomplete
N - NATed, L - Local, X - No Socket
T1 - Route Installed, T2 - Nexthop-override
C - CTS Capable
# Ent --> Number of NHRP entries with same NBMA peer
NHS Status: E --> Expecting Replies, R --> Responding, W --> Waiting
UpDn Time --> Up or Down Time for a Tunnel
=====
Interface: Tunnel0, IPv4 NHRP Details
Type:Spoke, NHRP Peers:2,

# Ent Peer NBMA Addr Peer Tunnel Add State UpDn Tm Attrb
-----
1 192.168.100.1 100.100.100.1 UP 00:02:49 S
2 192.168.100.10 100.100.100.10 UP 00:03:11 DT2
100.100.100.10 UP 00:03:11 DT2

R3#
R3#
R3#
R3#

```


# CCIE Lab Center

On R1

```

R1#sh ip nh
R1#sh ip nhrp
100.100.100.3/32 via 100.100.100.3
  Tunnel0 created 00:00:06, expire 01:59:53
  Type: dynamic, Flags: unique registered used nhop
  NBMA address: 192.168.100.3
100.100.100.6/32 via 100.100.100.6
  Tunnel0 created 00:00:05, expire 01:59:54
  Type: dynamic, Flags: unique registered used nhop
  NBMA address: 192.168.100.6
100.100.100.10/32 via 100.100.100.10
  Tunnel0 created 00:00:05, expire 01:59:54
  Type: dynamic, Flags: unique registered used nhop
  NBMA address: 192.168.100.10
100.100.100.12/32 via 100.100.100.12
  Tunnel0 created 00:00:05, expire 01:59:54
  Type: dynamic, Flags: unique registered used nhop
  NBMA address: 192.168.100.12
100.100.100.18/32 via 100.100.100.18
  Tunnel0 created 00:00:05, expire 01:59:54
  Type: dynamic, Flags: unique registered used nhop
  NBMA address: 192.168.100.18
R1#
    
```

Let's check failover on R5



# CCIE Lab Center

```

R5#sh ip sla su
R5#sh ip sla summary
IPSLAs Latest Operation Summary
Codes: * active, ^ inactive, ~ pending

ID          Type          Destination    Stats      Return      Last
-----          -----          -----          (ms)      Code        Run
-----          -----          -----          -----          -----          -----
*1          icmp-echo     100.100.100.1  RTT=4     Over thresh 2 seconds ago
                                         old

R5#

```

After suspending PRI tunnel 0

```

R5#ping 172.16.90.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.90.1, timeout is 2 seconds:
....!
Success rate is 20 percent (1/5), round-trip min/avg/max = 6/6/6 ms
R5#
*Oct 26 15:20:06.055: %TRACK-6-STATE: 1 ip sla 1 reachability Up -> Down
R5#ping 172.16.90.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.90.1, timeout is 2 seconds:
!!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 4/5/8 ms
R5#sh ip route 172.16.90.0
% Subnet not in table
R5#sh ip route
R5#sh ip route 0.0.0.0
Routing entry for 0.0.0.0/0, supernet
  Known via "static", distance 10, metric 0, candidate default path
  Routing Descriptor Blocks:
  * 10.10.10.21
    Route metric is 0, traffic share count is 1
R5#

```

```

R5#traceroute 172.16.90.1 nu
R5#traceroute 172.16.90.1 numeric
Type escape sequence to abort.
Tracing the route to 172.16.90.1
VRF info: (vrf in name/id, vrf out name/id)
 0  10.10.10.21 1 msec 1 msec 1 msec
 1  200.200.200.2 3 msec 2 msec 2 msec
 2  10.10.10.9 3 msec 3 msec 3 msec
 3  100.100.100.10 6 msec 5 msec 5 msec
 4  10.10.10.42 4 msec * 7 msec
R5#

```

# CCIE Lab Center

Let's enable PRI Tunnel 0

```
R5#traceroute 172.16.90.1 numeric
Type escape sequence to abort.
Tracing the route to 172.16.90.1
VRF info: (vrf in name/id, vrf out name/id)
 1 10.10.10.17 1 msec 1 msec 0 msec
 2 100.100.100.1 3 msec 3 msec 2 msec
 3 100.100.100.10 4 msec 3 msec 4 msec
 4 10.10.10.42 4 msec * 6 msec
```

On R4

```
R4#
R4#ping 172.16.90.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.90.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 9/10/11 ms
R4#sh ip route
R4#sh ip route 172.16.90.1 nu
R4#sh ip route 172.16.90.1 nu
R4#sh ip route 172.16.90.1
Routing entry for 172.16.90.0/24
  Known via "ospf 10", distance 110, metric 50, type extern 2, forward metric 1011
  Last update from 200.200.200.2 on Tunnel1, 1d00h ago
  Routing Descriptor Blocks:
  * 200.200.200.2, from 1.1.1.10, 1d00h ago, via Tunnel1
    Route metric is 50, traffic share count is 1
R4#trace 172.16.90.1 sou
R4#trace 172.16.90.1 source loo 0 nu
Type escape sequence to abort.
Tracing the route to 172.16.90.1
VRF info: (vrf in name/id, vrf out name/id)
 1 200.200.200.2 7 msec 6 msec 6 msec
 2 10.10.10.9 7 msec 6 msec 5 msec
 3 100.100.100.10 8 msec 8 msec 8 msec
 4 10.10.10.42 9 msec * 10 msec
R4#
```


# CCIE Lab Center

On R6

```

R6#ping 172.16.110.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.110.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 10/10/11 ms
R6#tra
R6#traceroute 172.16.110.1 so loo 0 nu
Type escape sequence to abort.
Tracing the route to 172.16.110.1
VRF info: (vrf in name/id, vrf out name/id)
 0 100.100.100.12 7 msec 6 msec 8 msec
 1 100.100.100.12 7 msec 6 msec 8 msec
 2 10.10.10.54 7 msec 7 msec 8 msec
 3 10.10.10.66 8 msec * 9 msec
R6#cle
R6#clear ip ng
R6#clear ip n
R6#clear ip nh
R6#clear ip nhrp
R6#traceroute 172.16.110.1 so loo 0 nu
Type escape sequence to abort.
Tracing the route to 172.16.110.1
VRF info: (vrf in name/id, vrf out name/id)
 0 100.100.100.1 7 msec 7 msec 6 msec
 1 100.100.100.12 12 msec 7 msec 7 msec
 2 100.100.100.12 12 msec 7 msec 7 msec
 3 10.10.10.54 6 msec 13 msec 16 msec
 4 10.10.10.66 8 msec * 10 msec
R6#traceroute 172.16.110.1 so loo 0 nu
Type escape sequence to abort.
Tracing the route to 172.16.110.1
VRF info: (vrf in name/id, vrf out name/id)
 0 100.100.100.12 8 msec 7 msec 8 msec
 1 100.100.100.12 8 msec 7 msec 8 msec
 2 10.10.10.54 8 msec 8 msec 7 msec
 3 10.10.10.66 8 msec * 9 msec
R6#
    
```

Let's do failover test, suspend PRI Tunnel 0 on R6



# CCIE Lab Center

```

Sending 5, 100-byte ICMP Echos to 172.16.110.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 6/6/7 ms
R6#ping 172.16.110.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.110.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 8/8/9 ms
R6#ping 172.16.110.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.110.1, timeout is 2 seconds:
*Oct 26 15:34:59.456: %LINK-3-UPDOWN: Interface Ethernet0/0, changed state to down
*Oct 26 15:34:59.465: %ADJ-5-PARENT: Midchain parent maintenance for IP midchain out of
Tunnel0, addr 100.100.100.1 - looped chain attempting to stack
*Oct 26 15:35:00.457: %LINEPROTO-5-UPDOWN: Line protocol on Interface Ethernet0/0, cha
nged state to down..
*Oct 26 15:35:03.867: %LINEPROTO-5-UPDOWN: Line protocol on Interface Tunnel0, changed
state to down
*Oct 26 15:35:03.868: %OSPF-5-ADJCHG: Process 10, Nbr 1.1.1.1 on Tunnel0 from FULL to
DOWN, Neighbor Down: Interface down or detached..
Success rate is 0 percent (0/5)
R6#ping 172.16.110.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.110.1, timeout is 2 seconds:
.....
Success rate is 0 percent (0/5)
R6#sh ip ei
R6#sh ip eigrp ne
R6#sh ip eigrp neighbors
EIGRP-IPv4 VR(CLC) Address-Family Neighbors for AS(100)
H   Address           Interface           Hold Uptime       SRTT  RTO  Q  Seq
                               (sec)              (ms)  Cnt  Num
1   10.10.10.30         Et0/2               14 1d08h          4   100  0  83
0   10.10.10.26         Et0/3               11 1d08h          1   100  0  110
R6#ping 172.16.110.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.110.1, timeout is 2 seconds:
.....
Success rate is 0 percent (0/5)

```

```

R6#sh ip eigrp ne
R6#sh ip eigrp neighbors
EIGRP-IPv4 VR(CLC) Address-Family Neighbors for AS(100)
H   Address           Interface           Hold Uptime       SRTT  RTO  Q  Seq
                               (sec)              (ms)  Cnt  Num
1   10.10.10.30         Et0/2               14 1d08h          4   100  0  83
0   10.10.10.26         Et0/3               11 1d08h          1   100  0  110
R6#ping 172.16.110.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.110.1, timeout is 2 seconds:
.....
Success rate is 0 percent (0/5)
R6#sh ip route
R6#sh ip route 172.16.110.0
Routing entry for 172.16.110.0/24
  Known via "eigrp 100", distance 170, metric 10752000, type external
  Redistributing via eigrp 100, ospf 10
  Advertised by ospf 10 metric 50 subnets
  Last update from 10.10.10.30 on Ethernet0/2, 00:00:49 ago
  Routing Descriptor Blocks:
  * 10.10.10.30, from 10.10.10.30, 00:00:49 ago, via Ethernet0/2
    Route metric is 10752000, traffic share count is 1
    Total delay is 11000 microseconds, minimum bandwidth is 1000 Kbit
    Reliability 255/255, minimum MTU 1500 bytes
    Loading 1/255, Hops 1
R6#ping 172.16.110.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.110.1, timeout is 2 seconds:
.....
Success rate is 0 percent (0/5)

```

# CCIE Lab Center

```
R6#traceroute 172.16.110.1 nu
R6#traceroute 172.16.110.1 numeric
Type escape sequence to abort.
Tracing the route to 172.16.110.1
VRF info: (vrf in name/id, vrf out name/id)
 1 10.10.10.30 2 msec 0 msec 1 msec
 2 *
   200.200.200.2 3 msec 2 msec
 3 200.200.200.13 5 msec 17 msec 3 msec
 4 10.10.10.58 4 msec 4 msec 4 msec
 5 10.10.10.62 5 msec * 8 msec
R6#ping 172.16.110.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.110.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 4/4/6 ms
R6#
```

We can verify from R8

```
R8#
R8#ping 172.16.110.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.110.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 4/4/6 ms
R8#tr
R8#traceroute 172.16.110.1 nu
R8#traceroute 172.16.110.1 numeric
Type escape sequence to abort.
Tracing the route to 172.16.110.1
VRF info: (vrf in name/id, vrf out name/id)
 1 10.10.10.33 2 msec 1 msec 1 msec
 2 200.200.200.2 3 msec 3 msec 2 msec
 3 200.200.200.13 4 msec 4 msec 4 msec
 4 10.10.10.58 5 msec 5 msec 6 msec
 5 10.10.10.62 6 msec * 8 msec
R8#
```

# CCIE Lab Center

Let's make it normal

```
R8#traceroute 172.16.110.1 numeric
Type escape sequence to abort.
Tracing the route to 172.16.110.1
VRF info: (vrf in name/id, vrf out name/id)
 1 10.10.10.33 2 msec 1 msec 0 msec
 2 200.200.200.2 2 msec 2 msec 2 msec
 3 200.200.200.13 4 msec 3 msec 4 msec
 4 10.10.10.58 5 msec 4 msec 4 msec
 5 10.10.10.62 5 msec *
   10.10.10.66 7 msec
R8#traceroute 172.16.110.1 numeric
Type escape sequence to abort.
Tracing the route to 172.16.110.1
VRF info: (vrf in name/id, vrf out name/id)
 1 10.10.10.25 2 msec 1 msec 1 msec
 2 100.100.100.1 3 msec 2 msec 3 msec
 3 100.100.100.12 5 msec 4 msec 4 msec
 4 10.10.10.54 5 msec 5 msec 5 msec
 5 10.10.10.66 5 msec * 5 msec
R8#
```

On R7

```
R7#ping 172.16.110.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.110.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 9/10/14 ms
R7#trace 172.16.110.1 so loo 0 nu
Type escape sequence to abort.
Tracing the route to 172.16.110.1
VRF info: (vrf in name/id, vrf out name/id)
 1 200.200.200.2 7 msec 6 msec 7 msec
 2 200.200.200.13 10 msec 5 msec 8 msec
 3 10.10.10.58 9 msec 9 msec 6 msec
 4 10.10.10.62 10 msec * 9 msec
R7#sh ip route 172.16.110.1
Routing entry for 172.16.110.0/24
  Known via "ospf 10", distance 110, metric 1022, type inter area
  Redistributing via eigrp 100
  Advertised by eigrp 100 metric 1000 1000 255 1 1500
  Last update from 200.200.200.2 on Tunnel1, 1d08h ago
  Routing Descriptor Blocks:
  * 200.200.200.2, from 10.10.10.61, 1d08h ago, via Tunnel1
    Route metric is 1022, traffic share count is 1
```

# CCIE Lab Center

On R10

```

R10#
R10#ping 172.16.50.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.50.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 3/6/9 ms
R10#tr
R10#traceroute 172.16.50.1 nu
R10#traceroute 172.16.50.1 numeric
Type escape sequence to abort.
Tracing the route to 172.16.50.1
VRF info: (vrf in name/id, vrf out name/id)
  1 100.100.100.3 8 msec 6 msec 6 msec
  2 10.10.10.18 11 msec * 8 msec
R10#cle
R10#clear ip nh
R10#clear ip nhrp
R10#traceroute 172.16.50.1 numeric
Type escape sequence to abort.
Tracing the route to 172.16.50.1
VRF info: (vrf in name/id, vrf out name/id)
  1 100.100.100.1 7 msec 6 msec 6 msec
  2 100.100.100.3 7 msec 7 msec 8 msec
  3 10.10.10.18 9 msec * 9 msec
R10#traceroute 172.16.50.1 numeric
Type escape sequence to abort.
Tracing the route to 172.16.50.1
VRF info: (vrf in name/id, vrf out name/id)
  1 100.100.100.3 6 msec 8 msec 4 msec
  2 10.10.10.18 9 msec * 9 msec
R10#

```

```

R10#sh dmvpn
Legend: Attrb --> S - Static, D - Dynamic, I - Incomplete
          N - NATed, L - Local, X - No Socket
          T1 - Route Installed, T2 - Nexthop-override
          C - CTS Capable
          # Ent --> Number of NHRP entries with same NBMA peer
          NHS Status: E --> Expecting Replies, R --> Responding, W --> Waiting
          UpDn Time --> Up or Down Time for a Tunnel
-----
Interface: Tunnel0, IPv4 NHRP Details
Type:Spoke, NHRP Peers:2,

# Ent Peer NBMA Addr Peer Tunnel Add State UpDn Tm Attrb
-----
  1 192.168.100.1      100.100.100.1   UP 05:41:18   S
  2 192.168.100.3      100.100.100.3   UP 00:00:32   DT2
                    100.100.100.3   UP 00:00:32   DT2
R10#

```

# CCIE Lab Center

```

R10#sh ip route
R10#sh ip route 172.16.50.0
Routing entry for 172.16.50.0/24
  Known via "ospf 10", distance 110, metric 20, type extern 2, forward metric 51
  Redistributing via eigrp 200
  Advertised by eigrp 200 metric 100000 100 255 1 1500
  Last update from 100.100.100.1 on Tunnel0, 00:25:13 ago
  Routing Descriptor Blocks:
  * 100.100.100.1, from 1.1.1.3, 00:25:13 ago, via Tunnel0
    Route metric is 20, traffic share count is 1
R10#sh ip route 172.16.50.1
Routing entry for 172.16.50.0/24
  Known via "ospf 10", distance 110, metric 20, type extern 2, forward metric 51
  Redistributing via eigrp 200
  Advertised by eigrp 200 metric 100000 100 255 1 1500
  Last update from 100.100.100.1 on Tunnel0, 00:25:21 ago
  Routing Descriptor Blocks:
  * 100.100.100.1, from 1.1.1.3, 00:25:21 ago, via Tunnel0
    Route metric is 20, traffic share count is 1
R10#

```

```

Route metric is 20, traffic share count is 1
R10#sh ip route | i %
+ - replicated route, % - next hop override
0 %    100.100.100.3/32 [110/51] via 100.100.100.1, 00:25:47, Tunnel0
0 E2%  172.16.50.0 [110/20] via 100.100.100.1, 00:25:47, Tunnel0
R10#

```


# CCIE Lab Center

Let's do failover test of suspending tunnel 0 of R10

Before suspending tunnel 0

```

R11#
R11#ping 172.16.50.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.50.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 3/4/5 ms
R11#tr
R11#tracert 172.16.50.1 nu
R11#tracert 172.16.50.1 numeric
Type escape sequence to abort.
Tracing the route to 172.16.50.1
VRF info: (vrf in name/id, vrf out name/id)
 0 10.10.10.41 1 msec 1 msec 0 msec
 1 100.100.100.3 3 msec 1 msec 1 msec
 2 10.10.10.18 2 msec * 4 msec
R11#
    
```





# CCIE Lab Center

Lets make it normal

```

Type escape sequence to abort.
Tracing the route to 172.16.50.1
VRF info: (vrf in name/id, vrf out name/id)
 1 10.10.10.45 2 msec 0 msec 1 msec
 2 200.200.200.2 3 msec 2 msec 2 msec
 3 200.200.200.4 3 msec 3 msec 3 msec
 4 10.10.10.22 5 msec * 6 msec
R11#traceroute 172.16.50.1 numeric
Type escape sequence to abort.
Tracing the route to 172.16.50.1
VRF info: (vrf in name/id, vrf out name/id)
 1 10.10.10.41 1 msec 2 msec 1 msec
 2 100.100.100.1 3 msec 2 msec 3 msec
 3 * * *
 4 * *
R11#traceroute 172.16.50.1 numeric
Type escape sequence to abort.
Tracing the route to 172.16.50.1
VRF info: (vrf in name/id, vrf out name/id)
 1 10.10.10.41 1 msec 1 msec 1 msec
 2 100.100.100.1 3 msec 3 msec 2 msec
 3 * * *
 4 *
R11#

```

It switched to PRI tunnel

On R9

```

R9#ping 172.16.50.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.50.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 9/9/11 ms
R9#trace 172.16.50.1 so loo 0 nu
Type escape sequence to abort.
Tracing the route to 172.16.50.1
VRF info: (vrf in name/id, vrf out name/id)
 1 200.200.200.2 6 msec 6 msec 6 msec
 2 200.200.200.4 7 msec 7 msec 7 msec
 3 10.10.10.22 9 msec * 11 msec
R9#sh dm
R9#sh dmvpn
Legend: Attrb --> S - Static, D - Dynamic, I - Incomplete
         N - NATed, L - Local, X - No Socket
         T1 - Route Installed, T2 - Nexthop-override
         C - CTS Capable
         # Ent --> Number of NHRP entries with same NBMA peer
         NHS Status: E --> Expecting Replies, R --> Responding, W --> Waiting
         UpDn Time --> Up or Down Time for a Tunnel
-----
Interface: Tunnel1, IPv4 NHRP Details
Type:Spoke, NHRP Peers:2,

# Ent Peer NBMA Addr Peer Tunnel Add State UpDn Tm Attrb
-----
 1 192.168.200.2 200.200.200.2 UP 1d09h S
 1 192.168.200.4 200.200.200.4 UP 00:00:10 D
R9#

```

# CCIE Lab Center

On R12

```

R12#ping 172.16.70.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.70.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 5/7/10 ms
R12#trace 172.16.70.1 sou loo 0 nu
Type escape sequence to abort.
Tracing the route to 172.16.70.1
VRF info: (vrf in name/id, vrf out name/id)
  1 100.100.100.6 8 msec 7 msec 8 msec
  2 10.10.10.26 9 msec * 8 msec
R12#cle
R12#clear ip nh
R12#clear ip nhrp
R12#trace 172.16.70.1 sou loo 0 nu
Type escape sequence to abort.
Tracing the route to 172.16.70.1
VRF info: (vrf in name/id, vrf out name/id)
  1 100.100.100.1 7 msec 6 msec 7 msec
  2 100.100.100.6 8 msec 8 msec 8 msec
  3 10.10.10.26 5 msec * 8 msec
R12#trace 172.16.70.1 sou loo 0 nu
Type escape sequence to abort.
Tracing the route to 172.16.70.1
VRF info: (vrf in name/id, vrf out name/id)
  1 100.100.100.6 8 msec 7 msec 7 msec
  2 10.10.10.26 8 msec * 8 msec
R12#

```

```

R12#sh ip route
R12#sh ip route 172.16.70.0
Routing entry for 172.16.70.0/24
  Known via "ospf 10", distance 110, metric 50, type extern 2, forward metric 51
  Redistributing via nhrp
  Last update from 100.100.100.1 on Tunnel0, 00:45:36 ago
  Routing Descriptor Blocks:
  * 100.100.100.1, from 1.1.1.6, 00:45:36 ago, via Tunnel0
    Route metric is 50, traffic share count is 1
R12#sh ip route | i %
+ - replicated route, % - next hop override
0 %    100.100.100.6/32 [110/51] via 100.100.100.1, 00:45:45, Tunnel0
0 E2%  172.16.70.0 [110/50] via 100.100.100.1, 00:45:45, Tunnel0
R12#

```

# CCIE Lab Center


Let's make it failover test to suspend tunnel 0 on R12

on R16

Before suspending PRI tunnel 0

```

R16#
R16#ping 172.16.70.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.70.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 4/5/9 ms
R16#trace 172.16.70.1 nu
R16#trace 172.16.70.1 numeric
Type escape sequence to abort.
Tracing the route to 172.16.70.1
VRF info: (vrf in name/id, vrf out name/id)
 0 10.10.10.65 1 msec 1 msec 1 msec
 1 10.10.10.53 1 msec 2 msec 1 msec
 2 100.100.100.6 3 msec 2 msec 3 msec
 3 10.10.10.26 4 msec * 5 msec
R16#
    
```



# CCIE Lab Center

Traffic shifted to Sec Tunnel 1

```
4 10.10.10.26 4 msec * 4 msec
R16#trace 172.16.70.1 numeric
Type escape sequence to abort.
Tracing the route to 172.16.70.1
VRF info: (vrf in name/id, vrf out name/id)
 1 10.10.10.65 1 msec 2 msec 1 msec
 2 10.10.10.53 2 msec 2 msec 1 msec
 3 100.100.100.6 3 msec 2 msec 2 msec
 4 10.10.10.26 3 msec * *
R16#trace 172.16.70.1 numeric
Type escape sequence to abort.
Tracing the route to 172.16.70.1
VRF info: (vrf in name/id, vrf out name/id)
 1 10.10.10.65 1 msec 1 msec 1 msec
 2 10.10.10.53 1 msec 1 msec 2 msec
 3 *
 10.10.10.50 2 msec 2 msec
 4 200.200.200.2 3 msec 2 msec 3 msec
 5 10.10.10.9 4 msec 3 msec 3 msec
 6 *
 10.10.10.26 7 msec *
R16#
```

```
R16#sh ip route
R16#sh ip route 172.16.70.0
Routing entry for 172.16.70.0/24
  Known via "ospf 10", distance 110, metric 50, type extern 2, forward metric 1031
  Last update from 10.10.10.61 on Ethernet0/0, 00:02:10 ago
  Routing Descriptor Blocks:
  * 10.10.10.61, from 1.1.1.6, 00:02:10 ago, via Ethernet0/0
    Route metric is 50, traffic share count is 1
R16#
```

# CCIE Lab Center

Traffic is going via

R16>R15>R13

Lets back to normal

```
Route metric is 50, traffic share count is 1
R16#sh ip route 172.16.70.0
Routing entry for 172.16.70.0/24
  Known via "ospf 10", distance 110, metric 50, type extern 2, forward metric 1031
  Last update from 10.10.10.61 on Ethernet0/0, 00:04:07 ago
  Routing Descriptor Blocks:
    * 10.10.10.61, from 1.1.1.6, 00:04:07 ago, via Ethernet0/0
      Route metric is 50, traffic share count is 1
R16#sh ip route 172.16.70.0
Routing entry for 172.16.70.0/24
  Known via "ospf 10", distance 110, metric 50, type extern 2, forward metric 71
  Last update from 10.10.10.65 on Ethernet0/1, 00:00:00 ago
  Routing Descriptor Blocks:
    * 10.10.10.65, from 1.1.1.6, 00:00:00 ago, via Ethernet0/1
      Route metric is 50, traffic share count is 1
R16#
```

Traffic shifted to PRI tunnel

```
R10#TRACE
R16#traceroute 172.16.70.1 nu
Type escape sequence to abort.
Tracing the route to 172.16.70.1
VRF info: (vrf in name/id, vrf out name/id)
 0 10.10.10.65 1 msec 1 msec 0 msec
 1 10.10.10.53 1 msec 1 msec 1 msec
 2 100.100.100.1 2 msec 2 msec 2 msec
```

# CCIE Lab Center

On R13

```


R13#trace 172.16.70.1 sou loo 0 nu
Type escape sequence to abort.
Tracing the route to 172.16.70.1
VRF info: (vrf in name/id, vrf out name/id)
 1 10.10.10.49 2 msec 2 msec 1 msec
 2 100.100.100.1 3 msec 2 msec 2 msec
 3 100.100.100.6 4 msec 3 msec 4 msec
 4 *
   10.10.10.26 6 msec *
R13#trace 172.16.70.1 sou loo 0 nu
Type escape sequence to abort.
Tracing the route to 172.16.70.1
VRF info: (vrf in name/id, vrf out name/id)
 1 10.10.10.49 1 msec 1 msec 1 msec
 2 100.100.100.6 5 msec 4 msec 3 msec
 3 10.10.10.26 4 msec * 6 msec
R13#sh ip route
R13#sh ip route 172.16.70.0
Routing entry for 172.16.70.0/24
  Known via "ospf 10", distance 110, metric 50, type extern 2, forward metric 61
  Redistributing via nhrp
  Last update from 10.10.10.49 on Ethernet0/2, 00:04:25 ago
  Routing Descriptor Blocks:
  * 10.10.10.49, from 1.1.1.6, 00:04:25 ago, via Ethernet0/2
    Route metric is 50, traffic share count is 1
R13#sh dm
Legend: Attrb --> S - Static, D - Dynamic, I - Incomplete
         N - NATed, L - Local, X - No Socket
         T1 - Route Installed, T2 - Nexthop-override
         C - CTS Capable
         # Ent --> Number of NHRP entries with same NBMA peer
         NHS Status: E --> Expecting Replies, R --> Responding, W --> Waiting
         UpDn Time --> Up or Down Time for a Tunnel
=====
Interface: Tunnell1, IPv4 NHRP Details
Type:Spoke, NHRP Peers:1,

# Ent Peer NBMA Addr Peer Tunnel Add State UpDn Tm Attrb
-----
 1 192.168.200.2 200.200.200.2 UP 1d09h 5
R13#

```

# CCIE Lab Center

We'll shutdown PRI path.



```

Routing entry for 172.16.70.0/24
  Known via "ospf 10", distance 110, metric 50, type extern 2, forward metric 1011
  Redistributing via nhrp
  Last update from 200.200.200.2 on Tunnel1, 00:01:54 ago
  Routing Descriptor Blocks:
    * 200.200.200.2, from 1.1.1.6, 00:01:54 ago, via Tunnel1
      Route metric is 50, traffic share count is 1
R13#ping 172.16.70.1
Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 172.16.70.1, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 8/9/10 ms
R13#tr
R13#traceroute 172.16.70.1 sou loo 0 nu
Type escape sequence to abort.
Tracing the route to 172.16.70.1
VRF info: (vrf in name/id, vrf out name/id)
 0  1 200.200.200.2 6 msec 7 msec 6 msec
 1  2 10.10.10.9 6 msec 7 msec 6 msec
 2  3 100.100.100.6 9 msec 7 msec 8 msec
 3  4 10.10.10.26 8 msec * 10 msec
R13#
    
```

# CCIE Lab Center

Thank You

100% Real | 100% Pass  
Visit [ccielabcenter.com](http://ccielabcenter.com)