

```
DSW2#
DSW2#show running-config
Building configuration...

Current configuration : 6019 bytes
!
! No configuration change since last restart
!
version 12.2
no service pad
service timestamps debug uptime
service timestamps log uptime
no service password-encryption
!
hostname DSW2
!
no logging console
!
no aaa new-model
ipv6 unicast-routing
ip subnet-zero
ip routing
!
ip multicast-routing
vtp domain netlearning
vtp mode transparent
!
!
crypto pki trustpoint TP-self-signed-4246780416
  enrollment selfsigned
  subject-name cn=IOS-Self-Signed-Certificate-4246780416
  revocation-check none
  rsakeypair TP-self-signed-4246780416
!
!
crypto pki certificate chain TP-self-signed-4246780416
  certificate self-signed 01
    3082023D 308201A6 A0030201 02020101 300D0609 2A864886 F70D0101 04050030
    31312F30 2D060355 04031326 494F532D 53656C66 2D536967 6E65642D 43657274
    69666963 6174652D 34323436 37383034 3136301E 170D3933 30333031 30303031
    30345A17 0D323030 31303130 30303030 305A3031 312F302D 06035504 03132649
    4F532D53 656C662D 5369676E 65642D43 65727469 66696361 74652D34 32343637
    38303431 3630819F 300D0609 2A864886 F70D0101 01050003 818D0030 81890281
    8100D699 D2A8BD0D A26CE645 B2CE1EC4 EF83204E CBA4D34A B03BC30C 7BF013B1
    5BDEC621 F3CE12CC BC929D9C 463A59DC D49CEF76 3D5193FD 7992F7FF 660F179F
    54CA6370 902081BB ABB71246 5DC79E39 D241B749 11CB4812 07CF1238 A25C59F6
    740464A7 6B3EAE02 6B6B0C13 9B534C70 85BD199E E52D4FB2 AB4C4B5F 678ECD24
    17B30203 010001A3 65306330 0F060355 1D130101 FF040530 030101FF 30100603
    551D1104 09300782 05445357 322E301F 0603551D 23041830 168014A7 8C27C43F
    00BEB401 3F63B68A 9CD582EF D7B15430 1D060355 1D0E0416 0414A78C 27C43F00
    BEB4013F 63B68A9C D582EFD7 B154300D 06092A86 4886F70D 01010405 00038181
    00B9A060 055A57EE 0EE7C450 128718FA 07A5DCE4 8EABE33F 56BA385F 8F9477E8
    191A361C EBEFB296 6A2E4637 11BB4D89 CDFA4DD8 7229B8F1 856DCE18 DF11CA57
    180C3686 28E9079C F004E71B A9F11040 7C952427 573ED2F5 AB38C4D9 768156A4
```

```
C597E2E3 B9D4C611 F902BEA8 A18209DD 239160AE E6AC24DE 41AD980B 261778F5
AA
quit
!
!
!
spanning-tree mode pvst
spanning-tree extend system-id
spanning-tree vlan 10,200 priority 8192
spanning-tree vlan 20 priority 4096
!
vlan internal allocation policy ascending
!
vlan 10,20,200
!
!
!
!
!
!
interface Tunnel67
no ip address
ipv6 address 2026::3:2/122
ipv6 enable
ipv6 rip RIPNG enable
tunnel source 10.2.4.14
tunnel destination 10.2.4.13
!
interface Port-channel12
no switchport
ip address 10.2.4.14 255.255.255.252
ip pim sparse-dense-mode
!
interface Port-channel23
switchport trunk encapsulation dot1q
switchport trunk allowed vlan 10,200
switchport mode trunk
!
interface Port-channel24
switchport trunk encapsulation dot1q
switchport trunk allowed vlan 20,200
switchport mode trunk
!
interface FastEthernet0/1
no switchport
ip address 10.1.4.10 255.255.255.252
ip pim sparse-dense-mode
!
interface FastEthernet0/2
switchport mode access
shutdown
!
interface FastEthernet0/3
switchport mode access
```

```
!  
interface FastEthernet0/4  
    switchport mode access  
    shutdown  
!  
interface FastEthernet0/5  
    switchport mode access  
    shutdown  
!  
interface FastEthernet0/6  
    switchport mode access  
    shutdown  
!  
interface FastEthernet0/7  
    switchport mode access  
    shutdown  
!  
interface FastEthernet0/8  
    switchport mode access  
    shutdown  
!  
interface FastEthernet0/9  
    switchport mode access  
    shutdown  
!  
interface FastEthernet0/10  
    switchport mode access  
    shutdown  
!  
interface FastEthernet0/11  
    switchport mode access  
    shutdown  
!  
interface FastEthernet0/12  
    switchport mode access  
    shutdown  
!  
interface FastEthernet0/13  
    switchport mode access  
    shutdown  
!  
interface FastEthernet0/14  
    switchport mode access  
    shutdown  
!  
interface FastEthernet0/15  
    switchport mode access  
!  
interface FastEthernet0/16  
    switchport trunk encapsulation dot1q  
    switchport trunk allowed vlan 20,200  
    switchport mode trunk  
    channel-group 24 mode desirable  
!
```

```
interface FastEthernet0/17
  switchport trunk encapsulation dot1q
  switchport trunk allowed vlan 20,200
  switchport mode trunk
  channel-group 24 mode desirable
!
interface FastEthernet0/18
  switchport trunk encapsulation dot1q
  switchport trunk allowed vlan 20,200
  switchport mode trunk
  channel-group 24 mode desirable
!
interface FastEthernet0/19
  switchport trunk encapsulation dot1q
  switchport trunk allowed vlan 10,200
  switchport mode trunk
  channel-group 23 mode active
!
interface FastEthernet0/20
  switchport trunk encapsulation dot1q
  switchport trunk allowed vlan 10,200
  switchport mode trunk
  channel-group 23 mode active
!
interface FastEthernet0/21
  switchport trunk encapsulation dot1q
  switchport trunk allowed vlan 10,200
  switchport mode trunk
  channel-group 23 mode active
!
interface FastEthernet0/22
  no switchport
  no ip address
  channel-group 12 mode on
!
interface FastEthernet0/23
  no switchport
  no ip address
  channel-group 12 mode on
!
interface FastEthernet0/24
  no switchport
  no ip address
  channel-group 12 mode on
!
interface GigabitEthernet0/1
  switchport mode dynamic desirable
  shutdown
!
interface GigabitEthernet0/2
  switchport mode dynamic desirable
  shutdown
!
interface Vlan1
```

```
no ip address
shutdown
!
interface Vlan10
 ip address 10.2.1.2 255.255.255.0
 ip helper-address 10.1.4.9
 ip pim sparse-dense-mode
 standby 10 ip 10.2.1.254
 standby 10 priority 20
!
interface Vlan20
 ip address 10.2.2.1 255.255.255.0
 ip pim sparse-dense-mode
!
interface Vlan200
 ip address 192.168.1.130 255.255.255.224
!
!
router eigrp 10
 metric weights 0 1 1 1 1 1
 no auto-summary
 network 10.1.4.10 0.0.0.0
 network 10.2.1.2 0.0.0.0
 network 10.2.2.1 0.0.0.0
 network 10.2.4.14 0.0.0.0
!
ip classless
ip http server
ip http secure-server
!
!
ip access-list standard DENY_10
 deny 10.0.0.0 0.255.255.255
 permit any
ip access-list standard DENY_ALL
 deny any
ip access-list standard PERMIT_10
 permit 10.0.0.0 0.255.255.255
ip access-list standard PERMIT_ALL
 permit any
!
ipv6 router rip RIPNG
!
!
control-plane
!
!
line con 0
 exec-timeout 0 0
 logging synchronous
line vty 0 4
 login
line vty 5 15
 login
```

```
!  
ntp clock-period 17179962  
ntp server 10.1.1.1  
end
```

```
DSW2#
```

```
DSW2#ping 209.65.200.241
```

```
Type escape sequence to abort.  
Sending 5, 100-byte ICMP Echos to 209.65.200.241, timeout is 2 seconds:  
!!!!!
```

Success rate is 100 percent (5/5), round-trip min/avg/max = 224/228/236
ms
DSW2#

DSW2#ping 209.65.200.226

Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 209.65.200.226, timeout is 2 seconds:
!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 224/226/228
ms
DSW2#

DSW2#ping 209.65.200.225

Type escape sequence to abort.

Sending 5, 100-byte ICMP Echos to 209.65.200.225, timeout is 2 seconds:

!!!!

Success rate is 100 percent (5/5), round-trip min/avg/max = 192/196/200
ms

DSW2#

```
DSW2#ping 10.1.1.1
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.1, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 192/194/196  
ms
```

```
DSW2#
```

```
DSW2#ping 10.1.1.2
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.2, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 128/130/132  
ms
```

```
DSW2#
```

```
DSW2#ping 10.1.1.5
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.5, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 128/130/132  
ms
```

```
DSW2#
```

```
DSW2#ping 10.1.1.6
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.6, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 64/66/68 ms
```

```
DSW2#
```

```
DSW2#ping 10.1.1.9
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.9, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 64/65/68 ms
```

```
DSW2#
```

```
DSW2#ping 10.1.1.10
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.10, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/2/4 ms
```

```
DSW2#
```

```
DSW2#ping 10.1.4.10
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.4.10, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/1/4 ms
```

```
DSW2#
```

```
DSW2#ping 10.1.4.9
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.4.9, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/2/4 ms
```

```
DSW2#
```

```
DSW2#ping 10.1.4.6
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.4.6, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 4/4/4 ms
```

```
DSW2#
```

```
DSW2#ping 10.1.4.5
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.4.5, timeout is 2 seconds:
```

```
!!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/2/4 ms
```

```
DSW2#
```

```
DSW2#ping 10.2.1.1
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.1.1, timeout is 2 seconds:
```

```
!!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 4/4/4 ms
```

```
DSW2#
```

```
DSW2#ping 10.2.2.2
```

Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 10.2.2.2, timeout is 2 seconds:
!!!!!
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/3/4 ms
DSW2#

DSW2#ping 10.2.1.254

Type escape sequence to abort.
Sending 5, 100-byte ICMP Echos to 10.2.1.254, timeout is 2 seconds:
!!!!!

Success rate is 100 percent (5/5), round-trip min/avg/max = 4/4/4 ms
DSW2#

DSW2#ping 10.2.4.14

Type escape sequence to abort.

Sending 5, 100-byte ICMP Echos to 10.2.4.14, timeout is 2 seconds:

!!!!

Success rate is 100 percent (5/5), round-trip min/avg/max = 1/1/4 ms

DSW2#

```
DSW2#ping 10.2.4.13
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.4.13, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/3/4 ms
```

```
DSW2#
```

DSW2#ping 10.2.1.2

Type escape sequence to abort.

Sending 5, 100-byte ICMP Echos to 10.2.1.2, timeout is 2 seconds:

!!!!

Success rate is 100 percent (5/5), round-trip min/avg/max = 1/1/4 ms

DSW2#

```
DSW2#ping 10.2.2.1
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.2.1, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/1/4 ms
```

```
DSW2#
```

```
DSW2#ping 10.2.1.4
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.1.4, timeout is 2 seconds:
```

```
.....
```

```
Success rate is 0 percent (0/5)
```

```
DSW2#
```

DSW2#show ip interface brief

Interface	IP-Address	OK?	Method	Status
Protocol				
Vlan1	unassigned	YES	NVRAM	administratively down
down				
Vlan10	10.2.1.2	YES	NVRAM	up
up				
Vlan20	10.2.2.1	YES	NVRAM	up
up				
Vlan200	192.168.1.130	YES	NVRAM	up
up				
FastEthernet0/1	10.1.4.10	YES	NVRAM	up
up				
FastEthernet0/2	unassigned	YES	unset	administratively down
down				
FastEthernet0/3	unassigned	YES	unset	down
down				
FastEthernet0/4	unassigned	YES	unset	administratively down
down				
FastEthernet0/5	unassigned	YES	unset	administratively down
down				
FastEthernet0/6	unassigned	YES	unset	administratively down
down				
FastEthernet0/7	unassigned	YES	unset	administratively down
down				
FastEthernet0/8	unassigned	YES	unset	administratively down
down				
FastEthernet0/9	unassigned	YES	unset	administratively down
down				

FastEthernet0/10 down	unassigned	YES	unset	administratively down
FastEthernet0/11 down	unassigned	YES	unset	administratively down
FastEthernet0/12 down	unassigned	YES	unset	administratively down
FastEthernet0/13 down	unassigned	YES	unset	administratively down
FastEthernet0/14 down	unassigned	YES	unset	administratively down
FastEthernet0/15 down	unassigned	YES	unset	down
FastEthernet0/16 up	unassigned	YES	unset	up
FastEthernet0/17 up	unassigned	YES	unset	up
FastEthernet0/18 up	unassigned	YES	unset	up
FastEthernet0/19 up	unassigned	YES	unset	up
FastEthernet0/20 up	unassigned	YES	unset	up
FastEthernet0/21 up	unassigned	YES	unset	up
FastEthernet0/22 up	unassigned	YES	NVRAM	up
FastEthernet0/23 up	unassigned	YES	NVRAM	up
FastEthernet0/24 up	unassigned	YES	NVRAM	up
GigabitEthernet0/1 down	unassigned	YES	unset	administratively down
GigabitEthernet0/2 down	unassigned	YES	unset	administratively down
Port-channel12 up	10.2.4.14	YES	NVRAM	up
Port-channel23 up	unassigned	YES	unset	up
Port-channel24 up	unassigned	YES	unset	up
Tunnel67 up	unassigned	YES	NVRAM	up

DSW2#

DSW2#show ip route

Codes: C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS
level-2
ia - IS-IS inter area, * - candidate default, U - per-user static
route
o - ODR, P - periodic downloaded static route

Gateway of last resort is 10.1.4.9 to network 0.0.0.0

10.0.0.0/8 is variably subnetted, 6 subnets, 2 masks
C 10.2.4.12/30 is directly connected, Port-channel12
D EX 10.1.1.8/30 [170/1023] via 10.1.4.9, 00:37:05, FastEthernet0/1
C 10.1.4.8/30 is directly connected, FastEthernet0/1
C 10.2.1.0/24 is directly connected, Vlan10
C 10.2.2.0/24 is directly connected, Vlan20
D 10.1.4.4/30 [90/111] via 10.2.2.2, 00:37:05, Vlan20
[90/111] via 10.2.1.1, 00:37:05, Vlan10
192.168.1.0/27 is subnetted, 1 subnets

```
C      192.168.1.128 is directly connected, Vlan200
D*EX 0.0.0.0/0 [170/1023] via 10.1.4.9, 00:37:05, FastEthernet0/1
DSW2#
```

```
DSW2#show processes cpu
CPU utilization for five seconds: 0%/0%; one minute: 0%; five minutes: 1%
  PID Runtime(ms)   Invoked    uSecs   5Sec   1Min   5Min  TTY Process
    1         0         8         0  0.00%  0.00%  0.00%   0 Chunk
Manager
    2         0      1551         0  0.00%  0.00%  0.00%   0 Load Meter
    3         4       35      114  0.00%  0.00%  0.00%   0 SpanTree
Helper
```

4	6888	922	7470	0.00%	0.06%	0.05%	0	Check
heaps								
5	0	5	0	0.00%	0.00%	0.00%	0	Pool
Manager								
6	0	2	0	0.00%	0.00%	0.00%	0	Timers
7	0	1	0	0.00%	0.00%	0.00%	0	Crash
writer								
8	40	199	201	0.00%	0.00%	0.00%	0	ARP Input
9	0	1	0	0.00%	0.00%	0.00%	0	CEF MIB
API								
10	0	1	0	0.00%	0.00%	0.00%	0	
AAA_SERVER_DEADT								
11	4	2	2000	0.00%	0.00%	0.00%	0	AAA high-
capacit								
12	0	1	0	0.00%	0.00%	0.00%	0	Policy
Manager								
13	16	3	5333	0.00%	0.00%	0.00%	0	Entity MIB
API								
14	0	1	0	0.00%	0.00%	0.00%	0	IFS Agent
Manage								
15	0	130	0	0.00%	0.00%	0.00%	0	IPC
Dynamic Cach								
16	0	1	0	0.00%	0.00%	0.00%	0	IPC Zone
Manager								
17	4	7767	0	0.00%	0.00%	0.00%	0	IPC
Periodic Tim								
18	0	1	0	0.00%	0.00%	0.00%	0	IPC
Managed Time								
19	0	7767	0	0.00%	0.00%	0.00%	0	IPC
Deferred Por								
20	0	2	0	0.00%	0.00%	0.00%	0	IPC Seat
Manager								
21	0	1	0	0.00%	0.00%	0.00%	0	IPC
Session Serv								
22	16	7767	2	0.00%	0.00%	0.00%	0	Dynamic
ARP Insp								
23	0	1	0	0.00%	0.00%	0.00%	0	ARP Snoop
24	0	1	0	0.00%	0.00%	0.00%	0	Net Input
25	0	7750	0	0.00%	0.00%	0.00%	0	GraphIt
26	0	2	0	0.00%	0.00%	0.00%	0	XML Proxy
Client								
27	0	1	0	0.00%	0.00%	0.00%	0	Critical
Bkgnd								
28	96	11142	8	0.00%	0.00%	0.00%	0	Net
Background								
29	0	10	0	0.00%	0.00%	0.00%	0	IDB Work
30	16	49	326	0.00%	0.00%	0.00%	0	Logger
31	0	7746	0	0.00%	0.00%	0.00%	0	TTY
Background								
32	16	7758	2	0.00%	0.00%	0.00%	0	Per-Second
Jobs								
33	1104	131	8427	0.00%	0.00%	0.00%	0	Per-minute
Jobs								

34	4	8	500	0.00%	0.00%	0.00%	0	IF-MGR
control p								
35	0	53	0	0.00%	0.00%	0.00%	0	IF-MGR
event pro								
36	0	1	0	0.00%	0.00%	0.00%	0	AggMgr
Process								
37	4	1552	2	0.00%	0.00%	0.00%	0	Compute
load avg								
38	0	2327	0	0.00%	0.00%	0.00%	0	HC Counter
Timer								
39	4	7660	0	0.00%	0.00%	0.00%	0	Vegas
Storm Cont								
40	3108	2238	1388	0.00%	0.08%	0.15%	0	Exec
41	8	148919	0	0.00%	0.00%	0.00%	0	
DownWhenLooped								
42	0	5	0	0.00%	0.00%	0.00%	0	Collection
proce								
43	5808	193540	30	0.07%	0.07%	0.08%	0	Vegas_LED
Proces								
44	0	1	0	0.00%	0.00%	0.00%	0	
SCQ_PROCESS								
45	176	48576	3	0.00%	0.00%	0.00%	0	RAM Access
46	172	92273	1	0.00%	0.00%	0.00%	0	SW Frame
Ager								
47	28	33	848	0.00%	0.00%	0.00%	0	VLAN Info
Update								
48	0	1	0	0.00%	0.00%	0.00%	0	JADE Gbit
lookup								
49	4	15499	0	0.00%	0.00%	0.00%	0	L2TM
Process								
50	120	15500	7	0.00%	0.00%	0.00%	0	L3TM
51	30824	22979	1341	0.39%	0.39%	0.39%	0	Vegas
Statistics								
52	48	107587	0	0.00%	0.00%	0.00%	0	HMATM
Learn proc								
53	24	7752	3	0.00%	0.00%	0.00%	0	HMATM Age
proces								
54	44	88	500	0.00%	0.00%	0.00%	0	VL2MM
55	12	7777	1	0.00%	0.00%	0.00%	0	L3MD
56	2432	19380	125	0.00%	0.00%	0.00%	0	L3MD_STAT
57	0	1	0	0.00%	0.00%	0.00%	0	Vegas
Bridging								
58	576	96852	5	0.00%	0.00%	0.00%	0	VegasPM
59	24	3935	6	0.00%	0.00%	0.00%	0	VUR_MGR bg
proce								
60	24	7753	3	0.00%	0.00%	0.00%	0	PI_MATM
Aging Pr								
61	0	1	0	0.00%	0.00%	0.00%	0	Switch
Backup In								
62	0	130	0	0.00%	0.00%	0.00%	0	MMN bkgrd
proces								
63	0	2	0	0.00%	0.00%	0.00%	0	Dot1x Mgr
Proces								

64	0	2	0	0.00%	0.00%	0.00%	0	802.1x
Accountin								
65	0	1	0	0.00%	0.00%	0.00%	0	MAB
Framework								
66	0	2	0	0.00%	0.00%	0.00%	0	802.1x
switch								
67	0	1	0	0.00%	0.00%	0.00%	0	802.1x
Webauth F								
68	276	2894	95	0.00%	0.00%	0.00%	0	DTP
Protocol								
69	0	1	0	0.00%	0.00%	0.00%	0	EAP
Framework								
70	0	130	0	0.00%	0.00%	0.00%	0	Port-
Security								
72	4	21	190	0.00%	0.00%	0.00%	0	Switch IP
Host T								
73	0	778	0	0.00%	0.00%	0.00%	0	Ethchnl
74	0	7754	0	0.00%	0.00%	0.00%	0	UDLD
75	0	1	0	0.00%	0.00%	0.00%	0	Vegas IPSPG
Proce								
76	0	31	0	0.00%	0.00%	0.00%	0	VMATM
Callback								
77	0	38	0	0.00%	0.00%	0.00%	0	HL3U PBR
bkgrd p								
78	0	65	0	0.00%	0.00%	0.00%	0	Vegas PBR
n-h re								
79	0	2	0	0.00%	0.00%	0.00%	0	AAA Server
80	0	1	0	0.00%	0.00%	0.00%	0	AAA ACCT
Proc								
81	0	1	0	0.00%	0.00%	0.00%	0	ACCT
Periodic Pr								
82	0	1	0	0.00%	0.00%	0.00%	0	AAA System
Acct								
83	0	1	0	0.00%	0.00%	0.00%	0	Auth-proxy
AAA B								
84	0	26	0	0.00%	0.00%	0.00%	0	IP Admin
SM Proc								
85	856	3044	281	0.00%	0.01%	0.00%	0	CDP
Protocol								
87	0	1	0	0.00%	0.00%	0.00%	0	Key Proc
88	0	2	0	0.00%	0.00%	0.00%	0	AAA
Dictionary R								
89	0	65	0	0.00%	0.00%	0.00%	0	DHCP
Snooping								
90	0	3	0	0.00%	0.00%	0.00%	0	CEF
switching ba								
91	1628	9552	170	0.00%	0.02%	0.01%	0	IP Input
92	0	1	0	0.00%	0.00%	0.00%	0	ICMP event
handl								
93	4	15145	0	0.00%	0.00%	0.00%	0	IP ARP
Track								
94	0	5	0	0.00%	0.00%	0.00%	0	ADJ
resolve proc								

95	1272	20803	61	0.07%	0.04%	0.01%	0	Spanning
Tree								
96	0	2	0	0.00%	0.00%	0.00%	0	EAPoUDP
Process								
97	0	2	0	0.00%	0.00%	0.00%	0	KRB5 AAA
98	0	132	0	0.00%	0.00%	0.00%	0	CEF
background p								
99	0	1	0	0.00%	0.00%	0.00%	0	IP IRDP
100	0	99	0	0.00%	0.00%	0.00%	0	Cluster L2
101	0	777	0	0.00%	0.00%	0.00%	0	Cluster
RARP								
102	248	2138	115	0.00%	0.00%	0.00%	0	Cluster
Base								
103	0	1	0	0.00%	0.00%	0.00%	0	TCP Timer
104	0	1	0	0.00%	0.00%	0.00%	0	TCP
Protocols								
105	0	1	0	0.00%	0.00%	0.00%	0	Socket
Timers								
106	4	28	142	0.00%	0.00%	0.00%	0	HTTP CORE
107	0	1	0	0.00%	0.00%	0.00%	0	RARP Input
108	0	1	0	0.00%	0.00%	0.00%	0	802.1x
Critical								
109	8	34	235	0.00%	0.00%	0.00%	0	L2MM
110	48	403	119	0.00%	0.00%	0.00%	0	MRD
111	48	485	98	0.00%	0.00%	0.00%	0	IGMPSN
112	0	1	0	0.00%	0.00%	0.00%	0	IGMPQR
113	0	2	0	0.00%	0.00%	0.00%	0	L2TRACE
SERVER								
114	0	1	0	0.00%	0.00%	0.00%	0	Vegas wccp
manag								
115	0	4	0	0.00%	0.00%	0.00%	0	Crypto ACL
116	12	149	80	0.00%	0.00%	0.00%	0	IP RIB
Update								
117	8	26	307	0.00%	0.00%	0.00%	0	DHCPD
Receive								
118	0	1	0	0.00%	0.00%	0.00%	0	Transport
Port A								
119	3896	24	162333	0.00%	0.00%	0.05%	0	crypto sw
pk pro								
120	0	2	0	0.00%	0.00%	0.00%	0	Crypto
Support								
121	0	2	0	0.00%	0.00%	0.00%	0	LOCAL AAA
122	0	2	0	0.00%	0.00%	0.00%	0	ENABLE AAA
123	0	2	0	0.00%	0.00%	0.00%	0	LINE AAA
125	0	2	0	0.00%	0.00%	0.00%	0	TPLUS
126	0	1	0	0.00%	0.00%	0.00%	0	CRYPTO QoS
proce								
127	0	1	0	0.00%	0.00%	0.00%	0	Crypto INT
128	0	4	0	0.00%	0.00%	0.00%	0	Crypto
IKMP								
129	100	391	255	0.00%	0.00%	0.00%	0	IPSEC key
engine								
130	0	1	0	0.00%	0.00%	0.00%	0	IPSEC
manual key								

131	0	1	0	0.00%	0.00%	0.00%	0 Crypto PAS
Proc							
132	0	12	0	0.00%	0.00%	0.00%	0 crypto
engine pr							
133	28	4	7000	0.00%	0.00%	0.00%	0 Crypto CA
134	0	1	0	0.00%	0.00%	0.00%	0 Crypto
PKI-CRL							
135	0	1	0	0.00%	0.00%	0.00%	0 Crypto SSL
136	0	1	0	0.00%	0.00%	0.00%	0 encrypt
proc							
137	0	7760	0	0.00%	0.00%	0.00%	0 Vegas
EnvMon Pro							
138	0	2	0	0.00%	0.00%	0.00%	0 VTPMIB
EDIT BUFF							
139	0	2	0	0.00%	0.00%	0.00%	0 DHCP
Security He							
140	20	13317	1	0.00%	0.00%	0.00%	0 PM
Callback							
141	16	57	280	0.00%	0.00%	0.00%	0 VLAN
Manager							
142	0	65	0	0.00%	0.00%	0.00%	0 DHCPD
Timer							
143	0	622	0	0.00%	0.00%	0.00%	0 dhcp
snooping sw							
144	436	2595	168	0.00%	0.00%	0.00%	0 Inline
Power							
145	340	17169	19	0.00%	0.00%	0.00%	0 Marvell
wk-a Pow							
146	0	2	0	0.00%	0.00%	0.00%	0 Inline
Power Twe							
147	0	1	0	0.00%	0.00%	0.00%	0 VFM Queue
Proces							
148	8	1	8000	0.00%	0.00%	0.00%	0 VFM/VQM
Merge Pr							
149	0	1	0	0.00%	0.00%	0.00%	0 VFM
Deferred Upd							
150	0	13	0	0.00%	0.00%	0.00%	0 VTP Trap
Process							
152	0	2	0	0.00%	0.00%	0.00%	0 AAA SEND
STOP EV							
153	0	1	0	0.00%	0.00%	0.00%	0 Syslog
Traps							
154	0	1	0	0.00%	0.00%	0.00%	0 DATA
Transfer Pr							
155	0	1	0	0.00%	0.00%	0.00%	0 DATA
Collector							
156	12	32	375	0.00%	0.00%	0.00%	0 Syslog
157	0	1	0	0.00%	0.00%	0.00%	0 C3550 DHCP
Snoop							
158	0	2	0	0.00%	0.00%	0.00%	0 STP STACK
TOPOLO							
159	0	2	0	0.00%	0.00%	0.00%	0 STP FAST
TRANSIT							

160	0	2	0	0.00%	0.00%	0.00%	0	STP STACK
TOPOLO								
161	0	2	0	0.00%	0.00%	0.00%	0	CSRT RAPID
TRANS								
163	0	7	0	0.00%	0.00%	0.00%	0	SSH Event
handle								
164	0	14	0	0.00%	0.00%	0.00%	0	IPv6 RIB
Redistr								
165	32	11766	2	0.00%	0.00%	0.00%	0	CEF: IPv4
proces								
166	0	1	0	0.00%	0.00%	0.00%	0	ADJ
background								
167	20	209	95	0.00%	0.00%	0.00%	0	IP
Background								
168	44	415	106	0.00%	0.00%	0.00%	0	IPv6 Input
169	0	315	0	0.00%	0.00%	0.00%	0	IPv6 IDB
170	0	4	0	0.00%	0.00%	0.00%	0	IPv6 ND
171	56	897	62	0.00%	0.00%	0.00%	0	IPv6 RIP
172	0	7763	0	0.00%	0.00%	0.00%	0	DVMRP
Timers								
173	88	8249	10	0.00%	0.00%	0.00%	0	IGMP Input
174	160	9981	16	0.00%	0.00%	0.00%	0	PIM
Process								
175	12	77585	0	0.00%	0.00%	0.00%	0	Mwheel
Process								
176	236	1698	138	0.00%	0.00%	0.00%	0	PAgP
177	172	2539	67	0.00%	0.00%	0.00%	0	LACP
Protocol								
178	104	3565	29	0.00%	0.00%	0.00%	0	HSRP
(Standby)								
180	20	7904	2	0.00%	0.00%	0.00%	0	NTP
181	0	2195	0	0.00%	0.00%	0.00%	0	DHCPD
Database								
182	0	19	0	0.00%	0.00%	0.00%	0	EIGRP:
Router								
183	788	6539	120	0.00%	0.00%	0.00%	0	EIGRP-
IPv4:								
184	488	12492	39	0.00%	0.00%	0.00%	0	EIGRP-
IPv4: Hell								
DSW2#								

```
DSW2#show interfaces
Vlan1 is administratively down, line protocol is down
  Hardware is EtherSVI, address is 000b.fd20.ba00 (bia 000b.fd20.ba00)
  MTU 1500 bytes, BW 1000000 Kbit, DLY 10 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive not supported
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input never, output never, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
  5 minute input rate 0 bits/sec, 0 packets/sec
  5 minute output rate 0 bits/sec, 0 packets/sec
    0 packets input, 0 bytes, 0 no buffer
    Received 0 broadcasts (0 IP multicasts)
    0 runts, 0 giants, 0 throttles
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
    0 packets output, 0 bytes, 0 underruns
    0 output errors, 1 interface resets
    0 output buffer failures, 0 output buffers swapped out
Vlan10 is up, line protocol is up
  Hardware is EtherSVI, address is 000b.fd20.ba00 (bia 000b.fd20.ba00)
  Internet address is 10.2.1.2/24
```

```
MTU 1500 bytes, BW 1000000 Kbit, DLY 10 usec,
    reliability 255/255, txload 1/255, rxload 1/255
Encapsulation ARPA, loopback not set
Keepalive not supported
ARP type: ARPA, ARP Timeout 04:00:00
Last input 00:00:00, output 00:00:00, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 6
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
    2314 packets input, 204750 bytes, 0 no buffer
    Received 0 broadcasts (605 IP multicasts)
    0 runs, 0 giants, 0 throttles
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
    4814 packets output, 328835 bytes, 0 underruns
    0 output errors, 0 interface resets
    0 output buffer failures, 0 output buffers swapped out
Vlan20 is up, line protocol is up
    Hardware is EtherSVI, address is 000b.fd20.ba00 (bia 000b.fd20.ba00)
    Internet address is 10.2.2.1/24
    MTU 1500 bytes, BW 1000000 Kbit, DLY 10 usec,
        reliability 255/255, txload 1/255, rxload 1/255
    Encapsulation ARPA, loopback not set
    Keepalive not supported
    ARP type: ARPA, ARP Timeout 04:00:00
    Last input 00:00:02, output 00:00:02, output hang never
    Last clearing of "show interface" counters never
    Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 6
    Queueing strategy: fifo
    Output queue: 0/40 (size/max)
    5 minute input rate 0 bits/sec, 0 packets/sec
    5 minute output rate 0 bits/sec, 0 packets/sec
        2016 packets input, 160508 bytes, 0 no buffer
        Received 0 broadcasts (1672 IP multicasts)
        0 runs, 0 giants, 0 throttles
        0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
        2181 packets output, 163230 bytes, 0 underruns
        0 output errors, 0 interface resets
        0 output buffer failures, 0 output buffers swapped out
Vlan200 is up, line protocol is up
    Hardware is EtherSVI, address is 000b.fd20.ba00 (bia 000b.fd20.ba00)
    Internet address is 192.168.1.130/27
    MTU 1500 bytes, BW 1000000 Kbit, DLY 10 usec,
        reliability 255/255, txload 1/255, rxload 1/255
    Encapsulation ARPA, loopback not set
    Keepalive not supported
    ARP type: ARPA, ARP Timeout 04:00:00
    Last input never, output 02:08:46, output hang never
    Last clearing of "show interface" counters never
    Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 6
    Queueing strategy: fifo
    Output queue: 0/40 (size/max)
```

```
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  0 packets input, 0 bytes, 0 no buffer
  Received 0 broadcasts (0 IP multicasts)
  0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  1 packets output, 60 bytes, 0 underruns
  0 output errors, 0 interface resets
  0 output buffer failures, 0 output buffers swapped out
FastEthernet0/1 is up, line protocol is up (connected)
  Hardware is Fast Ethernet, address is 000b.fd20.ba00 (bia
000b.fd20.ba00)
  Internet address is 10.1.4.10/30
  MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Full-duplex, 100Mb/s, media type is 10/100BaseTX
  input flow-control is off, output flow-control is unsupported
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input 00:00:02, output 00:00:03, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  3641 packets input, 319551 bytes, 0 no buffer
  Received 2240 broadcasts (1698 IP multicasts)
  0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog, 2237 multicast, 0 pause input
  0 input packets with dribble condition detected
  3465 packets output, 331141 bytes, 0 underruns
  0 output errors, 0 collisions, 3 interface resets
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier, 0 PAUSE output
  0 output buffer failures, 0 output buffers swapped out
FastEthernet0/2 is administratively down, line protocol is down
(disabled)
  Hardware is Fast Ethernet, address is 000b.fd20.ba02 (bia
000b.fd20.ba02)
  MTU 1500 bytes, BW 10000 Kbit, DLY 1000 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Auto-duplex, Auto-speed, media type is 10/100BaseTX
  input flow-control is off, output flow-control is unsupported
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input never, output never, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
```

```
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  0 packets input, 0 bytes, 0 no buffer
  Received 0 broadcasts (0 multicasts)
  0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog, 0 multicast, 0 pause input
  0 input packets with dribble condition detected
  0 packets output, 0 bytes, 0 underruns
  0 output errors, 0 collisions, 1 interface resets
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier, 0 PAUSE output
  0 output buffer failures, 0 output buffers swapped out
FastEthernet0/3 is down, line protocol is down (notconnect)
  Hardware is Fast Ethernet, address is 000b.fd20.ba03 (bia
000b.fd20.ba03)
  MTU 1500 bytes, BW 10000 Kbit, DLY 1000 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Auto-duplex, Auto-speed, media type is 10/100BaseTX
  input flow-control is off, output flow-control is unsupported
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input never, output never, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  0 packets input, 0 bytes, 0 no buffer
  Received 0 broadcasts (0 multicasts)
  0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog, 0 multicast, 0 pause input
  0 input packets with dribble condition detected
  0 packets output, 0 bytes, 0 underruns
  0 output errors, 0 collisions, 1 interface resets
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier, 0 PAUSE output
  0 output buffer failures, 0 output buffers swapped out
FastEthernet0/4 is administratively down, line protocol is down
(disabled)
  Hardware is Fast Ethernet, address is 000b.fd20.ba04 (bia
000b.fd20.ba04)
  MTU 1500 bytes, BW 10000 Kbit, DLY 1000 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Auto-duplex, Auto-speed, media type is 10/100BaseTX
  input flow-control is off, output flow-control is unsupported
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input never, output never, output hang never
  Last clearing of "show interface" counters never
```

Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
0 packets input, 0 bytes, 0 no buffer
Received 0 broadcasts (0 multicasts)
0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
0 watchdog, 0 multicast, 0 pause input
0 input packets with dribble condition detected
0 packets output, 0 bytes, 0 underruns
0 output errors, 0 collisions, 1 interface resets
0 babbles, 0 late collision, 0 deferred
0 lost carrier, 0 no carrier, 0 PAUSE output
0 output buffer failures, 0 output buffers swapped out
FastEthernet0/5 is administratively down, line protocol is down
(disabled)

Hardware is Fast Ethernet, address is 000b.fd20.ba05 (bia 000b.fd20.ba05)
MTU 1500 bytes, BW 10000 Kbit, DLY 1000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation ARPA, loopback not set
Keepalive set (10 sec)
Auto-duplex, Auto-speed, media type is 10/100BaseTX
input flow-control is off, output flow-control is unsupported
ARP type: ARPA, ARP Timeout 04:00:00
Last input never, output never, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
0 packets input, 0 bytes, 0 no buffer
Received 0 broadcasts (0 multicasts)
0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
0 watchdog, 0 multicast, 0 pause input
0 input packets with dribble condition detected
0 packets output, 0 bytes, 0 underruns
0 output errors, 0 collisions, 1 interface resets
0 babbles, 0 late collision, 0 deferred
0 lost carrier, 0 no carrier, 0 PAUSE output
0 output buffer failures, 0 output buffers swapped out
FastEthernet0/6 is administratively down, line protocol is down
(disabled)

Hardware is Fast Ethernet, address is 000b.fd20.ba06 (bia 000b.fd20.ba06)
MTU 1500 bytes, BW 10000 Kbit, DLY 1000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation ARPA, loopback not set
Keepalive set (10 sec)
Auto-duplex, Auto-speed, media type is 10/100BaseTX

```

input flow-control is off, output flow-control is unsupported
ARP type: ARPA, ARP Timeout 04:00:00
Last input never, output never, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  0 packets input, 0 bytes, 0 no buffer
  Received 0 broadcasts (0 multicasts)
  0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog, 0 multicast, 0 pause input
  0 input packets with dribble condition detected
  0 packets output, 0 bytes, 0 underruns
  0 output errors, 0 collisions, 1 interface resets
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier, 0 PAUSE output
  0 output buffer failures, 0 output buffers swapped out
FastEthernet0/7 is administratively down, line protocol is down
(disabled)
  Hardware is Fast Ethernet, address is 000b.fd20.ba07 (bia
000b.fd20.ba07)
  MTU 1500 bytes, BW 10000 Kbit, DLY 1000 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Auto-duplex, Auto-speed, media type is 10/100BaseTX
input flow-control is off, output flow-control is unsupported
ARP type: ARPA, ARP Timeout 04:00:00
Last input never, output never, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  0 packets input, 0 bytes, 0 no buffer
  Received 0 broadcasts (0 multicasts)
  0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog, 0 multicast, 0 pause input
  0 input packets with dribble condition detected
  0 packets output, 0 bytes, 0 underruns
  0 output errors, 0 collisions, 1 interface resets
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier, 0 PAUSE output
  0 output buffer failures, 0 output buffers swapped out
FastEthernet0/8 is administratively down, line protocol is down
(disabled)
  Hardware is Fast Ethernet, address is 000b.fd20.ba08 (bia
000b.fd20.ba08)
  MTU 1500 bytes, BW 10000 Kbit, DLY 1000 usec,

```

```
    reliability 255/255, txload 1/255, rxload 1/255
Encapsulation ARPA, loopback not set
Keepalive set (10 sec)
Auto-duplex, Auto-speed, media type is 10/100BaseTX
input flow-control is off, output flow-control is unsupported
ARP type: ARPA, ARP Timeout 04:00:00
Last input never, output never, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
    0 packets input, 0 bytes, 0 no buffer
    Received 0 broadcasts (0 multicasts)
    0 runts, 0 giants, 0 throttles
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
    0 watchdog, 0 multicast, 0 pause input
    0 input packets with dribble condition detected
    0 packets output, 0 bytes, 0 underruns
    0 output errors, 0 collisions, 1 interface resets
    0 babbles, 0 late collision, 0 deferred
    0 lost carrier, 0 no carrier, 0 PAUSE output
    0 output buffer failures, 0 output buffers swapped out
FastEthernet0/9 is administratively down, line protocol is down
(disabled)
    Hardware is Fast Ethernet, address is 000b.fd20.ba09 (bia
000b.fd20.ba09)
    MTU 1500 bytes, BW 10000 Kbit, DLY 1000 usec,
        reliability 255/255, txload 1/255, rxload 1/255
Encapsulation ARPA, loopback not set
Keepalive set (10 sec)
Auto-duplex, Auto-speed, media type is 10/100BaseTX
input flow-control is off, output flow-control is unsupported
ARP type: ARPA, ARP Timeout 04:00:00
Last input never, output never, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
    0 packets input, 0 bytes, 0 no buffer
    Received 0 broadcasts (0 multicasts)
    0 runts, 0 giants, 0 throttles
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
    0 watchdog, 0 multicast, 0 pause input
    0 input packets with dribble condition detected
    0 packets output, 0 bytes, 0 underruns
    0 output errors, 0 collisions, 1 interface resets
    0 babbles, 0 late collision, 0 deferred
    0 lost carrier, 0 no carrier, 0 PAUSE output
    0 output buffer failures, 0 output buffers swapped out
```

```
FastEthernet0/10 is administratively down, line protocol is down
(disabled)
  Hardware is Fast Ethernet, address is 000b.fd20.ba0a (bia
000b.fd20.ba0a)
  MTU 1500 bytes, BW 10000 Kbit, DLY 1000 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Auto-duplex, Auto-speed, media type is 10/100BaseTX
  input flow-control is off, output flow-control is unsupported
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input never, output never, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
  5 minute input rate 0 bits/sec, 0 packets/sec
  5 minute output rate 0 bits/sec, 0 packets/sec
    0 packets input, 0 bytes, 0 no buffer
    Received 0 broadcasts (0 multicasts)
    0 runts, 0 giants, 0 throttles
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
    0 watchdog, 0 multicast, 0 pause input
    0 input packets with dribble condition detected
    0 packets output, 0 bytes, 0 underruns
    0 output errors, 0 collisions, 1 interface resets
    0 babbles, 0 late collision, 0 deferred
    0 lost carrier, 0 no carrier, 0 PAUSE output
    0 output buffer failures, 0 output buffers swapped out
FastEthernet0/11 is administratively down, line protocol is down
(disabled)
  Hardware is Fast Ethernet, address is 000b.fd20.ba0b (bia
000b.fd20.ba0b)
  MTU 1500 bytes, BW 10000 Kbit, DLY 1000 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Auto-duplex, Auto-speed, media type is 10/100BaseTX
  input flow-control is off, output flow-control is unsupported
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input never, output never, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
  5 minute input rate 0 bits/sec, 0 packets/sec
  5 minute output rate 0 bits/sec, 0 packets/sec
    0 packets input, 0 bytes, 0 no buffer
    Received 0 broadcasts (0 multicasts)
    0 runts, 0 giants, 0 throttles
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
    0 watchdog, 0 multicast, 0 pause input
    0 input packets with dribble condition detected
    0 packets output, 0 bytes, 0 underruns
```

```

    0 output errors, 0 collisions, 1 interface resets
    0 babbles, 0 late collision, 0 deferred
    0 lost carrier, 0 no carrier, 0 PAUSE output
    0 output buffer failures, 0 output buffers swapped out
FastEthernet0/12 is administratively down, line protocol is down
(disabled)
  Hardware is Fast Ethernet, address is 000b.fd20.ba0c (bia
000b.fd20.ba0c)
  MTU 1500 bytes, BW 10000 Kbit, DLY 1000 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Auto-duplex, Auto-speed, media type is 10/100BaseTX
  input flow-control is off, output flow-control is unsupported
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input never, output never, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
  5 minute input rate 0 bits/sec, 0 packets/sec
  5 minute output rate 0 bits/sec, 0 packets/sec
    0 packets input, 0 bytes, 0 no buffer
    Received 0 broadcasts (0 multicasts)
    0 runts, 0 giants, 0 throttles
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
    0 watchdog, 0 multicast, 0 pause input
    0 input packets with dribble condition detected
    0 packets output, 0 bytes, 0 underruns
    0 output errors, 0 collisions, 1 interface resets
    0 babbles, 0 late collision, 0 deferred
    0 lost carrier, 0 no carrier, 0 PAUSE output
    0 output buffer failures, 0 output buffers swapped out
FastEthernet0/13 is administratively down, line protocol is down
(disabled)
  Hardware is Fast Ethernet, address is 000b.fd20.ba0d (bia
000b.fd20.ba0d)
  MTU 1500 bytes, BW 10000 Kbit, DLY 1000 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Auto-duplex, Auto-speed, media type is 10/100BaseTX
  input flow-control is off, output flow-control is unsupported
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input never, output never, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
  5 minute input rate 0 bits/sec, 0 packets/sec
  5 minute output rate 0 bits/sec, 0 packets/sec
    0 packets input, 0 bytes, 0 no buffer
    Received 0 broadcasts (0 multicasts)
    0 runts, 0 giants, 0 throttles

```

```

    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
    0 watchdog, 0 multicast, 0 pause input
    0 input packets with dribble condition detected
    0 packets output, 0 bytes, 0 underruns
    0 output errors, 0 collisions, 1 interface resets
    0 babbles, 0 late collision, 0 deferred
    0 lost carrier, 0 no carrier, 0 PAUSE output
    0 output buffer failures, 0 output buffers swapped out
FastEthernet0/14 is administratively down, line protocol is down
(disabled)
  Hardware is Fast Ethernet, address is 000b.fd20.ba0e (bia
000b.fd20.ba0e)
  MTU 1500 bytes, BW 10000 Kbit, DLY 1000 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Auto-duplex, Auto-speed, media type is 10/100BaseTX
  input flow-control is off, output flow-control is unsupported
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input never, output never, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
  5 minute input rate 0 bits/sec, 0 packets/sec
  5 minute output rate 0 bits/sec, 0 packets/sec
    0 packets input, 0 bytes, 0 no buffer
    Received 0 broadcasts (0 multicasts)
    0 runts, 0 giants, 0 throttles
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
    0 watchdog, 0 multicast, 0 pause input
    0 input packets with dribble condition detected
    0 packets output, 0 bytes, 0 underruns
    0 output errors, 0 collisions, 1 interface resets
    0 babbles, 0 late collision, 0 deferred
    0 lost carrier, 0 no carrier, 0 PAUSE output
    0 output buffer failures, 0 output buffers swapped out
FastEthernet0/15 is down, line protocol is down (notconnect)
  Hardware is Fast Ethernet, address is 000b.fd20.ba0f (bia
000b.fd20.ba0f)
  MTU 1500 bytes, BW 10000 Kbit, DLY 1000 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Auto-duplex, Auto-speed, media type is 10/100BaseTX
  input flow-control is off, output flow-control is unsupported
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input never, output never, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
  5 minute input rate 0 bits/sec, 0 packets/sec
  5 minute output rate 0 bits/sec, 0 packets/sec

```

```
0 packets input, 0 bytes, 0 no buffer
Received 0 broadcasts (0 multicasts)
0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
0 watchdog, 0 multicast, 0 pause input
0 input packets with dribble condition detected
0 packets output, 0 bytes, 0 underruns
0 output errors, 0 collisions, 1 interface resets
0 babbles, 0 late collision, 0 deferred
0 lost carrier, 0 no carrier, 0 PAUSE output
0 output buffer failures, 0 output buffers swapped out
FastEthernet0/16 is up, line protocol is up (connected)
Hardware is Fast Ethernet, address is 000b.fd20.ba10 (bia
000b.fd20.ba10)
MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
Encapsulation ARPA, loopback not set
Keepalive set (10 sec)
Full-duplex, 100Mb/s, media type is 10/100BaseTX
input flow-control is off, output flow-control is unsupported
ARP type: ARPA, ARP Timeout 04:00:00
Last input 00:00:01, output 00:00:01, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
1460 packets input, 147507 bytes, 0 no buffer
Received 681 broadcasts (0 multicasts)
0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
0 watchdog, 681 multicast, 0 pause input
0 input packets with dribble condition detected
3654 packets output, 327928 bytes, 0 underruns
0 output errors, 0 collisions, 1 interface resets
0 babbles, 0 late collision, 0 deferred
0 lost carrier, 0 no carrier, 0 PAUSE output
0 output buffer failures, 0 output buffers swapped out
FastEthernet0/17 is up, line protocol is up (connected)
Hardware is Fast Ethernet, address is 000b.fd20.ba11 (bia
000b.fd20.ba11)
MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
Encapsulation ARPA, loopback not set
Keepalive set (10 sec)
Full-duplex, 100Mb/s, media type is 10/100BaseTX
input flow-control is off, output flow-control is unsupported
ARP type: ARPA, ARP Timeout 04:00:00
Last input 00:00:02, output 00:00:02, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
```

```

5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  7453 packets input, 608607 bytes, 0 no buffer
  Received 6557 broadcasts (0 multicasts)
  0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog, 6554 multicast, 0 pause input
  0 input packets with dribble condition detected
  1493 packets output, 149898 bytes, 0 underruns
  0 output errors, 0 collisions, 1 interface resets
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier, 0 PAUSE output
  0 output buffer failures, 0 output buffers swapped out
FastEthernet0/18 is up, line protocol is up (connected)
  Hardware is Fast Ethernet, address is 000b.fd20.ba12 (bia
000b.fd20.ba12)
  MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Full-duplex, 100Mb/s, media type is 10/100BaseTX
  input flow-control is off, output flow-control is unsupported
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input 00:00:04, output 00:00:03, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  1461 packets input, 147597 bytes, 0 no buffer
  Received 682 broadcasts (0 multicasts)
  0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog, 682 multicast, 0 pause input
  0 input packets with dribble condition detected
  5362 packets output, 426958 bytes, 0 underruns
  0 output errors, 0 collisions, 1 interface resets
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier, 0 PAUSE output
  0 output buffer failures, 0 output buffers swapped out
FastEthernet0/19 is up, line protocol is up (connected)
  Hardware is Fast Ethernet, address is 000b.fd20.ba13 (bia
000b.fd20.ba13)
  MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Full-duplex, 100Mb/s, media type is 10/100BaseTX
  input flow-control is off, output flow-control is unsupported
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input 00:00:06, output 00:00:05, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0

```

```
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 1000 bits/sec, 2 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  9599 packets input, 802029 bytes, 0 no buffer
  Received 8732 broadcasts (0 multicasts)
  0 runs, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog, 8388 multicast, 0 pause input
  0 input packets with dribble condition detected
  6321 packets output, 528909 bytes, 0 underruns
  0 output errors, 0 collisions, 1 interface resets
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier, 0 PAUSE output
  0 output buffer failures, 0 output buffers swapped out
FastEthernet0/20 is up, line protocol is up (connected)
  Hardware is Fast Ethernet, address is 000b.fd20.ba14 (bia
000b.fd20.ba14)
  MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Full-duplex, 100Mb/s, media type is 10/100BaseTX
  input flow-control is off, output flow-control is unsupported
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input 00:00:07, output 00:00:06, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
  5 minute input rate 0 bits/sec, 0 packets/sec
  5 minute output rate 0 bits/sec, 0 packets/sec
    1467 packets input, 159101 bytes, 0 no buffer
    Received 683 broadcasts (0 multicasts)
    0 runs, 0 giants, 0 throttles
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
    0 watchdog, 683 multicast, 0 pause input
    0 input packets with dribble condition detected
    1651 packets output, 173024 bytes, 0 underruns
    0 output errors, 0 collisions, 1 interface resets
    0 babbles, 0 late collision, 0 deferred
    0 lost carrier, 0 no carrier, 0 PAUSE output
    0 output buffer failures, 0 output buffers swapped out
FastEthernet0/21 is up, line protocol is up (connected)
  Hardware is Fast Ethernet, address is 000b.fd20.ba15 (bia
000b.fd20.ba15)
  MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Full-duplex, 100Mb/s, media type is 10/100BaseTX
  input flow-control is off, output flow-control is unsupported
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input 00:00:04, output 00:00:04, output hang never
```

```

Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  1464 packets input, 158687 bytes, 0 no buffer
  Received 684 broadcasts (0 multicasts)
  0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog, 684 multicast, 0 pause input
  0 input packets with dribble condition detected
  3970 packets output, 338030 bytes, 0 underruns
  0 output errors, 0 collisions, 1 interface resets
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier, 0 PAUSE output
  0 output buffer failures, 0 output buffers swapped out
FastEthernet0/22 is up, line protocol is up (connected)
  Hardware is Fast Ethernet, address is 000b.fd20.ba00 (bia 000b.fd20.ba00)
  MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Full-duplex, 100Mb/s, media type is 10/100BaseTX
  input flow-control is off, output flow-control is unsupported
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input 00:00:00, output 00:00:02, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
  5 minute input rate 0 bits/sec, 0 packets/sec
  5 minute output rate 0 bits/sec, 0 packets/sec
    3379 packets input, 324702 bytes, 0 no buffer
    Received 2245 broadcasts (0 multicasts)
    0 runts, 0 giants, 0 throttles
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
    0 watchdog, 2245 multicast, 0 pause input
    0 input packets with dribble condition detected
    3379 packets output, 305303 bytes, 0 underruns
    0 output errors, 0 collisions, 3 interface resets
    0 babbles, 0 late collision, 0 deferred
    0 lost carrier, 0 no carrier, 0 PAUSE output
    0 output buffer failures, 0 output buffers swapped out
FastEthernet0/23 is up, line protocol is up (connected)
  Hardware is Fast Ethernet, address is 000b.fd20.ba00 (bia 000b.fd20.ba00)
  MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Full-duplex, 100Mb/s, media type is 10/100BaseTX
  input flow-control is off, output flow-control is unsupported

```

```
ARP type: ARPA, ARP Timeout 04:00:00
Last input 00:00:01, output 00:00:03, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  917 packets input, 100670 bytes, 0 no buffer
  Received 132 broadcasts (0 multicasts)
  0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog, 132 multicast, 0 pause input
  0 input packets with dribble condition detected
  914 packets output, 103520 bytes, 0 underruns
  0 output errors, 0 collisions, 3 interface resets
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier, 0 PAUSE output
  0 output buffer failures, 0 output buffers swapped out
FastEthernet0/24 is up, line protocol is up (connected)
  Hardware is Fast Ethernet, address is 000b.fd20.ba00 (bia
000b.fd20.ba00)
  MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Full-duplex, 100Mb/s, media type is 10/100BaseTX
  input flow-control is off, output flow-control is unsupported
ARP type: ARPA, ARP Timeout 04:00:00
Last input 00:00:03, output 00:00:05, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  912 packets input, 100080 bytes, 0 no buffer
  Received 132 broadcasts (0 multicasts)
  0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog, 132 multicast, 0 pause input
  0 input packets with dribble condition detected
  914 packets output, 103520 bytes, 0 underruns
  0 output errors, 0 collisions, 3 interface resets
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier, 0 PAUSE output
  0 output buffer failures, 0 output buffers swapped out
GigabitEthernet0/1 is administratively down, line protocol is down
(disabled)
  Hardware is Gigabit Ethernet, address is 000b.fd20.ba19 (bia
000b.fd20.ba19)
  MTU 1500 bytes, BW 10000 Kbit, DLY 1000 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
```

```

Keepalive not set
Auto-duplex, Auto-speed, link type is auto, media type is unknown
input flow-control is off, output flow-control is off
ARP type: ARPA, ARP Timeout 04:00:00
Last input never, output never, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  0 packets input, 0 bytes, 0 no buffer
  Received 0 broadcasts (0 multicasts)
  0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog, 0 multicast, 0 pause input
  0 input packets with dribble condition detected
  0 packets output, 0 bytes, 0 underruns
  0 output errors, 0 collisions, 1 interface resets
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier, 0 PAUSE output
  0 output buffer failures, 0 output buffers swapped out
GigabitEthernet0/2 is administratively down, line protocol is down
(disabled)
  Hardware is Gigabit Ethernet, address is 000b.fd20.bala (bia
000b.fd20.bala)
  MTU 1500 bytes, BW 10000 Kbit, DLY 1000 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive not set
  Auto-duplex, Auto-speed, link type is auto, media type is unknown
  input flow-control is off, output flow-control is off
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input never, output never, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
  5 minute input rate 0 bits/sec, 0 packets/sec
  5 minute output rate 0 bits/sec, 0 packets/sec
    0 packets input, 0 bytes, 0 no buffer
    Received 0 broadcasts (0 multicasts)
    0 runts, 0 giants, 0 throttles
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
    0 watchdog, 0 multicast, 0 pause input
    0 input packets with dribble condition detected
    0 packets output, 0 bytes, 0 underruns
    0 output errors, 0 collisions, 1 interface resets
    0 babbles, 0 late collision, 0 deferred
    0 lost carrier, 0 no carrier, 0 PAUSE output
    0 output buffer failures, 0 output buffers swapped out
Port-channel12 is up, line protocol is up (connected)
  Hardware is EtherChannel, address is 000b.fd20.ba00 (bia
000b.fd20.ba00)

```

```
Internet address is 10.2.4.14/30
MTU 1500 bytes, BW 300000 Kbit, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
Encapsulation ARPA, loopback not set
Keepalive set (10 sec)
Full-duplex, 100Mb/s, media type is 10/100BaseTX
input flow-control is off, output flow-control is unsupported
Members in this channel: Fa0/22 Fa0/23 Fa0/24
ARP type: ARPA, ARP Timeout 04:00:00
Last input 00:00:02, output 00:00:01, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 1000 bits/sec, 1 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
    5211 packets input, 525672 bytes, 0 no buffer
    Received 2511 broadcasts (1718 IP multicasts)
    0 runs, 0 giants, 0 throttles
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
    0 watchdog, 2510 multicast, 0 pause input
    0 input packets with dribble condition detected
    5212 packets output, 512727 bytes, 0 underruns
    0 output errors, 0 collisions, 4 interface resets
    0 babbles, 0 late collision, 0 deferred
    0 lost carrier, 0 no carrier, 0 PAUSE output
    0 output buffer failures, 0 output buffers swapped out
Port-channel23 is up, line protocol is up (connected)
  Hardware is EtherChannel, address is 000b.fd20.ba13 (bia
000b.fd20.ba13)
  MTU 1500 bytes, BW 300000 Kbit, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Full-duplex, 100Mb/s, media type is 10/100BaseTX
  input flow-control is off, output flow-control is unsupported
  Members in this channel: Fa0/19 Fa0/20 Fa0/21
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input 00:00:00, output 00:38:54, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
  5 minute input rate 1000 bits/sec, 2 packets/sec
  5 minute output rate 0 bits/sec, 0 packets/sec
    12532 packets input, 1119629 bytes, 0 no buffer
    Received 10101 broadcasts (0 multicasts)
    0 runs, 0 giants, 0 throttles
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
    0 watchdog, 9754 multicast, 0 pause input
    0 input packets with dribble condition detected
    11926 packets output, 1038293 bytes, 0 underruns
    0 output errors, 0 collisions, 1 interface resets
    0 babbles, 0 late collision, 0 deferred
```

```
    0 lost carrier, 0 no carrier, 0 PAUSE output
    0 output buffer failures, 0 output buffers swapped out
Port-channel24 is up, line protocol is up (connected)
  Hardware is EtherChannel, address is 000b.fd20.ba11 (bia
000b.fd20.ba11)
  MTU 1500 bytes, BW 300000 Kbit, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Full-duplex, 100Mb/s, media type is 10/100BaseTX
  input flow-control is off, output flow-control is unsupported
  Members in this channel: Fa0/16 Fa0/17 Fa0/18
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input 00:00:00, output 00:00:00, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
  5 minute input rate 0 bits/sec, 0 packets/sec
  5 minute output rate 0 bits/sec, 0 packets/sec
    10380 packets input, 904213 bytes, 0 no buffer
    Received 7920 broadcasts (0 multicasts)
    0 runts, 0 giants, 0 throttles
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
    0 watchdog, 7919 multicast, 0 pause input
    0 input packets with dribble condition detected
    10514 packets output, 906190 bytes, 0 underruns
    0 output errors, 0 collisions, 1 interface resets
    0 babbles, 0 late collision, 0 deferred
    0 lost carrier, 0 no carrier, 0 PAUSE output
    0 output buffer failures, 0 output buffers swapped out
Tunnel67 is up, line protocol is up
  Hardware is Tunnel
  MTU 1514 bytes, BW 100 Kbit, DLY 50000 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation TUNNEL, loopback not set
  Keepalive not set
  Tunnel source 10.2.4.14, destination 10.2.4.13
  Tunnel protocol/transport GRE/IP, key disabled, sequencing disabled
  Tunnel TTL 255
  Checksumming of packets disabled
  Last input 00:00:15, output 00:00:06, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/0 (size/max)
  5 minute input rate 0 bits/sec, 0 packets/sec
  5 minute output rate 0 bits/sec, 0 packets/sec
    289 packets input, 49712 bytes, 0 no buffer
    Received 0 broadcasts (0 IP multicasts)
    0 runts, 0 giants, 0 throttles
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
    289 packets output, 27712 bytes, 0 underruns
    0 output errors, 0 collisions, 0 interface resets
```

0 output buffer failures, 0 output buffers swapped out
DSW2#

DSW2#show interfaces counters errors

Port	Align-Err	FCS-Err	Xmit-Err	Rcv-Err	UnderSize
Fa0/1	0	0	0	0	0
Fa0/2	0	0	0	0	0
Fa0/3	0	0	0	0	0
Fa0/4	0	0	0	0	0
Fa0/5	0	0	0	0	0
Fa0/6	0	0	0	0	0

Fa0/7	0	0	0	0	0
Fa0/8	0	0	0	0	0
Fa0/9	0	0	0	0	0
Fa0/10	0	0	0	0	0
Fa0/11	0	0	0	0	0
Fa0/12	0	0	0	0	0
Fa0/13	0	0	0	0	0
Fa0/14	0	0	0	0	0
Fa0/15	0	0	0	0	0
Fa0/16	0	0	0	0	0
Fa0/17	0	0	0	0	0
Fa0/18	0	0	0	0	0
Fa0/19	0	0	0	0	0
Fa0/20	0	0	0	0	0
Fa0/21	0	0	0	0	0
Fa0/22	0	0	0	0	0
Fa0/23	0	0	0	0	0
Fa0/24	0	0	0	0	0
Gi0/1	0	0	0	0	0
Gi0/2	0	0	0	0	0
Po12	0	0	0	0	0
Po23	0	0	0	0	0
Po24	0	0	0	0	0

Port	Single-Col	Multi-Col	Late-Col	Excess-Col	Carri-Sen	Runts
Giants						
Fa0/1	0	0	0	0	0	0
0						
Fa0/2	0	0	0	0	0	0
0						
Fa0/3	0	0	0	0	0	0
0						
Fa0/4	0	0	0	0	0	0
0						
Fa0/5	0	0	0	0	0	0
0						
Fa0/6	0	0	0	0	0	0
0						
Fa0/7	0	0	0	0	0	0
0						
Fa0/8	0	0	0	0	0	0
0						
Fa0/9	0	0	0	0	0	0
0						
Fa0/10	0	0	0	0	0	0
0						
Fa0/11	0	0	0	0	0	0
0						
Fa0/12	0	0	0	0	0	0
0						
Fa0/13	0	0	0	0	0	0
0						
Fa0/14	0	0	0	0	0	0
0						

Fa0/15	0	0	0	0	0	0
0						
Fa0/16	0	0	0	0	0	0
0						
Fa0/17	0	0	0	0	0	0
0						
Fa0/18	0	0	0	0	0	0
0						
Fa0/19	0	0	0	0	0	0
0						
Fa0/20	0	0	0	0	0	0
0						
Fa0/21	0	0	0	0	0	0
0						
Fa0/22	0	0	0	0	0	0
0						
Fa0/23	0	0	0	0	0	0
0						
Fa0/24	0	0	0	0	0	0
0						
Gi0/1	0	0	0	0	0	0
0						
Gi0/2	0	0	0	0	0	0
0						
Po12	0	0	0	0	0	0
0						
Po23	0	0	0	0	0	0
0						
Po24	0	0	0	0	0	0
0						
DSW2#						

DSW2#show cdp neighbors

Capability Codes: R - Router, T - Trans Bridge, B - Source Route Bridge
S - Switch, H - Host, I - IGMP, r - Repeater, P - Phone

Device ID	Local Intrfce	Holdtme	Capability	Platform	Port
ID					
R4	Fas 0/1	153	R S I	1841	Fas
0/1					
DSW1	Fas 0/24	154	R S I	WS-C3550-	Fas
0/24					
DSW1	Fas 0/23	154	R S I	WS-C3550-	Fas
0/23					
DSW1	Fas 0/22	154	R S I	WS-C3550-	Fas
0/22					
ASW1	Fas 0/21	142	S I	WS-C2950-	Fas
0/18					
ASW1	Fas 0/20	142	S I	WS-C2950-	Fas
0/17					
ASW1	Fas 0/19	142	S I	WS-C2950-	Fas
0/16					
ASW2	Fas 0/18	143	S I	WS-C2950-	Fas
0/21					
ASW2	Fas 0/16	143	S I	WS-C2950-	Fas
0/19					
ASW2	Fas 0/17	143	S I	WS-C2950-	Fas
0/20					
DSW2#					

DSW2#show cdp neighbors detail

Device ID: R4

Entry address(es):

IP address: 10.1.4.9

Platform: Cisco 1841, Capabilities: Router Switch IGMP

Interface: FastEthernet0/1, Port ID (outgoing port): FastEthernet0/1

Holdtime : 144 sec

Version :

Cisco IOS Software, 1841 Software (C1841-ADVIPSERVICESK9-M), Version 12.4(25b), RELEASE SOFTWARE (fc1)

Technical Support: <http://www.cisco.com/techsupport>

Copyright (c) 1986-2009 by Cisco Systems, Inc.

Compiled Wed 12-Aug-09 10:49 by prod_rel_team

advertisement version: 2

VTP Management Domain: ''

Duplex: full
Management address(es):

Device ID: DSW1
Entry address(es):
 IP address: 10.2.4.13
Platform: Cisco WS-C3550-24, Capabilities: Router Switch IGMP
Interface: FastEthernet0/24, Port ID (outgoing port): FastEthernet0/24
Holdtime : 145 sec

Version :
Cisco IOS Software, C3550 Software (C3550-IPSERVICESK9-M), Version
12.2(44)SE6, RELEASE SOFTWARE (fc1)
Copyright (c) 1986-2009 by Cisco Systems, Inc.
Compiled Mon 09-Mar-09 20:28 by gereddy

advertisement version: 2
Protocol Hello: OUI=0x00000C, Protocol ID=0x0112; payload len=27,
value=00000000FFFFFFFFF0102250C0000000000000000DBDE36E00FF0000
VTP Management Domain: 'netlearning'
Duplex: full
Management address(es):
 IP address: 10.2.4.13

Device ID: DSW1
Entry address(es):
 IP address: 10.2.4.13
Platform: Cisco WS-C3550-24, Capabilities: Router Switch IGMP
Interface: FastEthernet0/23, Port ID (outgoing port): FastEthernet0/23
Holdtime : 143 sec

Version :
Cisco IOS Software, C3550 Software (C3550-IPSERVICESK9-M), Version
12.2(44)SE6, RELEASE SOFTWARE (fc1)
Copyright (c) 1986-2009 by Cisco Systems, Inc.
Compiled Mon 09-Mar-09 20:28 by gereddy

advertisement version: 2
Protocol Hello: OUI=0x00000C, Protocol ID=0x0112; payload len=27,
value=00000000FFFFFFFFF0102250C0000000000000000DBDE36E00FF0000
VTP Management Domain: 'netlearning'
Duplex: full
Management address(es):
 IP address: 10.2.4.13

Device ID: DSW1
Entry address(es):
 IP address: 10.2.4.13
Platform: Cisco WS-C3550-24, Capabilities: Router Switch IGMP
Interface: FastEthernet0/22, Port ID (outgoing port): FastEthernet0/22
Holdtime : 143 sec

Version :
Cisco IOS Software, C3550 Software (C3550-IPSERVICESK9-M), Version
12.2(44)SE6, RELEASE SOFTWARE (fc1)
Copyright (c) 1986-2009 by Cisco Systems, Inc.
Compiled Mon 09-Mar-09 20:28 by gereddy

advertisement version: 2
Protocol Hello: OUI=0x00000C, Protocol ID=0x0112; payload len=27,
value=00000000FFFFFFFFF0102250C0000000000000000DBDE36E00FF0000
VTP Management Domain: 'netlearning'
Duplex: full
Management address(es):
IP address: 10.2.4.13

Device ID: ASW1
Entry address(es):
IP address: 192.168.1.131
Platform: cisco WS-C2950-24, Capabilities: Switch IGMP
Interface: FastEthernet0/21, Port ID (outgoing port): FastEthernet0/18
Holdtime : 131 sec

Version :
Cisco Internetwork Operating System Software
IOS (tm) C2950 Software (C2950-I6Q4L2-M), Version 12.1(22)EA4a, RELEASE
SOFTWARE (fc1)
Copyright (c) 1986-2005 by cisco Systems, Inc.
Compiled Fri 16-Sep-05 10:46 by yenanh

advertisement version: 2
Protocol Hello: OUI=0x00000C, Protocol ID=0x0112; payload len=27,
value=00000000FFFFFFFFF0102250200000000000000015FAAC46C0FF0000
VTP Management Domain: 'netlearning'
Native VLAN: 1
Duplex: full
Management address(es):
IP address: 192.168.1.131

Device ID: ASW1
Entry address(es):
IP address: 192.168.1.131
Platform: cisco WS-C2950-24, Capabilities: Switch IGMP
Interface: FastEthernet0/20, Port ID (outgoing port): FastEthernet0/17
Holdtime : 130 sec

Version :
Cisco Internetwork Operating System Software
IOS (tm) C2950 Software (C2950-I6Q4L2-M), Version 12.1(22)EA4a, RELEASE
SOFTWARE (fc1)
Copyright (c) 1986-2005 by cisco Systems, Inc.
Compiled Fri 16-Sep-05 10:46 by yenanh

advertisement version: 2
Protocol Hello: OUI=0x00000C, Protocol ID=0x0112; payload len=27,
value=00000000FFFFFFFFF010225020000000000000015FAAC46C0FF0000
VTP Management Domain: 'netlearning'
Native VLAN: 1
Duplex: full
Management address(es):
 IP address: 192.168.1.131

Device ID: ASW1
Entry address(es):
 IP address: 192.168.1.131
Platform: cisco WS-C2950-24, Capabilities: Switch IGMP
Interface: FastEthernet0/19, Port ID (outgoing port): FastEthernet0/16
Holdtime : 130 sec

Version :
Cisco Internetwork Operating System Software
IOS (tm) C2950 Software (C2950-I6Q4L2-M), Version 12.1(22)EA4a, RELEASE
SOFTWARE (fc1)
Copyright (c) 1986-2005 by cisco Systems, Inc.
Compiled Fri 16-Sep-05 10:46 by yenanh

advertisement version: 2
Protocol Hello: OUI=0x00000C, Protocol ID=0x0112; payload len=27,
value=00000000FFFFFFFFF010225020000000000000015FAAC46C0FF0000
VTP Management Domain: 'netlearning'
Native VLAN: 1
Duplex: full
Management address(es):
 IP address: 192.168.1.131

Device ID: ASW2
Entry address(es):
 IP address: 192.168.1.132
Platform: cisco WS-C2950-24, Capabilities: Switch IGMP
Interface: FastEthernet0/18, Port ID (outgoing port): FastEthernet0/21
Holdtime : 129 sec

Version :
Cisco Internetwork Operating System Software
IOS (tm) C2950 Software (C2950-I6Q4L2-M), Version 12.1(22)EA4a, RELEASE
SOFTWARE (fc1)
Copyright (c) 1986-2005 by cisco Systems, Inc.
Compiled Fri 16-Sep-05 10:46 by yenanh

advertisement version: 2
Protocol Hello: OUI=0x00000C, Protocol ID=0x0112; payload len=27,
value=00000000FFFFFFFFF010225010000000000000015FAB82880FF0000
VTP Management Domain: 'netlearning'
Native VLAN: 1
Duplex: full

Management address(es):
IP address: 192.168.1.132

Device ID: ASW2
Entry address(es):
IP address: 192.168.1.132
Platform: cisco WS-C2950-24, Capabilities: Switch IGMP
Interface: FastEthernet0/16, Port ID (outgoing port): FastEthernet0/19
Holdtime : 128 sec

Version :
Cisco Internetwork Operating System Software
IOS (tm) C2950 Software (C2950-I6Q4L2-M), Version 12.1(22)EA4a, RELEASE
SOFTWARE (fc1)
Copyright (c) 1986-2005 by cisco Systems, Inc.
Compiled Fri 16-Sep-05 10:46 by yenanh

advertisement version: 2
Protocol Hello: OUI=0x00000C, Protocol ID=0x0112; payload len=27,
value=00000000FFFFFFFFF010225010000000000000015FAB82880FF0000
VTP Management Domain: 'netlearning'
Native VLAN: 1
Duplex: full
Management address(es):
IP address: 192.168.1.132

Device ID: ASW2
Entry address(es):
IP address: 192.168.1.132
Platform: cisco WS-C2950-24, Capabilities: Switch IGMP
Interface: FastEthernet0/17, Port ID (outgoing port): FastEthernet0/20
Holdtime : 127 sec

Version :
Cisco Internetwork Operating System Software
IOS (tm) C2950 Software (C2950-I6Q4L2-M), Version 12.1(22)EA4a, RELEASE
SOFTWARE (fc1)
Copyright (c) 1986-2005 by cisco Systems, Inc.
Compiled Fri 16-Sep-05 10:46 by yenanh

advertisement version: 2
Protocol Hello: OUI=0x00000C, Protocol ID=0x0112; payload len=27,
value=00000000FFFFFFFFF010225010000000000000015FAB82880FF0000
VTP Management Domain: 'netlearning'
Native VLAN: 1
Duplex: full
Management address(es):
IP address: 192.168.1.132

DSW2#

DSW2#show arp

Protocol	Address	Age (min)	Hardware Addr	Type	Interface
Internet	10.2.4.13	130	000d.bde3.6e00	ARPA	Port-
channel12					
Internet	10.2.4.14	-	000b.fd20.ba00	ARPA	Port-
channel12					
Internet	10.1.4.10	-	000b.fd20.ba00	ARPA	
FastEthernet0/1					
Internet	10.1.4.9	130	0019.5578.1cb3	ARPA	
FastEthernet0/1					
Internet	10.2.2.2	122	000d.bde3.6e00	ARPA	Vlan20
Internet	10.2.1.1	37	000d.bde3.6e00	ARPA	Vlan10
Internet	10.2.2.1	-	000b.fd20.ba00	ARPA	Vlan20

Internet	10.2.1.2	-	000b.fd20.ba00	ARPA	Vlan10
Internet	10.2.1.4	2	001c.238e.dbbc	ARPA	Vlan10
Internet	192.168.1.130	-	000b.fd20.ba00	ARPA	Vlan200
Internet	10.2.1.254	21	0000.0c07.ac0a	ARPA	Vlan10

DSW2#

DSW2#show ip arp

Protocol	Address	Age (min)	Hardware Addr	Type	Interface
Internet	10.2.4.13	130	000d.bde3.6e00	ARPA	Port-
channel12					
Internet	10.2.4.14	-	000b.fd20.ba00	ARPA	Port-
channel12					

Internet	10.1.4.10	-	000b.fd20.ba00	ARPA	
FastEthernet0/1					
Internet	10.1.4.9	130	0019.5578.1cb3	ARPA	
FastEthernet0/1					
Internet	10.2.2.2	122	000d.bde3.6e00	ARPA	Vlan20
Internet	10.2.1.1	37	000d.bde3.6e00	ARPA	Vlan10
Internet	10.2.2.1	-	000b.fd20.ba00	ARPA	Vlan20
Internet	10.2.1.2	-	000b.fd20.ba00	ARPA	Vlan10
Internet	10.2.1.4	2	001c.238e.dbbc	ARPA	Vlan10
Internet	192.168.1.130	-	000b.fd20.ba00	ARPA	Vlan200
Internet	10.2.1.254	21	0000.0c07.ac0a	ARPA	Vlan10

DSW2#

```
DSW2#show ip interface
Vlan1 is administratively down, line protocol is down
  Internet protocol processing disabled
Vlan10 is up, line protocol is up
  Internet address is 10.2.1.2/24
  Broadcast address is 255.255.255.255
  Address determined by non-volatile memory
  MTU is 1500 bytes
  Helper address is 10.1.4.9
  Directed broadcast forwarding is disabled
  Multicast reserved groups joined: 224.0.0.1 224.0.0.2 224.0.0.22
224.0.0.13
    224.0.0.10
  Outgoing access list is not set
  Inbound access list is not set
  Proxy ARP is enabled
  Local Proxy ARP is disabled
  Security level is default
  Split horizon is enabled
  ICMP redirects are always sent
  ICMP unreachable are always sent
  ICMP mask replies are never sent
  IP fast switching is enabled
  IP CEF switching is enabled
  IP CEF switching turbo vector
  IP Null turbo vector
  IP multicast fast switching is enabled
  IP multicast distributed fast switching is disabled
  IP route-cache flags are Fast, CEF
  Router Discovery is disabled
  IP output packet accounting is disabled
  IP access violation accounting is disabled
  TCP/IP header compression is disabled
  RTP/IP header compression is disabled
  Probe proxy name replies are disabled
  Policy routing is disabled
  Network address translation is disabled
  BGP Policy Mapping is disabled
  WCCP Redirect outbound is disabled
  WCCP Redirect inbound is disabled
  WCCP Redirect exclude is disabled
Vlan20 is up, line protocol is up
  Internet address is 10.2.2.1/24
  Broadcast address is 255.255.255.255
  Address determined by non-volatile memory
  MTU is 1500 bytes
  Helper address is not set
  Directed broadcast forwarding is disabled
  Multicast reserved groups joined: 224.0.0.1 224.0.0.2 224.0.0.22
224.0.0.13
    224.0.0.10
  Outgoing access list is not set
  Inbound access list is not set
```

Proxy ARP is enabled
Local Proxy ARP is disabled
Security level is default
Split horizon is enabled
ICMP redirects are always sent
ICMP unreachable are always sent
ICMP mask replies are never sent
IP fast switching is enabled
IP CEF switching is enabled
IP CEF switching turbo vector
IP Null turbo vector
IP multicast fast switching is enabled
IP multicast distributed fast switching is disabled
IP route-cache flags are Fast, CEF
Router Discovery is disabled
IP output packet accounting is disabled
IP access violation accounting is disabled
TCP/IP header compression is disabled
RTP/IP header compression is disabled
Probe proxy name replies are disabled
Policy routing is disabled
Network address translation is disabled
BGP Policy Mapping is disabled
WCCP Redirect outbound is disabled
WCCP Redirect inbound is disabled
WCCP Redirect exclude is disabled
Vlan200 is up, line protocol is up
Internet address is 192.168.1.130/27
Broadcast address is 255.255.255.255
Address determined by non-volatile memory
MTU is 1500 bytes
Helper address is not set
Directed broadcast forwarding is disabled
Outgoing access list is not set
Inbound access list is not set
Proxy ARP is enabled
Local Proxy ARP is disabled
Security level is default
Split horizon is enabled
ICMP redirects are always sent
ICMP unreachable are always sent
ICMP mask replies are never sent
IP fast switching is enabled
IP CEF switching is enabled
IP CEF switching turbo vector
IP Null turbo vector
IP multicast fast switching is enabled
IP multicast distributed fast switching is disabled
IP route-cache flags are Fast, CEF
Router Discovery is disabled
IP output packet accounting is disabled
IP access violation accounting is disabled
TCP/IP header compression is disabled
RTP/IP header compression is disabled

Probe proxy name replies are disabled
Policy routing is disabled
Network address translation is disabled
BGP Policy Mapping is disabled
WCCP Redirect outbound is disabled
WCCP Redirect inbound is disabled
WCCP Redirect exclude is disabled
FastEthernet0/1 is up, line protocol is up
 Internet address is 10.1.4.10/30
 Broadcast address is 255.255.255.255
 Address determined by non-volatile memory
 MTU is 1500 bytes
 Helper address is not set
 Directed broadcast forwarding is disabled
 Multicast reserved groups joined: 224.0.0.1 224.0.0.2 224.0.0.22
224.0.0.13
 224.0.0.10
 Outgoing access list is not set
 Inbound access list is not set
 Proxy ARP is enabled
 Local Proxy ARP is disabled
 Security level is default
 Split horizon is enabled
 ICMP redirects are always sent
 ICMP unreachable are always sent
 ICMP mask replies are never sent
 IP fast switching is enabled
 IP CEF switching is enabled
 IP CEF switching turbo vector
 IP Null turbo vector
 IP multicast fast switching is enabled
 IP multicast distributed fast switching is disabled
 IP route-cache flags are Fast, CEF
 Router Discovery is disabled
 IP output packet accounting is disabled
 IP access violation accounting is disabled
 TCP/IP header compression is disabled
 RTP/IP header compression is disabled
 Probe proxy name replies are disabled
 Policy routing is disabled
 Network address translation is disabled
 BGP Policy Mapping is disabled
 WCCP Redirect outbound is disabled
 WCCP Redirect inbound is disabled
 WCCP Redirect exclude is disabled
FastEthernet0/2 is administratively down, line protocol is down
 Inbound access list is not set
FastEthernet0/3 is down, line protocol is down
 Inbound access list is not set
FastEthernet0/4 is administratively down, line protocol is down
 Inbound access list is not set
FastEthernet0/5 is administratively down, line protocol is down
 Inbound access list is not set
FastEthernet0/6 is administratively down, line protocol is down

```
Inbound access list is not set
FastEthernet0/7 is administratively down, line protocol is down
Inbound access list is not set
FastEthernet0/8 is administratively down, line protocol is down
Inbound access list is not set
FastEthernet0/9 is administratively down, line protocol is down
Inbound access list is not set
FastEthernet0/10 is administratively down, line protocol is down
Inbound access list is not set
FastEthernet0/11 is administratively down, line protocol is down
Inbound access list is not set
FastEthernet0/12 is administratively down, line protocol is down
Inbound access list is not set
FastEthernet0/13 is administratively down, line protocol is down
Inbound access list is not set
FastEthernet0/14 is administratively down, line protocol is down
Inbound access list is not set
FastEthernet0/15 is down, line protocol is down
Inbound access list is not set
FastEthernet0/16 is up, line protocol is up
Inbound access list is not set
FastEthernet0/17 is up, line protocol is up
Inbound access list is not set
FastEthernet0/18 is up, line protocol is up
Inbound access list is not set
FastEthernet0/19 is up, line protocol is up
Inbound access list is not set
FastEthernet0/20 is up, line protocol is up
Inbound access list is not set
FastEthernet0/21 is up, line protocol is up
Inbound access list is not set
FastEthernet0/22 is up, line protocol is up
Internet protocol processing disabled
FastEthernet0/23 is up, line protocol is up
Internet protocol processing disabled
FastEthernet0/24 is up, line protocol is up
Internet protocol processing disabled
GigabitEthernet0/1 is administratively down, line protocol is down
Inbound access list is not set
GigabitEthernet0/2 is administratively down, line protocol is down
Inbound access list is not set
Port-channel12 is up, line protocol is up
Internet address is 10.2.4.14/30
Broadcast address is 255.255.255.255
Address determined by non-volatile memory
MTU is 1500 bytes
Helper address is not set
Directed broadcast forwarding is disabled
Multicast reserved groups joined: 224.0.0.1 224.0.0.2 224.0.0.22
224.0.0.13
224.0.0.10
Outgoing access list is not set
Inbound access list is not set
Proxy ARP is enabled
```

Local Proxy ARP is disabled
Security level is default
Split horizon is enabled
ICMP redirects are always sent
ICMP unreachable are always sent
ICMP mask replies are never sent
IP fast switching is enabled
IP CEF switching is enabled
IP CEF switching turbo vector
IP Null turbo vector
IP multicast fast switching is enabled
IP multicast distributed fast switching is disabled
IP route-cache flags are Fast, CEF
Router Discovery is disabled
IP output packet accounting is disabled
IP access violation accounting is disabled
TCP/IP header compression is disabled
RTP/IP header compression is disabled
Probe proxy name replies are disabled
Policy routing is disabled
Network address translation is disabled
BGP Policy Mapping is disabled
WCCP Redirect outbound is disabled
WCCP Redirect inbound is disabled
WCCP Redirect exclude is disabled
Port-channel23 is up, line protocol is up
Port-channel24 is up, line protocol is up
Tunnel67 is up, line protocol is up
Internet protocol processing disabled
DSW2#

DSW2#show ip cef

Prefix	Next Hop	Interface
0.0.0.0/0	10.1.4.9	FastEthernet0/1
0.0.0.0/32	receive	
10.1.1.8/30	10.1.4.9	FastEthernet0/1
10.1.4.4/30	10.2.1.1	Vlan10
	10.2.2.2	Vlan20
10.1.4.8/30	attached	FastEthernet0/1
10.1.4.8/32	receive	FastEthernet0/1
10.1.4.9/32	attached	FastEthernet0/1
10.1.4.10/32	receive	FastEthernet0/1
10.1.4.11/32	receive	FastEthernet0/1
10.2.1.0/24	attached	Vlan10
10.2.1.0/32	receive	Vlan10
10.2.1.1/32	attached	Vlan10
10.2.1.2/32	receive	Vlan10
10.2.1.4/32	attached	Vlan10
10.2.1.254/32	attached	Vlan10
10.2.1.255/32	receive	Vlan10
10.2.2.0/24	attached	Vlan20
10.2.2.0/32	receive	Vlan20
10.2.2.1/32	receive	Vlan20
10.2.2.2/32	attached	Vlan20
10.2.2.255/32	receive	Vlan20
10.2.4.12/30	attached	Port-channel12
10.2.4.12/32	receive	Port-channel12
10.2.4.13/32	attached	Port-channel12
10.2.4.14/32	receive	Port-channel12
10.2.4.15/32	receive	Port-channel12
192.168.1.128/27	attached	Vlan200
192.168.1.128/32	receive	Vlan200
192.168.1.130/32	receive	Vlan200
192.168.1.159/32	receive	Vlan200
224.0.0.0/4	multicast	
224.0.0.0/24	receive	

```
240.0.0.0/4      drop
255.255.255.255/32  receive
DSW2#
```

```
DSW2#show tcp statistics
Rcvd: 0 Total, 0 no port
      0 checksum error, 0 bad offset, 0 too short
      0 packets (0 bytes) in sequence
      0 dup packets (0 bytes)
      0 partially dup packets (0 bytes)
      0 out-of-order packets (0 bytes)
      0 packets (0 bytes) with data after window
```

0 packets after close
0 window probe packets, 0 window update packets
0 dup ack packets, 0 ack packets with unsend data
0 ack packets (0 bytes)
Sent: 0 Total, 0 urgent packets
0 control packets (including 0 retransmitted)
0 data packets (0 bytes)
0 data packets (0 bytes) retransmitted
0 data packets (0 bytes) fastretransmitted
0 ack only packets (0 delayed)
0 window probe packets, 0 window update packets
0 Connections initiated, 0 connections accepted, 0 connections
established
0 Connections closed (including 0 dropped, 0 embryonic dropped)
0 Total rxmt timeout, 0 connections dropped in rxmt timeout
0 Keepalive timeout, 0 keepalive probe, 0 Connections dropped in
keepalive
DSW2#

```
DSW2#show ip protocols
*** IP Routing is NSF aware ***
```

```
Routing Protocol is "eigrp 10"
  Outgoing update filter list for all interfaces is not set
  Incoming update filter list for all interfaces is not set
  Default networks flagged in outgoing updates
  Default networks accepted from incoming updates
  Redistributing: eigrp 10
```

```
Address Family Protocol EIGRP-IPv4:(10)
  EIGRP metric weight K1=1, K2=1, K3=1, K4=1, K5=1
  EIGRP maximum hopcount 100
  EIGRP maximum metric variance 1
  EIGRP NSF-aware route hold timer is 240
  Topologies : 0(base)
```

```
Automatic network summarization is not in effect
```

```
Maximum path: 4
```

```
Routing for Networks:
```

```
  10.1.4.10/32
  10.2.1.2/32
  10.2.2.1/32
  10.2.4.14/32
```

```
Routing Information Sources:
```

Gateway	Distance	Last Update
10.2.4.13	90	00:39:41
10.1.4.9	90	00:39:41
10.2.1.1	90	00:39:41
10.2.2.2	90	00:39:41

```
Distance: internal 90 external 170
```

```
DSW2#
```

```
DSW2#show access-lists
Standard IP access list DENY_10
  10 deny 10.0.0.0, wildcard bits 0.255.255.255
  20 permit any
Standard IP access list DENY_ALL
  10 deny any
Standard IP access list PERMIT_10
  10 permit 10.0.0.0, wildcard bits 0.255.255.255
Standard IP access list PERMIT_ALL
  10 permit any
DSW2#
```

```
DSW2#show ip route eigrp
      10.0.0.0/8 is variably subnetted, 6 subnets, 2 masks
D EX    10.1.1.8/30 [170/1023] via 10.1.4.9, 00:39:55, FastEthernet0/1
D       10.1.4.4/30 [90/111] via 10.2.2.2, 00:39:55, Vlan20
          [90/111] via 10.2.1.1, 00:39:55, Vlan10
D*EX 0.0.0.0/0 [170/1023] via 10.1.4.9, 00:39:55, FastEthernet0/1
DSW2#
```

```
EIGRP-IPv4:(10) neighbors for process 10
```

DSW2#

```
DSW2#show ip eigrp interfaces
EIGRP-IPv4:(10) interfaces for process 10
```

Pending Interface Routes	Peers	Xmit Queue Un/Reliable	Mean SRTT	Pacing Time Un/Reliable	Multicast Flow Timer
Fa0/1 0	1	0/0	1	0/1	50
Vl10 0	1	0/0	3	0/1	50
Vl20 0	1	0/0	1	0/1	50
Pol2 0	1	0/0	1	0/1	50

```
DSW2#
```

DSW2#show vlan

VLAN	Name	Status	Ports
1	default	active	Fa0/2, Fa0/3, Fa0/4, Fa0/5 Fa0/6, Fa0/7, Fa0/8, Fa0/9 Fa0/10, Fa0/11, Fa0/12, Fa0/13 Fa0/14, Fa0/15, Gi0/1, Gi0/2
10	VLAN0010	active	
20	VLAN0020	active	
200	VLAN0200	active	
1002	fddi-default	act/unsup	
1003	trcrf-default	act/unsup	
1004	fddinet-default	act/unsup	
1005	trbrf-default	act/unsup	

VLAN	Type	SAID	MTU	Parent	RingNo	BridgeNo	Stp	BrdgMode	Trans1	Trans2
1	enet	100001	1500	-	-	-	-	-	0	0
10	enet	100010	1500	-	-	-	-	-	0	0
20	enet	100020	1500	-	-	-	-	-	0	0
200	enet	100200	1500	-	-	-	-	-	0	0
1002	fddi	101002	1500	-	-	-	-	-	0	0
1003	trcrf	101003	4472	1005	3276	-	-	srb	0	0
1004	fdnet	101004	1500	-	-	-	ieee	-	0	0
1005	trbrf	101005	4472	-	-	15	ibm	-	0	0

VLAN	AREHops	STEHops	Backup	CRF
1003	7	7	off	

Remote SPAN VLANs

Primary	Secondary	Type	Ports
---------	-----------	------	-------

DSW2#

DSW2#show spanning-tree

VLAN0010

Spanning tree enabled protocol ieee

Root ID Priority 4106
 Address 000d.bde3.6e00
 Cost 18
 Port 66 (Port-channel23)
 Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec

Bridge ID Priority 8202 (priority 8192 sys-id-ext 10)
 Address 000b.fd20.ba00
 Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
 Aging Time 300

Interface	Role	Sts	Cost	Prio.Nbr	Type
Po23	Root	FWD	9	128.66	P2p

VLAN0020

Spanning tree enabled protocol ieee

Root ID Priority 4116
 Address 000b.fd20.ba00
 This bridge is the root
 Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec

Bridge ID Priority 4116 (priority 4096 sys-id-ext 20)
 Address 000b.fd20.ba00
 Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
 Aging Time 300

Interface	Role	Sts	Cost	Prio.Nbr	Type
-----------	------	-----	------	----------	------

Po24 Desg FWD 9 128.67 P2p

VLAN0200

Spanning tree enabled protocol ieee

Root ID Priority 4296
 Address 000d.bde3.6e00
 Cost 18
 Port 66 (Port-channel23)
 Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec

Bridge ID Priority 8392 (priority 8192 sys-id-ext 200)
 Address 000b.fd20.ba00
 Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
 Aging Time 300

Interface	Role	Sts	Cost	Prio.Nbr	Type
Po23	Root	FWD	9	128.66	P2p
Po24	Altn	BLK	9	128.67	P2p

DSW2#

DSW2#show interfaces status

Port	Name	Status	Vlan	Duplex	Speed	Type
Fa0/1		connected	routed	a-full	a-100	
10/100BaseTX						
Fa0/2		disabled	1	auto	auto	
10/100BaseTX						
Fa0/3		notconnect	1	auto	auto	
10/100BaseTX						
Fa0/4		disabled	1	auto	auto	
10/100BaseTX						
Fa0/5		disabled	1	auto	auto	
10/100BaseTX						
Fa0/6		disabled	1	auto	auto	
10/100BaseTX						
Fa0/7		disabled	1	auto	auto	
10/100BaseTX						
Fa0/8		disabled	1	auto	auto	
10/100BaseTX						
Fa0/9		disabled	1	auto	auto	
10/100BaseTX						
Fa0/10		disabled	1	auto	auto	
10/100BaseTX						
Fa0/11		disabled	1	auto	auto	
10/100BaseTX						
Fa0/12		disabled	1	auto	auto	
10/100BaseTX						
Fa0/13		disabled	1	auto	auto	
10/100BaseTX						
Fa0/14		disabled	1	auto	auto	
10/100BaseTX						
Fa0/15		notconnect	1	auto	auto	
10/100BaseTX						
Fa0/16		connected	trunk	a-full	a-100	
10/100BaseTX						
Fa0/17		connected	trunk	a-full	a-100	
10/100BaseTX						
Fa0/18		connected	trunk	a-full	a-100	
10/100BaseTX						
Fa0/19		connected	trunk	a-full	a-100	
10/100BaseTX						

Fa0/20	connected	trunk	a-full	a-100
10/100BaseTX				
Fa0/21	connected	trunk	a-full	a-100
10/100BaseTX				
Fa0/22	connected	routed	a-full	a-100
10/100BaseTX				
Fa0/23	connected	routed	a-full	a-100
10/100BaseTX				
Fa0/24	connected	routed	a-full	a-100
10/100BaseTX				
Gi0/1	disabled	1	auto	auto
unknown				
Gi0/2	disabled	1	auto	auto
unknown				
Po12	connected	routed	a-full	a-100
Po23	connected	trunk	a-full	a-100
Po24	connected	trunk	a-full	a-100
DSW2#				

DSW2#show interfaces switchport

Name: Fa0/2
Switchport: Enabled
Administrative Mode: static access
Operational Mode: down
Administrative Trunking Encapsulation: negotiate
Negotiation of Trunking: Off
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Fa0/3
Switchport: Enabled
Administrative Mode: static access
Operational Mode: down
Administrative Trunking Encapsulation: negotiate
Negotiation of Trunking: Off
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none

Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Fa0/4
Switchport: Enabled
Administrative Mode: static access
Operational Mode: down
Administrative Trunking Encapsulation: negotiate
Negotiation of Trunking: Off
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Fa0/5
Switchport: Enabled
Administrative Mode: static access
Operational Mode: down
Administrative Trunking Encapsulation: negotiate
Negotiation of Trunking: Off
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none

Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Fa0/6
Switchport: Enabled
Administrative Mode: static access
Operational Mode: down
Administrative Trunking Encapsulation: negotiate
Negotiation of Trunking: Off
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Fa0/7
Switchport: Enabled
Administrative Mode: static access
Operational Mode: down
Administrative Trunking Encapsulation: negotiate
Negotiation of Trunking: Off
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)

Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Fa0/8
Switchport: Enabled
Administrative Mode: static access
Operational Mode: down
Administrative Trunking Encapsulation: negotiate
Negotiation of Trunking: Off
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Fa0/9
Switchport: Enabled
Administrative Mode: static access
Operational Mode: down

Administrative Trunking Encapsulation: negotiate
Negotiation of Trunking: Off
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Fa0/10
Switchport: Enabled
Administrative Mode: static access
Operational Mode: down
Administrative Trunking Encapsulation: negotiate
Negotiation of Trunking: Off
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Fa0/11
Switchport: Enabled
Administrative Mode: static access
Operational Mode: down
Administrative Trunking Encapsulation: negotiate
Negotiation of Trunking: Off
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Fa0/12
Switchport: Enabled
Administrative Mode: static access
Operational Mode: down
Administrative Trunking Encapsulation: negotiate
Negotiation of Trunking: Off
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL

Protected: false

Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Fa0/13
Switchport: Enabled
Administrative Mode: static access
Operational Mode: down
Administrative Trunking Encapsulation: negotiate
Negotiation of Trunking: Off
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Fa0/14
Switchport: Enabled
Administrative Mode: static access
Operational Mode: down
Administrative Trunking Encapsulation: negotiate
Negotiation of Trunking: Off
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001

Capture Mode Disabled
Capture VLANs Allowed: ALL

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Fa0/15
Switchport: Enabled
Administrative Mode: static access
Operational Mode: down
Administrative Trunking Encapsulation: negotiate
Negotiation of Trunking: Off
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Fa0/16
Switchport: Enabled
Administrative Mode: trunk
Operational Mode: trunk (member of bundle Po24)
Administrative Trunking Encapsulation: dot1q
Operational Trunking Encapsulation: dot1q
Negotiation of Trunking: On
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none

Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: 20,200
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Fa0/17
Switchport: Enabled
Administrative Mode: trunk
Operational Mode: trunk (member of bundle Po24)
Administrative Trunking Encapsulation: dot1q
Operational Trunking Encapsulation: dot1q
Negotiation of Trunking: On
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: 20,200
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Fa0/18
Switchport: Enabled
Administrative Mode: trunk
Operational Mode: trunk (member of bundle Po24)
Administrative Trunking Encapsulation: dot1q
Operational Trunking Encapsulation: dot1q
Negotiation of Trunking: On
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none

Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: 20,200
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Fa0/19
Switchport: Enabled
Administrative Mode: trunk
Operational Mode: trunk (member of bundle Po23)
Administrative Trunking Encapsulation: dot1q
Operational Trunking Encapsulation: dot1q
Negotiation of Trunking: On
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: 10,200
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Fa0/20
Switchport: Enabled
Administrative Mode: trunk
Operational Mode: trunk (member of bundle Po23)
Administrative Trunking Encapsulation: dot1q

Operational Trunking Encapsulation: dot1q
Negotiation of Trunking: On
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: 10,200
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Fa0/21
Switchport: Enabled
Administrative Mode: trunk
Operational Mode: trunk (member of bundle Po23)
Administrative Trunking Encapsulation: dot1q
Operational Trunking Encapsulation: dot1q
Negotiation of Trunking: On
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: 10,200
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Gi0/1
Switchport: Enabled
Administrative Mode: dynamic desirable
Operational Mode: down
Administrative Trunking Encapsulation: negotiate
Negotiation of Trunking: On
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Gi0/2
Switchport: Enabled
Administrative Mode: dynamic desirable
Operational Mode: down
Administrative Trunking Encapsulation: negotiate
Negotiation of Trunking: On
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Po23
Switchport: Enabled
Administrative Mode: trunk
Operational Mode: trunk
Administrative Trunking Encapsulation: dot1q
Operational Trunking Encapsulation: dot1q
Negotiation of Trunking: On
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: 10,200
Pruning VLANs Enabled: 2-1001

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Po24
Switchport: Enabled
Administrative Mode: trunk
Operational Mode: trunk
Administrative Trunking Encapsulation: dot1q
Operational Trunking Encapsulation: dot1q
Negotiation of Trunking: On
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: 20,200

Pruning VLANs Enabled: 2-1001

Protected: false

Unknown unicast blocked: disabled

Unknown multicast blocked: disabled

Appliance trust: none

DSW2#

DSW2#show interfaces trunk

Port	Mode	Encapsulation	Status	Native vlan
Po23	on	802.1q	trunking	1

Po24	on	802.1q	trunking	1
------	----	--------	----------	---

Port	Vlans allowed on trunk
------	------------------------

Po23	10,200
------	--------

Po24	20,200
------	--------

Port	Vlans allowed and active in management domain
------	---

Po23	10,200
------	--------

Po24	20,200
------	--------

Port	Vlans in spanning tree forwarding state and not pruned
------	--

Po23	10,200
------	--------

Po24	20
------	----

DSW2#

```
DSW2#show vtp status
VTP Version                : running VTP2
Configuration Revision      : 0
Maximum VLANs supported locally : 1005
Number of existing VLANs    : 8
VTP Operating Mode         : Transparent
VTP Domain Name            : netlearning
VTP Pruning Mode           : Disabled
VTP V2 Mode                : Enabled
VTP Traps Generation       : Disabled
MD5 digest                 : 0x99 0xF7 0xCE 0x74 0x55 0xA6 0x6A 0xC7
Configuration last modified by 0.0.0.0 at 0-0-00 00:00:00
DSW2#
```

```
DSW2#show vtp password
VTP Password: cisco1
DSW2#
```

```
DSW2#show etherchannel detail
Channel-group listing:
-----
```

Group: 12

Group state = L3

Ports: 3 Maxports = 8

Port-channels: 1 Max Port-channels = 1

Protocol: -

Minimum Links: 0

Ports in the group:

Port: Fa0/22

Port state = Up Mstr In-Bndl

Channel group = 12 Mode = On

Gcchange = -

Port-channel = Po12 GC = -

Pseudo port-channel =

Po12

Port index = 0 Load = 0x00

Protocol = -

Age of the port in the current state: 0d:02h:13m:31s

Port: Fa0/23

Port state = Up Mstr In-Bndl

Channel group = 12 Mode = On

Gcchange = -

Port-channel = Po12 GC = -

Pseudo port-channel =

Po12

Port index = 0 Load = 0x00

Protocol = -

Age of the port in the current state: 0d:02h:13m:32s

Port: Fa0/24

Port state = Up Mstr In-Bndl

Channel group = 12 Mode = On

Gcchange = -

Port-channel = Po12 GC = -

Pseudo port-channel =

Po12

Port index = 0 Load = 0x00

Protocol = -

Age of the port in the current state: 0d:02h:13m:32s

Port-channels in the group:

Port-channel: Po12

Age of the Port-channel = 0d:02h:13m:39s

Logical slot/port = 1/0 Number of ports = 3

GC = 0x00000000 HotStandBy port = null

Passive port list = Fa0/22 Fa0/23 Fa0/24

Port state = Port-channel L3-Ag Ag-Inuse

Protocol = -
Port security = Disabled

Ports in the Port-channel:

Index	Load	Port	EC state	No of bits
0	00	Fa0/22	On	0
0	00	Fa0/23	On	0
0	00	Fa0/24	On	0

Time since last port bundled: 0d:02h:13m:32s Fa0/24
Time since last port Un-bundled: 0d:02h:13m:34s Fa0/24

Group: 23

Group state = L2
Ports: 3 Maxports = 16
Port-channels: 1 Max Port-channels = 1
Protocol: LACP
Minimum Links: 0

Ports in the group:

Port: Fa0/19

Port state = Up Mstr Assoc In-Bndl
Channel group = 23 Mode = Active Gcchange = -
Port-channel = Po23 GC = - Pseudo port-channel =
Po23
Port index = 0 Load = 0x00 Protocol = LACP

Flags: S - Device is sending Slow LACPDUs F - Device is sending fast LACPDUs.
A - Device is in active mode. P - Device is in passive mode.

Local information:

Port	Flags	State	LACP port	Admin	Oper	Port
Port	Flags	State	Priority	Key	Key	Number
Fa0/19	SA	bndl	32768	0x17	0x17	0x10
0x3D						

Partner's information:

Port	Flags	Priority	LACP port	Admin	Oper	Port	
Port	Flags	Priority	Dev ID	Age	key	Key	Number
Fa0/19	SA	32768	0015.faac.46c0	22s	0x0	0x2	0x10
0x3D							

Age of the port in the current state: 0d:02h:13m:28s

Port: Fa0/20

Port state = Up Mstr Assoc In-Bndl
Channel group = 23 Mode = Active Gcchange = -
Port-channel = Po23 GC = - Pseudo port-channel =
Po23
Port index = 0 Load = 0x00 Protocol = LACP

Flags: S - Device is sending Slow LACPDUs F - Device is sending fast
LACPDUs.

A - Device is in active mode. P - Device is in passive
mode.

Local information:

Port	Flags	State	LACP port Priority	Admin Key	Oper Key	Port Number
Fa0/20 0x3D	SA	bndl	32768	0x17	0x17	0x11

Partner's information:

Port	Flags	Priority	LACP port Dev ID	Admin Age	Oper key	Port Key	Port Number
Fa0/20 0x3D	SA	32768	0015.faac.46c0	18s	0x0	0x2	0x11

Age of the port in the current state: 0d:02h:13m:28s

Port: Fa0/21

Port state = Up Mstr Assoc In-Bndl
Channel group = 23 Mode = Active Gcchange = -
Port-channel = Po23 GC = - Pseudo port-channel =
Po23
Port index = 0 Load = 0x00 Protocol = LACP

Flags: S - Device is sending Slow LACPDUs F - Device is sending fast
LACPDUs.

A - Device is in active mode. P - Device is in passive
mode.

Local information:

Port	Flags	State	LACP port Priority	Admin Key	Oper Key	Port Number
Fa0/21 0x3D	SA	bndl	32768	0x17	0x17	0x11

Fa0/21 SA bndl 32768 0x17 0x17 0x12
0x3D

Partner's information:

Port	Flags	Priority	Dev ID	Age	Admin key	Oper Key	Port Number
Fa0/21	SA	32768	0015.faac.46c0	2s	0x0	0x2	0x12
0x3D							

Age of the port in the current state: 0d:02h:13m:29s

Port-channels in the group:

Port-channel: Po23 (Primary Aggregator)

Age of the Port-channel = 0d:02h:13m:44s
Logical slot/port = 1/1 Number of ports = 3
HotStandBy port = null
Port state = Port-channel Ag-Inuse
Protocol = LACP
Port security = Disabled

Ports in the Port-channel:

Index	Load	Port	EC state	No of bits
0	00	Fa0/19	Active	0
0	00	Fa0/20	Active	0
0	00	Fa0/21	Active	0

Time since last port bundled: 0d:02h:13m:30s Fa0/21

Group: 24

Group state = L2
Ports: 3 Maxports = 8
Port-channels: 1 Max Port-channels = 1
Protocol: PAgP
Minimum Links: 0

Ports in the group:

Port: Fa0/16

Port state = Up Mstr In-Bndl
Channel group = 24 Mode = Desirable-S1 Gcchange = 0
Port-channel = Po24 GC = 0x00180001 Pseudo port-channel =
Po24

Port index = 0 Load = 0x00 Protocol = PAgP

Flags: S - Device is sending Slow hello. C - Device is in Consistent state.

A - Device is in Auto mode. P - Device learns on physical port.

d - PAgP is down.

Timers: H - Hello timer is running. Q - Quit timer is running.

S - Switching timer is running. I - Interface timer is running.

Local information:

Group	Port	Flags	State	Timers	Hello Interval	Partner Count	PAgP Priority	Learning Method
	Fa0/16	SC	U6/S7	H	30s	1	128	Any 32

Partner's information:

Group	Partner	Partner	Partner	Partner
Port	Name	Device ID	Port	Age
Cap.				Flags
Fa0/16	ASW2	0015.fab8.2880	Fa0/19	5s SC
10001				

Age of the port in the current state: 0d:02h:13m:33s

Port: Fa0/17

Port state = Up Mstr In-Bndl

Channel group = 24 Mode = Desirable-Sl Gcchange = 0

Port-channel = Po24 GC = 0x00180001 Pseudo port-channel = Po24

Port index = 0 Load = 0x00 Protocol = PAgP

Flags: S - Device is sending Slow hello. C - Device is in Consistent state.

A - Device is in Auto mode. P - Device learns on physical port.

d - PAgP is down.

Timers: H - Hello timer is running. Q - Quit timer is running.

S - Switching timer is running. I - Interface timer is running.

Local information:

Group	Port	Flags	State	Timers	Hello Interval	Partner Count	PAgP Priority	Learning Method
	Fa0/17	SC	U6/S7	H	30s	1	128	Any 32

Partner's information:

Group	Partner	Partner	Partner	Partner
Port	Name	Device ID	Port	Age
Cap.				Flags
Fa0/17	ASW2	0015.fab8.2880	Fa0/20	1s SC
10001				

Age of the port in the current state: 0d:02h:13m:34s

Port: Fa0/18

Port state = Up Mstr In-Bndl
Channel group = 24 Mode = Desirable-Sl Gcchange = 0
Port-channel = Po24 GC = 0x00180001 Pseudo port-channel = Po24
Port index = 0 Load = 0x00 Protocol = PAgP

Flags: S - Device is sending Slow hello. C - Device is in Consistent state.

A - Device is in Auto mode. P - Device learns on physical port.

d - PAgP is down.

Timers: H - Hello timer is running. Q - Quit timer is running.

S - Switching timer is running. I - Interface timer is running.

Local information:

Group	Flags	State	Timers	Hello Interval	Partner Count	PAgP Priority	Learning Method
Fa0/18	SC	U6/S7	H	30s	1	128	Any 32

Partner's information:

Group	Partner	Partner	Partner	Partner
Port	Name	Device ID	Port	Age
Cap.				Flags
Fa0/18	ASW2	0015.fab8.2880	Fa0/21	11s SC
10001				

Age of the port in the current state: 0d:02h:13m:35s

Port-channels in the group:

Port-channel: Po24

Age of the Port-channel = 0d:02h:13m:49s

Logical slot/port = 1/2 Number of ports = 3
GC = 0x00180001 HotStandBy port = null
Port state = Port-channel Ag-Inuse
Protocol = PAgP
Port security = Disabled

Ports in the Port-channel:

Index	Load	Port	EC state	No of bits
0	00	Fa0/16	Desirable-S1	0
0	00	Fa0/17	Desirable-S1	0
0	00	Fa0/18	Desirable-S1	0

Time since last port bundled: 0d:02h:13m:37s Fa0/18

DSW2#

```
DSW2#show standby
Vlan10 - Group 10
  State is Standby
    4 state changes, last state change 00:41:50
  Virtual IP address is 10.2.1.254
  Active virtual MAC address is 0000.0c07.ac0a
    Local virtual MAC address is 0000.0c07.ac0a (v1 default)
  Hello time 3 sec, hold time 10 sec
    Next hello sent in 0.244 secs
  Preemption disabled
  Active router is 10.2.1.1, priority 110 (expires in 9.120 sec)
  Standby router is local
  Priority 20 (configured 20)
  IP redundancy name is "hsrp-Vl10-10" (default)
DSW2#
```

```
DSW2#show standby brief
```

P indicates configured to preempt.

1

Interface	Grp	Prio	P	State	Active	Standby	Virtual
-----------	-----	------	---	-------	--------	---------	---------

IP

```
Vl10      10  20      Standby  10.2.1.1      local
```

10.2.1.254

DSW2#

DSW2#show power inline

Available:360(w) Used:0(w) Remaining:360(w)

Interface	Admin	Oper	Power (Watts)	Device	Class	Max
Fa0/1	auto	off	0.0	n/a	n/a	15.4
Fa0/2	auto	off	0.0	n/a	n/a	15.4
Fa0/3	auto	off	0.0	n/a	n/a	15.4
Fa0/4	auto	off	0.0	n/a	n/a	15.4
Fa0/5	auto	off	0.0	n/a	n/a	15.4
Fa0/6	auto	off	0.0	n/a	n/a	15.4
Fa0/7	auto	off	0.0	n/a	n/a	15.4
Fa0/8	auto	off	0.0	n/a	n/a	15.4
Fa0/9	auto	off	0.0	n/a	n/a	15.4
Fa0/10	auto	off	0.0	n/a	n/a	15.4
Fa0/11	auto	off	0.0	n/a	n/a	15.4
Fa0/12	auto	off	0.0	n/a	n/a	15.4
Fa0/13	auto	off	0.0	n/a	n/a	15.4
Fa0/14	auto	off	0.0	n/a	n/a	15.4
Fa0/15	auto	off	0.0	n/a	n/a	15.4
Fa0/16	auto	off	0.0	n/a	n/a	15.4
Fa0/17	auto	off	0.0	n/a	n/a	15.4
Fa0/18	auto	off	0.0	n/a	n/a	15.4
Fa0/19	auto	off	0.0	n/a	n/a	15.4
Fa0/20	auto	off	0.0	n/a	n/a	15.4
Fa0/21	auto	off	0.0	n/a	n/a	15.4
Fa0/22	auto	off	0.0	n/a	n/a	15.4
Fa0/23	auto	off	0.0	n/a	n/a	15.4
Fa0/24	auto	off	0.0	n/a	n/a	15.4

DSW2#

```
DSW2#show spanning-tree inconsistentports
```

Name	Interface	Inconsistency
-----	-----	-----

```
Number of inconsistent ports (segments) in the system : 0
```

```
DSW2#
```

DSW2#show spanning-tree summary

Switch is in pvst mode

Root bridge for: VLAN0020

Extended system ID is enabled

Portfast Default is disabled

PortFast BPDU Guard Default is disabled

Portfast BPDU Filter Default is disabled

Loopguard Default is disabled

EtherChannel misconfig guard is enabled

UplinkFast is disabled

BackboneFast is disabled

Configured Pathcost method used is short

Name	Blocking	Listening	Learning	Forwarding	STP Active
-----	-----	-----	-----	-----	-----
VLAN0010	0	0	0	1	1
VLAN0020	0	0	0	1	1
VLAN0200	1	0	0	1	2
-----	-----	-----	-----	-----	-----
3 vlans	1	0	0	3	4

DSW2#

```
DSW2#show udld
```

```
Interface Fa0/1
```

```
---
```

```
Port enable administrative configuration setting: Disabled
```

```
Port enable operational state: Disabled
```

```
Current bidirectional state: Unknown
```

```
Interface Fa0/2
```

```
---
```

```
Port enable administrative configuration setting: Disabled
```

```
Port enable operational state: Disabled
```

```
Current bidirectional state: Unknown
```

```
Interface Fa0/3
```

```
---
```

```
Port enable administrative configuration setting: Disabled
```

```
Port enable operational state: Disabled
```

```
Current bidirectional state: Unknown
```

Interface Fa0/4

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/5

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/6

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/7

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/8

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/9

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/10

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/11

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/12

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/13

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/14

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/15

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/16

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/17

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/18

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/19

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/20

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/21

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/22

Port enable administrative configuration setting: Disabled

Port enable operational state: Disabled

Current bidirectional state: Unknown

Interface Fa0/23

Port enable administrative configuration setting: Disabled

Port enable operational state: Disabled

Current bidirectional state: Unknown

Interface Fa0/24

Port enable administrative configuration setting: Disabled

Port enable operational state: Disabled

Current bidirectional state: Unknown

Interface Gi0/1

Port enable administrative configuration setting: Disabled

Port enable operational state: Disabled

Current bidirectional state: Unknown

Interface Gi0/2

Port enable administrative configuration setting: Disabled

Port enable operational state: Disabled

Current bidirectional state: Unknown

DSW2#

DSW2#show etherchannel summary

Flags: D - down P - bundled in port-channel
I - stand-alone s - suspended
H - Hot-standby (LACP only)
R - Layer3 S - Layer2
U - in use f - failed to allocate aggregator

M - not in use, minimum links not met
u - unsuitable for bundling
w - waiting to be aggregated
d - default port

Number of channel-groups in use: 3

Number of aggregators: 3

Group	Port-channel	Protocol	Ports
12	Po12 (RU)	-	Fa0/22 (P) Fa0/23 (P) Fa0/24 (P)
23	Po23 (SU)	LACP	Fa0/19 (P) Fa0/20 (P) Fa0/21 (P)
24	Po24 (SU)	PAgP	Fa0/16 (P) Fa0/17 (P) Fa0/18 (P)

DSW2#

```
DSW2#show etherchannel protocol
      Channel-group listing:
      -----
```

```
Group: 12
-----
```

```
Protocol:  -  (Mode ON)
```

```
Group: 23
-----
```

```
Protocol:  LACP
```

```
Group: 24
-----
```

```
Protocol:  PAgP
```

```
DSW2#
```

```
DSW2#show etherchannel port
      Channel-group listing:
```

```
-----
Group: 12
-----
```

```
Ports in the group:
-----
```

```
Port: Fa0/22
-----
```

Port state	= Up Mstr In-Bndl		
Channel group	= 12	Mode = On	Gcchange = -
Port-channel	= Po12	GC = -	Pseudo port-channel =
Po12			
Port index	= 0	Load = 0x00	Protocol = -

Age of the port in the current state: 0d:02h:14m:50s

Port: Fa0/23

Port state = Up Mstr In-Bndl
Channel group = 12 Mode = On Gcchange = -
Port-channel = Po12 GC = - Pseudo port-channel =
Po12
Port index = 0 Load = 0x00 Protocol = -

Age of the port in the current state: 0d:02h:14m:50s

Port: Fa0/24

Port state = Up Mstr In-Bndl
Channel group = 12 Mode = On Gcchange = -
Port-channel = Po12 GC = - Pseudo port-channel =
Po12
Port index = 0 Load = 0x00 Protocol = -

Age of the port in the current state: 0d:02h:14m:51s

Group: 23

Ports in the group:

Port: Fa0/19

Port state = Up Mstr Assoc In-Bndl
Channel group = 23 Mode = Active Gcchange = -
Port-channel = Po23 GC = - Pseudo port-channel =
Po23
Port index = 0 Load = 0x00 Protocol = LACP

Flags: S - Device is sending Slow LACPDUs F - Device is sending fast LACPDUs.

A - Device is in active mode. P - Device is in passive mode.

Local information:

Port	Flags	State	LACP port Priority	Admin Key	Oper Key	Port Number
Fa0/19	SA	bndl	32768	0x17	0x17	0x10
0x3D						

Partner's information:

LACP port					Admin	Oper	Port
Port	Flags	Priority	Dev ID	Age	key	Key	Number
Fa0/19	SA	32768	0015.faac.46c0	20s	0x0	0x2	0x10

Age of the port in the current state: 0d:02h:14m:47s

Port: Fa0/20

Port state = Up Mstr Assoc In-Bndl
Channel group = 23 Mode = Active Gcchange = -
Port-channel = Po23 GC = - Pseudo port-channel =
Po23
Port index = 0 Load = 0x00 Protocol = LACP

Flags: S - Device is sending Slow LACPDUs F - Device is sending fast LACPDUs.
A - Device is in active mode. P - Device is in passive mode.

Local information:

LACP port				Admin	Oper	Port
Port	Flags	State	Priority	Key	Key	Number
Fa0/20	SA	bndl	32768	0x17	0x17	0x11

Partner's information:

LACP port					Admin	Oper	Port
Port	Flags	Priority	Dev ID	Age	key	Key	Number
Fa0/20	SA	32768	0015.faac.46c0	18s	0x0	0x2	0x11

Age of the port in the current state: 0d:02h:14m:46s

Port: Fa0/21

Port state = Up Mstr Assoc In-Bndl
Channel group = 23 Mode = Active Gcchange = -
Port-channel = Po23 GC = - Pseudo port-channel =
Po23
Port index = 0 Load = 0x00 Protocol = LACP

Flags: S - Device is sending Slow LACPDUs F - Device is sending fast LACPDUs.

A - Device is in active mode. P - Device is in passive mode.

Local information:

Port	Flags	State	LACP port	Admin	Oper	Port
Port	Flags	State	Priority	Key	Key	Number
Fa0/21	SA	bndl	32768	0x17	0x17	0x12
0x3D						

Partner's information:

Port	Flags	Priority	LACP port	Admin	Oper	Port	
Port	Flags	Priority	Dev ID	Age	key	Key	Number
Fa0/21	SA	32768	0015.faac.46c0	28s	0x0	0x2	0x12
0x3D							

Age of the port in the current state: 0d:02h:14m:47s

Group: 24

Ports in the group:

Port: Fa0/16

Port state = Up Mstr In-Bndl
Channel group = 24 Mode = Desirable-Sl Gcchange = 0
Port-channel = Po24 GC = 0x00180001 Pseudo port-channel = Po24
Port index = 0 Load = 0x00 Protocol = PAgP

Flags: S - Device is sending Slow hello. C - Device is in Consistent state.

A - Device is in Auto mode. P - Device learns on physical port.

d - PAgP is down.

Timers: H - Hello timer is running. Q - Quit timer is running.

S - Switching timer is running. I - Interface timer is running.

Local information:

Group	Flags	State	Timers	Hello	Partner	PAgP	Learning	
Port	Flags	State	Timers	Interval	Count	Priority	Method	
Fa0/16	SC	U6/S7	H	30s	1	128	Any	32

Partner's information:

Group	Partner	Partner	Partner	Partner
Port	Name	Device ID	Port	Age Flags
Cap.				
Fa0/16	ASW2	0015.fab8.2880	Fa0/19	0s SC
10001				

Age of the port in the current state: 0d:02h:14m:50s

Port: Fa0/17

Port state = Up Mstr In-Bndl
Channel group = 24 Mode = Desirable-Sl Gcchange = 0
Port-channel = Po24 GC = 0x00180001 Pseudo port-channel = Po24
Port index = 0 Load = 0x00 Protocol = PAgP

Flags: S - Device is sending Slow hello. C - Device is in Consistent state.
A - Device is in Auto mode. P - Device learns on physical port.
d - PAgP is down.
Timers: H - Hello timer is running. Q - Quit timer is running.
S - Switching timer is running. I - Interface timer is running.

Local information:

				Hello	Partner	PAgP	Learning
Group							
Port	Flags	State	Timers	Interval	Count	Priority	Method
Ifindex							
Fa0/17	SC	U6/S7	H	30s	1	128	Any 32

Partner's information:

Group	Partner	Partner	Partner	Partner
Port	Name	Device ID	Port	Age Flags
Cap.				
Fa0/17	ASW2	0015.fab8.2880	Fa0/20	24s SC
10001				

Age of the port in the current state: 0d:02h:14m:51s

Port: Fa0/18

Port state = Up Mstr In-Bndl
Channel group = 24 Mode = Desirable-Sl Gcchange = 0
Port-channel = Po24 GC = 0x00180001 Pseudo port-channel = Po24
Port index = 0 Load = 0x00 Protocol = PAgP

Flags: S - Device is sending Slow hello. C - Device is in Consistent state.
 A - Device is in Auto mode. P - Device learns on physical port.
 d - PAgP is down.
 Timers: H - Hello timer is running. Q - Quit timer is running.
 S - Switching timer is running. I - Interface timer is running.

Local information:

Group	Port	Flags	State	Timers	Hello Interval	Partner Count	PAgP Priority	Learning Method
	Fa0/18	SC	U6/S7	H	30s	1	128	Any 32

Partner's information:

Group	Partner	Partner	Partner	Partner
Port	Name	Device ID	Port	Age Flags
Fa0/18	ASW2	0015.fab8.2880	Fa0/21	6s SC
10001				

Age of the port in the current state: 0d:02h:14m:53s

DSW2#

```
DSW2#show etherchannel load-balance
EtherChannel Load-Balancing Configuration:
    src-mac
```

```
EtherChannel Load-Balancing Addresses Used Per-Protocol:
Non-IP: Source MAC address
    IPv4: Source MAC address
```

```
DSW2#
```

```
DSW2#show etherchannel port-channel
      Channel-group listing:
      -----
```

```
Group: 12
-----
```

```
      Port-channels in the group:
      -----
```

```
Port-channel: Po12
-----
```

```
Age of the Port-channel   = 0d:02h:15m:19s
Logical slot/port         = 1/0           Number of ports = 3
GC                         = 0x00000000    HotStandBy port = null
Passive port list         = Fa0/22 Fa0/23 Fa0/24
Port state                 = Port-channel L3-Ag Ag-Inuse
Protocol                   = -
Port security              = Disabled
```

Ports in the Port-channel:

Index	Load	Port	EC state	No of bits
0	00	Fa0/22	On	0
0	00	Fa0/23	On	0
0	00	Fa0/24	On	0

```
Time since last port bundled:    0d:02h:15m:11s    Fa0/24
Time since last port Un-bundled: 0d:02h:15m:13s    Fa0/24
```

```
Group: 23
-----
```

```
      Port-channels in the group:
      -----
```

```
Port-channel: Po23      (Primary Aggregator)
```

Age of the Port-channel = 0d:02h:15m:20s
Logical slot/port = 1/1 Number of ports = 3
HotStandBy port = null
Port state = Port-channel Ag-Inuse
Protocol = LACP
Port security = Disabled

Ports in the Port-channel:

Index	Load	Port	EC state	No of bits
0	00	Fa0/19	Active	0
0	00	Fa0/20	Active	0
0	00	Fa0/21	Active	0

Time since last port bundled: 0d:02h:15m:06s Fa0/21

Group: 24

Port-channels in the group:

Port-channel: Po24

Age of the Port-channel = 0d:02h:15m:20s
Logical slot/port = 1/2 Number of ports = 3
GC = 0x00180001 HotStandBy port = null
Port state = Port-channel Ag-Inuse
Protocol = PAgP
Port security = Disabled

Ports in the Port-channel:

Index	Load	Port	EC state	No of bits
0	00	Fa0/16	Desirable-Sl	0
0	00	Fa0/17	Desirable-Sl	0
0	00	Fa0/18	Desirable-Sl	0

Time since last port bundled: 0d:02h:15m:08s Fa0/18

DSW2#

DSW2#show pagp neighbor

Flags: S - Device is sending Slow hello. C - Device is in Consistent state.

A - Device is in Auto mode. P - Device learns on physical port.

Channel group 24 neighbors

Group	Partner	Partner	Partner	Partner
Port	Name	Device ID	Port	Age Flags
Fa0/16	ASW2	0015.fab8.2880	Fa0/19	26s SC
10001				
Fa0/17	ASW2	0015.fab8.2880	Fa0/20	20s SC
10001				
Fa0/18	ASW2	0015.fab8.2880	Fa0/21	3s SC
10001				

DSW2#

DSW2#show lacp neighbor

Flags: S - Device is requesting Slow LACPDUs

F - Device is requesting Fast LACPDUs

A - Device is in Active mode

P - Device is in Passive mode

Channel group 23 neighbors

Partner's information:

		LACP port			Admin	Oper	Port
Port							
Port	Flags	Priority	Dev ID	Age	key	Key	Number
State							

Fa0/19 0x3D	SA	32768	0015.faac.46c0	4s	0x0	0x2	0x10
Fa0/20 0x3D	SA	32768	0015.faac.46c0	25s	0x0	0x2	0x11
Fa0/21 0x3D DSW2#	SA	32768	0015.faac.46c0	8s	0x0	0x2	0x12

```
DSW2#show port-security
Secure Port    MaxSecureAddr  CurrentAddr    SecurityViolation  Security
Action
                (Count)        (Count)        (Count)
```

```
Total Addresses in System (excluding one mac per port)      : 0
Max Addresses limit in System (excluding one mac per port) : 5120
DSW2#
```

```
DSW2#show port-security address
Secure Mac Address Table
```

Vlan	Mac Address	Type	Ports	Remaining Age
------	-------------	------	-------	---------------

```
----- (mins) -----
-----
-----
Total Addresses in System (excluding one mac per port) : 0
Max Addresses limit in System (excluding one mac per port) : 5120
DSW2#
```